ItalTherm

FORNO RIBALTABILE PER FUSIONE METALLI CON TRASMISSIONE AD INGRANAGGI

GEAR-DRIVEN TILTING METAL MELTING FURNACE

Mod IT.GT







Il forno ribaltabile per fusione metalli con trasmissione a ingranaggi ITALTHERM fornisce elevate prestazioni per la fusione di metalli preziosi come oro e argento, con capacità comprese tra 20 kg e 50 kg.

È dotato di un efficiente generatore di potenza a induzione a media frequenza energetica e di un controllo preciso della temperatura per un riscaldamento rapido e uniforme.

Il meccanismo di ribaltamento è guidato da un sistema di riduzione a ingranaggi economico, che garantisce un ribaltamento fluido e controllato e una traiettoria di colata curva precisa.

ITALTHERM Gear-Driven Tilting Metal Melting Furnace delivers robust capabilities for melting precious metals such as gold, silver, with capacities ranging from 20 kg to 50 kg.

Equipped with energy-efficient medium frequency induction power generator and precise temperature control for rapid and uniform heating.

The tilting mechanism is driven by a cost-effective gear reduction drive system with smooth controlled tilting and precise curved pouring trajectory.

TECHNICAL SPECIFICATIONS

MODEL NUMBER	IT.GT20	IT.GT30	IT.GT50
VOLTAGGIO / VOLTAGE	3P, 380 V, 50/60HZ	3P, 380 V, 50/60HZ	3P, 380 V, 50/60HZ
POTENZA / POWER	30KW (ADJUSTABLE)	30KW (ADJUSTABLE)	35KW (ADJUSTABLE)
PESO / WEIGHT	230 KG	230 KG	250 KG
CAPACITÀ MAX. / MAX CAPACITY	ORO / GOLD: 20 KG ARGENTO / SILVER:10 KG	ORO / GOLD: 30KG ARGENTO / SILVER:15KG	ORO / GOLD: 50KG ARGENTO / SILVER:25KG
TEMPO DI FUSIONE / MELTING TIME	10-20 MIN	10-30 MIN	10-30 MIN
DIMENSIONI / DIMENSION (LWH)	1210*750*1340MM	1210*750*1340MM	1210*750*1340MM
TEMPERATURA MASSIMA / MAX TEMPERATURE	1500°C	1500°C	1500°C
CONTROLLO TEMPERATURA TIPO K/ TEMPERATURE CONTROL K-TYPE	FORNITO / EQUIPPED	FORNITO / EQUIPPED	FORNITO / EQUIPPED