

JavaScript Errors - Throw and Try to Catch

[< Previous](#)

[Next >](#)

The `try` statement lets you test a block of code for errors.

The `catch` statement lets you handle the error.

The `throw` statement lets you create custom errors.

The `finally` statement lets you execute code, after try and catch, regardless of the result.

Errors Will Happen!

When executing JavaScript code, different errors can occur.

Errors can be coding errors made by the programmer, errors due to wrong input, and other unforeseeable things.

Example

In this example we have written alert as adddalert to deliberately produce an error:

```

<p id="demo"></p>

<script>
try {
  adddalert("Welcome guest!");
}
catch(err) {
  document.getElementById("demo").innerHTML = err.message;
}

```

[Try it Yourself »](#)

JavaScript catches **addlert** as an error, and executes the catch code to handle it.

JavaScript try and catch

The `try` statement allows you to define a block of code to be tested for errors while it is being executed.

The `catch` statement allows you to define a block of code to be executed, if an error occurs in the try block.

The JavaScript statements `try` and `catch` come in pairs:

```
try {  
    Block of code to try  
}  
catch(err) {  
    Block of code to handle errors  
}
```

JavaScript Throws Errors

When an error occurs, JavaScript will normally stop and generate an error message.

The technical term for this is: JavaScript will **throw an exception (throw an error)**.

JavaScript will actually create an **Error object** with two properties: **name** and **message**.

The throw Statement

The `throw` statement allows you to create a custom error.

Technically you can **throw an exception (throw an error)**.

The exception can be a JavaScript `String`, a `Number`, a `Boolean` or an `Object` :

```
throw "Too big";    // throw a text
throw 500;          // throw a number
```

If you use `throw` together with `try` and `catch`, you can control program flow and generate custom error messages.

Input Validation Example

This example examines input. If the value is wrong, an exception (err) is thrown.

The exception (err) is caught by the catch statement and a custom error message is displayed:

```
<!DOCTYPE html>
<html>
<body>

<p>Please input a number between 5 and 10:</p>

<input id="demo" type="text">
<button type="button" onclick="myFunction()">Test Input</button>
<p id="p01"></p>

<script>
function myFunction() {
  var message, x;
  message = document.getElementById("p01");
  message.innerHTML = "";
  x = document.getElementById("demo").value;
  try {
    if(x == "") throw "empty";
    if(isNaN(x)) throw "not a number";
```

```

    if(x > 10) throw "too high";
  }
  catch(err) {
    message.innerHTML = "Input is " + err;
  }
}
</script>

</body>
</html>

```

Try it Yourself »

HTML Validation

The code above is just an example.

Modern browsers will often use a combination of JavaScript and built-in HTML validation, using predefined validation rules defined in HTML attributes:

```
<input id="demo" type="number" min="5" max="10" step="1">
```

You can read more about forms validation in a later chapter of this tutorial.

The finally Statement

The `finally` statement lets you execute code, after try and catch, regardless of the result:

Syntax

```

try {
  Block of code to try
}
catch(err) {
  Block of code to handle errors
}

```

Block of code to be executed regardless of the `try` / `catch` result

```
}
```

Example

```
function myFunction() {
  var message, x;
  message = document.getElementById("p01");
  message.innerHTML = "";
  x = document.getElementById("demo").value;
  try {
    if(x == "") throw "is empty";
    if(isNaN(x)) throw "is not a number";
    x = Number(x);
    if(x > 10) throw "is too high";
    if(x < 5) throw "is too low";
  }
  catch(err) {
    message.innerHTML = "Error: " + err + ".";
  }
  finally {
    document.getElementById("demo").value = "";
  }
}
```

Try it Yourself »

The Error Object

JavaScript has a built in error object that provides error information when an error occurs.

The error object provides two useful properties: name and message.

Error Object Properties

Property	Description



message

Sets or returns an error message (a string)

Error Name Values

Six different values can be returned by the error name property:

Error Name	Description
EvalError	An error has occurred in the eval() function
RangeError	A number "out of range" has occurred
ReferenceError	An illegal reference has occurred
SyntaxError	A syntax error has occurred
TypeError	A type error has occurred
URIError	An error in encodeURIComponent() has occurred

The six different values are described below.

Eval Error

An `EvalError` indicates an error in the eval() function.

Newer versions of JavaScript do not throw EvalError. Use SyntaxError instead.

Range Error

A `RangeError` is thrown if you use a number that is outside the range of legal values.

For example: You cannot set the number of significant digits of a number to 500.

Example

```

    try {
      num.toPrecision(500); // A number cannot have 500 significant digits
    }
    catch(err) {
      document.getElementById("demo").innerHTML = err.name;
    }
  }

```

Try it Yourself »

Reference Error

A **ReferenceError** is thrown if you use (reference) a variable that has not been declared:

Example

```

var x;
try {
  x = y + 1; // y cannot be referenced (used)
}
catch(err) {
  document.getElementById("demo").innerHTML = err.name;
}

```

Try it Yourself »

Syntax Error

A **SyntaxError** is thrown if you try to evaluate code with a syntax error.

Example

```

try {
  eval("alert('Hello)"); // Missing ' will produce an error
}
catch(err) {

```

[Try it Yourself »](#)

Type Error

A **TypeError** is thrown if you use a value that is outside the range of expected types:

Example

```
var num = 1;
try {
  num.toUpperCase();    // You cannot convert a number to upper case
}
catch(err) {
  document.getElementById("demo").innerHTML = err.name;
}
```

[Try it Yourself »](#)

URI (Uniform Resource Identifier) Error

A **URIError** is thrown if you use illegal characters in a URI function:

Example

```
try {
  decodeURI("%%%");    // You cannot URI decode percent signs
}
catch(err) {
  document.getElementById("demo").innerHTML = err.name;
}
```

[Try it Yourself »](#)

Non-Standard Error Object Properties

Mozilla and Microsoft defines some non-standard error object properties:

- fileName (Mozilla)
- lineNumber (Mozilla)
- columnNumber (Mozilla)
- stack (Mozilla)
- description (Microsoft)
- number (Microsoft)

Do not use these properties in public web sites. They will not work in all browsers.

Complete Error Reference

For a complete reference of the Error object, go to our [Complete JavaScript Error Reference](#).

◀ Previous

Next ▶

COLOR PICKER



LIKE US





HOW TO

Tabs
Dropdowns
Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

Certificates

HTML

CSS

JavaScript

Python

SQL

PHP

And more

[REPORT ERROR](#)[FORUM](#)[ABOUT](#)[SHOP](#)

Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [Java Examples](#)
- [XML Examples](#)
- [jQuery Examples](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [Angular Reference](#)
- [jQuery Reference](#)

Web Certificates

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [SQL Certificate](#)
- [Python Certificate](#)
- [PHP Certificate](#)
- [Bootstrap Certificate](#)
- [XML Certificate](#)
- [jQuery Certificate](#)

[Get Certified »](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content.

While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

W3Schools is Powered by W3.CSS.

