

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall Dimensions:**
 - Width: 52.70
 - Height: 90.80
- Internal Dimensions and Hole Locations:**
 - Distance from top edge to first hole center: 25.50
 - Distance between first and second hole centers: 31.90
 - Distance between second and third hole centers: 31.90
 - Distance from third hole center to bottom edge: 25.50
- Edge Dimensions:**
 - Distance from left edge to hole center line: 3.95
 - Distance from right edge to hole center line: 3.95
- Internal Spacing:**
 - Distance between hole center lines: 44.80 ± 0.05
- Other Features:**
 - Four circular holes, one in each corner.
 - Four circular holes, one on each long side (left and right).
 - Four circular holes, one on each short side (top and bottom).
 - Four circular holes, one in each corner.
 - Four circular holes, one on each long side (left and right).
 - Four circular holes, one on each short side (top and bottom).
 - Four circular holes, one in each corner.

SECTION A-A → edge profile DETAIL B → corner boss

PARAMETER:

1. MATERIAL: TITANIUM Gr5 (TC4) = Ti-6Al-4V GRADE 5. 2. FINISH: BEAD-BLAST MATTE (UNIFORM ON THE STEPPED BACK FACE). REAR ART LASER-MARKED IN THE RECESSED BACK FIELD. 3. GENERAL TOLERANCE PER ISO 2768-1 (MEDIUM). C1-C4 TOLERANCES AS LISTED; C1 & C3 = ± 0.05. DATUMS: A = LEFT EDGE, B = BOTTOM EDGE, C = PCB-REST PLANE. 4. BRACE REGISTRATION: THE RESIN H-BRACE REGISTERS TO THIS SHELL BY FITMENT - ITS 4 OUTBOARD RAILS + THE COMPONENT POCKETS + THE BOARD PRESS-FIT. NO LOCATOR PILLARS; THE CAVITY FLOOR IS A FULL 1.00 EVERYWHERE. 5. EDGE BREAKS - ALL 0.10x45°, FELT NOT SEEN, MODELED. CALLED OUT ON SEC A-A / DETAIL B: RIM = outer rim (top & bottom); MOUTH = recess mouth (around PCB); LIP = inner (cavity-side) lip edge; FRAME = proud back-frame bottom edges; BOSS = boss + spotface bottom edges (Detail B). BREAK ALL OTHER EXPOSED EDGES 0.10x45°. CONCAVE JUNCTION CORNERS (BOSS CORNERS) 0.10x45°. 6. FLOOR IS A TRUE 1.00, UNIFORM ACROSS THE CAVITY, AT THE ~1.0 TI MIN-WALL GUIDANCE SO IT ALSO CLEARS ALUMINIUM / COPPER / STAINLESS. CAVITY 1.80 $\pm$ 0.05 -> 1.75 WORST-CASE, MINUS WS17 1.70 MAX (DATASHEET CASE WS17 HEIGHT) = 0.05 NON-CONTACT; THE BRACE + SOLAR-CELL SANDWICHES CARRY THE BOARD. 7. NO U7 RELIEF POCKET. U7 IS THE 0.90 mm MB85RC512TY DFN-8, WELL UNDER THE 1.70 CAP-LIMITED CAVITY, SO THE FLOOR IS UNIFORM 1.00. (A POCKET EXISTED FOR A 1.75 SOIC-8 THE V4 BOARD DOES NOT CARRY.) 8. FRONT SUPPORT LIP IS ASYMMETRIC (SECTION A-A): WEST 2.5 / NORTH 2.0 / SOUTH 2.0 FOR PCB RIGIDITY; EAST 1.0 CLEARING THE JP1/TP1 PADS, THE NFC COIL (A GROUNDED LIP WOULD DETUNE IT), AND C7 (x49.55, THE ONE EAST-EDGE PART LEFT AFTER V4 REMOVED THE Q1/U4/R7/R9 CLAMP CLUSTER + D9/D10/D11); WIDENING TO 2.5 ONLY AT THE SOUTH END (y0-10, CLEAR C7). 9. NO INTERNAL RIBS OR SUPPORT POSTS: THE RESIN BRACE (SEPARATE PART) CARRIES CENTER SUPPORT. A PCB LAYOUT CHANGE = A BRACE REPRINT, NOT A SHELL RE-MACHINE. 10. PCB RECESS = 0.60 DEEP (RECEIVES THE 0.60 mm BOARD; SLIP FIT, NOT A PRESS FIT). 3D STEP GOVERNS ALL GEOMETRY; STL NOT FOR CNC. 11. PART = BACK-SHELL ONLY. PCB, RESIN BRACE, AND 8x M2x3 BRASS SLOTTED-CHEESE SCREWS (HEAD Ø3.8) SUPPLIED SEPARATELY.		DWG solar-glow-drh-v3_0-backshell-0p6b-brace REV v3.0 MATERIAL Ti Gr5 (TC4) FINISH BEAD-BLAST UNITS mm SCALE AS NOTED BBOX 52.70 x 90.80 x 3.55 3rd-angle SHEET 1/1
---	--	---



SOLAR-GLOW DRH v3.0 — Ti BACK-SHELL (0.6mm-BOARD DUMB BOX)	
DWG solar-glow-drh-v3_0-backshell-0p6b-brace REV v3.0	
= boss + spotface bottom edges (Detail B). BREAK ALL OTHER EXPOSED EDGES 0.10x45°. CONCAVE JUNCTION CORNERS TO MATCH SURFACE.	
MATERIAL Ti Gr5 (TC4) FINISH BEAD-BLAST	
UNITS mm	SCALE AS NOTED
FOR V4 REMOVED THE Q1/U4/R7/R9 CLAMP CLUSTER + D9/D10/D11); WIDENING TO 2.5 ONLY AT THE SOUTH END (y0-10)	
BBOX 52.70 x 90.80 x 3.55 3rd-angle	SHEET 1/1