

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall Dimensions:**
 - Width: 52.70
 - Height: 83.16 ± 0.05 (corners)
- Internal Dimensions and Hole Locations:**
 - Distance from top edge to first hole center: 25.76
 - Distance between first and second hole centers: 31.64
 - Distance from second hole center to bottom edge: 25.76
 - Distance from left edge to first hole center: 3.82
 - Distance between first and last hole centers: 45.06 ± 0.05
 - Distance from last hole center to right edge: 3.82
- Features:**
 - Four circular holes, one in each corner.
 - Four circular holes, one on each long side.

8x M2 THREAD, THRU
 Ø1.6 TAP DRILL • TAP FROM RESTING FACE (BACK)
 Ø3 SPOTFACE, BACK (depth per Detail B)

SECTION A-A → edge profile DETAIL B → corner boss

OPEN FRAME — NO BACK FACE. THE PLAN ABOVE SHOWS THE FRAME FROM THE BACK; THE OPENING IS THE CAVITY VOID, CLEAN THROUGH (NO FLOOR, NO BORDER, NO FINs, NO MEDALLION).



C1	Frame depth (PCB-rest plane → resting plane; OPEN FRAME)	1.20 ±0.05
C2	PCB-rest plane flatness (lip + 8 bosses)	FLAT 0.05
C3	8× mounting holes (x 45.06; y rows 2.87/28.63/60.27/86.03)	±0.05 (linear)
C4	Mounting holes — tapped, thru, from back	M2 / Ø1.6 drill

1. MATERIAL: 316L STAINLESS (AUSTENITIC, MU_R-1.02 -- NOT CARBON/MARTENSITIC STEEL).
2. FINISH: BEAD-BLAST MATTE, ALL OVER. NO MARKING SERVICE — OPEN FRAME: NO BACK FACE, NO REAR ART.
3. GENERAL TOLERANCE PER ISO 2768-1 (MEDIUM). C1-C4 TOLERANCED AS LISTED; C1 & C3 = ± 0.05 . DATUMS: A = LEFT EDGE, B = BOTTOM EDGE, C = PCB-REST PLANE.
4. NO BRACE: AN OPEN FRAME HAS NO FLOOR TO RETAIN ONE (fit_rules.VARIANTS: brace_name=None). THE PCB REGISTERS IN THE 0.60 RECESS AND ON THE 8 BOSSES.
5. EDGE BREAKS - ALL 0.10x45°, FELT NOT SEEN, MODELED. CALLED OUT ON SEC A-A / DETAIL B: RIM = outer rim (top & bottom); MOUTH = recess mouth (around PCB); LIP = inner (cavity-side) lip edge; BOSS = boss + spotface bottom edges (Detail B).
6. NO FLOOR - OPEN FRAME. THE BACK OF EVERY B-SIDE COMPONENT FACES THE TABLE; THE FRAME'S RESTING PLANE (BOTTOM FACE) CARRIES THE ASSEMBLY.
DEPTH 1.20 = TALLEST B-SIDE PART 1.00 + 2x0.10 RESTING CLEARANCE (fit_rules.VARIANTS: resting-clearance-limited).
7. FRONT SUPPORT LIP IS ASYMMETRIC (SECTION A-A): WEST 2.5 / NORTH 2.0 / SOUTH 2.0 FOR PCB RIGIDITY; EAST 1.0 CLEARING THE JP1/TP1 PADS, THE NFC COIL (A GROUNDED LIP WOULD DETUNE IT), AND C7 (x49.55, THE ONE EAST-EDGE PART LEFT AF).
8. NO INTERNAL RIBS, SUPPORT POSTS, OR BRACE: OPEN FRAME. THE BOARD SPANS FREE BETWEEN THE LIP AND THE 8 BOSSES — HANDLE THE ASSEMBLY ACCORDINGLY.
9. PCB RECESS = 0.60 DEEP (RECEIVES THE 0.60 mm BOARD; SLIP FIT, NOT A PRESS FIT). 3D STEP GOVERNS ALL GEOMETRY; STL NOT FOR CNC.
10. PART = OPEN FRAME ONLY. PCB, AND 8x M2x1.6 BRASS SLOTTED-CHEESE SCREWS (HEAD Ø3.8) SUPPLIED SEPARATELY.

GENERAL TOLERANCES (UNLESS OTHERWISE NOTED, mm)	
LINEAR & HOLE-POSITION DIMS	ISO 2768-m
FRAME DEPTH C1 (SECTION A-A)	1.20 ±0.05
HOLE-PATTERN PITCH C3 (8 HOLES)	x 45.06 / y 25.76-31.64-25.76 ±0.05
PCB-REST FLATNESS C2	FLAT 0.05

SOLAR-GLOW DRH — AIR OPEN FRAME (316L, NO BACK FACE)	
DWG solar-glow-drh-frame-air-316L	REV air
BREAK ALL OTHER EXPOSED EDGES 0.10x45°. CONCAVE JUNCTION CORNERS LEFT SHARP IN THE MODEL; FINISH W/	
MATERIAL 316L stainless	FINISH BEAD-BLAST MATTE
RV4 REMOVED THE Q1/U4/R7/R9 CLAMP CLUSTER + D9/D10/D11); WIDENING TO 2.5 ONLY AT THE SOUTH END (y0-UNITS mm	SCALE AS NOTED
BBOX 52.70 x 90.80 x 1.80 3rd-angle	SHEET 1/1