

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall Dimensions:**
 - Width: 52.70
 - Height: 90.80
- Internal Dimensions and Hole Locations:**
 - Distance from top edge to first hole center: 25.76
 - Distance between first and second hole centers: 31.64
 - Distance from second hole center to bottom edge: 25.76
 - Distance from left edge to first hole center: 3.82
 - Distance between first and second hole centers: 45.06 ± 0.05
 - Distance from second hole center to right edge: 3.82
- Other Features:**
 - Four circular holes, one in each corner.
 - Four small circular features, one on each side, centered vertically.
 - Blue dimension lines and values (2.0) indicating specific offsets or radii.

8x M2 THREAD, THRU
Ø1.6 TAP DRILL • TAP FROM BACK FACE
Ø3 SPOTFACE, BACK (depth per Detail B)

SECTION A-A → edge profile DETAIL B → corner boss

THE 0.60 FLOOR CANNOT TAKE THE FIN VALLEYS (0.60 DEEP) OR THE MEDALLION FLOORS (~0.55-0.75) — PHYSICS-FORCED OFF in `fit_rules.VARIANTS`, NOT STYLING. BACK FACE = PLAIN RECESSED ART FIELD INSIDE THE 2.0 BORDER + 8 BOSS ANNULI, NOTHING ELSE.



PCB + M2x2 BRASS SCREW — REF, NOT THIS PART

M2 THREAD
Ø1.6 TAP DRILL, THRU
TAP FROM BACK

0.10x45° BOSS/SPOTFACE (typ)
spotface bottom = M2x2
screw-tip plane (flush)

Ø3 SPOTFACE (BACK)

Ø5.20

GENERAL TOLERANCES (UNLESS OTHERWISE NOTED, mm)	
LINEAR & HOLE-POSITION DIMS	ISO 2768-m
CAVITY DEPTH C1 (SECTION A-A)	1.22 ±0.05
HOLE-PATTERN PITCH C3 (8 HOLES)	x 45.06 / y 25.76-31.64-25.76 ±0.05
PCB-REST FLATNESS C2	FLAT 0.05

C1	Cavity depth (boss-top plane → cavity floor)	1.22 ±0.05
C2	PCB-rest plane flatness (lip + 8 bosses)	FLAT 0.05
C3	8× mounting holes (x 45.06; y rows 2.87/28.63/60.27/86.03)	±0.05 (linear)
C4	Mounting holes — tapped, thru, from back	M2 / Ø1.6 drill

1. MATERIAL: TITANIUM Gr5 (TC4) = Ti-6Al-4V GRADE 5. [Ti Gr5 (thinned floor; the 0.60 is the shop-minimum conversation)]	DWG solar-glow-drh-shell-lite-Ti REV lite
2. FINISH: BEAD-BLAST MATTE, ALL OVER. NO MARKING SERVICE. NO REAR ART — THE 0.60 FLOOR CANNOT TAKE THE FIN VALLEYS (0.60 DEEP) OR THE MEDALLION FLOORS (~0.55-0.75); BOTH PHYSICS-FORCED OFF (fit_rules.VARIANTS).	
3. GENERAL TOLERANCE PER ISO 2768-1 (MEDIUM). C1-C4 TOLERANCED AS LISTED; C1 & C3 = ±0.05. DATUMS: A = LEFT EDGE, B = BOTTOM EDGE, C = PCB-REST PLANE.	
4. BRACE REGISTRATION: THE RESIN H-BRACE REGISTERS TO THIS SHELL BY FITMENT - ITS 4 OUTBOARD RAILS + THE COMPONENT POCKETS + THE BOARD PRESS-FIT. NO LOCATOR PILLARS; THE CAVITY FLOOR IS A FULL 0.60 EVERYWHERE.	
5. EDGE BREAKS - ALL 0.10x45°, FELT NOT SEEN, MODELED. CALLED OUT ON SEC A-A / DETAIL B: RIM = outer rim (top & bottom); MOUTH = recess mouth (around PCB); LIP = inner (cavity-side) lip edge; FRAME = proud back-frame bottom edges; BOSS = boss + spotface bottom edges (Detail B). BREAK ALL OTHER EXPOSED EDGES 0.10x45°. CONCAVE JUNCTION CORNERS (BOSS	MATERIAL Ti Gr5 (TC4) FINISH BEAD-BLAST MATTE
6. FLOOR IS A TRUE 0.60, UNIFORM ACROSS THE CAVITY, BELOW THE ~1.0 TI MIN-WALL GUIDANCE - THE 0.60 IS THE SHOP-MINIMUM CONVERSATION (fit_rules.VARIANTS); CONFIRM THE SHOP HOLDS IT BEFORE QUOTING. CAVITY 1.22 ±0.05 -> 1.17 WORST-CASE, MINUS THIN CAP 1.00 MAX (PROVISIONAL — part_heights.SUPERCAP_H_THIN) = 0.17 NON-CONTACT; THE BRACE + SOLAR-CELL SANDWICHES CARRY THE BOARD.	
7. NO U7 RELIEF POCKET. U7 IS THE 0.90 mm MB85RC512TY DFN-8, WELL UNDER THE 1.22 CAVITY, SO THE FLOOR IS UNIFORM 0.60. (A POCKET EXISTED FOR A 1.75 SOIC-8 THE v4 BOARD DOES NOT CARRY.)	
8. FRONT SUPPORT LIP IS ASYMMETRIC (SECTION A-A): WEST 2.5 / NORTH 2.0 / SOUTH 2.0 FOR PCB RIGIDITY; EAST 1.0 CLEARING THE JP1/TP1 PADS, THE NFC COIL (A GROUNDED LIP WOULD DETUNE IT), AND C7 (x49.55, THE ONE EAST-EDGE PART LEFT AFTER v4 REMOVED THE Q1/U4/R7/R9 CLAMP CLUSTER + D9/D10/D11); WIDENING TO 2.5 ONLY AT THE SOUTH END (y0-10, CLEAR C	
9. NO INTERNAL RIBS OR SUPPORT POSTS: THE RESIN BRACE (SEPARATE PART) CARRIES CENTER SUPPORT. A PCB LAYOUT CHANGE = A BRACE REPRINT, NOT A SHELL RE-MACHINE.	UNITS: mm SCALE: AS NOTED
10. PCB RECESS = 0.60 DEEP (RECEIVES THE 0.60 mm BOARD; SLIP FIT, NOT A PRESS FIT). 3D STEP GOVERNS ALL GEOMETRY; STL NOT FOR CNC.	
11. PART = BACK-SHELL ONLY. PCB, RESIN BRACE, AND 8x M2x2 BRASS SLOTTED-CHEESE SCREWS (HEAD Ø3.8) SUPPLIED SEPARATELY.	
	BBOX 52.70 x 90.80 x 2.57 3rd-angle SHEET 1/1

DWG solar-glow-drh-shell-lite-Ti	REV lite
= boss + spotface bottom edges (Detail B). BREAK ALL OTHER EXPOSED EDGES 0.10x45°. CONCAVE JUNCTION CORNER R0.50. MATERIAL Ti Gr5 (TC4) FINISH BEAD-BLAST MATTE	
UNITS: mm	SCALE: AS NOTED
BBOX 52.70 x 90.80 x 2.57 3rd-angle	SHEET 1/1