

Technical drawing of a rectangular plate with the following dimensions and features:

- Overall width: 52.70
- Overall height: 90.80
- Inner width: 44.80 ± 0.05
- Inner height: 82.90 ± 0.05
- Corner features: 2x LOCATOR PILLAR $\varnothing 3.0 \times 0.6$ TALL (NOTE 4)
- Central feature: U2 RELIEF POCKET (NOTE 7)

C1	Cavity depth (boss-top plane → cavity floor)	1.85 ±0.05
C2	PCB-rest plane flatness (lip + 4 corner bosses)	FLAT 0.05
C3	4× mounting-hole pattern, pitch 44.80×82.90	±0.05 (linear)
C4	Mounting holes — tapped, thru, from back	M2 / Ø1.6 drill

1. MATERIAL: TITANIUM Gr5 (TC4) = Ti-6Al-4V GRADE 5.
2. FINISH: BEAD-BLAST MATTE (UNIFORM ON THE STEPPED BACK FACE). REAR ART LASER-MARKED IN THE RECESSED BACK FIELD.
3. GENERAL TOLERANCE PER ISO 2768-1 (MEDIUM). C1-C4 TOLERANCED AS LISTED; C1 & C3 = ± 0.05 . DATUMS: A = LEFT EDGE, B = BOTTOM EDGE, C = PCB-REST PLANE.
4. 2x LOCATOR PILLAR: $\varnothing 3.0 \times 0.6$ TALL, STANDING ON THE CAVITY FLOOR AT (13, 35) AND (33, 55) - BOTH WEST OF THE NFC COIL. LEFT AS ISLANDS IN THE SAME CAVITY PASS AS THE BOSSES. LOCATE THE RESIN BRACE (SEPARATE PART) VIA MATCHING $\varnothing 3.2$ RECESSES. FLOOR STAYS A FULL 0.95 (NO LOCATING HOLES). MODELED IN THE STEP.
5. BREAK ALL SHARP EDGES ~ 0.1 (Ti). OUTER TOP/BOTTOM RIM EASED $0.20 \times 45^\circ$ (MODELED).
6. THIN-WALL ADVISORY: FLOOR IS A UNIFORM 0.95 (0.90 LOCAL UNDER THE U2 POCKET), BELOW THE ~ 1.0 Ti MIN-WALL GUIDANCE BUT WELL ABOVE THE EARLIER 0.55/0.75. IF YOU CANNOT RELIABLY HOLD 0.95 TI OVER THIS $\sim 48 \times 86$ POCKET, ADVISE THE MIN FLOOR YOU WILL HOLD; PART RE-ISSUED TO THAT VALUE.
7. U2 RELIEF POCKET: 7.8×5.4 CENTERED (28.5, 37) ON THE CAVITY FLOOR, 0.05 DEEP (LOCAL FLOOR 0.90) - CLEARANCE FOR U2 (1.75). GENERAL FLOOR 0.95. MODELED IN THE STEP.
8. PERIMETER LIP / BACK-FRAME = 1.00 (NARROWED FROM 1.50 TO CLEAR THE JP1/TP1 EDGE PADS AT $x47.55-49.25$). SHELL CONTACTS LAND ON BARE LAMINATE / GND POUR; NO KAPTON.
9. NO INTERNAL RIBS OR SUPPORT POSTS: THE RESIN BRACE (SEPARATE PART) CARRIES CENTER SUPPORT. A PCB LAYOUT CHANGE = A BRACE REPRINT, NOT A SHELL RE-MACHINE.
10. PCB RECESS = 0.60 DEEP (RECEIVES THE 0.60 mm BOARD; SLIP FIT, NOT A PRESS FIT). 3D STEP GOVERNS ALL GEOMETRY; STL NOT FOR CNC.
11. PART = BACK-SHELL ONLY PCB, RESIN BRACE, AND $4 \times M2 \times 3$ BRASS SLOTTED-CHEESE SCREWS (HEAD $\varnothing 3.8$) SUPPLIED SEPARATELY.

SECTION A-A → edge profile DETAIL B → corner boss



SOLAR-GLOW DRH v3.0 — Ti BACK-SHELL (0.6mm-BOARD DUMB BOX)	
DWG solar-glow-drh-v3_0-backshell-0p6b-brace	
REV v3.0	
MATERIAL Ti Gr5 (TC4)	
FINISH BEAD-BLAST	
UNITS mm	SCALE AS NOTED
BBOX 52.70 x 90.80 x 3.55 3rd-angle	SHEET 1/1