Notes for Figure 6H-19—Typical Application 19 Detour for One Travel Direction

Guidance:

- 1. This plan should be used for streets without posted route numbers.
- 2. On multi-lane streets, Detour signs with an Advance Turn Arrow should be used in advance of a turn. Option:
 - 3. The STREET CLOSED legend may be used in place of ROAD CLOSED.
 - 4. Additional DO NOT ENTER signs may be used at intersections with intervening streets.
 - 5. Warning lights may be used on Type 3 Barricades.
 - 6. Detour signs may be located on the far side of intersections.
 - 7. A Street Name sign may be mounted with the Detour sign. The Street Name sign may be either white on green or black on orange.

Standard:

8. When used, the Street Name sign shall be placed above the Detour sign.

Guidance.

9. The DETOUR (M4-8) sign should be placed on tangent sections at intervals not to exceed 1300 feet and at major intersections.

Option:

10. In urban areas, the M4-8 signs may be placed at every intersection.

W20-3 **AHEAD** D3-1 M4-9 **AHEAD** W20-1 MOKK M4-10 CLOSED **GA09 CFOSED QA09** 12 nisM M3-3 **AHEAD** D3-1 **DETOUR R5-1** ROAD WORK AHEAD W20-1 **R6-1** DETOUR 12 nisM D3-1 M4-9 D3-1 100 ft **ROAD WORK** W20-1 **AHEAD DETOUR** M4-8a Note: See Tables 6H-2 and 6H-3 **END** for the meaning of the symbols and/or letter **Typical Application 19** codes used in this figure.

Figure 6H-19. Detour for One Travel Direction (TA-19)