Whish Web Service

Technical Specifications

Version Control

Version	Author	Date	Comment
1.0	TecFrac	2022-11-08	Initial Release
1.1	TecFrac	2025-05-12	Adding test cases and request content-type requirements.
1.2	TecFrac	2025-09-17	Get Status Endpoint update to include payerPhoneNumber in the response payload.
1.3	TecFrac	2025-10-03	Sandbox Base URL update.
1.3.1	TecFrac	2025-12-11	Production Base URL update.
1.4	TecFrac	2025-12-23	User-Agent Requirement addition and additional field descriptions and notes.
1.4.1	TecFrac	2026-02-03	Get Balance now supports LBP and USD.
1.4.2	TecFrac	2026-02-09	Get Rate removed with minor adjustment.

Disclaimer

The information in this document is provided for Whish clients and business partners. Whish retains the right to make changes to this specification at any time. Web service requests, responses, and error codes are subject to change. This document is provided for informational purposes only. The content of this document is the sole property of Whish.

Table of Contents

Version Control 2

Overview 4

Environments 4

Production 4

Sandbox 4

Communication Requirements 4

Request Headers 4

Response Structure 4

Get Balance 5

Post Payment 6

Get Status 8

Overview

The Whish API is a REST based service accessible over HTTPS. It supports JSON formatted requests and responses and is intended to be consumed by authorized distributors.

Environments

Production

URL: https://api.whish.money/itel-service/api

Sandbox

URL: https://api.sandbox.whish.money/itel-service/api

Communication Requirements

Protocol and Format

- The distributor must be capable of producing and consuming JSON over HTTPS.
- All requests and responses use the application/json format.

Request Headers

All requests sent to Whish services must include the following HTTP headers.

Header Name	Description
channel	Value provided by Whish
secret	Value provided by Whish
websiteUrl	URL of the third party website or application name where the API is integrated
User-Agent	Identifies the consuming website or application

User-Agent format: "`Whish/1.0 (https://whish.money; support@whish.money)`"

Response Structure

All API responses follow a unified structure with the attributes listed below.

Attribute	Description
status	Boolean value indicating success or failure
code	Operation-specific failure code
dialog	Contains an optional title and message to be displayed to the user
data	Contains the response payload based on the executed operation

Notes

- Missing or invalid headers may result in request rejection.
- The User-Agent header is required for monitoring, analytics, and support purposes.

Get Balance

This method returns the real balance of the account.

You can specify the currency (LBP or USD) using “?currency=LBP” or “?currency=USD”.

Voided items are items which are sold and not used for some reason, so they are put on hold for later usages.

URI

LBP: GET /payment/account/balance?currency=LBP

USD: GET /payment/account/balance?currency=USD

Request

No request body attributes are needed; just include the required headers and specify the currency (LBP or USD) in the query.

Response Data

Field	Description	Type
balanceDetails		Complex Type
balance	The real balance of the account.	Double

Response Example

Successful Response:

USD:

```
{
   "status": true,
   "code": null,
   "dialog": null,
   "actions": null,
   "extra": null,
   "data": {
      "balance": 10439.0
   }
}
```

LBP:

```
{
   "status": true,
   "code": null,
   "dialog": null,
   "actions": null,
   "extra": null,
   "data": {
      "balance": 943975.0
   }
}
```

Post Payment

This method returns the URL, where the client will be redirected to pay for the merchant through WHISH Balance.

URI

POST /payment/whish

Request

Besides the header attributes which are mandatory in all requests, following are the attributes needed to be attached in the requests body:

Field	Description	Type
amount	Amount to be paid by client	Double
currency	The amount's currency. Supported currencies: LBP/USD	String
invoice	Details/Description about the payment	String
externalId	ID provided by third party	Long
successCallbackUrl	GET Callback URL provided by third party for successful transaction	String
failureCallbackUrl	GET Callback URL provided by third party for failed transaction	String
successRedirectUrl	GET Redirect URL provided by third party for successful transaction	String
failureRedirectUrl	GET Redirect URL provided by third party for failed transaction	String

Test Cases:

- Success: Use the phone number 96170902894 on the payment page with the OTP 111111.
- Failure: Use any phone number with an OTP other than 111111.

Notes

- The callback and redirect URLs are fully specified by the third party integrating with Whish.

- Callback URLs are triggered by Whish using a GET request to notify the third party of the transaction result.
- Redirect URLs are used to redirect the client after the payment flow is completed.
- The third party may append any custom query parameters to the callback or redirect URLs, such as a unique identifier, timestamp, order reference, or any other tracking information.
- Whish will call or redirect to the provided URLs as received, without altering the query parameters.
- externalId must be a numeric value generated by the third party and must be unique per request, serving as the reference identifier for the transaction.
- No OTP is delivered in sandbox environment.

Request Sample:

```
{
"amount": "1",
"currency": "USD",
"invoice": "Order #1",
"externalId": 1,
"successCallbackUrl": "https://example.com/api/payment/success",
"failureCallbackUrl": "https://example.com/api/payment/failure",
"successRedirectUrl": "https://example.com/thank-you",
"failureRedirectUrl": "https://example.com/payment-error"
}
```

Response Data

Field	Description	Type
collectUrl	The payment page URL	String

Response Example

Successful Response:

```
{
   "status":true,
   "code":null,
   "dialog":null,
   "extra":null,
   "data":{
      "collectUrl": “https://whish.money/pay/8nQS2mL”
   }
}
```

Get Status

This method returns the collect status of Whish Pay transactions.

URI

POST /payment/collect/status

Request

Besides the header attributes which are mandatory in all requests, following are the attributes needed to be attached in the requests body:

Field	Description	Type
currency	The amount currency. Supported currencies: “LBP, “USD”	String
externalId	ID provided by third party	Long

Response Data

Field	Description	Type
collectStatus	The collect status (success, failed, pending)	String

payerPhoneNumber	The phone number that performed the payment	Long

Response Example

Successful Response:

```
{
   "status":true,
   "code":null,
   "dialog":null,
   "extra":null,
   "data":{
      " collectStatus": “success”,
      " payerPhoneNumber": “96170902894”
   }
}
```