

# **OpenAPI Specification**

## **USER MANUAL**

**© 2016 Enter your company name**

**Enter your company name**

This page is intentionally left blank.  
Remove this text from the manual  
template if you want it completely blank.

<b>1. Annotated Introduction</b>	<b>5</b>
<b>2. SwaggerUI</b>	<b>7</b>
2.1     Swagger Header .....	8
<b>3. Swashbuckle Code</b>	<b>9</b>
3.1     Swashbuckle Header .....	10
<b>4. Specification</b>	<b>11</b>
4.1     Title Page .....	12
4.2     Introductions .....	12
4.3     Revision History .....	12
4.4     Definitions .....	12
4.5     Format .....	13
4.6     File Structure .....	14
4.7     Data Types .....	14
4.8     Schema .....	15
4.8.1     Swagger Object .....	15
4.8.2     Info Object .....	17
4.8.3     Contact Object .....	18
4.8.4     License Object .....	19
4.8.5     Paths Object .....	20
4.8.6     Path Item Object .....	21
4.8.7     Operation Object .....	25
4.8.8     External Documentation Object .....	31
4.8.9     Parameter Object .....	32
4.8.10     Items Object .....	40
4.8.11     Responses Object .....	42
4.8.12     Response Object .....	44
4.8.13     Headers Object .....	47
4.8.14     Header Object .....	48
4.8.15     Example Object .....	51
4.8.16     Tag Object .....	51
4.8.17     Reference Object .....	52
4.8.18     Schema Object .....	53
4.8.19     XML Object .....	65
4.8.20     Definitions Object .....	73
4.8.21     Parameters Definitions Object .....	75
4.8.22     Responses Definitions Object .....	76

# Table of Contents

4

4.8.23	Security Definitions Object .....	77
4.8.24	Security Scheme Object .....	79
4.8.25	Scopes Object .....	81
4.8.26	Security Requirement Object .....	82
<b>4.9</b>	<b>Security Filtering .....</b>	<b>83</b>
<b>4.10</b>	<b>Vendor Extensions .....</b>	<b>83</b>
<b>5.</b>	<b>Pet Store JSON</b>	<b>85</b>
<b>Index</b>		<b>0</b>

# **Annotated Introduction**

## 1 Annotated Introduction

Swashbuckle

Swagger

.NET Core

[Official OpenAPI Specification](#)

[Swagger Home Page](#)

# SwaggerUI

## 2 SwaggerUI

Enter topic text here.

### 2.1 Swagger Header

The screenshot shows the Swagger UI homepage for the Petstore API. At the top, there is a green header bar with the Swagger logo, the URL <http://petstore.swagger.io/v2/swagger.json>, and two buttons: "Authorize" and "Explore". Below the header, the title "Swagger Petstore" is displayed, with a purple arrow pointing from the text "info.title (code)" to it. A descriptive text follows, mentioning it's a sample server Petstore server and providing links to Swagger documentation and developer contact information. Another purple arrow points from the text "info.description (code)" to the descriptive text. Below this, sections for "pet", "store", and "user" are listed, each with "Show/Hide", "List Operations", and "Expand Operations" buttons. At the bottom left, the base URL "[ BASE URL: /v2 , API VERSION: 1.0.0 ]" is shown, and at the bottom right, there are "VALID" and a three-dot menu button.

# **Swashbuckle Code**

## 3 Swashbuckle Code

Enter topic text here.

### 3.1 Swashbuckle Header

```
services.AddSwaggerGen(c =>
{
    c.SingleApiVersion(new Info
    {
        Version = "v1",
        Title = "Swagger Petstore",
        Description = "This is a sample server Petstore server. You can find out more about Swagger <u>here</u> at [http://swagger.io](http://swagger.io) or on [irc.freenode.net, #swagger] <u>(http://swagger.io/irc/)</u>. For this sample, you can use the api key 'special-key' <u>here</u> to test the authorization filters.\n\nFind out more about Swagger",
        TermsOfService = "http://swagger.io/terms/",
        Contact = new Contact()
        {
            Email = "mailto:apiteam@swagger.io?subject=Swagger",
            Name = "Swagger",
            Url = "http://swagger.io",
        },
        License = new License()
        {
            Name = "Apache 2.0",
            Url = "http://www.apache.org/licenses/LICENSE-2.0.html",
        },
    });
});
```

# **Specification**

## 4 Specification

### 4.1 Title Page

Version 2.0

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#).

The Swagger specification is licensed under [The Apache License, Version 2.0](#).

### 4.2 Introductions

Swagger™ is a project used to describe and document RESTful APIs.

The Swagger specification defines a set of files required to describe such an API. These files can then be used by the Swagger-UI project to display the API and Swagger-Codegen to generate clients in various languages. Additional utilities can also take advantage of the resulting files, such as testing tools.

### 4.3 Revision History

Version	Date	Notes
2.0	2014-09-08	Release of Swagger 2.0
1.2	2014-03-14	Initial release of the formal document.
1.1	2012-08-22	Release of Swagger 1.1
1.0	2011-08-10	First release of the Swagger Specification

### 4.4 Definitions

#### Path Templating

Path templating refers to the usage of curly braces ({} ) to mark a section of a URL path as replaceable using path parameters.

#### Mime Types

Mime type definitions are spread across several resources. The mime type definitions should be in compliance with [RFC 6838](#).

Some examples of possible mime type definitions:

```
text/plain; charset=utf-8  
application/json  
application/vnd.github+json  
application/vnd.github.v3+json  
application/vnd.github.v3.raw+json  
application/vnd.github.v3.text+json  
application/vnd.github.v3.html+json  
application/vnd.github.v3.full+json  
application/vnd.github.v3.diff  
application/vnd.github.v3.patch
```

## HTTP Status Codes

The HTTP Status Codes are used to indicate the status of the executed operation. The available status codes are described by [RFC 7231](#) and in the [IANA Status Code Registry](#).

## 4.5 Format

The files describing the RESTful API in accordance with the Swagger specification are represented as JSON objects and conform to the JSON standards. YAML, being a superset of JSON, can be used as well to represent a Swagger specification file.

For example, if a field is said to have an array value, the JSON array representation will be used:

```
{  
  "field" : [...]  
}
```

While the API is described using JSON it does not impose a JSON input/output to the API itself.

All field names in the specification are **case sensitive**.

The schema exposes two types of fields. Fixed fields, which have a declared name, and Patterned fields, which declare a regex pattern for the field name. Patterned fields can have multiple occurrences as long as each has a unique name.

## 4.6 File Structure

The Swagger representation of the API is made of a single file. However, parts of the definitions can be split into separate files, at the discretion of the user. This is applicable for \$ref fields in the specification as follows from the [JSON Schema](#) definitions.

By convention, the Swagger specification file is named **swagger.json**.

## 4.7 Data Types

Primitive data types in the Swagger Specification are based on the types supported by the [JSON-Schema Draft 4](#). Models are described using the [Schema Object](#)  which is a subset of JSON Schema Draft 4.

An additional primitive data type "file" is used by the [Parameter Object](#)  and the [Response Object](#)  to set the parameter type or the response as being a file.

Primitives have an optional modifier property format. Swagger uses several known formats to more finely define the data type being used. However, the format property is an open string-valued property, and can have any value to support documentation needs. Formats such as "email", "uuid", etc., can be used even though they are not defined by this specification. Types that are not accompanied by a format property follow their definition from the JSON Schema (except for file type which is defined above). The formats defined by the Swagger Specification are:

Common Name	<a href="#">type</a> 	<a href="#">format</a> 	Comments
integer	integer	int32	signed 32 bits
long	integer	int64	signed 64 bits
float	number	float	
double	number	double	
string	string		
byte	string	byte	base64 encoded characters
binary	string	binary	any sequence of octets
boolean	boolean		
date	string	date	As defined by full-date - <a href="#">RFC3339</a>
dateTime	string	date-time	As defined by date-time - <a href="#">RFC3339</a>
password	string	password	Used to hint UIs the input needs to be obscured.

## 4.8 Schema

### 4.8.1 Swagger Object

This is the root document object for the API specification. It combines what previously was the Resource Listing and API Declaration (version 1.2 and earlier) together into one document.

#### Fixed Fields

Field Name	Type	Description
swagger	string	<b>Required.</b> Specifies the Swagger Specification version being used. It can be used by the Swagger UI and other clients to interpret the API listing. The value MUST be "2.0".
info	<a href="#">Info Object</a> <small>17</small>	<b>Required.</b> Provides metadata about the API. The metadata can be used by the clients if needed.
host	string	The host (name or ip) serving the API. This MUST be the host only and does not include the scheme nor sub-paths. It MAY include a port. If the host is not included, the host serving the documentation is to be used (including the port). The host does not support <a href="#">path templating</a> <small>12</small> .
basePath	string	The base path on which the API is served, which is relative to the <a href="#">host</a> <small>15</small> . If it is not included, the API is served directly under the host. The value MUST start with a leading slash (/). The basePath does not support <a href="#">path templating</a> <small>12</small> .
schemes	[string]	The transfer protocol of the API. Values MUST be from the list: "http", "https", "ws", "wss". If the schemes is not included, the default scheme to be used is the one used to access the Swagger definition itself.
consumes	[string]	A list of MIME types the APIs can consume. This is global to all APIs but can be overridden on specific

Field Name	Type	Description
		API calls. Value MUST be as described under <a href="#">Mime Types</a> <small>[12]</small> .
produces	[string]	A list of MIME types the APIs can produce. This is global to all APIs but can be overridden on specific API calls. Value MUST be as described under <a href="#">Mime Types</a> <small>[12]</small> .
paths	<a href="#">Paths Object</a> <small>[20]</small>	<b>Required.</b> The available paths and operations for the API.
definitions	<a href="#">Definitions Object</a> <small>[73]</small>	An object to hold data types produced and consumed by operations.
parameters	<a href="#">Parameters Definitions Object</a> <small>[75]</small>	An object to hold parameters that can be used across operations. This property <i>does not</i> define global parameters for all operations.
responses	<a href="#">Responses Definitions Object</a> <small>[76]</small>	An object to hold responses that can be used across operations. This property <i>does not</i> define global responses for all operations.
securityDefinitions	<a href="#">Security Definitions Object</a> <small>[77]</small>	Security scheme definitions that can be used across the specification.
security	<a href="#">[Security Requirement Object]</a> <small>[82]</small>	A declaration of which security schemes are applied for the API as a whole. The list of values describes alternative security schemes that can be used (that is, there is a logical OR between the security requirements). Individual operations can override this definition.
tags	<a href="#">[Tag Object]</a> <small>[51]</small>	A list of tags used by the specification with additional metadata. The order of the tags can be used to reflect on their order by the parsing tools. Not all tags that are used by the <a href="#">Operation Object</a> <small>[25]</small> must be declared. The tags that are not declared may be organized randomly or based on the tools' logic. Each tag name in the list MUST be unique.
externalDocs	<a href="#">External Documentation Object</a> <small>[31]</small>	Additional external documentation.

## Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

### 4.8.2 Info Object

#### Info Object

The object provides metadata about the API. The metadata can be used by the clients if needed, and can be presented in the Swagger-UI for convenience.

Field Name	Type	Description
<code>title</code>	<code>string</code>	<b>Required.</b> The title of the application.
<code>description</code>	<code>string</code>	A short description of the application. <a href="#">GFM syntax</a> can be used for rich text representation.
<code>termsOfService</code>	<code>string</code>	The Terms of Service for the API.
<code>contact</code>	<a href="#">Contact Object</a> <small>18</small>	The contact information for the exposed API.
<code>license</code>	<a href="#">License Object</a> <small>19</small>	The license information for the exposed API.
<code>version</code>	<code>string</code>	<b>Required</b> Provides the version of the application API (not to be confused with the specification version).

#### Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

#### Info Object Example:

```
{  
    "title": "Swagger Sample App",  
    "description": "This is a sample server Petstore server.",  
    "termsOfService": "http://swagger.io/terms/",  
    "contact": {  
        "name": "API Support",  
        "url": "http://www.swagger.io/support",  
        "email": "support@swagger.io"  
    },  
    "license": {  
        "name": "Apache 2.0",  
        "url": "http://www.apache.org/licenses/LICENSE-2.0.html"  
    },  
    "version": "1.0.1"  
}
```

```
title: Swagger Sample App  
description: This is a sample server Petstore server.  
termsOfService: http://swagger.io/terms/  
contact:  
    name: API Support  
    url: http://www.swagger.io/support  
    email: support@swagger.io  
license:  
    name: Apache 2.0  
    url: http://www.apache.org/licenses/LICENSE-2.0.html  
version: 1.0.1
```

### 4.8.3 Contact Object

Contact information for the exposed API.

#### Fixed Fields

Field Name	Type	Description
name	string	The identifying name of the contact person/organization.
url	string	The URL pointing to the contact information. MUST be in the format of a URL.
email	string	The email address of the contact person/organization. MUST be in the format of an email

Field Name	Type	Description
		address.

## Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> 83 for further details.

## Contact Object Example:

```
{
  "name": "API Support",
  "url": "http://www.swagger.io/support",
  "email": "support@swagger.io"
}
```

```
name: API Support
url: http://www.swagger.io/support
email: support@swagger.io
```

## 4.8.4 License Object

License information for the exposed API.

## Fixed Fields

Field Name	Type	Description
name	string	<b>Required.</b> The license name used for the API.
url	string	A URL to the license used for the API. MUST be in the format of a URL.

## Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See

Field Pattern	Type	Description
		<a href="#">Vendor Extensions</a> <small>83</small> for further details.

### License Object Example:

```
{
  "name": "Apache 2.0",
  "url": "http://www.apache.org/licenses/LICENSE-2.0.html"
}
```

```
name: Apache 2.0
url: http://www.apache.org/licenses/LICENSE-2.0.html
```

#### 4.8.5 Paths Object

Holds the relative paths to the individual endpoints. The path is appended to the [basePath](#) 15 in order to construct the full URL.

The Paths may be empty, due to [ACL constraints](#) 83.

### Patterned Fields

Field Pattern	Type	Description
{path}	<a href="#">Path Item Object</a> <small>21</small>	A relative path to an individual endpoint. The field name MUST begin with a slash. The path is appended to the <a href="#">basePath</a> <small>15</small> in order to construct the full URL. <a href="#">Path templating</a> <small>12</small> is allowed.
^x-	Any	Allows extensions to the Swagger Schema. The field name MUST begin with x-, for example, x-internal-id. The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

### Paths Object Example

```
{  
  "/pets": {  
    "get": {  
      "description": "Returns all pets from the system that the user has access to",  
      "produces": [  
        "application/json"  
      ],  
      "responses": {  
        "200": {  
          "description": "A list of pets.",  
          "schema": {  
            "type": "array",  
            "items": {  
              "$ref": "#/definitions/pet"  
            }  
          }  
        }  
      }  
    }  
  }  
}
```

```
/pets:  
  get:  
    description: Returns all pets from the system that the user has access to  
    produces:  
    - application/json  
    responses:  
      '200':  
        description: A list of pets.  
        schema:  
          type: array  
          items:  
            $ref: '#/definitions/pet'
```

#### 4.8.6 Path Item Object

Describes the operations available on a single path.

A Path Item may be empty, due to [ACL constraints](#)<sup>83</sup>. The path itself is still exposed to the documentation viewer but they will not know which operations and parameters are available.

## Fixed Fields

Field Name	Type	Description
\$ref	string	Allows for an external definition of this path item. The referenced structure MUST be in the format of a <a href="#">Path Item Object</a> <sup>21</sup> . If there are conflicts between the referenced definition and this Path Item's definition, the behavior is <i>undefined</i> .
get	<a href="#">Operation Object</a> <sup>25</sup>	A definition of a GET operation on this path.
put	<a href="#">Operation Object</a> <sup>25</sup>	A definition of a PUT operation on this path.
post	<a href="#">Operation Object</a> <sup>25</sup>	A definition of a POST operation on this path.
delete	<a href="#">Operation Object</a> <sup>25</sup>	A definition of a DELETE operation on this path.
options	<a href="#">Operation Object</a> <sup>25</sup>	A definition of a OPTIONS operation on this path.
head	<a href="#">Operation Object</a> <sup>25</sup>	A definition of a HEAD operation on this path.
patch	<a href="#">Operation Object</a> <sup>25</sup>	A definition of a PATCH operation on this path.
parameters	[ <a href="#">Parameter Object</a> <sup>32</sup>   <a href="#">Reference Object</a> <sup>52</sup> ]	A list of parameters that are applicable for all the operations described under this path. These parameters can be overridden at the operation level, but cannot be removed there. The list MUST NOT include duplicated parameters. A unique parameter is defined by a combination of a <a href="#">name</a> <sup>32</sup> and <a href="#">location</a> <sup>33</sup> . The list can use the <a href="#">Reference Object</a> <sup>52</sup> to link to parameters that are defined at the <a href="#">Swagger Object's parameters</a> <sup>18</sup> . There can be one "body" parameter at most.

## Patterned Fields

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>[83]</small> for further details.

## Path Item Object Example

```
{  
  "get": {  
    "description": "Returns pets based on ID",  
    "summary": "Find pets by ID",  
    "operationId": "getPetsById",  
    "produces": [  
      "application/json",  
      "text/html"  
    ],  
    "responses": {  
      "200": {  
        "description": "pet response",  
        "schema": {  
          "type": "array",  
          "items": {  
            "$ref": "#/definitions/Pet"  
          }  
        }  
      },  
      "default": {  
        "description": "error payload",  
        "schema": {  
          "$ref": "#/definitions/ErrorModel"  
        }  
      }  
    },  
    "parameters": [  
      {  
        "name": "id",  
        "in": "path",  
        "description": "ID of pet to use",  
        "required": true,  
        "type": "array",  
        "items": {  
          "type": "string"  
        },  
        "collectionFormat": "csv"  
      }  
    ]  
  }  
}
```

```
get:
  description: Returns pets based on ID
  summary: Find pets by ID
  operationId: getPetById
  produces:
    - application/json
    - text/html
  responses:
    '200':
      description: pet response
      schema:
        type: array
        items:
          $ref: '#/definitions/Pet'
    default:
      description: error payload
      schema:
        $ref: '#/definitions/ErrorModel'
  parameters:
    - name: id
      in: path
      description: ID of pet to use
      required: true
      type: array
      items:
        type: string
  collectionFormat: csv
```

#### 4.8.7 Operation Object

Describes a single API operation on a path.

##### Fixed Fields

Field Name	Type	Description
tags	[string]	A list of tags for API documentation control. Tags can be used for logical grouping of operations by resources or any other qualifier.

Field Name	Type	Description
summary	string	A short summary of what the operation does. For maximum readability in the swagger-ui, this field SHOULD be less than 120 characters.
description	string	A verbose explanation of the operation behavior. <a href="#">GFM syntax</a> can be used for rich text representation.
externalDocs	<a href="#">External Documentation Object</a> <small>[31]</small>	Additional external documentation for this operation.
operationId	string	Unique string used to identify the operation. The id MUST be unique among all operations described in the API. Tools and libraries MAY use the operationId to uniquely identify an operation, therefore, it is recommended to follow common programming naming conventions.
consumes	[string]	A list of MIME types the operation can consume. This overrides the <a href="#">consumes</a> <small>[15]</small> definition at the Swagger Object. An empty value MAY be used to clear the global definition. Value MUST be as described under <a href="#">Mime Types</a> <small>[12]</small> .
produces	[string]	A list of MIME types the operation can produce. This overrides the <a href="#">produces</a> <small>[16]</small> definition at the Swagger Object. An empty value MAY be used to clear the global definition. Value MUST be as described under <a href="#">Mime Types</a> <small>[12]</small> .
parameters	<a href="#">Parameter Object</a> <small>[32]</small>   <a href="#">Reference Object</a> <small>[52]</small>	A list of parameters that are applicable for this operation. If a parameter is already defined at the <a href="#">Path Item</a> <small>[22]</small> , the new definition will override it, but can never remove it. The list MUST NOT include duplicated parameters. A unique parameter is defined by a combination of a <a href="#">name</a> <small>[32]</small> and <a href="#">location</a> <small>[33]</small> . The list can use the <a href="#">Reference Object</a> <small>[52]</small> to link to parameters that are defined at the <a href="#">Swagger Object's parameters</a>

Field Name	Type	Description
		<small>16</small> . There can be one "body" parameter at most.
responses	<a href="#">Responses Object</a> <small>42</small>	<b>Required.</b> The list of possible responses as they are returned from executing this operation.
schemes	[string]	The transfer protocol for the operation. Values MUST be from the list: "http", "https", "ws", "wss". The value overrides the Swagger Object <a href="#">schemas</a> <small>15</small> definition.
deprecated	boolean	Declares this operation to be deprecated. Usage of the declared operation should be refrained. Default value is false.
security	[Security Requirement Object] <small>82</small>	A declaration of which security schemes are applied for this operation. The list of values describes alternative security schemes that can be used (that is, there is a logical OR between the security requirements). This definition overrides any declared top-level <a href="#">security</a> <small>16</small> . To remove a top-level security declaration, an empty array can be used.

#### Patterned Objects

Field Pattern	Type	Description
<small>^x-</small>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with x-, for example, x-internal-id. The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

## Operation Object Example

```
{  
  "tags": [  
    "pet"  
,  
  ],  
  "summary": "Updates a pet in the store with form data",  
  "description": "",  
  "operationId": "updatePetWithForm",  
  "consumes": [  
    "application/x-www-form-urlencoded"  
,  
  ],  
  "produces": [  
    "application/json",  
    "application/xml"  
,  
  ],  
  "parameters": [  
    {  
      "name": "petId",  
      "in": "path",  
      "description": "ID of pet that needs to be updated",  
      "required": true,  
      "type": "string"  
,  
    },  
    {  
      "name": "name",  
      "in": "formData",  
      "description": "Updated name of the pet",  
      "required": false,  
      "type": "string"  
,  
    },  
    {  
      "name": "status",  
      "in": "formData",  
      "description": "Updated status of the pet",  
      "required": false,  
      "type": "string"  
,  
    }  
  ]  
}
```

```
],
"responses": {
  "200": {
    "description": "Pet updated."
  },
  "405": {
    "description": "Invalid input"
  }
},
"security": [
  {
    "petstore_auth": [
      "write:pets",
      "read:pets"
    ]
  }
]
```

```
tags:
- pet

summary: Updates a pet in the store with form data
description: ""
operationId: updatePetWithForm
consumes:
- application/x-www-form-urlencoded
produces:
- application/json
- application/xml
parameters:
- name: petId
  in: path
  description: ID of pet that needs to be updated
  required: true
  type: string
- name: name
  in: formData
  description: Updated name of the pet
  required: false
  type: string
- name: status
  in: formData
  description: Updated status of the pet
  required: false
  type: string
responses:
'200':
  description: Pet updated.
'405':
  description: Invalid input
security:
- petstore_auth:
  - write:pets
  - read:pets
```

#### 4.8.8 External Documentation Object

Allows referencing an external resource for extended documentation.

#### Fixed Fields

Field Name	Type	Description
description	string	A short description of the target documentation. <a href="#">GFM syntax</a> can be used for rich text representation.
url	string	<b>Required.</b> The URL for the target documentation. Value MUST be in the format of a URL.

#### Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

#### External Documentation Object Example

```
{  
  "description": "Find more info here",  
  "url": "https://swagger.io"  
}
```

```
description: Find more info here  
url: https://swagger.io
```

#### 4.8.9 Parameter Object

Describes a single operation parameter.

A unique parameter is defined by a combination of a [name](#)<sup>32</sup> and [location](#)<sup>33</sup>.

**There are five possible parameter types.**

- Path - Used together with [Path Templating](#)<sup>12</sup>, where the parameter value is actually part of the operation's URL. This does not include the host or base path of the API. For example, in /items/{itemId}, the path parameter is itemId.
- Query - Parameters that are appended to the URL. For example, in /items?id=###, the query parameter is id.
- Header - Custom headers that are expected as part of the request.
- Body - The payload that's appended to the HTTP request. Since there can only be one payload, there can only be one body parameter. The name of the body parameter has no effect on the parameter itself and is used for documentation purposes only. Since Form parameters are also in the payload, body and form parameters cannot exist together for the same operation.
- Form - Used to describe the payload of an HTTP request when either application/x-www-form-urlencoded, multipart/form-data or both are used as the content type of the request (in Swagger's definition, the [consumes](#)<sup>15</sup> property of an operation). This is the only parameter type that can be used to send files, thus supporting the file type. Since form parameters are sent in the payload, they cannot be declared together with a body parameter for the same operation. Form parameters have a different format based on the content-type used (for further details, consult <http://www.w3.org/TR/html401/interact/forms.html#h-17.13.4>):
  - application/x-www-form-urlencoded - Similar to the format of Query parameters but as a payload. For example, foo=1&bar=swagger - both foo and bar are form parameters. This is normally used for simple parameters that are being transferred.
  - multipart/form-data - each parameter takes a section in the payload with an internal header. For example, for the header Content-Disposition: form-data; name="submit-name" the name of the parameter is submit-name. This type of form parameters is more commonly used for file transfers.

#### Fixed Fields

Field Name	Type	Description
name	string	<p><b>Required.</b> The name of the parameter. Parameter names are <i>case sensitive</i>.</p> <ul style="list-style-type: none"> <li>• If <a href="#">in</a><sup>33</sup> is "path", the name field MUST correspond to the associated path segment from</li> </ul>

Field Name	Type	Description
		<p>the <a href="#">path</a> <sup>20</sup> field in the <a href="#">Paths Object</a> <sup>20</sup>. See <a href="#">Path Templating</a> <sup>12</sup> for further information.</p> <ul style="list-style-type: none"> <li>For all other cases, the name corresponds to the parameter name used based on the <a href="#">in</a> <sup>33</sup> property.</li> </ul>
in	string	<b>Required.</b> The location of the parameter. Possible values are "query", "header", "path", "formData" or "body".
description	string	A brief description of the parameter. This could contain examples of use. <a href="#">GFM syntax</a> can be used for rich text representation.
required	boolean	Determines whether this parameter is mandatory. If the parameter is <a href="#">in</a> <sup>33</sup> "path", this property is <b>required</b> and its value MUST be true. Otherwise, the property MAY be included and its default value is false.

If `in` is "body":

Field Name	Type	Description
schema	<a href="#">Schema Object</a> <sup>53</sup>	<b>Required.</b> The schema defining the type used for the body parameter.

If [in](#) <sup>33</sup> is any value other than "body":

Field Name	Type	Description
type	string	<b>Required.</b> The type of the parameter. Since the parameter is not located at the request body, it is limited to simple types (that is, not an object). The value MUST be one of "string", "number", "integer", "boolean", "array" or "file". If type is "file", the <a href="#">consumes</a> <sup>15</sup> MUST be either

Field Name	Type	Description
		"multipart/form-data", "application/x-www-form-urlencoded" or both and the parameter MUST be <a href="#">in</a> <sup>33</sup> "formData".
format	string	The extending format for the previously mentioned <a href="#">type</a> <sup>14</sup> . See <a href="#">Data Type Formats</a> <sup>14</sup> for further details.
allowEmptyValue	boolean	Sets the ability to pass empty-valued parameters. This is valid only for either query or formData parameters and allows you to send a parameter with a name only or an empty value. Default value is false.
items	<a href="#">Items Object</a> <sup>40</sup>	Required if <a href="#">type</a> <sup>12</sup> is "array". Describes the type of items in the array.
collectionFormat	string	<p>Determines the format of the array if type array is used. Possible values are:</p> <ul style="list-style-type: none"> <li>• csv - comma separated values foo,bar.</li> <li>• ssv - space separated values foo bar.</li> <li>• tsv - tab separated values foo \tbar.</li> <li>• pipes - pipe separated values foo bar.</li> <li>• multi - corresponds to multiple parameter instances instead of multiple values for a single instance foo=bar&amp;foo=baz. This is valid only for parameters <a href="#">in</a> <sup>33</sup> "query" or "formData".</li> </ul> <p>Default value is csv.</p>
default	*	Declares the value of the parameter that the server will use if none is provided, for example a "count" to

Field Name	Type	Description
		control the number of results per page might default to 100 if not supplied by the client in the request. (Note: "default" has no meaning for required parameters.) See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor101">http://json-schema.org/latest/json-schema-validation.html#anchor101</a> . Unlike JSON Schema this value MUST conform to the defined <a href="#">type</a> <small><sup>14</sup></small> for this parameter.
maximum	number	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor17">http://json-schema.org/latest/json-schema-validation.html#anchor17</a> .
exclusiveMaximum	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor17">http://json-schema.org/latest/json-schema-validation.html#anchor17</a> .
minimum	number	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor21">http://json-schema.org/latest/json-schema-validation.html#anchor21</a> .
exclusiveMinimum	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor21">http://json-schema.org/latest/json-schema-validation.html#anchor21</a> .
maxLength	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor26">http://json-schema.org/latest/json-schema-validation.html#anchor26</a> .
minLength	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor29">http://json-schema.org/latest/json-schema-validation.html#anchor29</a> .
pattern	string	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor33">http://json-schema.org/latest/json-schema-validation.html#anchor33</a> .
maxItems	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor42">http://json-schema.org/latest/json-schema-validation.html#anchor42</a> .
minItems	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor45">http://json-schema.org/latest/json-schema-validation.html#anchor45</a> .
uniqueItems	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor49">http://json-schema.org/latest/json-schema-validation.html#anchor49</a> .
enum	[*]	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor76">http://json-schema.org/latest/json-schema-validation.html#anchor76</a> .
multipleOf	number	See <a href="http://json-schema.org/latest/json-schema-">http://json-schema.org/latest/json-schema-</a>

Field Name	Type	Description
		<a href="#">validation.html#anchor14</a> .

#### Patterned Fields

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> [83] for further details.

## Parameter Object Examples

### Body Parameters

A body parameter with a referenced schema definition (normally for a model definition):

```
{
  "name": "user",
  "in": "body",
  "description": "user to add to the system",
  "required": true,
  "schema": {
    "$ref": "#/definitions/User"
  }
}
```

```
name: user
in: body
description: user to add to the system
required: true
schema:
  $ref: '#/definitions/User'
```

A body parameter that is an array of string values:

```
{  
    "name": "user",  
    "in": "body",  
    "description": "user to add to the system",  
    "required": true,  
    "schema": {  
        "type": "array",  
        "items": {  
            "type": "string"  
        }  
    }  
}
```

```
name: user  
in: body  
description: user to add to the system  
required: true  
schema:  
  type: array  
  items:  
    type: string
```

## Other Parameters

A header parameter with an array of 64 bit integer numbers:

```
{  
    "name": "token",  
    "in": "header",  
    "description": "token to be passed as a header",  
    "required": true,  
    "type": "array",  
    "items": {  
        "type": "integer",  
        "format": "int64"  
    },  
    "collectionFormat": "csv"  
}
```

```
name: token
in: header
description: token to be passed as a header
required: true
type: array
items:
  type: integer
  format: int64
collectionFormat: csv
```

A path parameter of a string value:

```
{
  "name": "username",
  "in": "path",
  "description": "username to fetch",
  "required": true,
  "type": "string"
}
```

```
name: username
in: path
description: username to fetch
required: true
type: string
```

An optional query parameter of a string value, allowing multiple values by repeating the query parameter:

```
{  
    "name": "id",  
    "in": "query",  
    "description": "ID of the object to fetch",  
    "required": false,  
    "type": "array",  
    "items": {  
        "type": "string"  
    },  
    "collectionFormat": "multi"  
}
```

```
name: id  
in: query  
description: ID of the object to fetch  
required: false  
type: array  
items:  
    type: string  
collectionFormat: multi
```

A form data with file type for a file upload:

```
{  
    "name": "avatar",  
    "in": "formData",  
    "description": "The avatar of the user",  
    "required": true,  
    "type": "file"  
}
```

```
name: avatar  
in: formData  
description: The avatar of the user  
required: true  
type: file
```

## 4.8.10 Items Object

A limited subset of JSON-Schema's items object. It is used by parameter definitions that are not located [in](#)<sup>33</sup> "body".

### Fixed Fields

Field Name	Type	Description
type	string	<b>Required.</b> The internal type of the array. The value MUST be one of "string", "number", "integer", "boolean", or "array". Files and models are not allowed.
format	string	The extending format for the previously mentioned <a href="#">type</a> <sup>14</sup> . See <a href="#">Data Type Formats</a> <sup>14</sup> for further details.
items	<a href="#">Items Object</a> <sup>40</sup>	<b>Required if</b> <a href="#">type</a> <sup>14</sup> <b>is</b> "array". Describes the type of items in the array.
collectionFormat	string	Determines the format of the array if type array is used. Possible values are: <ul style="list-style-type: none"> <li>• csv - comma separated values foo,bar.</li> <li>• ssv - space separated values foo bar.</li> <li>• tsv - tab separated values foo \tbar.</li> <li>• pipes - pipe separated values foo bar.</li> </ul> Default value is csv.
default	*	Declares the value of the item that the server will use if none is provided. (Note: "default" has no meaning for required items.) See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor101">http://json-schema.org/latest/json-schema-validation.html#anchor101</a> . Unlike JSON Schema this value MUST conform to the defined <a href="#">type</a> <sup>14</sup> for the data type.

Field Name	Type	Description
maximum	number	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor17">http://json-schema.org/latest/json-schema-validation.html#anchor17</a> .
exclusiveMaximum	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor17">http://json-schema.org/latest/json-schema-validation.html#anchor17</a> .
minimum	number	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor21">http://json-schema.org/latest/json-schema-validation.html#anchor21</a> .
exclusiveMinimum	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor21">http://json-schema.org/latest/json-schema-validation.html#anchor21</a> .
maxLength	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor26">http://json-schema.org/latest/json-schema-validation.html#anchor26</a> .
minLength	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor29">http://json-schema.org/latest/json-schema-validation.html#anchor29</a> .
pattern	string	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor33">http://json-schema.org/latest/json-schema-validation.html#anchor33</a> .
maxItems	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor42">http://json-schema.org/latest/json-schema-validation.html#anchor42</a> .
minItems	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor45">http://json-schema.org/latest/json-schema-validation.html#anchor45</a> .
uniqueItems	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor49">http://json-schema.org/latest/json-schema-validation.html#anchor49</a> .
enum	[*]	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor76">http://json-schema.org/latest/json-schema-validation.html#anchor76</a> .
multipleOf	number	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor14">http://json-schema.org/latest/json-schema-validation.html#anchor14</a> .

## Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> 83 for further details.

## Items Object Examples

Items must be of type string and have the minimum length of 2 characters:

```
{  
  "type": "string",  
  "minLength": 2  
}
```

```
type: string  
minLength: 2
```

An array of arrays, the internal array being of type integer, numbers must be between 0 and 63 (inclusive):

```
{  
  "type": "array",  
  "items": {  
    "type": "integer",  
    "minimum": 0,  
    "maximum": 63  
  }  
}
```

```
type: array  
items:  
  type: integer  
  minimum: 0  
  maximum: 63
```

### 4.8.11 Responses Object

A container for the expected responses of an operation. The container maps a HTTP response code to the expected response. It is not expected from the documentation to necessarily cover all possible HTTP response codes, since they may not be known in advance. However, it is expected from the documentation to cover a successful operation response and any known errors.

The default can be used a default response object for all HTTP codes that are not covered individually by the specification.

The Responses Object MUST contain at least one response code, and it SHOULD be the response for a successful operation call.

## Fixed Fields

Field Name	Type	Description
default	<a href="#">Response Object</a> 44   <a href="#">Reference Object</a> 52	The documentation of responses other than the ones declared for specific HTTP response codes. It can be used to cover undeclared responses. <a href="#">Reference Object</a> 52 can be used to link to a response that is defined at the <a href="#">Swagger Object's responses</a> 16 section.

## Patterned Fields

Field Pattern	Type	Description
{ <a href="#">HTTP Status Code</a> } 13	<a href="#">Response Object</a> 44   <a href="#">Reference Object</a> 52	Any <a href="#">HTTP status code</a> 13 can be used as the property name (one property per HTTP status code). Describes the expected response for that HTTP status code. <a href="#">Reference Object</a> 52 can be used to link to a response that is defined at the <a href="#">Swagger Object's responses</a> 16 section.
^x-	Any	Allows extensions to the Swagger Schema. The field name MUST begin with x-, for example, x-internal-id. The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> 83 for further details.

## Responses Object Example

A 200 response for successful operation and a default response for others (implying an error):

```
{
  "200": {
    "description": "a pet to be returned",
    "schema": {
      "$ref": "#/definitions/Pet"
    }
  },
  "default": {
    "description": "Unexpected error",
    "schema": {
      "$ref": "#/definitions/ErrorModel"
    }
  }
}
```

```
'200':
  description: a pet to be returned
  schema:
    $ref: '#/definitions/Pet'
default:
  description: Unexpected error
  schema:
    $ref: '#/definitions/ErrorModel'
```

#### 4.8.12 Response Object

Describes a single response from an API Operation.

#### Fixed Fields

Field Name	Type	Description
description	string	<b>Required.</b> A short description of the response. <a href="#">GFM syntax</a> can be used for rich text representation.
schema	<a href="#">Schema Object</a> <small>53</small>	A definition of the response structure. It can be a primitive, an array or an object. If this field does not exist, it means no content is returned as part of the response. As an extension to the <a href="#">Schema Object</a> <small>53</small> , its root type value may

Field Name	Type	Description
		also be "file". This SHOULD be accompanied by a relevant produces mime-type.
headers	<a href="#">Headers Object</a> <small>47</small>	A list of headers that are sent with the response.
examples	<a href="#">Example Object</a> <small>51</small>	An example of the response message.

## Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

## Response Object Examples

Response of an array of a complex type:

```
{
  "description": "A complex object array response",
  "schema": {
    "type": "array",
    "items": {
      "$ref": "#/definitions/VeryComplexType"
    }
  }
}
```

```
description: A complex object array response
schema:
  type: array
  items:
    $ref: '#/definitions/VeryComplexType'
```

Response with a string type:

```
{  
  "description": "A simple string response",  
  "schema": {  
    "type": "string"  
  }  
}
```

```
description: A simple string response  
schema:  
  type: string
```

Response with headers:

```
{  
  "description": "A simple string response",  
  "schema": {  
    "type": "string"  
  },  
  "headers": {  
    "X-Rate-Limit-Limit": {  
      "description": "The number of allowed requests in the current period",  
      "type": "integer"  
    },  
    "X-Rate-Limit-Remaining": {  
      "description": "The number of remaining requests in the current period",  
      "type": "integer"  
    },  
    "X-Rate-Limit-Reset": {  
      "description": "The number of seconds left in the current period",  
      "type": "integer"  
    }  
  }  
}
```

```
description: A simple string response
schema:
  type: string
headers:
  X-Rate-Limit-Limit:
    description: The number of allowed requests in the current period
    type: integer
  X-Rate-Limit-Remaining:
    description: The number of remaining requests in the current period
    type: integer
  X-Rate-Limit-Reset:
    description: The number of seconds left in the current period
    type: integer
```

Response with no return value:

```
{  
  "description": "object created"  
}
```

```
description: object created
```

#### 4.8.13 Headers Object

Lists the headers that can be sent as part of a response.

##### Patterned Fields

Field Pattern	Type	Description
{name}	<a href="#">Header Object</a> <small>48</small>	The name of the property corresponds to the name of the header. The value describes the type of the header.

#### Headers Object Example

Rate-limit headers:

```
{
    "X-Rate-Limit-Limit": {
        "description": "The number of allowed requests in the current period",
        "type": "integer"
    },
    "X-Rate-Limit-Remaining": {
        "description": "The number of remaining requests in the current period",
        "type": "integer"
    },
    "X-Rate-Limit-Reset": {
        "description": "The number of seconds left in the current period",
        "type": "integer"
    }
}
```

```
X-Rate-Limit-Limit:
    description: The number of allowed requests in the current period
    type: integer
X-Rate-Limit-Remaining:
    description: The number of remaining requests in the current period
    type: integer
X-Rate-Limit-Reset:
    description: The number of seconds left in the current period
    type: integer
```

#### 4.8.14 Header Object

A header sent as part of a response.

Field Name	Type	Description
description	string	A short description of the header.
type	string	<b>Required.</b> The type of the object. The value MUST be one of "string", "number", "integer", "boolean", or "array".
format	string	The extending format for the previously mentioned <a href="#">type</a> <sup>14</sup> . See <a href="#">Data Type Formats</a> <sup>14</sup> for further details.

Field Name	Type	Description
items	<a href="#">Items Object</a>	Required if <a href="#">type</a> <sup>14</sup> is "array". Describes the type of items in the array.
collectionFormat	string	Determines the format of the array if type array is used. Possible values are: <ul style="list-style-type: none"> <li>csv - comma separated values foo,bar.</li> <li>ssv - space separated values foo bar.</li> <li>tsv - tab separated values foo \tbar.</li> <li>pipes - pipe separated values foo bar.</li> </ul> Default value is csv.
default	*	Declares the value of the header that the server will use if none is provided. (Note: "default" has no meaning for required headers.) See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor101">http://json-schema.org/latest/json-schema-validation.html#anchor101</a> . Unlike JSON Schema this value MUST conform to the defined <a href="#">type</a> <sup>14</sup> for the header.
maximum	number	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor17">http://json-schema.org/latest/json-schema-validation.html#anchor17</a> .
exclusiveMaximum	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor17">http://json-schema.org/latest/json-schema-validation.html#anchor17</a> .
minimum	number	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor21">http://json-schema.org/latest/json-schema-validation.html#anchor21</a> .
exclusiveMinimum	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor21">http://json-schema.org/latest/json-schema-validation.html#anchor21</a> .
maxLength	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor26">http://json-schema.org/latest/json-schema-validation.html#anchor26</a> .
minLength	integer	See <a 210="" 89="" 967="" 982"="" data-label="Page-Footer" href="http://json-schema.org/latest/json-schema-&lt;/a&gt;&lt;/td&gt;&lt;/tr&gt; &lt;/tbody&gt; &lt;/table&gt; &lt;/div&gt; &lt;div data-bbox=">OpenAPI Specification</a>

Field Name	Type	Description
		<a href="#">validation.html#anchor29.</a>
pattern	string	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor33">http://json-schema.org/latest/json-schema-validation.html#anchor33</a> .
maxItems	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor42">http://json-schema.org/latest/json-schema-validation.html#anchor42</a> .
minItems	integer	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor45">http://json-schema.org/latest/json-schema-validation.html#anchor45</a> .
uniqueItems	boolean	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor49">http://json-schema.org/latest/json-schema-validation.html#anchor49</a> .
enum	[*]	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor76">http://json-schema.org/latest/json-schema-validation.html#anchor76</a> .
multipleOf	number	See <a href="http://json-schema.org/latest/json-schema-validation.html#anchor14">http://json-schema.org/latest/json-schema-validation.html#anchor14</a> .

## Patterned Objects

Field Pattern	Type	Description
^x-	Any	Allows extensions to the Swagger Schema. The field name MUST begin with x-, for example, x-internal-id. The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> for further details.

## Header Object Example

A simple header with of an integer type:

```
{
  "description": "The number of allowed requests in the current period",
  "type": "integer"
}
```

```
description: The number of allowed requests in the current period
type: integer
```

#### 4.8.15 Example Object

Allows sharing examples for operation responses.

#### Patterned Fields

Field Pattern	Type	Description
{mime type} <small>[12]</small>	Any	The name of the property MUST be one of the Operation produces values (either implicit or inherited). The value SHOULD be an example of what such a response would look like.

#### Example Object Example

Example response for application/json mimetype of a Pet data type:

```
{  
  "application/json": {  
    "name": "Puma",  
    "type": "Dog",  
    "color": "Black",  
    "gender": "Female",  
    "breed": "Mixed"  
  }  
}
```

```
application/json:  
  name: Puma  
  type: Dog  
  color: Black  
  gender: Female  
  breed: Mixed
```

#### 4.8.16 Tag Object

Allows adding meta data to a single tag that is used by the [Operation Object](#) [25]. It is not mandatory to have a Tag Object per tag used there.

## Fixed Fields

Field Name	Type	Description
name	string	<b>Required.</b> The name of the tag.
description	string	A short description for the tag. <a href="#">GFM syntax</a> can be used for rich text representation.
externalDocs	<a href="#">External Documentation Object</a> <small>31</small>	Additional external documentation for this tag.

## Patterned Fields

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

## Tag Object Example

```
{
  "name": "pet",
  "description": "Pets operations"
}
```

```
name: pet
description: Pets operations
```

### 4.8.17 Reference Object

A simple object to allow referencing other definitions in the specification. It can be used to reference parameters and responses that are defined at the top level for reuse.

The Reference Object is a [JSON Reference](#) that uses a [JSON Pointer](#) as its value. For this specification, only [canonical dereferencing](#) is supported.

## Fixed Fields

Field Name	Type	Description
\$ref	string	<b>Required.</b> The reference string.

### Reference Object Example

```
{  
  "$ref": "#/definitions/Pet"  
}
```

```
$ref: '#/definitions/Pet'
```

### Relative Schema File Example

```
{  
  "$ref": "Pet.json"  
}
```

```
$ref: 'Pet.yaml'
```

### Relative Files With Embedded Schema Example

```
{  
  "$ref": "definitions.json#/Pet"  
}
```

```
$ref: 'definitions.yaml#/Pet'
```

#### 4.8.18 Schema Object

The Schema Object allows the definition of input and output data types. These types can be objects, but also primitives and arrays. This object is based on the [JSON Schema Specification Draft 4](#) and uses a predefined subset of it. On top of this subset, there are extensions provided by this specification to allow for more complete documentation.

Further information about the properties can be found in [JSON Schema Core](#) and [JSON Schema Validation](#). Unless stated otherwise, the property definitions follow the JSON Schema specification as referenced here.

The following properties are taken directly from the JSON Schema definition and follow the same specifications:

- \$ref - As a [JSON Reference](#)
- format (See [Data Type Formats](#)<sup>14</sup> for further details)
- title
- description ([GFM syntax](#) can be used for rich text representation)
- default (Unlike JSON Schema, the value MUST conform to the defined type for the Schema Object)
- multipleOf
- maximum
- exclusiveMaximum
- minimum
- exclusiveMinimum
- maxLength
- minLength
- pattern
- maxItems
- minItems
- uniqueItems
- maxProperties
- minProperties
- required
- enum
- type

The following properties are taken from the JSON Schema definition but their definitions were adjusted to the Swagger Specification. Their definition is the same as the one from JSON Schema, only where the original definition references the JSON Schema definition, the [Schema Object](#)<sup>53</sup> definition is used instead.

- items
- allOf
- properties
- additionalProperties

Other than the JSON Schema subset fields, the following fields may be used for further schema documentation.

## Fixed Fields

Field Name	Type	Description
discriminator	string	Adds support for polymorphism. The discriminator is the schema

Field Name	Type	Description
		property name that is used to differentiate between other schema that inherit this schema. The property name used MUST be defined at this schema and it MUST be in the required property list. When used, the value MUST be the name of this schema or any schema that inherits it.
readOnly	boolean	Relevant only for Schema "properties" definitions. Declares the property as "read only". This means that it MAY be sent as part of a response but MUST NOT be sent as part of the request. Properties marked as readOnly being true SHOULD NOT be in the required list of the defined schema. Default value is false.
xml	<a href="#">XML Object</a> <small>65</small>	This MAY be used only on properties schemas. It has no effect on root schemas. Adds Additional metadata to describe the XML representation format of this property.
externalDocs	<a href="#">External Documentation Object</a> <small>31</small>	Additional external documentation for this schema.
example	Any	A free-form property to include an example of an instance for this schema.

## Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

## Composition and Inheritance (Polymorphism)

Swagger allows combining and extending model definitions using the `allOf` property of JSON Schema, in effect offering model composition. `allOf` takes in an array of object definitions that are validated independently but together compose a single object.

While composition offers model extensibility, it does not imply a hierarchy between the models. To support polymorphism, Swagger adds the support of the discriminator field. When used, the discriminator will be the name of the property used to decide which schema definition is used to validate the structure of the model. As such, the discriminator field **MUST** be a required field. The value of the chosen property has to be the friendly name given to the model under the `definitions` property. As such, inline schema definitions, which do not have a given id, cannot be used in polymorphism.

## XML Modeling

The [xml](#) 55 property allows extra definitions when translating the JSON definition to XML.

The [XML Object](#) 65 contains additional information about the available options.

## Schema Object Examples

### Primitive Sample

Unlike previous versions of Swagger, Schema definitions can be used to describe primitive and arrays as well.

```
{  
  "type": "string",  
  "format": "email"  
}
```

```
type: string  
format: email
```

### Simple Model

```
{  
  "type": "object",  
  "required": [  
    "name"  
,  
  "properties": {  
    "name": {  
      "type": "string"  
    },  
    "address": {  
      "$ref": "#/definitions/Address"  
    },  
    "age": {  
      "type": "integer",  
      "format": "int32",  
      "minimum": 0  
    }  
  }  
}
```

```
type: object  
required:  
- name  
properties:  
  name:  
    type: string  
  address:  
    $ref: '#/definitions/Address'  
  age:  
    type: integer  
    format: int32  
    minimum: 0
```

## Model with Map/Dictionary Properties

For a simple string to string mapping:

```
{  
  "type": "object",  
  "additionalProperties": {  
    "type": "string"  
  }  
}
```

```
type: object  
additionalProperties:  
  type: string
```

For a string to model mapping:

```
{  
  "type": "object",  
  "additionalProperties": {  
    "$ref": "#/definitions/ComplexModel"  
  }  
}
```

```
type: object  
additionalProperties:  
  $ref: '#/definitions/ComplexModel'
```

Model with Example

```
{  
  "type": "object",  
  "properties": {  
    "id": {  
      "type": "integer",  
      "format": "int64"  
    },  
    "name": {  
      "type": "string"  
    }  
  },  
  "required": [  
    "name"  
  ],  
  "example": {  
    "name": "Puma",  
    "id": 1  
  }  
}
```

```
type: object  
properties:  
  id:  
    type: integer  
    format: int64  
  name:  
    type: string  
required:  
- name  
example:  
  name: Puma  
  id: 1
```

Models with Composition

```
{  
    "definitions": {  
        "ErrorModel": {  
            "type": "object",  
            "required": [  
                "message",  
                "code"  
            ],  
            "properties": {  
                "message": {  
                    "type": "string"  
                },  
                "code": {  
                    "type": "integer",  
                    "minimum": 100,  
                    "maximum": 600  
                }  
            }  
        },  
        "ExtendedErrorModel": {  
            "allOf": [  
                {  
                    "$ref": "#/definitions/ErrorModel"  
                },  
                {  
                    "type": "object",  
                    "required": [  
                        "rootCause"  
                    ],  
                    "properties": {  
                        "rootCause": {  
                            "type": "string"  
                        }  
                    }  
                }  
            ]  
        }  
    }  
}
```

```
definitions:  
  ErrorModel:  
    type: object  
    required:  
      - message  
      - code  
    properties:  
      message:  
        type: string  
      code:  
        type: integer  
        minimum: 100  
        maximum: 600  
  ExtendedErrorModel:  
    allOf:  
      - $ref: '#/definitions/ErrorModel'  
      - type: object  
    required:  
      - rootCause  
    properties:  
      rootCause:  
        type: string
```

## Models with Polymorphism Support

```
{  
  "definitions": {  
    "Pet": {  
      "type": "object",  
      "discriminator": "petType",  
      "properties": {  
        "name": {  
          "type": "string"  
        },  
        "petType": {  
          "type": "string"  
        }  
      },  
      "required": [  
        "name",  
        "petType"  
      ]  
    },  
    "Cat": {  
      "description": "A representation of a cat",  
      "allOf": [  
        {  
          "$ref": "#/definitions/Pet"  
        },  
        {  
          "type": "object",  
          "properties": {  
            "huntingSkill": {  
              "type": "string",  
              "description": "The measured skill for hunting",  
              "default": "lazy",  
              "enum": [  
                "clueless",  
                "lazy",  
                "adventurous",  
                "aggressive"  
              ]  
            }  
          }  
      ],  
      "required": [  
        "huntingSkill"  
      ]  
    }  
  }  
}
```

```
        ]
    }
]
},
"Dog": {
  "description": "A representation of a dog",
  "allOf": [
    {
      "$ref": "#/definitions/Pet"
    },
    {
      "type": "object",
      "properties": {
        "packSize": {
          "type": "integer",
          "format": "int32",
          "description": "the size of the pack the dog is from",
          "default": 0,
          "minimum": 0
        }
      },
      "required": [
        "packSize"
      ]
    }
  ]
}
```

```
definitions:  
  Pet:  
    type: object  
    discriminator: petType  
    properties:  
      name:  
        type: string  
      petType:  
        type: string  
    required:  
      - name  
      - petType  
  Cat:  
    description: A representation of a cat  
    allOf:  
      - $ref: '#/definitions/Pet'  
      - type: object  
        properties:  
          huntingSkill:  
            type: string  
            description: The measured skill for hunting  
            default: lazy  
            enum:  
              - clueless  
              - lazy  
              - adventurous  
              - aggressive  
        required:  
          - huntingSkill  
  Dog:  
    description: A representation of a dog  
    allOf:  
      - $ref: '#/definitions/Pet'  
      - type: object  
        properties:  
          packSize:  
            type: integer  
            format: int32  
            description: the size of the pack the dog is from  
            default: 0  
            minimum: 0
```

```
required:
- packSize
```

#### 4.8.19 XML Object

A metadata object that allows for more fine-tuned XML model definitions.

When using arrays, XML element names are not inferred (for singular/plural forms) and the name property should be used to add that information. See examples for expected behavior.

#### Fixed Fields

Field Name	Type	Description
name	string	Replaces the name of the element/attribute used for the described schema property. When defined within the Items Object (items), it will affect the name of the individual XML elements within the list. When defined alongside type being array (outside the items), it will affect the wrapping element and only if wrapped is true. If wrapped is false, it will be ignored.
namespace	string	The URL of the namespace definition. Value SHOULD be in the form of a URL.
prefix	string	The prefix to be used for the <a href="#">name</a> <small>65</small> .
attribute	boolean	Declares whether the property definition translates to an attribute instead of an element. Default value is false.
wrapped	boolean	MAY be used only for an array definition. Signifies whether the array is wrapped (for example, <books><book/><book/></books>) or unwrapped (<book/><book/>). Default value is false. The definition takes effect only when defined alongside type being array (outside the items).

## Patterned Objects

Field Pattern	Type	Description
<code>^x-</code>	Any	Allows extensions to the Swagger Schema. The field name MUST begin with <code>x-</code> , for example, <code>x-internal-id</code> . The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

## XML Object Examples

The examples of the XML object definitions are included inside a property definition of a [Schema Object](#) 53 with a sample of the XML representation of it.

### No XML Element

Basic string property:

```
{  
  "animals": {  
    "type": "string"  
  }  
}
```

```
animals:  
  type: string  
<animals>...</animals>
```

Basic string array property ([wrapped](#) 65 is false by default):

```
{  
  "animals": {  
    "type": "array",  
    "items": {  
      "type": "string"  
    }  
  }  
}
```

```
animals:  
  type: array  
  items:  
    type: string  
<animals>...</animals>  
<animals>...</animals>  
<animals>...</animals>
```

## XML Name Replacement

```
{  
  "animals": {  
    "type": "string",  
    "xml": {  
      "name": "animal"  
    }  
  }  
}
```

```
animals:  
  type: string  
  xml:  
    name: animal  
<animal>...</animal>
```

## XML Attribute, Prefix and Namespace

In this example, a full model definition is shown.

```
{  
  "Person": {  
    "type": "object",  
    "properties": {  
      "id": {  
        "type": "integer",  
        "format": "int32",  
        "xml": {  
          "attribute": true  
        },  
        "name": {  
          "type": "string",  
          "xml": {  
            "namespace": "http://swagger.io/schema/sample",  
            "prefix": "sample"  
          }  
        }  
      }  
    }  
  }  
}
```

```
Person:  
  type: object  
  properties:  
    id:  
      type: integer  
      format: int32  
      xml:  
        attribute: true  
    name:  
      type: string  
      xml:  
        namespace: http://swagger.io/schema/sample  
        prefix: sample  
<Person id="123">  
  <sample:name xmlns:sample="http://swagger.io/schema/sample">example</sample:name>  
</Person>
```

## XML Arrays

Changing the element names:

```
{  
  "animals": {  
    "type": "array",  
    "items": {  
      "type": "string",  
      "xml": {  
        "name": "animal"  
      }  
    }  
  }  
}
```

```
animals:  
  type: array  
  items:  
    type: string  
    xml:  
      name: animal  
<animal>value</animal>  
<animal>value</animal>
```

The external name property has no effect on the XML:

```
{  
  "animals": {  
    "type": "array",  
    "items": {  
      "type": "string",  
      "xml": {  
        "name": "animal"  
      }  
    },  
    "xml": {  
      "name": "aliens"  
    }  
  }  
}
```

```
animals:  
  type: array  
  items:  
    type: string  
    xml:  
      name: animal  
  xml:  
    name: aliens  
<animal>value</animal>  
<animal>value</animal>
```

Even when the array is wrapped, if no name is explicitly defined, the same name will be used both internally and externally:

```
{  
  "animals": {  
    "type": "array",  
    "items": {  
      "type": "string"  
    },  
    "xml": {  
      "wrapped": true  
    }  
  }  
}
```

```
animals:  
  type: array  
  items:  
    type: string  
  xml:  
    wrapped: true  
<animals>  
  <animals>value</animals>  
  <animals>value</animals>  
</animals>
```

To overcome the above example, the following definition can be used:

```
{  
  "animals": {  
    "type": "array",  
    "items": {  
      "type": "string",  
      "xml": {  
        "name": "animal"  
      }  
    },  
    "xml": {  
      "wrapped": true  
    }  
  }  
}
```

```
animals:  
  type: array  
  items:  
    type: string  
    xml:  
      name: animal  
  xml:  
    wrapped: true  
<animals>  
  <animal>value</animal>  
  <animal>value</animal>  
</animals>
```

Affecting both internal and external names:

```
{  
  "animals": {  
    "type": "array",  
    "items": {  
      "type": "string",  
      "xml": {  
        "name": "animal"  
      }  
    },  
    "xml": {  
      "name": "aliens",  
      "wrapped": false  
    }  
  }  
}
```

```
animals:  
  type: array  
  items:  
    type: string  
    xml:  
      name: animal  
  xml:  
    name: aliens  
    wrapped: false  
<aliens>  
  <animal>value</animal>  
  <animal>value</animal>  
</aliens>
```

If we change the external element but not the internal ones:

```
{
  "animals": {
    "type": "array",
    "items": {
      "type": "string"
    },
    "xml": {
      "name": "aliens",
      "wrapped": true
    }
  }
}
```

```
animals:
  type: array
  items:
    type: string
  xml:
    name: aliens
    wrapped: true
<aliens>
  <aliens>value</aliens>
  <aliens>value</aliens>
</aliens>
```

#### 4.8.20 Definitions Object

An object to hold data types that can be consumed and produced by operations. These data types can be primitives, arrays or models.

#### Patterned Fields

Field Pattern	Type	Description
{name}	<a href="#">Schema Object</a> <small>53</small>	A single definition, mapping a "name" to the schema it defines.

#### Definitions Object Example

```
{  
  "Category": {  
    "type": "object",  
    "properties": {  
      "id": {  
        "type": "integer",  
        "format": "int64"  
      },  
      "name": {  
        "type": "string"  
      }  
    }  
  },  
  "Tag": {  
    "type": "object",  
    "properties": {  
      "id": {  
        "type": "integer",  
        "format": "int64"  
      },  
      "name": {  
        "type": "string"  
      }  
    }  
  }  
}
```

```
Category:  
  type: object  
  properties:  
    id:  
      type: integer  
      format: int64  
    name:  
      type: string  
Tag:  
  type: object  
  properties:  
    id:  
      type: integer  
      format: int64  
    name:  
      type: string
```

#### 4.8.21 Parameters Definitions Object

An object to hold parameters to be reused across operations. Parameter definitions can be referenced to the ones defined here.

This does not define global operation parameters.

#### Patterned Fields

Field Pattern	Type	Description
{name}	<a href="#">Parameter Object</a> <small>32</small>	A single parameter definition, mapping a "name" to the parameter it defines.

#### Parameters Definition Object Example

```
{  
  "skipParam": {  
    "name": "skip",  
    "in": "query",  
    "description": "number of items to skip",  
    "required": true,  
    "type": "integer",  
    "format": "int32"  
  },  
  "limitParam": {  
    "name": "limit",  
    "in": "query",  
    "description": "max records to return",  
    "required": true,  
    "type": "integer",  
    "format": "int32"  
  }  
}
```

```
skipParam:  
  name: skip  
  in: query  
  description: number of items to skip  
  required: true  
  type: integer  
  format: int32  
limitParam:  
  name: limit  
  in: query  
  description: max records to return  
  required: true  
  type: integer  
  format: int32
```

#### 4.8.22 Responses Definitions Object

An object to hold responses to be reused across operations. Response definitions can be referenced to the ones defined here.

This does not define global operation responses.

## Patterned Fields

Field Pattern	Type	Description
{name}	<a href="#">Response Object</a> <small>44</small>	A single response definition, mapping a "name" to the response it defines.

## Responses Definitions Object Example

```
{
  "NotFound": {
    "description": "Entity not found."
  },
  "IllegalInput": {
    "description": "Illegal input for operation."
  },
  "GeneralError": {
    "description": "General Error",
    "schema": {
      "$ref": "#/definitions/GeneralError"
    }
  }
}
```

```
NotFound:
  description: Entity not found.
IllegalInput:
  description: Illegal input for operation.
GeneralError:
  description: General Error
  schema:
    $ref: '#/definitions/GeneralError'
```

### 4.8.23 Security Definitions Object

A declaration of the security schemes available to be used in the specification. This does not enforce the security schemes on the operations and only serves to provide the relevant details for each scheme.

## Patterned Fields

Field Pattern	Type	Description
{name}	<a href="#">Security Scheme Object</a> 79	A single security scheme definition, mapping a "name" to the scheme it defines.

### Security Definitions Object Example

```
{  
    "api_key": {  
        "type": "apiKey",  
        "name": "api_key",  
        "in": "header"  
    },  
    "petstore_auth": {  
        "type": "oauth2",  
        "authorizationUrl": "http://swagger.io/api/oauth/dialog",  
        "flow": "implicit",  
        "scopes": {  
            "write:pets": "modify pets in your account",  
            "read:pets": "read your pets"  
        }  
    }  
}
```

```
api_key:  
  type: apiKey  
  name: api_key  
  in: header  
petstore_auth:  
  type: oauth2  
  authorizationUrl: http://swagger.io/api/oauth/dialog  
  flow: implicit  
  scopes:  
    write:pets: modify pets in your account  
    read:pets: read your pets
```

#### 4.8.24 Security Scheme Object

Allows the definition of a security scheme that can be used by the operations. Supported schemes are basic authentication, an API key (either as a header or as a query parameter) and OAuth2's common flows (implicit, password, application and access code).

#### Fixed Fields

Field Name	Type	Validity	Description
type	string	Any	<b>Required.</b> The type of the security scheme. Valid values are "basic", "apiKey" or "oauth2".
description	string	Any	A short description for security scheme.
name	string	apiKey	<b>Required.</b> The name of the header or query parameter to be used.
in	string	apiKey	<b>Required</b> The location of the API key. Valid values are "query" or "header".
flow	string	oauth2	<b>Required.</b> The flow used by the OAuth2 security scheme. Valid values are "implicit", "password", "application" or "accessCode".
authorizationUrl	string	oauth2 ("implicit", "accessCode")	<b>Required.</b> The authorization URL to be used for this flow. This SHOULD be in the form of a URL.
tokenUrl	string	oauth2 ("password", "application", "accessCode")	<b>Required.</b> The token URL to be used for this flow. This SHOULD be in the form of a URL.
scopes	<a href="#">Scopes Object</a> 81	oauth2	<b>Required.</b> The available scopes for the OAuth2 security scheme.

#### Patterned Fields

Field Name	Type	Description
^x-	Any	Allows extensions to the Swagger Schema. The field name MUST begin with x-, for example, x-internal-id. The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> for further details.

## Security Scheme Object Example

### Basic Authentication Sample

```
{  
  "type": "basic"  
}
```

```
type: basic
```

### API Key Sample

```
{  
  "type": "apiKey",  
  "name": "api_key",  
  "in": "header"  
}
```

```
type: apiKey  
name: api_key  
in: header
```

### Implicit OAuth2 Sample

```
{
  "type": "oauth2",
  "authorizationUrl": "http://swagger.io/api/oauth/dialog",
  "flow": "implicit",
  "scopes": {
    "write:pets": "modify pets in your account",
    "read:pets": "read your pets"
  }
}
```

```
type: oauth2
authorizationUrl: http://swagger.io/api/oauth/dialog
flow: implicit
scopes:
  write:pets: modify pets in your account
  read:pets: read your pets
```

#### 4.8.25 Scopes Object

Lists the available scopes for an OAuth2 security scheme.

#### Patterned Fields

Field Pattern	Type	Description
{name}	string	Maps between a name of a scope to a short description of it (as the value of the property).

#### Patterned Objects

Field Pattern	Type	Description
^x-	Any	Allows extensions to the Swagger Schema. The field name MUST begin with x-, for example, x-internal-id. The value can be null, a primitive, an array or an object. See <a href="#">Vendor Extensions</a> <small>83</small> for further details.

#### Scopes Object Example

```
{  
  "write:pets": "modify pets in your account",  
  "read:pets": "read your pets"  
}
```

```
write:pets: modify pets in your account  
read:pets: read your pets
```

#### 4.8.26 Security Requirement Object

Lists the required security schemes to execute this operation. The object can have multiple security schemes declared in it which are all required (that is, there is a logical AND between the schemes).

The name used for each property MUST correspond to a security scheme declared in the [Security Definitions](#) <sup>77</sup>.

#### Patterned Fields

Field Pattern	Type	Description
{name}	[string]	Each name must correspond to a security scheme which is declared in the <a href="#">Security Definitions</a> <sup>77</sup> . If the security scheme is of type "oauth2", then the value is a list of scope names required for the execution. For other security scheme types, the array MUST be empty.

#### Security Requirement Object Examples

##### Non-OAuth2 Security Requirement

```
{  
  "api_key": []  
}
```

```
api_key: []
```

## OAuth2 Security Requirement

```
{  
  "petstore_auth": [  
    "write:pets",  
    "read:pets"  
  ]  
}
```

```
petstore_auth:  
- write:pets  
- read:pets
```

## 4.9 Security Filtering

Some objects in the Swagger specification may be declared and remain empty, or completely be removed, even though they are inherently the core of the API documentation.

The reasoning behind it is to allow an additional layer of access control over the documentation itself. While not part of the specification itself, certain libraries may choose to allow access to parts of the documentation based on some form of authentication/authorization.

Two examples for this:

1. The [Paths Object](#)<sup>20</sup> may be empty. It may be counterintuitive, but this may tell the viewer that they got to the right place, but can't access any documentation. They'd still have access to the [Info Object](#)<sup>17</sup> which may contain additional information regarding authentication.
2. The [Path Item Object](#)<sup>21</sup> may be empty. In this case, the viewer will be aware that the path exists, but will not be able to see any of its operations or parameters. This is different than hiding the path itself from the [Paths Object](#)<sup>20</sup> so the user will not be aware of its existence. This allows the documentation provider a finer control over what the viewer can see.

## 4.10 Vendor Extensions

aka Specification Extensions

While the Swagger Specification tries to accommodate most use cases, additional data can be added to extend the specification at certain points.

The extensions properties are always prefixed by "x-" and can have any valid JSON format value.

The extensions may or may not be supported by the available tooling, but those may be extended as well to add requested support (if tools are internal or open-sourced).

# Pet Store JSON

## 5 Pet Store JSON

```
{  
    "swagger": "2.0",  
    "info": {  
        "description": "This is a sample server Petstore server. You can find ou  
        "version": "1.0.0",  
        "title": "Swagger Petstore",  
        "termsOfService": "http://swagger.io/terms/",  
        "contact": {  
            "email": "apiteam@swagger.io"  
        },  
        "license": {  
            "name": "Apache 2.0",  
            "url": "http://www.apache.org/licenses/LICENSE-2.0.html"  
        }  
    },  
    "host": "petstore.swagger.io",  
    "basePath": "/v2",  
    "tags": [{  
        "name": "pet",  
        "description": "Everything about your Pets",  
        "externalDocs": {  
            "description": "Find out more",  
            "url": "http://swagger.io"  
        }  
    },  
    {  
        "name": "store",  
        "description": "Access to Petstore orders"  
    },  
    {  
        "name": "user",  
        "description": "Operations about user",  
        "externalDocs": {  
            "description": "Find out more about our store",  
            "url": "http://swagger.io"  
        }  
    }],  
    "schemes": ["http"],  
    "paths": {  
        "/pet": {  
            "post": {  
                "tags": ["pet"],  
                "summary": "Add a new pet to the store",  
                "description": "",  
                "operationId": "addPet",  
                "consumes": ["application/json",  
                            "application/xml"],  
                "produces": ["application/xml",  
                            "application/json"],  
                "parameters": [  
                    {  
                        "in": "body",  
                        "name": "body",  
                        "description": "Pet object that needs to be added to the store",  
                        "required": true,  
                        "schema": {  
                            "$ref": "#/definitions/Pet"  
                        }  
                    }  
                ]  
            }  
        }  
    }  
}
```

```
        }
    ],
    "responses": {
        "405": {
            "description": "Invalid input"
        }
    },
    "security": [
        {
            "petstore_auth": ["write:pets",
                "read:pets"]
        }
    ]
},
"put": {
    "tags": ["pet"],
    "summary": "Update an existing pet",
    "description": "",
    "operationId": "updatePet",
    "consumes": ["application/json",
        "application/xml"],
    "produces": ["application/xml",
        "application/json"],
    "parameters": [
        {
            "in": "body",
            "name": "body",
            "description": "Pet object that needs to be added to the store",
            "required": true,
            "schema": {
                "$ref": "#/definitions/Pet"
            }
        }
    ],
    "responses": {
        "400": {
            "description": "Invalid ID supplied"
        },
        "404": {
            "description": "Pet not found"
        },
        "405": {
            "description": "Validation exception"
        }
    },
    "security": [
        {
            "petstore_auth": ["write:pets",
                "read:pets"]
        }
    ]
},
"/pet/findByStatus": {
    "get": {
        "tags": ["pet"],
        "summary": "Finds Pets by status",
        "description": "Multiple status values can be provided with comma separated values. The status value that needs to be considered for a pet is specified by the query parameter",
        "operationId": "findPetsByStatus",
        "produces": ["application/xml",
            "application/json"],
        "parameters": [
            {
                "name": "status",
                "in": "query",
                "description": "Status values that need to be considered for filtering"
            }
        ]
    }
}
```

```
        "required": true,
        "type": "array",
        "items": {
            "type": "string",
            "enum": ["available",
            "pending",
            "sold"],
            "default": "available"
        },
        "collectionFormat": "multi"
    ],
    "responses": {
        "200": {
            "description": "successful operation",
            "schema": {
                "type": "array",
                "items": {
                    "$ref": "#/definitions/Pet"
                }
            }
        },
        "400": {
            "description": "Invalid status value"
        }
    },
    "security": [
        {
            "petstore_auth": ["write:pets",
            "read:pets"]
        }
    ]
},
"/pet/findByTags": {
    "get": {
        "tags": ["pet"],
        "summary": "Finds Pets by tags",
        "description": "Multiple tags can be provided with comma separated values. To filter by a single tag, just include that tag name as value in the comma separated list",
        "operationId": "findPetsByTags",
        "produces": ["application/xml",
        "application/json"],
        "parameters": [
            {
                "name": "tags",
                "in": "query",
                "description": "Tags to filter by",
                "required": true,
                "type": "array",
                "items": {
                    "type": "string"
                }
            },
            "collectionFormat": "multi"
        ],
        "responses": {
            "200": {
                "description": "successful operation",
                "schema": {
                    "type": "array",
                    "items": {
                        "$ref": "#/definitions/Pet"
                    }
                }
            }
        }
    }
}
```

```
        },
        "400": {
            "description": "Invalid tag value"
        }
    },
    "security": [
        "petstore_auth": ["write:pets",
            "read:pets"]
    ],
    "deprecated": true
}
},
"/pet/{petId)": {
    "get": {
        "tags": ["pet"],
        "summary": "Find pet by ID",
        "description": "Returns a single pet",
        "operationId": "getPetById",
        "produces": ["application/xml",
            "application/json"],
        "parameters": [
            {
                "name": "petId",
                "in": "path",
                "description": "ID of pet to return",
                "required": true,
                "type": "integer",
                "format": "int64"
            }
        ],
        "responses": {
            "200": {
                "description": "successful operation",
                "schema": {
                    "$ref": "#/definitions/Pet"
                }
            },
            "400": {
                "description": "Invalid ID supplied"
            },
            "404": {
                "description": "Pet not found"
            }
        },
        "security": [
            "api_key": []
        ]
},
    "post": {
        "tags": ["pet"],
        "summary": "Updates a pet in the store with form data",
        "description": "",
        "operationId": "updatePetWithForm",
        "consumes": ["application/x-www-form-urlencoded"],
        "produces": ["application/xml",
            "application/json"],
        "parameters": [
            {
                "name": "petId",
                "in": "path",
                "description": "ID of pet that needs to be updated",
                "required": true,
                "type": "integer"
            }
        ],
        "responses": {
            "200": {
                "description": "Updated"
            },
            "400": {
                "description": "Invalid ID supplied"
            },
            "404": {
                "description": "Pet not found"
            }
        }
    }
}
```

```
        "type": "integer",
        "format": "int64"
    },
    {
        "name": "name",
        "in": "formData",
        "description": "Updated name of the pet",
        "required": false,
        "type": "string"
    },
    {
        "name": "status",
        "in": "formData",
        "description": "Updated status of the pet",
        "required": false,
        "type": "string"
    }
],
"responses": {
    "405": {
        "description": "Invalid input"
    }
},
"security": [
    {
        "petstore_auth": ["write:pets",
        "read:pets"]
    }
]
},
"delete": {
    "tags": ["pet"],
    "summary": "Deletes a pet",
    "description": "",
    "operationId": "deletePet",
    "produces": ["application/xml",
    "application/json"],
    "parameters": [
        {
            "name": "api_key",
            "in": "header",
            "required": false,
            "type": "string"
        },
        {
            "name": "petId",
            "in": "path",
            "description": "Pet id to delete",
            "required": true,
            "type": "integer",
            "format": "int64"
        }
    ],
    "responses": {
        "400": {
            "description": "Invalid ID supplied"
        },
        "404": {
            "description": "Pet not found"
        }
    },
    "security": [
        {
            "petstore_auth": ["write:pets",
            "read:pets"]
        }
    ]
}
```

```
        }
    }
},
"/pet/{petId}/uploadImage": {
    "post": {
        "tags": ["pet"],
        "summary": "uploads an image",
        "description": "",
        "operationId": "uploadFile",
        "consumes": ["multipart/form-data"],
        "produces": ["application/json"],
        "parameters": [
            {
                "name": "petId",
                "in": "path",
                "description": "ID of pet to update",
                "required": true,
                "type": "integer",
                "format": "int64"
            },
            {
                "name": "additionalMetadata",
                "in": "formData",
                "description": "Additional data to pass to server",
                "required": false,
                "type": "string"
            },
            {
                "name": "file",
                "in": "formData",
                "description": "file to upload",
                "required": false,
                "type": "file"
            }
        ],
        "responses": {
            "200": {
                "description": "successful operation",
                "schema": {
                    "$ref": "#/definitions/ApiResponse"
                }
            }
        },
        "security": [
            {
                "petstore_auth": ["write:pets",
                    "read:pets"]
            }
        ]
    }
},
"/store/inventory": {
    "get": {
        "tags": ["store"],
        "summary": "Returns pet inventories by status",
        "description": "Returns a map of status codes to quantities",
        "operationId": "getInventory",
        "produces": ["application/json"],
        "parameters": [],
        "responses": {
            "200": {
                "description": "successful operation",
                "schema": {

```

```
        "type": "object",
        "additionalProperties": {
            "type": "integer",
            "format": "int32"
        }
    }
},
"security": [
    "api_key": []
]
}
},
"/store/order": {
    "post": {
        "tags": ["store"],
        "summary": "Place an order for a pet",
        "description": "",
        "operationId": "placeOrder",
        "produces": ["application/xml",
        "application/json"],
        "parameters": [
            {
                "in": "body",
                "name": "body",
                "description": "order placed for purchasing the pet",
                "required": true,
                "schema": {
                    "$ref": "#/definitions/Order"
                }
            }
        ],
        "responses": {
            "200": {
                "description": "successful operation",
                "schema": {
                    "$ref": "#/definitions/Order"
                }
            },
            "400": {
                "description": "Invalid Order"
            }
        }
    }
},
"/store/order/{orderId)": {
    "get": {
        "tags": ["store"],
        "summary": "Find purchase order by ID",
        "description": "For valid response try integer IDs with value 1000 or greater. Recommended test values are 10, 20, 30, 50, 100, 200, 500, 1000, 2000, and 5000",
        "operationId": "getOrderById",
        "produces": ["application/xml",
        "application/json"],
        "parameters": [
            {
                "name": "orderId",
                "in": "path",
                "description": "ID of pet that needs to be fetched",
                "required": true,
                "type": "integer",
                "maximum": 10.0,
                "minimum": 1.0,
                "format": "float"
            }
        ]
    }
}
```

```
        "format": "int64"
    }],
    "responses": {
        "200": {
            "description": "successful operation",
            "schema": {
                "$ref": "#/definitions/Order"
            }
        },
        "400": {
            "description": "Invalid ID supplied"
        },
        "404": {
            "description": "Order not found"
        }
    }
},
"delete": {
    "tags": ["store"],
    "summary": "Delete purchase order by ID",
    "description": "For valid response try integer IDs with positive integer value. Invalid IDs should produce an error response.",
    "operationId": "deleteOrder",
    "produces": ["application/xml",
    "application/json"],
    "parameters": [
        {
            "name": "orderId",
            "in": "path",
            "description": "ID of the order that needs to be deleted",
            "required": true,
            "type": "integer",
            "minimum": 1.0,
            "format": "int64"
        }],
    "responses": {
        "400": {
            "description": "Invalid ID supplied"
        },
        "404": {
            "description": "Order not found"
        }
    }
}
},
"/user": {
    "post": {
        "tags": ["user"],
        "summary": "Create user",
        "description": "This can only be done by the logged in user.",
        "operationId": "createUser",
        "produces": ["application/xml",
        "application/json"],
        "parameters": [
            {
                "in": "body",
                "name": "body",
                "description": "Created user object",
                "required": true,
                "schema": {
                    "$ref": "#/definitions/User"
                }
            }
        ]
    }
}
```

```
        },
        "responses": {
            "default": {
                "description": "successful operation"
            }
        }
    },
    "/user/createWithArray": {
        "post": {
            "tags": ["user"],
            "summary": "Creates list of users with given input array",
            "description": "",
            "operationId": "createUsersWithArrayInput",
            "produces": ["application/xml",
            "application/json"],
            "parameters": [
                {
                    "in": "body",
                    "name": "body",
                    "description": "List of user object",
                    "required": true,
                    "schema": {
                        "type": "array",
                        "items": {
                            "$ref": "#/definitions/User"
                        }
                    }
                }
            ],
            "responses": {
                "default": {
                    "description": "successful operation"
                }
            }
        }
    },
    "/user/createWithList": {
        "post": {
            "tags": ["user"],
            "summary": "Creates list of users with given input array",
            "description": "",
            "operationId": "createUsersWithListInput",
            "produces": ["application/xml",
            "application/json"],
            "parameters": [
                {
                    "in": "body",
                    "name": "body",
                    "description": "List of user object",
                    "required": true,
                    "schema": {
                        "type": "array",
                        "items": {
                            "$ref": "#/definitions/User"
                        }
                    }
                }
            ],
            "responses": {
                "default": {
                    "description": "successful operation"
                }
            }
        }
    }
}
```

```
        }
    },
    "/user/login": {
        "get": {
            "tags": ["user"],
            "summary": "Logs user into the system",
            "description": "",
            "operationId": "loginUser",
            "produces": ["application/xml",
            "application/json"],
            "parameters": [
                {
                    "name": "username",
                    "in": "query",
                    "description": "The user name for login",
                    "required": true,
                    "type": "string"
                },
                {
                    "name": "password",
                    "in": "query",
                    "description": "The password for login in clear text",
                    "required": true,
                    "type": "string"
                }
            ],
            "responses": {
                "200": {
                    "description": "successful operation",
                    "schema": {
                        "type": "string"
                    },
                    "headers": {
                        "X-Rate-Limit": {
                            "type": "integer",
                            "format": "int32",
                            "description": "calls per hour allowed before being blocked by rate limit"
                        },
                        "X-Expires-After": {
                            "type": "string",
                            "format": "date-time",
                            "description": "date in UTC when token expires"
                        }
                    }
                },
                "400": {
                    "description": "Invalid username/password supplied"
                }
            }
        }
    },
    "/user/logout": {
        "get": {
            "tags": ["user"],
            "summary": "Logs out current logged in user session",
            "description": "",
            "operationId": "logoutUser",
            "produces": ["application/xml",
            "application/json"],
            "parameters": []
        }
    }
}
```

```
        "responses": {
            "default": {
                "description": "successful operation"
            }
        }
    },
    "/user/{username}": {
        "get": {
            "tags": ["user"],
            "summary": "Get user by user name",
            "description": "",
            "operationId": "getUserByName",
            "produces": ["application/xml",
            "application/json"],
            "parameters": [
                {
                    "name": "username",
                    "in": "path",
                    "description": "The name that needs to be fetched. Use this to find user based on name",
                    "required": true,
                    "type": "string"
                }],
            "responses": {
                "200": {
                    "description": "successful operation",
                    "schema": {
                        "$ref": "#/definitions/User"
                    }
                },
                "400": {
                    "description": "Invalid username supplied"
                },
                "404": {
                    "description": "User not found"
                }
            }
        },
        "put": {
            "tags": ["user"],
            "summary": "Updated user",
            "description": "This can only be done by the logged in user.",
            "operationId": "updateUser",
            "produces": ["application/xml",
            "application/json"],
            "parameters": [
                {
                    "name": "username",
                    "in": "path",
                    "description": "name that need to be updated",
                    "required": true,
                    "type": "string"
                },
                {
                    "in": "body",
                    "name": "body",
                    "description": "Updated user object",
                    "required": true,
                    "schema": {
                        "$ref": "#/definitions/User"
                    }
                }
            ]
        }
    }
}
```

```
        },
        "responses": {
            "400": {
                "description": "Invalid user supplied"
            },
            "404": {
                "description": "User not found"
            }
        }
    },
    "delete": {
        "tags": ["user"],
        "summary": "Delete user",
        "description": "This can only be done by the logged in user.",
        "operationId": "deleteUser",
        "produces": ["application/xml",
        "application/json"],
        "parameters": [
            {
                "name": "username",
                "in": "path",
                "description": "The name that needs to be deleted",
                "required": true,
                "type": "string"
            }],
        "responses": {
            "400": {
                "description": "Invalid username supplied"
            },
            "404": {
                "description": "User not found"
            }
        }
    }
},
"securityDefinitions": {
    "petstore_auth": {
        "type": "oauth2",
        "authorizationUrl": "http://petstore.swagger.io/oauth/dialog",
        "flow": "implicit",
        "scopes": {
            "write:pets": "modify pets in your account",
            "read:pets": "read your pets"
        }
    },
    "api_key": {
        "type": "apiKey",
        "name": "api_key",
        "in": "header"
    }
},
"definitions": {
    "Order": {
        "type": "object",
        "properties": {
            "id": {
                "type": "integer",
                "format": "int64"
            },
            "name": {
                "type": "string"
            },
            "status": {
                "type": "string"
            }
        }
    }
}
```

```
"petId": {
    "type": "integer",
    "format": "int64"
},
"quantity": {
    "type": "integer",
    "format": "int32"
},
"shipDate": {
    "type": "string",
    "format": "date-time"
},
"status": {
    "type": "string",
    "description": "Order Status",
    "enum": ["placed",
        "approved",
        "delivered"]
},
"complete": {
    "type": "boolean",
    "default": false
}
},
"xml": {
    "name": "Order"
}
},
"Category": {
    "type": "object",
    "properties": {
        "id": {
            "type": "integer",
            "format": "int64"
        },
        "name": {
            "type": "string"
        }
    },
    "xml": {
        "name": "Category"
    }
},
>User": {
    "type": "object",
    "properties": {
        "id": {
            "type": "integer",
            "format": "int64"
        },
        "username": {
            "type": "string"
        },
        "firstName": {
            "type": "string"
        },
        "lastName": {
            "type": "string"
        },
        "password": {
            "type": "string"
        }
    }
},
```

```
        "email": {
            "type": "string"
        },
        "password": {
            "type": "string"
        },
        "phone": {
            "type": "string"
        },
        "userStatus": {
            "type": "integer",
            "format": "int32",
            "description": "User Status"
        }
    },
    "xml": {
        "name": "User"
    }
},
"Tag": {
    "type": "object",
    "properties": {
        "id": {
            "type": "integer",
            "format": "int64"
        },
        "name": {
            "type": "string"
        }
    },
    "xml": {
        "name": "Tag"
    }
},
"Pet": {
    "type": "object",
    "required": ["name", "photoUrls"],
    "properties": {
        "id": {
            "type": "integer",
            "format": "int64"
        },
        "category": {
            "$ref": "#/definitions/Category"
        },
        "name": {
            "type": "string",
            "example": "doggie"
        },
        "photoUrls": {
            "type": "array",
            "xml": {
                "name": "photoUrl",
                "wrapped": true
            },
            "items": {
                "type": "string"
            }
        }
    }
}
```

```
        },
        "tags": {
            "type": "array",
            "xml": {
                "name": "tag",
                "wrapped": true
            },
            "items": {
                "$ref": "#/definitions/Tag"
            }
        },
        "status": {
            "type": "string",
            "description": "pet status in the store",
            "enum": ["available",
            "pending",
            "sold"]
        }
    },
    "xml": {
        "name": "Pet"
    }
},
"ApiResponse": {
    "type": "object",
    "properties": {
        "code": {
            "type": "integer",
            "format": "int32"
        },
        "type": {
            "type": "string"
        },
        "message": {
            "type": "string"
        }
    }
},
"externalDocs": {
    "description": "Find out more about Swagger",
    "url": "http://swagger.io"
}
}
```