

INTRODUCTION TO SQL

SQL (Structured Query Language) is a database computer language designed for the retrieval and management of data in relational database management systems (RDBMS), database schema creation and modification, and database object access control management.

SQL is a programming language for querying and modifying data and managing databases. SQL was standardized first by the ANSI and (later) by the ISO. Most database management systems implement a majority of one of these standards and add their proprietary extensions. SQL allows the retrieval, insertion, updating, and deletion of data.

A database management system also includes management and administrative functions. Most -- if not all -- implementations also include a Command-line Interface (SQL/CLI) that allows for the entry and execution of the language commands, as opposed to only providing an API intended for access from a GUI.

The first version of SQL was developed at IBM by Donald D. Chamberlin and Raymond F. Boyce in the early 1970s. This version, initially called SEQUEL, was designed to manipulate and retrieve data stored in IBM's original relational database product, System R. IBM patented their version of SQL in 1985, while the SQL language was not formally standardized until 1986, by the American National Standards Institute (ANSI) as SQL-86. Subsequent versions of the SQL standard have been released by ANSI and as International Organization for Standardization (ISO) standards.

Originally designed as a declarative query and data manipulation language, variations of SQL have been created by SQL database management system (DBMS) vendors that add procedural constructs, control-of-flow statements, user-defined data types, and various other language extensions. With the release of the SQL:1999 standard, many such extensions were formally adopted as part of the SQL language via the SQL Persistent Stored Modules (SQL/PSM) portion of the standard.

Common criticisms of SQL include a perceived lack of cross-platform portability between vendors, inappropriate handling of missing data (see Null (SQL)), and unnecessarily complex and occasionally ambiguous language grammar and semantics.

FEATURES OF SQL:

SQL is both an easy-to-understand language and a comprehensive tool for managing data. Some of the major features of SQL are

- Vendor independence
- Portability across computer systems
- SQL standards
- IBM endorsement and commitment (DB2)
- Microsoft commitment (SQL Server , ODBC, and ADO)

- Relational foundation
- High-level, English-like structure
- Interactive, ad hoc queries
- Programmatic database access
- Multiple views of data
- Complete database language
- Dynamic data definition
- Client/server architecture
- Enterprise application support
- Extensibility and object technology
- Internet database access
- Java integration (JDBC)
- Industry infrastructure

SQL COMMANDS

SQL Consisting of DDL,DML,DCL,TCL COMMANDS.

DDL

Data Definition Language (DDL) statements are used to define the database structure or schema.

DDL Commands: Create , Alter ,Drop , Rename, Truncate

CREATE - to create objects in the database

ALTER - alters the structure of the database

DROP - delete objects from the database

TRUNCATE - remove all records from a table, including all spaces allocated
for the records are removed

RENAME - rename an object

DML

Data Manipulation Language (DML) statements are used for managing data within schema objects

DML Commands: Insert ,Update, Delete, Select

INSERT - insert data into a table

UPDATE - updates existing data within a table

DELETE - deletes all records from a table, the space for the records remain
SELECT - retrieve data from the a database

DCL

Data Control Language (DCL) statements is used to create roles, permissions, and referential integrity as well it is used to control access to database by securing it.

DCL Commands: Grant, Revoke

GRANT - gives user's access privileges to database

REVOKE - withdraw access privileges given with the GRANT command

TCL

Transaction Control (TCL) statements are used to manage the changes made by DML statements. It allows statements to be grouped together into logical transactions.

TCL Commands: Commit, Rollback, Save point

COMMIT - save work done

SAVEPOINT - identify a point in a transaction to which you can

later roll back

ROLLBACK - restore database to original since the last COMMIT

SYNTAX'S OF COMMANDS

CREATE TABLE

```
CREATE TABLE table_name  
(  
column_name1 data_type,  
column_name2 data_type,  
column_name3 data_type,  
....  
);
```

ALTER A TABLE

To add a column in a table

```
ALTER TABLE table_name  
ADD column_name datatype;
```

To delete a column in a table

ALTER TABLE table_name
DROP COLUMN column_name;

DROP TABLE

DROP TABLE table_name;

TRUNCATE TABLE

TRUNCATE TABLE table_name;

INSERT

INSERT INTO table_name
VALUES (value1, value2, value3,...);

(OR)

INSERT INTO table_name (column1, column2, column3,...)
VALUES (value1, value2, value3,...);

UPDATE

UPDATE table_name
SET column1=value, column2=value2,...
WHERE some_column=some_value;

DELETE

DELETE FROM table_name
WHERE some_column=some_value;

SELECT

SELECT column_name(s)
FROM table_name;

CREATE, INSERT , UPDATE, DELETE, RENAME, TRUNCATE, ON TABLES

SQL>CREATE TABLE STUDENT(SNO NUMBER(5),SNAME VARCHAR2(15),DOJ DATE);

OUTPUT:-TABLE CREATED

```
SQL> INSERT INTO STUDENT100 VALUES(&SNO,&SNAME','&DOJ');
```

OUTPUT:-

Enter value for sno: 501

Enter value for sname: ABI

Enter value for doj: 12-OCT-07

old 1: INSERT INTO STUDENT100 VALUES(&SNO,&SNAME','&DOJ')

new 1: INSERT INTO STUDENT100 VALUES(501,'ABI','12-OCT-07')

1 row created.

```
SQL> /
```

Enter value for sno: 502

Enter value for sname: ASHOK

Enter value for doj: 03-OCT-07

old 1: INSERT INTO STUDENT100 VALUES(&SNO,&SNAME','&DOJ')

new 1: INSERT INTO STUDENT100 VALUES(502,'ASHOK','03-OCT-07')

1 row created.

```
SQL> /
```

Enter value for sno: 503

Enter value for sname: BHAVYA

Enter value for doj: 10-OCT-07

old 1: INSERT INTO STUDENT100 VALUES(&SNO,&SNAME','&DOJ')

new 1: INSERT INTO STUDENT100 VALUES(503,'BHAVYA','10-OCT-07')

1 row created.

```
SQL> /
```

Enter value for sno: 504

Enter value for sname: AKASH

Enter value for doj: 05-OCT-07

old 1: INSERT INTO STUDENT100 VALUES(&SNO,&SNAME','&DOJ')

new 1: INSERT INTO STUDENT100 VALUES(504,'AKASH','05-OCT-07')

1 row created.

SQL> /

Enter value for sno: 505

Enter value for sname: NIKHIL

Enter value for doj: 08-OCT-07

old 1: INSERT INTO STUDENT100 VALUES(&SNO,'&SNAME','&DOJ')

new 1: INSERT INTO STUDENT100 VALUES(505,'NIKHIL','08-OCT-07')

1 row created.

SQL> RENAME STUDENT TO CSESTUDENT;

OUTPUT:-Table renamed.

SQL>SELECT * FROM CSESTUDENT;

OUTPUT:-

| SNO | SNAME | DOJ |
|-----|--------|-----------|
| 501 | ABI | 12-OCT-07 |
| 502 | ASHOK | 03-OCT-07 |
| 503 | BHAVYA | 10-OCT-07 |
| 504 | AKASH | 05-OCT-07 |
| 505 | NIKHIL | 08-OCT-07 |

SQL> UPDATE CSESTUDENT SET SNAME='ABILASH' WHERE SNAME='ABI';

OUTPUT:-1 row updated.

SQL> ALTER TABLE CSESTUDENT ADD BRANCH VARCHAR2(6);

OUTPUT:-Table altered.

SQL> UPDATE CSESTUDENT SET BRANCH='CSE' WHERE SNO=501;

OUTPUT:-1 row updated.

SQL> UPDATE CSESTUDENT SET BRANCH='CSE' WHERE SNO=502;

OUTPUT:-1 row updated.

SQL> UPDATE CSESTUDENT SET BRANCH='CSE' WHERE SNO=503;

OUTPUT:-1 row updated.

SQL> UPDATE CSESTUDENT SET BRANCH='CSE' WHERE SNO=504;

OUTPUT:-1 row updated.

SQL> UPDATE CSESTUDENT SET BRANCH='CSE' WHERE SNO=505;

OUTPUT:-1 row updated.

SQL> SELECT * FROM CSESTUDENT;

| SNO | SNAME | DOJ | BRANCH |
|-----|---------|-----------|--------|
| 501 | ABILASH | 12-OCT-07 | CSE |
| 502 | ASHOK | 03-OCT-07 | CSE |
| 503 | BHAVYA | 10-OCT-07 | CSE |
| 504 | AKASH | 05-OCT-07 | CSE |
| 505 | NIKHIL | 08-OCT-07 | CSE |

SQL> DELETE FROM CSESTUDENT WHERE SNO=501;

OUTPUT:-1 row deleted.

SQL> SELECT * FROM CSESTUDENT;

OUTPUT:-

| SNO | SNAME | DOJ | BRANCH |
|-----|--------|-----------|--------|
| 502 | ASHOK | 03-OCT-07 | CSE |
| 503 | BHAVYA | 10-OCT-07 | CSE |
| 504 | AKASH | 05-OCT-07 | CSE |
| 505 | NIKHIL | 08-OCT-07 | CSE |
| 502 | ASHOK | 03-OCT-07 | CSE |

SQL> DROP TABLE CSESTUDENT;

OUTPUT:-Table dropped.

CREATING TABLES WITH CONSTRAINTS

(NOT NULL)

SQL> CREATE TABLE STUD(ROLLNO NUMBER(6) NOT NULL,NAME
VARCHAR2(10),BRANCH VARCHAR2(6));

Table created.

SQL> DESC STUD;

| Name | Null? | Type |
|--------|----------|--------------|
| ROLLNO | NOT NULL | NUMBER(6) |
| NAME | | VARCHAR2(10) |
| BRANCH | | VARCHAR2(6) |

SQL> INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH);

Enter value for rollno: 501

Enter value for name: ABHILASH

Enter value for branch: CSE

old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH')

new 1: INSERT INTO STUD VALUES(501,'ABHILASH','CSE')

1 row created.

SQL> /

Enter value for rollno: 502

Enter value for name: ABI

Enter value for branch: CSE

old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH')

new 1: INSERT INTO STUD VALUES(502,'ABI','CSE')

1 row created.

SQL> SELECT * FROM STUD;

| ROLLNO | NAME | BRANCH |
|--------|------|--------|
|--------|------|--------|

| | | |
|-----|----------|-----|
| 501 | ABHILASH | CSE |
|-----|----------|-----|


```
SQL> INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH);
```

Enter value for rollno:

Enter value for name: BHAVYA

Enter value for branch: CSE

```
old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH)
```

```
new 1: INSERT INTO STUD VALUES('BHAVYA','CSE')
```

```
INSERT INTO STUD VALUES('BHAVYA','CSE')
```

*

```
ERROR:CANNOT INSERT NULL INTO("SCOTT",'STUD',ROLLNO)
```

(UNIQUE)

```
SQL> CREATE TABLE STUD(ROLLNO NUMBER(6) UNIQUE ,NAME  
VARCHAR2(10),BRANCH VARCHAR2(6));
```

Table created.

```
SQL> INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH);
```

Enter value for rollno: 501

Enter value for name: abhilash

Enter value for branch: cse

```
old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH)
```

```
new 1: INSERT INTO STUD VALUES(501,'abhilash','cse')
```

1 row created.

```
SQL> /
```

Enter value for rollno: 502

Enter value for name: ABI

Enter value for branch: CSE

```
old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH)
```

```
new 1: INSERT INTO STUD VALUES(502,'ABI','CSE')
```

1 row created.

```
SQL> /
```

Enter value for rollno: 502

Enter value for name: BHAVYA

Enter value for branch: CSE

old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH')

new 1: INSERT INTO STUD VALUES(502,'BHAVYA','CSE')

INSERT INTO STUD VALUES(502,'BHAVYA','CSE')

*

ERROR at line 1:

ORA-00001: unique constraint (SCOTT.SYS_C001290) violated

(PRIMARY KEY)

```
SQL> CREATE TABLE STUD(ROLLNO NUMBER(6) PRIMARY KEY,NAME
VARCHAR2(10),BRANCH VARCHAR2(6));
```

Table created.

```
SQL> INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH');
```

Enter value for rollno: 501

Enter value for name: abhilash

Enter value for branch: cse

old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH')

new 1: INSERT INTO STUD VALUES(501,'abhilash','cse')

1 row created.

```
SQL> /
```

Enter value for rollno: 502

Enter value for name: ABI

Enter value for branch: CSE

old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH')

new 1: INSERT INTO STUD VALUES(502,'ABI','CSE')

1 row created.

```
SQL> /
```

Enter value for rollno: 502

Enter value for name: BHAVYA

Enter value for branch: CSE

old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH')

new 1: INSERT INTO STUD VALUES(502,'BHAVYA','CSE')

INSERT INTO STUD VALUES(502,'BHAVYA','CSE')

*

ERROR at line 1:

ORA-00001: unique constraint (SCOTT.SYS_C001290) violated

```
SQL> INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH);
```

Enter value for rollno:

Enter value for name: BHAVYA

Enter value for branch: CSE

```
old 1: INSERT INTO STUD VALUES(&ROLLNO,&NAME,&BRANCH)
```

```
new 1: INSERT INTO STUD VALUES('BHAVYA','CSE')
```

```
INSERT INTO STUD VALUES('BHAVYA','CSE')
```

*

```
ERROR:CANNOT INSERT NULL INTO("SCOTT",'STUD',ROLLNO)
```

```
SQL> SELECT * FROM STUD;
```

| ROLLNO | NAME | BRANCH |
|--------|----------|--------|
| 501 | ABHILASH | CSE |
| 502 | ABI | CSE |

(CHECK)

```
SQL> create table stud(rno number(5),name varchar2(10),sal number(10) constraint no_ck  
check(sal between 10000 and 30000));
```

Table created.

```
SQL> insert into stud values(&rno,&name,&sal);
```

Enter value for rno: 567

Enter value for name: sachin

Enter value for sal: 29000

```
old 1: insert into stud values(&rno,&name,&sal)
```

```
new 1: insert into stud values(567,'sachin',29000)
```

1 row created.

```
SQL> /
```

Enter value for rno: 565

Enter value for name: rohit

Enter value for sal: 35000

```
old 1: insert into stud values(&rno,&name,&sal)
```

```
new 1: insert into stud values(565,'rohit',35000)
```

```
insert into stud values(565,'rohit',35000)
```

*

ERROR at line 1:

ORA-02290: check constraint (SCOTT.NO_CK) violated

(FOREIGN KEY)

```
SOL>create table adm(stuid number(6) constraint stuid_pk primary key,sname varchar2(15),per
number(5));
```

Table created.

```
SQL> insert into adm values(&stuid,&sname',&per);
```

Enter value for stuid: 1

Enter value for sname: abi

Enter value for per: 80

```
old 1: insert into adm values(&stuid,&sname',&per)
```

```
new 1: insert into adm values(1,'abi',80)
```

1 row created.

```
SQL> /
```

Enter value for stuid: 2

Enter value for sname: rohit

Enter value for per: 89

```
old 1: insert into adm values(&stuid,&sname',&per)
```

```
new 1: insert into adm values(2,'rohit',89)
```

1 row created.

```
SQL> /
```

Enter value for stuid: 3

Enter value for sname: sachin

Enter value for per: 99

```
old 1: insert into adm values(&stuid,&sname',&per)
```

```
new 1: insert into adm values(3,'sachin',99)
```

1 row created.

```
SQL> /
```

Enter value for stuid: 4

Enter value for sname: naveen

Enter value for per: 70

```
old 1: insert into adm values(&stuid,&sname',&per)
```

```
new 1: insert into adm values(4,'naveen',70)
```

1 row created.

SQL> select * from adm;

| STUID | SNAME | PER |
|-------|--------|-----|
| 1 | abi | 80 |
| 2 | rohit | 89 |
| 3 | sachin | 99 |
| 4 | naveen | 70 |

SQL> create table course(stuid number(6) constraint sid_fk references adm(stuid),branch varchar2(5),sec varchar2(10));

Table created.

SQL> insert into course values(&stuid,&branch,&sec);

Enter value for stuid: 1

Enter value for branch: cse

Enter value for sec: a

old 1: insert into course values(&stuid,&branch,&sec')

new 1: insert into course values(1,'cse','a')

1 row created.

SQL> /

Enter value for stuid: 5

Enter value for branch: cse

Enter value for sec: b

old 1: insert into course values(&stuid,&branch,&sec')

new 1: insert into course values(5,'cse','b')

insert into course values(5,'cse','b')

*

ERROR at line 1:

ORA-02291: integrity constraint (SCOTT.SID_FK) violated - parent key not found

SQL> delete from adm where stuid=1;

*

ERROR at line 1:

ORA-02292: integrity constraint (SCOTT.SID_FK) violated - child record found

SQL> delete from course where stuid=1;

1 row deleted.

SQL> delete from adm where stuid=1;

1 row deleted.

SQL>select * from adm;

| STUID | SNAME | PER |
|-------|--------|-----|
| 2 | rohit | 89 |
| 3 | sachin | 99 |
| 4 | naveen | 70 |

CREATING AND DROPIING OF VIEWS

SQL> select * from emp2;

OUTPUT:-

| ENAME | STREET | CITY |
|----------|----------|--------------|
| coyote | toon | hollywood |
| rabbit | tunnel | carrot ville |
| smith | revolver | death valley |
| williams | sea view | sea attle |

SQL> create view emp22 as select * from emp2;

OUTPUT:-

View created.

SQL> select * from emp22;

OUTPUT:-

| ENAME | STREET | CITY |
|----------|----------|--------------|
| coyote | toon | hollywood |
| rabbit | tunnel | carrot ville |
| smith | revolver | death valley |
| williams | sea view | sea attle |

SQL> update emp22 set city='hyd' where ename='coyote';

OUTPUT:-

1 row updated.

SQL> select * from emp2;

OUTPUT:-

| ENAME | STREET | CITY |
|----------|----------|--------------|
| coyote | toon | hyd |
| rabbit | tunnel | carrot ville |
| smith | revolver | death valley |
| williams | sea view | sea attle |

SQL> select * from emp22;

OUTPUT:-

| ENAME | STREET | CITY |
|----------|----------|--------------|
| coyote | toon | hyd |
| rabbit | tunnel | carrot ville |
| smith | revolver | death valley |
| williams | sea view | sea attle |

SQL> drop table emp2;

OUTPUT:-

Table dropped.

SQL> select * from emp22;

OUTPUT:-

select * from emp22
*

ERROR at line 1:

ORA-04063: view "SCOTT.EMP22" has errors

DCL AND TCL COMMANDS

CREATING A USER

SQL>CONNECT SYSTEM/MANAGER;

SQL>CREATE USER "USERNAME" IDENTIFIED BY "PASSWORD"

SQL>GRANT DBA TO "USERNAME"

SQL>CONNECT "USERNAME"/"PASSWORD";

EXAMPLE

CREATING A USER

SQL>CONNECT SYSTEM/MANAGER;

SQL>CREATE USER CSE2 IDENTIFIED BY CSECSE;

SQL>GRANT DBA TO CSE2;

SQL>CONNECT CSE2/CSECSE;

SQL>REVOKE DBA FROM CSE2;

IMPLEMENTING COMMIT, SAVEPOINT, ROLLBACK

SQL> select * from emp1;

OUTPUT:-

| EID | ENAME | ESAL | EBRANCH |
|-----|--------|-------|---------|
| 1 | scotty | 6000 | a |
| 2 | wayne | 10000 | b |
| 3 | david | 7000 | c |
| 4 | max | 8000 | b |
| 5 | mark | 7000 | a |
| 6 | jeff | 12000 | a |
| 7 | matt | 10000 | b |
| 8 | steve | 7000 | c |

8 rows selected.

SQL> savepoint s1;

OUTPUT:-
Savepoint created.

SQL> update emp1 set esal=6500 where ename='scotty';

OUTPUT:-
1 row updated.

SQL> savepoint s2;

OUTPUT:-
Savepoint created.

SQL> delete from emp1 where ename='wayne';

OUTPUT:-
1 row deleted.

SQL> savepoint s3;

OUTPUT:-
Savepoint created.

SQL> insert into emp1 values(9,'bruce',11000,'c');

OUTPUT:-
1 row created.

SQL> select * from emp1;

OUTPUT:-

| EID | ENAME | ESAL | EBRANCH |
|-----|--------|-------|---------|
| 1 | scotty | 6500 | a |
| 3 | david | 7000 | c |
| 4 | max | 8000 | b |
| 5 | mark | 7000 | a |
| 6 | jeff | 12000 | a |
| 7 | matt | 10000 | b |
| 8 | steve | 7000 | c |

9 bruce 11000 c

8 rows selected.

SQL> rollback to s3;

OUTPUT:-

Rollback complete.

SQL> select * from emp1;

OUTPUT:-

| EID | ENAME | ESAL | EBRANCH |
|-----|--------|-------|---------|
| 1 | scotty | 6500 | a |
| 3 | david | 7000 | c |
| 4 | max | 8000 | b |
| 5 | mark | 7000 | a |
| 6 | jeff | 12000 | a |
| 7 | matt | 10000 | b |
| 8 | steve | 7000 | c |

SQL> rollback to s2;

OUTPUT:-

Rollback complete.

SQL> select * from emp1;

OUTPUT:-

| EID | ENAME | ESAL | EBRANCH |
|-----|--------|-------|---------|
| 1 | scotty | 6500 | a |
| 2 | wayne | 10000 | b |
| 3 | david | 7000 | c |
| 4 | max | 8000 | b |
| 5 | mark | 7000 | a |
| 6 | jeff | 12000 | a |
| 7 | matt | 10000 | b |
| 8 | steve | 7000 | c |

SQL> rollback to s1;

OUTPUT:-

Rollback complete.

SQL> select * from emp1;

OUTPUT:-

| EID | ENAME | ESAL | EBRANCH |
|-------|--------|-------|---------|
| ----- | ----- | ----- | ----- |
| 1 | scotty | 6000 | a |
| 2 | wayne | 10000 | b |
| 3 | david | 7000 | c |
| 4 | max | 8000 | b |
| 5 | mark | 7000 | a |
| 6 | jeff | 12000 | a |
| 7 | matt | 10000 | b |
| 8 | steve | 7000 | c |

SQL> savepoint s4;

OUTPUT:-

Savepoint created.

SQL> delete from emp1 where eid=1;

OUTPUT:-

1 row deleted.

SQL> select * from emp1;

OUTPUT:-

| EID | ENAME | ESAL | EBRANCH |
|-------|-------|-------|---------|
| ----- | ----- | ----- | ----- |
| 2 | wayne | 10000 | b |
| 3 | david | 7000 | c |
| 4 | max | 8000 | b |

| | | | |
|---|-------|-------|---|
| 5 | mark | 7000 | a |
| 6 | jeff | 12000 | a |
| 7 | matt | 10000 | b |
| 8 | steve | 7000 | c |

7 rows selected.

SQL> commit;

OUTPUT:-

Commit complete.

SQL> rollback to s4;

OUTPUT:-

*

ERROR at line 1:

ORA-01086 :savepoint 's4' never established

SQL> select * from emp1;

OUTPUT:-

| EID | ENAME | ESAL | EBRANCH |
|-----|-------|-------|---------|
| 2 | wayne | 10000 | b |
| 3 | david | 7000 | c |
| 4 | max | 8000 | b |
| 5 | mark | 7000 | a |
| 6 | jeff | 12000 | a |
| 7 | matt | 10000 | b |
| 8 | steve | 7000 | c |

7 rows selected.

DRL-DATA RETRIEVAL LANGUAGE

IMPLEMENTING SELECT COMMANDS

SQL> select * from emp;

| EMPNO | ENAME | JOB | MGR | HIREDATE | SAL | COMM | DEPTNO |
|-------|--------|-----------|------|-----------|------|--------|--------|
| 7369 | SMITH | CLERK | 7902 | 17-DEC-80 | 800 | 20 | |
| 7499 | ALLEN | SALESMAN | 7698 | 20-FEB-81 | 1600 | 300 30 | |
| 7521 | WARD | SALESMAN | 7698 | 22-FEB-81 | 1250 | 500 30 | |
| 7566 | JONES | MANAGER | 7839 | 02-APR-81 | 2975 | 20 | |
| 7654 | MARTIN | SALESMAN | 7698 | 28-SEP-81 | 1250 | 1400 | |
| 7698 | BLAKE | MANAGER | 7839 | 01-MAY-81 | 2850 | 30 | |
| 7782 | CLARK | MANAGER | 7839 | 09-JUN-81 | 2450 | 10 | |
| 7788 | SCOTT | ANALYST | 7566 | 19-APR-87 | 3000 | 20 | |
| 7839 | KING | PRESIDENT | | 17-NOV-81 | 5000 | 10 | |
| 7844 | TURNER | SALESMAN | 7698 | 08-SEP-81 | 1500 | 0 30 | |
| 7876 | ADAMS | CLERK | 7788 | 23-MAY-87 | 1100 | 20 | |
| 7900 | JAMES | CLERK | 7698 | 03-DEC-81 | 950 | 30 | |
| 7902 | FORD | ANALYST | 7566 | 03-DEC-81 | 3000 | 20 | |

7934 MILLER CLERK 7782 23-JAN-82 1300 10

14 rows selected.

SQL> select empno,ename,sal from emp;

| EMPNO | ENAME | SAL |
|-------|--------|------|
| 7369 | SMITH | 800 |
| 7499 | ALLEN | 1600 |
| 7521 | WARD | 1250 |
| 7566 | JONES | 2975 |
| 7654 | MARTIN | 1250 |
| 7698 | BLAKE | 2850 |
| 7782 | CLARK | 2450 |
| 7788 | SCOTT | 3000 |
| 7839 | KING | 5000 |
| 7844 | TURNER | 1500 |
| 7876 | ADAMS | 1100 |

| EMPNO | ENAME | SAL |
|-------|--------|------|
| 7900 | JAMES | 950 |
| 7902 | FORD | 3000 |
| 7934 | MILLER | 1300 |

14 rows selected.

SQL> select empno,ename,sal from emp where sal between 2500 and 5000;

| EMPNO | ENAME | SAL |
|-------|-------|------|
| 7566 | JONES | 2975 |
| 7698 | BLAKE | 2850 |
| 7788 | SCOTT | 3000 |
| 7839 | KING | 5000 |
| 7902 | FORD | 3000 |

SQL>select ename,job,sal,deptno from emp where sal not between 1500 and 5000;

| ENAME | JOB | SAL | DEPTNO |
|-------|-----|-----|--------|
|-------|-----|-----|--------|

| | | | |
|--------|----------|------|----|
| SMITH | CLERK | 800 | 20 |
| WARD | SALESMAN | 1250 | 30 |
| MARTIN | SALESMAN | 1250 | 30 |
| ADAMS | CLERK | 1100 | 20 |
| JAMES | CLERK | 950 | 30 |
| MILLER | CLERK | 1300 | 10 |

6 rows selected.

SQL> select empno,ename,sal from emp where sal in (800,5000);

| EMPNO | ENAME | SAL |
|-------|-------|------|
| 7369 | SMITH | 800 |
| 7839 | KING | 5000 |

SQL> select empno,ename,sal from emp where sal not in(800,1250,3000,5000);

| EMPNO | ENAME | SAL |
|-------|--------|------|
| 7499 | ALLEN | 1600 |
| 7566 | JONES | 2975 |
| 7698 | BLAKE | 2850 |
| 7782 | CLARK | 2450 |
| 7844 | TURNER | 1500 |
| 7876 | ADAMS | 1100 |
| 7900 | JAMES | 950 |
| 7934 | MILLER | 1300 |

8 rows selected.

SQL> select empno,ename,sal from emp where comm is null;

| EMPNO | ENAME | SAL |
|-------|-------|------|
| 7369 | SMITH | 800 |
| 7566 | JONES | 2975 |
| 7698 | BLAKE | 2850 |
| 7782 | CLARK | 2450 |
| 7788 | SCOTT | 3000 |
| 7839 | KING | 5000 |
| 7876 | ADAMS | 1100 |

| | |
|-------------|------|
| 7900 JAMES | 950 |
| 7902 FORD | 3000 |
| 7934 MILLER | 1300 |

10 rows selected.

SQL> select empno,ename,sal from emp where comm is not null;

| EMPNO | ENAME | SAL |
|-------|--------|------|
| 7499 | ALLEN | 1600 |
| 7521 | WARD | 1250 |
| 7654 | MARTIN | 1250 |
| 7844 | TURNER | 1500 |

SQL> select empno,ename,job,sal from emp where ename like 'S%';

| EMPNO | ENAME | JOB | SAL |
|-------|-------|---------|------|
| 7369 | SMITH | CLERK | 800 |
| 7788 | SCOTT | ANALYST | 3000 |

SQL> select empno,ename,job,sal from emp where job not like 'S%';

| EMPNO | ENAME | JOB | SAL |
|-------|--------|-----------|------|
| 7369 | SMITH | CLERK | 800 |
| 7566 | JONES | MANAGER | 2975 |
| 7698 | BLAKE | MANAGER | 2850 |
| 7782 | CLARK | MANAGER | 2450 |
| 7788 | SCOTT | ANALYST | 3000 |
| 7839 | KING | PRESIDENT | 5000 |
| 7876 | ADAMS | CLERK | 1100 |
| 7900 | JAMES | CLERK | 950 |
| 7902 | FORD | ANALYST | 3000 |
| 7934 | MILLER | CLERK | 1300 |

10 rows selected.

SQL> select ename,job,sal from emp where sal>2500;

| ENAME | JOB | SAL |
|-------|-----------|------|
| JONES | MANAGER | 2975 |
| BLAKE | MANAGER | 2850 |
| SCOTT | ANALYST | 3000 |
| KING | PRESIDENT | 5000 |
| FORD | ANALYST | 3000 |

SQL> select ename,job,sal from emp where sal<2500;

| ENAME | JOB | SAL |
|--------|----------|------|
| SMITH | CLERK | 800 |
| ALLEN | SALESMAN | 1600 |
| WARD | SALESMAN | 1250 |
| MARTIN | SALESMAN | 1250 |
| CLARK | MANAGER | 2450 |
| TURNER | SALESMAN | 1500 |
| ADAMS | CLERK | 1100 |
| JAMES | CLERK | 950 |
| MILLER | CLERK | 1300 |

9 rows selected.

SQL> select empno,ename,job,sal from emp order by sal;

| EMPNO | ENAME | JOB | SAL |
|-------|--------|----------|------|
| 7369 | SMITH | CLERK | 800 |
| 7900 | JAMES | CLERK | 950 |
| 7876 | ADAMS | CLERK | 1100 |
| 7521 | WARD | SALESMAN | 1250 |
| 7654 | MARTIN | SALESMAN | 1250 |
| 7934 | MILLER | CLERK | 1300 |
| 7844 | TURNER | SALESMAN | 1500 |
| 7499 | ALLEN | SALESMAN | 1600 |
| 7782 | CLARK | MANAGER | 2450 |
| 7698 | BLAKE | MANAGER | 2850 |
| 7566 | JONES | MANAGER | 2975 |

| EMPNO | ENAME | JOB | SAL |
|-------|-------|---------|------|
| 7788 | SCOTT | ANALYST | 3000 |
| 7902 | FORD | ANALYST | 3000 |

7839 KING PRESIDENT 5000

14 rows selected.

SQL> select empno,ename,job,sal from emp order by sal desc;

| EMPNO | ENAME | JOB | SAL |
|-------|--------|-----------|------|
| 7839 | KING | PRESIDENT | 5000 |
| 7788 | SCOTT | ANALYST | 3000 |
| 7902 | FORD | ANALYST | 3000 |
| 7566 | JONES | MANAGER | 2975 |
| 7698 | BLAKE | MANAGER | 2850 |
| 7782 | CLARK | MANAGER | 2450 |
| 7499 | ALLEN | SALESMAN | 1600 |
| 7844 | TURNER | SALESMAN | 1500 |
| 7934 | MILLER | CLERK | 1300 |
| 7521 | WARD | SALESMAN | 1250 |
| 7654 | MARTIN | SALESMAN | 1250 |

| EMPNO | ENAME | JOB | SAL |
|-------|-------|-------|------|
| 7876 | ADAMS | CLERK | 1100 |
| 7900 | JAMES | CLERK | 950 |
| 7369 | SMITH | CLERK | 800 |

14 rows selected.

SUBQUERIES (APPLYING IN, ALL, ANY, EXISTS, NOT EXISTS, UNION, INTERSECT, MINUS)

SQL>select * from emp;

OUTPUT:-

| EMPNO | ENAME | JOB | MGR | HIREDATE | SAL | COMM |
|-------|-------|----------|------|-----------|------|--------|
| 7369 | SMITH | CLERK | 7902 | 17-DEC-80 | 800 | 20 |
| 7499 | ALLEN | SALESMAN | 7698 | 20-FEB-81 | 1600 | 300 30 |
| 7521 | WARD | SALESMAN | 7698 | 22-FEB-81 | 1250 | 500 30 |

| | | | | | | | |
|------|--------|-----------|------|-----------|------|------|----|
| 7566 | JONES | MANAGER | 7839 | 02-APR-81 | 2975 | | 20 |
| 7654 | MARTIN | SALESMAN | 7698 | 28-SEP-81 | 1250 | 1400 | 30 |
| 7698 | BLAKE | MANAGER | 7839 | 01-MAY-81 | 2850 | | 30 |
| 7782 | CLARK | MANAGER | 7839 | 09-JUN-81 | 2450 | | 10 |
| 7788 | SCOTT | ANALYST | 7566 | 19-APR-87 | 3000 | | 20 |
| 7839 | KING | PRESIDENT | | 17-NOV-81 | 5000 | | 10 |
| 7844 | TURNER | SALESMAN | 7698 | 08-SEP-81 | 1500 | 0 | 30 |
| 7876 | ADAMS | CLERK | 7788 | 23-MAY-87 | 1100 | | 20 |
| 7900 | JAMES | CLERK | 7698 | 03-DEC-81 | 950 | | 30 |
| 7902 | FORD | ANALYST | 7566 | 03-DEC-81 | 3000 | | 20 |
| 7934 | MILLER | CLERK | 7782 | 23-JAN-82 | 1300 | | 10 |

SQL>select * from dept;

OUTPUT:-

| DEPTNO | DNAME | LOC |
|--------|------------|----------|
| ----- | ----- | ----- |
| 10 | ACCOUNTING | NEW YORK |
| 20 | RESEARCH | DALLAS |
| 30 | SALES | CHICAGO |
| 40 | OPERATIONS | BOSTON |

SQL> select * from emp where sal in(3000,5000);

OUTPUT:-

| EMPNO | ENAME | JOB | MGR | HIREDATE | SAL | COMM |
|--------|-------|-----------|------|-----------|-----|------|
| DEPTNO | | | | | | |
| 7788 | SCOTT | ANALYST | 7566 | 19-APR-87 | | 3000 |
| 7839 | KING | PRESIDENT | | 17-NOV-81 | | 5000 |
| 7902 | FORD | ANALYST | 7566 | 03-DEC-81 | | 3000 |

SQL> select empno,ename from emp where sal in(select max(sal) from emp);

OUTPUT:-

| EMPNO | ENAME |
|-------|-------|
| 7839 | KING |

SQL> select empno,ename from emp where sal in(select max(sal) from emp group by deptno);

OUTPUT:-

| EMPNO | ENAME |
|-------|-------|
| 7698 | BLAKE |
| 7788 | SCOTT |
| 7902 | FORD |
| 7839 | KING |

SQL> select empno,ename,job,sal from emp where sal>all(select avg(sal) from emp group by deptno);

OUTPUT:-

| EMPNO | ENAME | JOB | SAL |
|-------|-------|-----------|------|
| 7566 | JONES | MANAGER | 2975 |
| 7788 | SCOTT | ANALYST | 3000 |
| 7839 | KING | PRESIDENT | 5000 |
| 7902 | FORD | ANALYST | 3000 |

SQL> select empno,ename,job,sal from emp where sal<all(select avg(sal) from emp group by deptno);

OUTPUT:-

| EMPNO | ENAME | JOB | SAL |
|-------|--------|----------|------|
| 7369 | SMITH | CLERK | 800 |
| 7521 | WARD | SALESMAN | 1250 |
| 7654 | MARTIN | SALESMAN | 1250 |
| 7844 | TURNER | SALESMAN | 1500 |
| 7876 | ADAMS | CLERK | 1100 |
| 7900 | JAMES | CLERK | 950 |
| 7934 | MILLER | CLERK | 1300 |

7 rows selected.

SQL> select ename,job,sal from emp where sal>any(select sal from emp where job='CLERK');

OUTPUT:-

| ENAME | JOB | SAL |
|--------|-----------|------|
| ALLEN | SALESMAN | 1600 |
| WARD | SALESMAN | 1250 |
| JONES | MANAGER | 2975 |
| MARTIN | SALESMAN | 1250 |
| BLAKE | MANAGER | 2850 |
| CLARK | MANAGER | 2450 |
| SCOTT | ANALYST | 3000 |
| KING | PRESIDENT | 5000 |
| TURNER | SALESMAN | 1500 |
| ADAMS | CLERK | 1100 |
| JAMES | CLERK | 950 |

| ENAME | JOB | SAL |
|--------|---------|------|
| FORD | ANALYST | 3000 |
| MILLER | CLERK | 1300 |

13 rows selected.

SQL> select ename,job,sal from emp where sal<any(select sal from emp where job='CLERK');

OUTPUT:-

| ENAME | JOB | SAL |
|-------|-----|-----|
|-------|-----|-----|

| | | |
|--------|----------|------|
| SMITH | CLERK | 800 |
| WARD | SALESMAN | 1250 |
| MARTIN | SALESMAN | 1250 |
| ADAMS | CLERK | 1100 |
| JAMES | CLERK | 950 |

SQL> select ename,job,sal from emp where sal=any(select sal from emp where job='CLERK');

OUTPUT:-

| ENAME | JOB | SAL |
|--------|-------|------|
| SMITH | CLERK | 800 |
| JAMES | CLERK | 950 |
| ADAMS | CLERK | 1100 |
| MILLER | CLERK | 1300 |

SQL> select deptno,dname from dept d where exists(select * from emp e where d.deptno=e.deptno);

OUTPUT:-

| DEPTNO | DNAME |
|--------|------------|
| 10 | ACCOUNTING |
| 20 | RESEARCH |
| 30 | SALES |

SQL> select deptno,dname from dept d where not exists(select * from emp e where d.deptno=e.deptno);

OUTPUT:-

| DEPTNO | DNAME |
|--------|------------|
| 40 | OPERATIONS |

SQL> create table s1(sid number(5),sname varchar2(10),rating number(5),age number(10));

Table created.

SQL> insert into s1 values(&sid,'&sname',&rating,&age);

Enter value for sid: 22
Enter value for sname: dustin
Enter value for rating: 7
Enter value for age: 45
old 1: insert into s1 values(&sid,&sname',&rating,&age)
new 1: insert into s1 values(22,'dustin',7,45)

1 row created.

SQL> /
Enter value for sid: 31
Enter value for sname: lubber
Enter value for rating: 8
Enter value for age: 56
old 1: insert into s1 values(&sid,&sname',&rating,&age)
new 1: insert into s1 values(31,'lubber',8,56)

1 row created.

SQL> /
Enter value for sid: 58
Enter value for sname: rusty
Enter value for rating: 10
Enter value for age: 35
old 1: insert into s1 values(&sid,&sname',&rating,&age)
new 1: insert into s1 values(58,'rusty',10,35)

1 row created.

SQL> create table s2(sid number(5),sname varchar2(10),rating number(5),age number(10));

Table created.

SQL> insert into s2 values(&sid,&sname',&rating,&age);
Enter value for sid: 28
Enter value for sname: yuppy
Enter value for rating: 9
Enter value for age: 25
old 1: insert into s2 values(&sid,&sname',&rating,&age)
new 1: insert into s2 values(28,'yuppy',9,25)

1 row created.

SQL> /
Enter value for sid: 31
Enter value for sname: lubber

Enter value for rating: 8
Enter value for age: 55
old 1: insert into s2 values(&sid,&sname,&rating,&age)
new 1: insert into s2 values(31,'lubber',8,55)

1 row created.

SQL> /
Enter value for sid: 44
Enter value for sname: guppy
Enter value for rating: 5
Enter value for age: 35
old 1: insert into s2 values(&sid,&sname,&rating,&age)
new 1: insert into s2 values(44,'guppy',5,35)

1 row created.

SQL> /
Enter value for sid: 58
Enter value for sname: rusty
Enter value for rating: 10
Enter value for age: 35
old 1: insert into s2 values(&sid,&sname,&rating,&age)
new 1: insert into s2 values(58,'rusty',10,35)

1 row created.

SQL> select * from s2;

| SID | SNAME | RATING | AGE |
|-----|--------|--------|-----|
| 28 | yuppy | 9 | 25 |
| 31 | lubber | 8 | 55 |
| 44 | guppy | 5 | 35 |
| 58 | rusty | 10 | 35 |

SQL> select sname from s1 union select sname from s2;

SNAME

dustin
guppy
lubber
rusty
yuppy

SQL> select sname from s1 union select sname from s2;

SNAME

dustin
lubber
rusty
yuppy
lubber
guppy
rusty

7 rows selected.

SQL> select sid from s1 intersect select sid from s2;

SID

31
58

SQL> select age from s1 minus select age from s2;

AGE

45
56

FUNCTIONS:

AGGREGATE FUNCTIONS

SQL> SELECT * FROM EMP;

output:-

| ENO | ENAME | JOB | SAL |
|------|-------|----------|------|
| 1001 | STEVE | SALESMAN | 1500 |
| 1002 | ADAM | CLERK | 1000 |
| 1003 | EVE | MANAGER | 5220 |
| 1004 | JAMES | DIRECTOR | 7000 |

SQL> SELECT COUNT(*)FROM EMP;

output:-

| COUNT(*) |
|----------|
| 4 |

SQL> SELECT SUM(SAL) FROM EMP;

output:-

| SUM(SAL) |
|----------|
| 14720 |

SQL> SELECT AVG(SAL) FROM EMP;

output:-

| AVG(SAL) |
|----------|
| 3680 |

SQL> SELECT MAX(SAL) FROM EMP;

output:-

| MAX(SAL) |
|----------|
| 7000 |

SQL> SELECT MIN(SAL) FROM EMP;

output:-

MIN(SAL)

1000

SQL>select * from emp;

OUTPUT:-

| EMPNO | ENAME | JOB | SAL | DEPTNO |
|-------|--------|-----------|------|--------|
| 7369 | SMITH | CLERK | 800 | 20 |
| 7499 | ALLEN | SALESMAN | 1600 | 30 |
| 7521 | WARD | SALESMAN | 1250 | 30 |
| 7566 | JONES | MANAGER | 2975 | 20 |
| 7654 | MARTIN | SALESMAN | 1250 | 30 |
| 7698 | BLAKE | MANAGER | 2850 | 30 |
| 7782 | CLARK | MANAGER | 2450 | 10 |
| 7788 | SCOTT | ANALYST | 3000 | 20 |
| 7839 | KING | PRESIDENT | 5000 | 10 |
| 7844 | TURNER | SALESMAN | 1500 | 30 |
| 7876 | ADAMS | CLERK | 1100 | 20 |
| 7900 | JAMES | CLERK | 950 | 30 |
| 7902 | FORD | ANALYST | 3000 | 20 |
| 7934 | MILLER | CLERK | 1300 | 10 |

14 rows selected.

APPLYING BY GROUP BY ---

SQL> select deptno,max(sal) from emp group by deptno;

OUTPUT:-

| DEPTNO | MAX(SAL) |
|--------|----------|
| 10 | 5000 |

| | |
|----|------|
| 20 | 3000 |
| 30 | 2850 |

SQL> select deptno,min(sal) from emp group by deptno;

OUTPUT:-

| DEPTNO | MIN(SAL) |
|--------|----------|
| ----- | ----- |
| 10 | 1300 |
| 20 | 800 |
| 30 | 950 |

SQL> select deptno,max(sal) from emp group by deptno having max(sal)<3000;

OUTPUT:-

| DEPTNO | MAX(SAL) |
|--------|----------|
| ----- | ----- |
| 30 | 2850 |

SQL>select deptno,min(sal) from emp group by deptno having min(sal)>1000;

OUTPUT:-

| DEPTNO | MIN(SAL) |
|--------|----------|
| ----- | ----- |
| 10 | 1300 |

SQL> select ename,count(*) from emp group by deptno;

OUTPUT:-

| DEPTNO | COUNT(*) |
|--------|----------|
| ----- | ----- |
| 10 | 3 |
| 20 | 5 |
| 30 | 6 |

3 rows selected.

CONVERSION FUNCTIONS(TO_CHAR)

SQL>select to_char(65,'RN')from dual;

OUTPUT:LXV

SQL>select to_char(65,'rn')from dual;

OUTPUT:lxv

SQL>select to_char(58,'s9999')from dual;

OUTPUT:+58

SQL>select to_char(-100,'s9999')from dual;

OUTPUT:-100

SQL> select to_char(41,'XXXX')from dual;

OUTPUT:29

SQL> select to_char(10,'XXXX')from dual;

OUTPUT:A

SQL> select to_char(sysdate,'day')from dual;

OUTPUT:MONDAY

SQL> SELECT TO_CHAR(SYSDATE,'MONTH')FROM DUAL;

OUTPUT:JANUARY

SQL> SELECT TO_CHAR(SYSDATE,'YEAR')FROM DUAL;

OUTPUT:TWO THOUSAND NINE

SQL> select to_char(123456,'9g99g999')from dual;

OUTPUT:1,23,456

SQL> select to_char(1234,'l9999')from dual;

OUTPUT:\$1234

SQL> select to_char(123456,'9g99g999d999')from dual;

OUTPUT:1,23,456.000

SELECT TO_CHAR(2234,'L9999','NLS_CURRENCY=RS')FROM DUAL;

OUTPUT:RS2234

STRING FUNCTIONS

SQL>SELECT CONCAT('ORACLE','CORPORATION')FROM DUAL;

OUTPUT:-ORACLECORPORATION

SQL>SELECT LPAD('ORACLE',15,'*')FROM DUAL;

OUTPUT:-*****ORACLE

SQL>SELECT RPAD('ORACLE',15,'*')FROM DUAL;

OUTPUT:-ORACLE*****

SQL>SELECT LTRIM('SSMITHSS','S')FROM DUAL;

OUTPUT:-MITHSS

SQL>SELECT RTRIM('SSMITHSS','S')FROM DUAL;

OUTPUT:-SSMITH

SQL>SELECT LOWER('DBMS')FROM DUAL;

OUTPUT:-dbms

SQL>SELECT UPPER('dbms')FROM DUAL;

OUTPUT:-DBMS

SQL>SELECT INITCAP('ORACLE','CORPORATION')FROM DUAL;

OUTPUT:-Oracle Corporation

SQL>SELECT LENGTH('DATABASE')FROM DUAL;

OUTPUT:-8

SQL>SELECT SUBSTR('ABCDEFGHIJ',3,4)FROM DUAL;

OUTPUT:-CDEF

SQL>SELECT INSTR('CORPORATE FLOOR','OR',3,2)FROM DUAL;

OUTPUT:-14

DATE FUNCTIONS

SQL>SELECT SYSDATE FROM DUAL;

OUTPUT:-29-DEC-08

SQL>SELECT NEXT_DAY(SYSDATE,'WED')FROM DUAL;

OUTPUT:-05-JAN-09

SQL>SELECT ADD_MONTHS(SYSDATE,2)FROM DUAL;

OUTPUT:-28-FEB-09

SQL>SELECT LAST_DAY(SYSDATE)FROM DUAL;

OUTPUT:-31-DEC-08

SQL>SELECT MONTHS_BETWEEN(SYSDATE,HIREDATE)FROM EMP;

OUTPUT:-

SQL>SELECT LEAST('10-JAN-07','12-OCT-07')FROM DUAL;

OUTPUT:-10-JAN-07

SQL>SELECT GREATEST('10-JAN-07','12-OCT-07')FROM DUAL;

OUTPUT:-10-JAN-07

SQL>SELECT TRUNC(SYSDATE,'DAY')FROM DUAL;

OUTPUT:-28-DEC-08

SQL>SELECT TRUNC(SYSDATE,'MONTH')FROM DUAL;

OUTPUT:-01-DEC-08

SQL>SELECT TRUNC(SYSDATE,'YEAR')FROM DUAL;

OUTPUT:-01-JAN-08

SQL>SELECT ROUND(SYSDATE,'DAY')FROM DUAL;

OUTPUT:-28-DEC-08

SQL>SELECT ROUND(SYSDATE,'MONTH')FROM DUAL;

OUTPUT:-01-JAN-09

SQL>SELECT ROUND(SYSDATE,'YEAR')FROM DUAL;

OUTPUT:-01-JAN-09

NUMBER FUNCTIONS

SQL> select round(12.36), round(14.63) from dual;

OUTPUT:-

| ROUND(12.36) | ROUND(14.63) |
|--------------|--------------|
| ----- | ----- |
| 12 | 15 |

SQL> select floor(12.87), floor(11.23) from dual;

OUTPUT:-

| FLOOR(12.87) | FLOOR(11.23) |
|--------------|--------------|
| ----- | ----- |
| 12 | 11 |

SQL> select ceil(16.23), ceil(12.78) from dual;

OUTPUT:-

| CEIL(16.23) | CEIL(12.78) |
|-------------|-------------|
| ----- | ----- |
| 17 | 13 |

SQL> select trunc(56.63) from dual;

OUTPUT:-

TRUNC(56.63)

56

SQL> select mod(11,4) from dual;

OUTPUT:-

MOD(11,4)

3

SQL> select power(2,3) from dual;

OUTPUT:-

POWER(2,3)

8

SQL> select sign(0),sign(34),sign(-56) from dual;

OUTPUT:-

| SIGN(0) | SIGN(34) | SIGN(-56) |
|---------|----------|-----------|
| ----- | ----- | ----- |
| 0 | 1 | -1 |

SQL> select abs(12),abs(-89) from dual;

OUTPUT:-

| ABS(12) | ABS(-89) |
|---------|----------|
| ----- | ----- |
| 12 | 89 |

SQL> select sqrt(25) from dual;

OUTPUT:-

SQRT(25)

5

INTRODUCTION TO PL/SQL

PL/SQL stands for PROCEDURAL Language Extensions to SQL.

PL/SQL extends SQL by adding programming structures and subroutines available in any high level language.

PL/SQL can be used for both server-side and Client side Development.

PL/SQL has syntax and rules that determine how programming statements work together.

PL/SQL is not a stand alone Programming Language.

PL/SQL is a part of the ORACLE RDBMS and hence can reside in two environments, the CLIENT and the SERVER.

Any MODULE that is developed using PL/SQL can be moved easily between SERVER SIDE and CLIENT SIDE applications.

Either in CLIENT/SERVER environments any PL/SQL Block or the PL/SQL Engine processes Subroutine.

PL/SQL Engine is a special component that processes and executes any PL/SQL statements and sends any SQL statement to the SQL statement processor.

The SQL statement processes are always located on the ORACLE SERVER.

As per the necessity the PL/SQL Engine can be located either at

SERVER

CLIENT

When PL/SQL Engine is located upon the SERVER, the whole PL/SQL block is passed to the PL/SQL Engine on the ORACLE SERVER.

When the PL/SQL Engine is located upon the CLIENT, the PL/SQL processing is done on the CLIENT SIDE. All SQL statements that are embedded within the PL/SQL block, are sent to the ORACLE SERVER for further processing.

If the PL/SQL block does not contain any SQL statements, the entire block is executed on the CLIENT SIDE.

PL/SQL BLOCK

DECLARE

--Declarations of memory variables, constants, cursors etc., in PL/SQL

BEGIN

--SQL executable statements

--PL/SQL executable statements

EXCEPTION

/*SQL or PL/SQL code to handle errors that may arise during the execution of the code block between BEGIN and EXCEPTION section

END;

SYNTAX's of CONTROL STATEMENTS in PL/SQL

1. BRANCHING
2. SELECTION
3. LOOPING

BRANCHING STATEMENTS

- 1.Simple IF
- 2.ELSIF
- 3.ELSE IF

SIMPLE IF

```
IF condition THEN
    statement1;
    statement2;
END IF;
```

IF-THEN-ELSE STATEMENT

```
IF condition THEN
    statement1;
ELSE
    statement2;
END IF;
```

ELSIF STATEMENTS

```
IF condition1 THEN
    statement1;
ELSIF condition2 THEN
    statement2;
ELSIF condition3 THEN
    statement3;
ELSE
```

```
    statementn;  
END IF;
```

NESTED IF

```
IF condition THEN  
    statement1;  
ELSE  
    IF condition THEN  
        statement2;  
    ELSE  
        statement3;  
    END IF;  
END IF;  
ELSE  
    statement3;  
END IF;
```

SELECTION IN PL/SQL

SIMPLE CASE

```
CASE SELECTOR  
    WHEN Expr1 THEN statement1;  
    WHEN Expr2 THEN statement2;  
    :  
    :  
    :  
ELSE  
    statementn;  
  
END CASE;
```

SEARCHED CASE

```
CASE
  WHEN searchcondition1 THEN statement1;
  WHEN searchcondition2 THEN statement2;
  :
  :
  :
ELSE
  statementn;
END CASE;
```

ITERATIONS IN PL/SQL

SIMPLE LOOP

```
LOOP
  statement1;
EXIT [ WHEN Condition];
END LOOP;
```

WHILE LOOP

```
WHILE condition LOOP
  statement1;
  statement2;
END LOOP;
```

FOR LOOP

```
FOR counter IN [REVERSE]
  LowerBound..UpperBound
LOOP
  statement1;
  statement2;
END LOOP;
```

WRITE A PL/SQL PROGRAM TO SWAP TWO NUMBERS WITH OUT TAKING THIRD VARIABLE

```

declare
a number(10);
b number(10);
begin
a:=&a;
b:=&b;
dbms_output.put_line('THE PREV VALUES OF A AND B WERE');
dbms_output.put_line(a);
dbms_output.put_line(b);
a:=a+b;
b:=a-b;
a:=a-b;
dbms_output.put_line('THE VALUES OF A AND B ARE');
dbms_output.put_line(a);
dbms_output.put_line(b);
end;

```

OUTPUT:

```

SQL> @ SWAPPING.SQL
17 /
Enter value for a: 5
old 5: a:=&a;
new 5: a:=5;
Enter value for b: 3
old 6: b:=&b;
new 6: b:=3;
THE PREV VALUES OF A AND B WERE
5
3
THE VALUES OF A AND B ARE
3
5

PL/SQL procedure successfully completed.

```

WRITE A PL/SQL PROGRAM TO SWAP TWO NUMBERS BY TAKING THIRD VARIABLE

```

declare
a number(10);
b number(10);
c number(10);
begin
dbms_output.put_line('THE PREV VALUES OF A AND B WERE');
dbms_output.put_line(a);
dbms_output.put_line(b);
a:=&a;
b:=&b;
c:=a;
a:=b;
b:=c;
dbms_output.put_line('THE VALUES OF A AND B ARE');
dbms_output.put_line(a);
dbms_output.put_line(b);
end;

```

OUTPUT:

```

SQL> @ SWAPPING2.SQL
19 /
Enter value for a: 5
old 6: a:=&a;
new 6: a:=5;
Enter value for b: 3
old 7: b:=&b;
new 7: b:=3;
THE PREV VALUES OF A AND B WERE
5
3
THE VALUES OF A AND B ARE
3
5

PL/SQL procedure successfully completed.

```

WRITE A PL/SQL PROGRAM TO FIND THE LARGEST OF TWO NUMBERS

```
declare
a number;
b number;
begin
a:=&a;
b:=&b;
if a=b then
dbms_output.put_line('BOTH ARE EQUAL');
elsif a>b then
dbms_output.put_line('A IS GREATER');
else
dbms_output.put_line('B IS GREATER');
end if;
end;
```

OUTPUT:

SQL> @ GREATESTOF2.sql

13 /

Enter value for a: 5

old 5: a:=&a;

new 5: a:=5;

Enter value for b: 2

old 6: b:=&b;

new 6: b:=2;

A IS GREATER

PL/SQL procedure successfully completed.

WRITE A PL/SQL PROGRAM TO FIND THE LARGEST OF THREE NUMBERS


```
declare
a number;
b number;
c number;
begin
a:=&a;
b:=&b;
c:=&c;
if a=b and b=c and c=a then
dbms_output.put_line('ALL ARE EQUAL');
elsif a>b and a>c then
dbms_output.put_line('A IS GREATER');
elsif b>c then
dbms_output.put_line('B IS GREATER');
else
dbms_output.put_line('C IS GREATER');
end if;
end;
```

OUTPUT:

SQL> @ GREATESTOF3.sql

17 /

Enter value for a: 8

old 6: a:=&a;

new 6: a:=8;

Enter value for b: 9

old 7: b:=&b;

new 7: b:=9;

Enter value for c: 7

old 8: c:=&c;

new 8: c:=7;

B IS GREATER

PL/SQL procedure successfully completed.

WRITE A PL/SQL PROGRAM TO FIND THE TOTAL AND AVERAGE OF 6 SUBJECTS AND DISPLAY THE GRADE

```

declare
java number(10);
dbms number(10);
co number(10);
se number(10);
es number(10);
ppl number(10);
total number(10);
avgs number(10);
per number(10);
begin
dbms_output.put_line('ENTER THE MARKS');
java:=&java;
dbms:=&dbms;
co:=&co;
se:=&se;
es:=&es;
ppl:=&ppl;
total:=(java+dbms+co+se+es+ppl);
per:=(total/600)*100;
if java<40 or dbms<40 or co<40 or se<40 or es<40 or ppl<40 then
dbms_output.put_line('FAIL');
if per>75 then
dbms_output.put_line('GRADE A');
elsif per>65 and per<75 then
dbms_output.put_line('GRADE B');
elsif per>55 and per<65 then
dbms_output.put_line('GRADE C');
else
dbms_output.put_line('INVALID INPUT');
end if;
dbms_output.put_line('PERCENTAGE IS ' || per);
dbms_output.put_line('TOTAL IS ' || total);
end;

```

OUTPUT:

```

SQL> @ GRADE.sql
31 /
Enter value for java: 80
old 12: java:=&java;
new 12: java:=80;
Enter value for dbms: 70

```

```
old 13: dbms:=&dbms;
new 13: dbms:=70;
Enter value for co: 89
old 14: co:=&co;
new 14: co:=89;
Enter value for se: 72
old 15: se:=&se;
new 15: se:=72;
Enter value for es: 76
old 16: es:=&es;
new 16: es:=76;
Enter value for ppl: 71
old 17: ppl:=&ppl;
new 17: ppl:=71;
GRADE A
PERCENTAGE IS 76
TOTAL IS 458
PL/SQL procedure successfully completed.
```

WRITE A PL/SQL PROGRAM TO CHECK WHETHER THE GIVEN NUMBER IS AN ARMSTRONG NUMBER OR NOT

```

declare
a number;
t number;
arm number;
d number;
begin
a:=&a;
t:=a;
arm:=0;
while t>0
loop
d:=mod(t,10);
arm:=arm+power(d,3);
t:=trunc(t/10);
end loop;
if arm=a then
dbms_output.put_line('given no is an armstrong no' || a);
else
dbms_output.put_line('given no is not an armstrong no');
end if;
end;

```

OUTPUT:

```

SQL> @ ARMSTRONGNUM.sql
Enter value for a: 407
old 7: a:=&a;
new 7: a:=407;
given no is an armstrong no407

```

PL/SQL procedure successfully completed.

```

SQL> /
Enter value for a: 406
old 7: a:=&a;
new 7: a:=406;
given no is not an armstrong no

```

PL/SQL procedure successfully completed.

WRITE A PL/SQL PROGRAM TO FIND THE SUM OF DIGITS IN A GIVEN NUMBER

```

declare

```

```
a number;  
d number:=0;  
sum1 number:=0;  
begin  
a:=&a;  
while a>0  
loop  
d:=mod(a,10);  
sum1:=sum1+d;  
a:=trunc(a/10);  
end loop;  
dbms_output.put_line('sum is' || sum1);  
end;
```

OUTPUT:

```
SQL> @ SUMOFDIGITS.sql
```

```
16 /
```

```
Enter value for a: 564
```

```
old 7: a:=&a;
```

```
new 7: a:=564;
```

```
sum is15
```

```
PL/SQL procedure successfully completed.
```

WRITE A PL/SQL PROGRAM TO DISPLAY THE NUMBER IN REVERSE ORDER

```
declare
a number;
rev number;
d number;
begin
a:=&a;
rev:=0;
while a>0
loop
d:=mod(a,10);
rev:=(rev*10)+d;
a:=trunc(a/10);
end loop;
dbms_output.put_line('no is' || rev);
end;
```

OUTPUT:

```
SQL> @ REVERSE2.sql
16 /
Enter value for a: 536
old 6: a:=&a;
new 6: a:=536;
no is635
```

PL/SQL procedure successfully completed.

WRITE A PL/SQL PROGRAM TO DISPLAY NUMBER IN REVERSE ORDER USING STRING FUNCTION

```
declare
gn varchar2(5):=4567;
sl number(2);
rv varchar2(5);
begin
sl:=length(gn);
for i in reverse 1..sl
loop
rv:=rv || substr(gn,i,1);
end loop;
dbms_output.put_line('given no r is' || gn);
dbms_output.put_line('given no in reverse order is' || rv);
end;
```

OUTPUT:

```
SQL> @ REVERSE.sql
14 /
given no r is4567
given no in reverse order is7654
```

PL/SQL procedure successfully completed.

WRITE A PL/SQL PROGRAM TO CHECK WHETHER THE GIVEN NUMBER IS PRIME OR NOT

```
declare
```

```

a number;
c number:=0;
i number;
begin
a:=&a;
for i in 1..a
loop
if mod(a,i)=0 then
c:=c+1;
end if;
end loop;
if c=2 then
dbms_output.put_line(a || 'is a prime number');
else
dbms_output.put_line(a || 'is not a prime number');
end if;
end;

```

OUTPUT:

SQL> @ PRIME.SQL

19 /

Enter value for a: 11

old 6: a:=&a;

new 6: a:=11;

11is a prime number

PL/SQL procedure successfully completed.

WRITE A PL/SQL PROGRAM TO FIND THE FACTORIAL OF A GIVEN NUMBER

```

declare
n number;

```



```
f number:=1;
begin
n:=&n;
for i in 1..n
loop
f:=f*i;
end loop;
dbms_output.put_line('the factorial is' || f);
end;
```

OUTPUT:

```
SQL> @ FACTORIAL.sql
12 /
Enter value for n: 5
old 5: n:=&n;
new 5: n:=5;
the factorial is120
```

PL/SQL procedure successfully completed.

WRITE A PL/SQL PROGRAM TO GENERATE FIBONACCI SERIES

```
declare
a number;
```

```
b number;  
c number;  
n number;  
i number;  
begin  
n:=&n;  
a:=0;  
b:=1;  
dbms_output.put_line(a);  
dbms_output.put_line(b);  
for i in 1..n-2  
loop  
c:=a+b;  
dbms_output.put_line(c);  
a:=b;  
b:=c;  
end loop;  
end;
```

OUTPUT:

SQL> @ FIBONACCI.sql

21 /

Enter value for n: 5

old 8: n:=&n;

new 8: n:=5;

0

1

1

2

3

PL/SQL procedure successfully completed.

**WRITE A PL/SQL CODE BLOCK TO CALCULATE THE AREA OF A CIRCLE FOR A VALUE OF RADIUS VARYING FROM 3 TO 7.
STORE THE RADIUS AND THE CORRESPONDING VALUES OF CALCULATED AREA IN AN EMPTY TABLE NAMED AREAS ,CONSISTING OF TWO COLUMNS RADIUS & AREA**

TABLE NAME:AREAS

RADIUS AREA

SQL> create table areas(radius number(10),area number(6,2));

Table created.

--PROGRAM

declare

pi constant number(4,2):=3.14;

radius number(5):=3;

area number(6,2);

begin

while radius<7

loop

area:=pi*power(radius,2);

insert into areas values(radius,area);

radius:=radius+1;

end loop;

end;

OUTPUT:

SQL> @ AREAOFCIRCLE.SQL

13 /

PL/SQL procedure successfully completed.

SQL> SELECT * FROM AREAS;

| RADIUS | AREA |
|--------|--------|
| 3 | 28.26 |
| 4 | 50.24 |
| 5 | 78.5 |
| 6 | 113.04 |

WRITE A PL/SQL CODE BLOCK THAT WILL ACCEPT AN ACCOUNT NUMBER FROM THE USER,CHECK IF THE USERS BALANCE IS LESS THAN MINIMUM BALANCE,ONLY THEN DEDUCT RS.100/- FROM THE BALANCE.THIS PROCESS IS FIRED ON THE ACCT TABLE.

```
SQL> create table acct(name varchar2(10),cur_bal number(10),acctno number(6,2));
```

```
SQL> insert into stud values('&sname',&rollno,&marks);
```

```
SQL> select * from acct;
```

| ACCTNO | NAME | CUR_BAL |
|--------|--------|---------|
| ----- | ----- | ----- |
| 777 | sirius | 10000 |
| 765 | john | 1000 |
| 855 | sam | 500 |
| 353 | peter | 800 |

--PROGRAM

```
declare
mano number(5);
mcb number(6,2);
minibal constant number(7,2):=1000.00;
fine number(6,2):=100.00;
begin
mano:=&mano;
select cur_bal into mcb from acct where acctno=mano;
if mcb<minibal then
update acct set cur_bal=cur_bal-fine where acctno=mano;
end if;
end;
```

OUTPUT:

```
SQL> @ BANKACC.sql
13 /
Enter value for mano: 855
old 7: mano:=&mano;
new 7: mano:=855;
```

PL/SQL procedure successfully completed.

```
SQL> select * from acct;
```

| ACCTNO | NAME | CUR_BAL |
|--------|--------|---------|
| ----- | ----- | ----- |
| 777 | sirius | 10000 |

| | | |
|-----|-------|------|
| 765 | john | 1000 |
| 855 | sam | 400 |
| 353 | peter | 800 |

PL/SQL PROGRAMS- FUNCTIONS

CUBE

create or replace function cube(n number) return number
as

```
c number;  
begin  
c:=n*n*n;  
return c;  
end;
```

output:-

```
SQL> @cub  
/
```

Function created.

```
SQL> select cube(6)from dual;
```

```
CUBE(6)  
-----  
216
```

FACTORIAL

create or replace function fact(n number)return number
as

```
fac number:=1;  
begin
```

```
for i in 1..n
loop
fac:=fac*i;
end loop;
return fac;
end;
```

output:-

```
SQL> @func.sql;
12 /
```

Function created.

```
SQL> select fact(5) from dual;
```

```
FACT(5)
-----
120
```

IN- PROCEDURE

```
create or replace procedure inpro(dno number,depname varchar2,city varchar2)
as
begin
insert into dept (deptno,dname,loc)values(dno,depname,city);
end;
```

OUTPUT:-

SQL> select * from dept;

| DEPTNO | DNAME | LOC |
|--------|------------|----------|
| 10 | ACCOUNTING | NEW YORK |
| 20 | RESEARCH | DALLAS |
| 30 | SALES | CHICAGO |
| 40 | OPERATIONS | BOSTON |

SQL> @pro1
/

Procedure created.

SQL> exec inpro(50,'MARKETING','HYDERABAD');

PL/SQL procedure successfully completed.

SQL> select * from dept;

| DEPTNO | DNAME | LOC |
|--------|------------|-----------|
| 10 | ACCOUNTING | NEW YORK |
| 20 | RESEARCH | DALLAS |
| 30 | SALES | CHICAGO |
| 40 | OPERATIONS | BOSTON |
| 50 | MARKETING | HYDERABAD |

OUT-PROCEDURE

```
create or replace procedure outpro(dno number,depname out varchar2,city out varchar2)
as
begin
select dname,loc into depname,city from dept where deptno=dno;
end;
```


OUTPUT:

```
SQL> @proc2  
/
```

Procedure created.

```
SQL> declare  
2 x varchar2(20);  
3 y varchar2(30);  
4 ch number;  
5 begin  
6 ch:=&ch;  
7 outpro(ch,x,y);  
8 dbms_output.put_line(x || ' ' || y);  
9 end;  
10 /
```

Enter value for ch: 10

old 6: ch:=&ch;

new 6: ch:=10;

ACCOUNTING NEW YORK

PL/SQL procedure successfully completed.

BEFORE TRIGGER

create or replace trigger tday before insert or delete or update on emp

declare

we varchar2(10);

begin

we:=to_char(sysdate,'dy');

if we='sat' or we='sun' then

```
raise_application_error(-20015,'its a weekend');
end if;
end;
```

output:-

```
SQL> @trig1
/
```

Trigger created.

```
SQL> delete from emp where empno=7902;
```

ERROR at line 1:

ORA-20015: its a weekend

ORA-06512: at "SCOTT.TDAY", line 6

ORA-04088: error during execution of trigger 'SCOTT.TDAY'

AFTER TRIGGER

```
create or replace trigger ttime after insert or delete or update on emp1 for each row
declare
tt varchar2(5);
begin
tt:=to_char(sysdate,'hh24');
if tt not between 10 and 17 then
```

```
raise_application_error(-20010,'not working hours');  
end if;  
end;
```

output:-

```
SQL> @trig2;  
10 /
```

Trigger created.

```
SQL> update emp1 set empno=7777 where empno=7902;
```

*

ERROR at line 1:

ORA-20010: not working hours

ORA-06512: at "SCOTT.TTIME", line 6

ORA-04088: error during execution of trigger 'SCOTT.TTIME'