Bit Addresses

For I/O and RAM


7FH
General Purpose RAM
30H
2FH
Bit Addressable
Locations
20H
1FH
BANK 3
BANK 2
BANK 1
BANK 0
00H


2F
27
20


2F
7F
78
7D
7C
7B
7A
79
78
27
3F
3E
3D
3C
3B
3A
39
38
20
07
06
05
04
03
02
01
00


2E
77
76
75
74
73
72
71
70
26
37
36
35
34
33
32
31
30
21
0F
0E
0D
0C
0B
0A
09
08

Single Bit Instructions

SETB bit Set the bit (bit = 1)

```
SETB 42H   ;set bit 42H to 1
```

2F	7F	7E	7D	7C	7B	7A	79	78
2E	77	76	75	74	73	72	71	70
2D	6F	6E	6D	6C	6B	6A	69	68
2C	67	66	65	64	63	62	61	60
2B	5F	5E	5D	5C	5B	5A	59	58
2A	57	56	55	54	53	52	51	50
29	4F	4E	4D	4C	4B	4A	49	48
28	47	46	45	44	43	42	41	40
27	3F	3E	3D	3C	3B	3A	39	38
26	37	36	35	34	33	32	31	30
25	2F	2E	2D	2C	2B	2A	29	28
24	27	26	25	24	23	22	21	20
23	1F	1E	1D	1C	1B	1A	19	18
22	17	16	15	14	13	12	11	10
21	0F	0E	0D	0C	0B	0A	09	08
20	07	06	05	04	03	02	01	00

Single Bit Instructions

CLR bit Clear the bit (bit = 0)

```
CLR 67H        ; clear bit 67
```

2F	7F	7E	7D	7C	7B	7A	79	78
2E	77	76	75	74	73	72	71	70
2D	6F	6E	6D	6C	6B	6A	69	68
2C	67	66	65	64	63	62	61	60
2B	5F	5E	5D	5C	5B	5A	59	58
2A	57	56	55	54	53	52	51	50
29	4F	4E	4D	4C	4B	4A	49	48
28	47	46	45	44	43	42	41	40
27	3F	3E	3D	3C	3B	3A	39	38
26	37	36	35	34	33	32	31	30
25	2F	2E	2D	2C	2B	2A	29	28
24	27	26	25	24	23	22	21	20
23	1F	1E	1D	1C	1B	1A	19	18
22	17	16	15	14	13	12	11	10
21	0F	0E	0D	0C	0B	0A	09	08
20	07	06	05	04	03	02	01	00

Single Bit Instructions

CPL bit

Complement the (bit = NOT bit)

```
CPL 0FH          ; complem. bit 0F
```

2F	7F	7E	7D	7C	7B	7A	79	78
2E	77	76	75	74	73	72	71	70
2D	6F	6E	6D	6C	6B	6A	69	68
2C	67	66	65	64	63	62	61	60
2B	5F	5E	5D	5C	5B	5A	59	58
2A	57	56	55	54	53	52	51	50
29	4F	4E	4D	4C	4B	4A	49	48
28	47	46	45	44	43	42	41	40
27	3F	3E	3D	3C	3B	3A	39	38
26	37	36	35	34	33	32	31	30
25	2F	2E	2D	2C	2B	2A	29	28
24	27	26	25	24	23	22	21	20
23	1F	1E	1D	1C	1B	1A	19	18
22	17	16	15	14	13	12	11	10
21	0F	0E	0D	0C	0B	0A	09	08
20	07	06	05	04	03	02	01	00

Single Bit Instructions

JB bit, target

Jump to target if bit = 1 (jump if bit)

```
JB 28H,LOOP   ; jump if 28H = 1
```

2F	7F	7E	7D	7C	7B	7A	79	78
2E	77	76	75	74	73	72	71	70
2D	6F	6E	6D	6C	6B	6A	69	68
2C	67	66	65	64	63	62	61	60
2B	5F	5E	5D	5C	5B	5A	59	58
2A	57	56	55	54	53	52	51	50
29	4F	4E	4D	4C	4B	4A	49	48
28	47	46	45	44	43	42	41	40
27	3F	3E	3D	3C	3B	3A	39	38
26	37	36	35	34	33	32	31	30
25	2F	2E	2D	2C	2B	2A	29	28
24	27	26	25	24	23	22	21	20
23	1F	1E	1D	1C	1B	1A	19	18
22	17	16	15	14	13	12	11	10
21	0F	0E	0D	0C	0B	0A	09	08
20	07	06	05	04	03	02	01	00

Single Bit Instructions

JNB bit, target

Jump to target if bit = 0 (jump if no bit)

```
JNB 12,LOOP  ;jump if bit 12 = 0
```

2F	7F	7E	7D	7C	7B	7A	79	78
2E	77	76	75	74	73	72	71	70
2D	6F	6E	6D	6C	6B	6A	69	68
2C	67	66	65	64	63	62	61	60
2B	5F	5E	5D	5C	5B	5A	59	58
2A	57	56	55	54	53	52	51	50
29	4F	4E	4D	4C	4B	4A	49	48
28	47	46	45	44	43	42	41	40
27	3F	3E	3D	3C	3B	3A	39	38
26	37	36	35	34	33	32	31	30
25	2F	2E	2D	2C	2B	2A	29	28
24	27	26	25	24	23	22	21	20
23	1F	1E	1D	1C	1B	1A	19	18
22	17	16	15	14	13	12	11	10
21	0F	0E	0D	0C	0B	0A	09	08
20	07	06	05	04	03	02	01	00

Single Bit Instructions

JBC bit, target

Jump to target if bit = 1 (jump if bit, then clear)

```
JBC 5,LOOP  ;jump if bit 5 = 1,

;and clear bit 5
```

2F	7F	7E	7D	7C	7B	7A	79	78
2E	77	76	75	74	73	72	71	70
2D	6F	6E	6D	6C	6B	6A	69	68
2C	67	66	65	64	63	62	61	60
2B	5F	5E	5D	5C	5B	5A	59	58
2A	57	56	55	54	53	52	51	50
29	4F	4E	4D	4C	4B	4A	49	48
28	47	46	45	44	43	42	41	40
27	3F	3E	3D	3C	3B	3A	39	38
26	37	36	35	34	33	32	31	30
25	2F	2E	2D	2C	2B	2A	29	28
24	27	26	25	24	23	22	21	20
23	1F	1E	1D	1C	1B	1A	19	18
22	17	16	15	14	13	12	11	10
21	0F	0E	0D	0C	0B	0A	09	08
20	07	06	05	04	03	02	01	00

Processor Status Word



PSW bit addressability

Syntax

BIT instruction PSW.Bit number

```
SETB PSW.3    ;set the 3 bit
```

PSW bit addressability

Write a program to save the accumulator in R7 of bank 2

PSW bit addressability

```
CLR PSW.3

SETB PSW.4

MOV R7, A
```


Accumulator Register A
(MSB)
ACC.7
ACC.6
ACC.5
ACC.4
ACC.3
ACC.2
ACC.1
(LSB)
ACC.0
Direct Address E0H
Bit Address
E7
E6
E5
E4
E3
E2
E1
E0
www.CircuitsToday.com

Accumulator bit address.

Write a program to see if the RAM location 37H contains an even value. If yes, jump to location “YES”

Accumulator bit address.

```
MOV A, 37H

JNB ACC.0, YES
```


Register B
(MSB)
B.7
B.6
B.5
B.4
B.3
B.2
B.1
(LSB)
B.0
Direct Address F0H
Bit Address
F7
F6
F5
F4
F3
F2
F1
F0
www.CircuitsToday.com