SkripsiBench: Which Language Model for Indonesian Academic Writing and Research Code? Quality, Cost and Provenance of Local and API Models

Andi Agung Dwi Arya B
Program Studi Magister Teknik Informatika, Fakultas Teknik
Universitas Hasanuddin
Makassar, Indonesia
D082251054 · [TODO: email]

***Abstract*—Indonesian undergraduates end their degree with a *skripsi*: a thesis whose methods and results chapters follow the conventions of the study programme, whose literature review must cite real sources, whose statistics are computed in code, and whose language must follow the national spelling rules. Which large language model (LLM) should students, supervisors and the tools built for them use? We introduce SkripsiBench, 255 items in eight tasks taken from this workflow—chapter outlines per programme, methodology questions, methods extraction from real theses, grounded literature reviews, reference lists, formal Indonesian, data-analysis code and LaTeX—scored deterministically wherever possible, with LLM judges of other vendors for prose, and with the served model, tokens, cost and GPU energy recorded for every call. Evaluating 15 economy- and standard-tier API models of the GitHub Copilot SDK and 10 local open-weight models (7,356 API calls, US$46.65 in total), we find no significant difference among the three best API models (overall 0.931–0.941), while cost spans two orders of magnitude: a model 0.04 below the leader costs 104 times less per item. Methodology questions and formal Indonesian are near ceiling for API models; producing artefacts separates them. 0–40 % of the references the API models listed are not found in Crossref, and 0–31 % are found neither there nor in doi.org, Scopus or OpenAlex, against 61–85 % for local models. The best local model (0.745) stays below the weakest API model (0.777) and is not cheaper per item at rental prices; an Indonesian-tuned 9B model did not write formal Indonesian better than a newer general model of similar size. The three judges agree (Krippendorff's $\alpha = 0.86$) and track the deterministic checks ($\rho = 0.82$ across models), and the SDK reported the requested model as the serving model for every call. Code, public items, per-item scores and the cost-gated runner are released.**

***Index Terms*—large language models, benchmark, Indonesian, academic writing, research code, LLM-as-a-judge, hallucinated references, inference cost, provenance**

I. Introduction

An Indonesian undergraduate degree ends with the *skripsi*, a thesis whose chapters follow the conventions of the study programme: a methods chapter (*BAB III*) whose sub-sections are almost fixed in some programmes, a results chapter (*BAB IV*) whose shape follows the research design, statistics computed in SPSS, Excel or Python, a literature review that must cite real sources, and formal Indonesian that follows the national spelling rules (EYD) and dictionary (KBBI). Students, supervisors and the tools built for them increasingly hand parts of this work to large language models (LLMs). Which model should they use?

The question has become harder, not easier. One vendor SDK now exposes dozens of models from several vendors, at prices per call that differ by two orders of magnitude and often with a reasoning-effort setting; open-weight models run on a laboratory GPU for the price of electricity. Public leaderboards rank models on English knowledge and reasoning [1], [2], and Indonesian benchmarks measure language understanding, sentiment and school-exam knowledge [3]–[7]. None of them asks whether a model outlines a methods chapter the way an agribusiness or an Islamic family-law programme expects, cites only the sources it was given, lists references that exist, writes an abstract in formal Indonesian without inventing numbers, or computes a correct Mann–Whitney test from a CSV file. Nor do they report what an answer costs or which model produced it—not a trivial question, since a vendor SDK can silently serve a different model than the one requested [8].

We present *SkripsiBench*, eight tasks drawn from the skripsi workflow, and use it to compare 15 API models of one SDK, which we grouped into two tiers by name, with 10 local models under identical Indonesian prompts. Our contributions are:

- **Tasks and items** (Section III): 255 items: 225 newly written public items and 30 private excerpts of real theses (published as hashes only); deterministic scoring for six tasks and for the deterministic half of the two prose tasks, whose other half comes from LLM judges of other vendors than the candidate's, with leniency calibration and a reliability analysis.
- **Accounting** (Section IV): every call records the model that the SDK reports as answering, the reasoning effort, tokens and the vendor's AI units (converted to US$); local runs record GPU time (converted at an on-demand price for the same GPU) and measured board energy.
- **Findings** (Section V): the three best API models are not significantly different, while the cost per item of the leader

is 104 times that of a model 0.04 below it; methodology questions and formal Indonesian are near ceiling for API models, whereas real references, programme-specific outlines and LaTeX repair separate them; most references that Crossref does not know are found in no other database either; on average, local models trail API models on every task, most on references and code and least on formal Indonesian.

- **An open kit**: runner with a cost gate and a budget cap, scorers, sandbox, reference audit, public items, per-item scores and a generator of blind sheets for human raters, in the paper-agent repository (https://github.com/devnolife/paper-agent).

II. Related Work

a) General and Indonesian benchmarks: MMLU measures multitask knowledge with multiple-choice questions [1]; HELM argues for many scenarios and metrics per model, efficiency included [2]. For Indonesian, IndoNLU [3] and IndoLEM [4] collect understanding tasks, NusaX [5] sentiment and translation for local languages, IndoMMLU [6] school examinations—on which models passed only primary-school levels—and SeaEval [7] multilingual and cultural reasoning in South-East Asia; Cendol instruction-tunes open models for Indonesian languages [9]. These resources test knowledge and understanding. SkripsiBench tests the production of academic artefacts and the code behind them.

b) LLMs as judges: Strong LLMs agree with human preferences on open-ended answers [10]–[12], but they favour their own generations [13]. We therefore never let a vendor's model judge that vendor's models, use three judges from three vendors, remove each judge's leniency, and prepare blind sheets to compare the judges with human raters.

c) Citations and references: Text generated with citations to given passages can be checked automatically [14], as can factual precision [15]; LLMs are known to fabricate bibliographic references [16], [17]. Our grounded-writing task restricts citations to six given abstracts and flags numbers found in none of them; the references task verifies every listed work in bibliographic databases, as paper-agent does for its own manuscripts [8].

d) Code: HumanEval [18] and DS-1000 [19] test generated code with unit tests. Our coding task executes complete analysis programs on synthetic thesis-like data in a sandbox and compares the statistics they print with reference values within tolerances.

e) Cost: The energy and cost of NLP models [20] and of inference in particular [21] matter for deployment decisions; we report vendor billing units for API models and measured GPU energy and time for local ones, side by side with quality.

III. SkripsiBench

A. Design

Four principles guided the benchmark. (i) Every task is a step a student or supervisor actually performs while writing a skripsi. (ii) A score is computed deterministically wherever the task allows it; LLM judges are used only for prose quality, and the kit prepares blind sheets to check them against people. (iii) Real thesis text is used only where nothing else will do, and is never published. (iv) Every call is accounted for: who answered (as the serving stack reports it), at what effort, for how many tokens, at what cost. All prompts are in Indonesian. Table I summarises the eight tasks.

B. Tasks and items

Items were drafted with the help of LLM assistants and then verified mechanically wherever possible: computed answers and reference programs were recomputed with independent implementations, LaTeX items were compiled, BibTeX fields and source works were looked up in bibliographic databases, and the methodology keys were audited before any model was run by a separate LLM reviewer instructed as an examiner. A human review of every key is part of the planned validation (Section VI).

a) Structure: The reference for a study programme is the set of sub-section *families* (e.g. "population and sample", "data analysis technique", "general description of the research site", "discussion") that occur in at least 25 % of that programme's theses, with their prevalence, aggregated from a local thesis dataset of one Indonesian university (1,251 theses; 25 programmes with enough theses). Titles are new and fictitious (35 items; two titles for the ten largest programmes). Model subsection titles are mapped to the same families with the same regular expressions; untitled results sub-sections that follow the research questions form their own family. Per chapter we compute prevalence-weighted recall, precision and F1; the item score is the mean F1 of both chapters. We also flag a *generic* results chapter built around assumption, instrument or hypothesis tests in a programme whose theses do not have them.

b) Methodology: Sixty four-option questions (19 concept, 25 scenario, 16 computation) cover descriptive statistics, validity and reliability, Likert scales, sampling (Slovin, Krejcie–Morgan), classical regression assumptions, regression, correlation, difference tests, ANOVA and designed experiments with post-hoc tests, chi-square, PLS-SEM, classroom experiments with N-gain, classroom action research, R&D models, Miles–Huberman, trustworthiness criteria, content and discourse analysis, normative legal research, systematic reviews, system testing and SUS, machine-learning metrics, farm-business analysis, laboratory experiments and ethics. Where textbooks disagree, the stem states the convention. The audit led to six revisions: four items whose key was not unique as worded, and two whose wording or attribution was imprecise.

c) Extraction: Thirty excerpts of real theses (five or four per faculty, seven faculties), masked for names, student numbers and the university's name and address, contain the title, research questions, objectives, the methods chapter and the outline of the results chapter (at most 8,700 characters). The model fills a JSON record with closed vocabularies (14 approaches, 12 collection techniques, 31 analysis techniques, 14 software tools) and quotes evidence. There is no gold label for all items, so a

TABLE I
THE EIGHT SKRIPSIBENCH TASKS. *Pub.* PUBLIC ITEMS IN THE REPOSITORY; *Priv.* PRIVATE ITEMS (HASHES ONLY). ALL ITEMS EXCEPT THE EXTRACTION EXCERPTS WERE WRITTEN FOR THE BENCHMARK.

Task	What the model does	Pub.	Priv.	Scored by
`structure`	outline the sub-sections of chapter III (methods) and IV (results) for a thesis title in a given study programme	35	–	prevalence-weighted F1 of sub-section families against the programme's typical structure
`methodology`	answer multiple-choice questions on research methods and statistics (concepts, choosing a design or test, computations)	60	–	accuracy
`extraction`	fill a closed-vocabulary methods record (approach, data, collection, analysis, software, sample size, hypothesis) from a masked thesis excerpt	–	30	field agreement with cross-vendor silver labels; verbatim evidence
`grounded`	write a 250–400-word literature review from six given abstracts, citing them as `[P1]`–`[P6]`	30	–	coverage, cited sentences, invalid and author–year citations, unsupported numbers, length; LLM judges
`references`	list five real references with DOI for a research topic	20	–	lookup in Crossref (DOI, then title and first author); DOI correctness; misses audited in doi.org, Scopus and OpenAlex
`language`	write an abstract from a research summary, or rewrite an informal draft in formal Indonesian	30	–	length, English leakage, non-standard words, kept and invented numbers, key terms, sentence length; LLM judges
`coding`	write a Python analysis program for a synthetic CSV (regression, assumption tests, t/Mann–Whitney/Wilcoxon, ANOVA and post-hoc tests, chi-square, Cronbach's α, N-gain, SUS, metrics)	30	–	sandboxed execution; printed statistics within tolerance; pass@1 and pass after one repair
`latex`	fix a broken document, typeset a table with booktabs, convert an APA reference to BibTeX	20	–	pdflatex in the sandbox and PDF text; cell-by-cell comparison; BibTeX fields

panel of three strong models from three vendors (gpt-6.1-sol and claude-sonnet-5 at low effort, gemini-4-argon) provides silver labels by field-wise majority; a candidate is scored against the majority of the panel members *not* of its own vendor (for a panel member: the agreement of the other two), and fields without agreement are not scored.

d) Grounded writing: Thirty topics frequent in Indonesian theses each come with six OpenAlex works (articles 2015–2025 with an abstract and at least 20 citations), abstracts cut at a sentence end before 1,200 characters and frozen in a snapshot. The model must cite `[P`n`]` only. The deterministic score averages source coverage, the share of sentences with a valid citation, absence of out-of-range and author–year citations, the share of numbers that occur in some source, and length compliance.

e) References: For each of 20 topics the model lists five references with DOI and is told that fewer is better than invented. Each reference is looked up in Crossref [22], the largest registration agency for journal and proceedings DOIs: first by the DOI given, then by title and first author, with paper-agent's matching rule [8]: title similarity ≥ 0.90 (Crossref's title and subtitle joined), year ± 1 of any of the work's publication dates, and first-author surname; arXiv DOIs are checked against arXiv. Crossref answers other than "found" or "not found" (rate limits, server errors) leave the item unscored rather than wrong. Credit is 1 for an existing work with the correct DOI, 0.75 without a DOI, 0.5 with a wrong DOI and 0 if the work is not found; the score divides by five, so abstaining costs as much as an unverifiable reference. Because a real work can be missing from Crossref, an audit looks every miss up again with the same rule—a given DOI at doi.org (all registration agencies), the title in Scopus and in OpenAlex [23]; Semantic Scholar refused our requests—and classifies it as found, matching only a real title, or found nowhere. The audit does not change the scores (Section V).

f) Language: Fifteen structured research summaries (eight fields, quantitative and qualitative designs) must become one abstract of 150–250 words; fifteen informal drafts, full of colloquial words, non-standard spellings and unnecessary English, must become formal academic Indonesian. Deterministic checks use a list of 438 non-standard words with their KBBI/EYD forms and Indonesian and English function-word lists.

g) Coding: Thirty tasks on synthetic data (fixed seeds; the CSV files are the canonical data) specify the analysis and its options exactly (e.g. sample variance, two-sided tests, Student vs. Welch, continuity correction) and the JSON keys to print. Reference values were cross-checked with independent implementations, and common mistakes (population variance, Welch instead of Student, unadjusted p-values) fall outside the tolerances. A program that crashes, times out or prints no complete JSON gets one repair turn with the error message—never with the expected values.

h) LaTeX: Eight documents with one to three injected errors (unescaped specials, unbalanced braces, wrong environments, math outside math mode, malformed tables) must compile and keep their text; six tables must be typeset with booktabs, caption and label; six APA references (verified in Crossref or library catalogues) must become BibTeX entries.

C. Judges and human raters

For the two prose tasks, three judges from three vendors (the models of the extraction panel) rate each answer on five 1–5 criteria (faithfulness to the sources or summary, coverage or completeness, coherence, formal Indonesian, instruction compliance) without seeing the model name; a judge never rates models of its own vendor, so an answer receives two or three ratings. Each judge's leniency—its mean deviation from the judges' average on the answers all three rated—is subtracted before averaging. The item score of a prose task is the mean of the deterministic score and the judge score. We report the judges' agreement with each other (Krippendorff's α [24]) and with the deterministic checks (Spearman's ρ). The kit generates blind, stratified sheets for two human raters (30 answers rated with the same rubric, 20 silver extraction records to verify) and computes their agreement with each other and with the judges; this comparison is not part of the present version.

D. Sandbox

Model-written programs and LaTeX run in Linux user, mount, network and PID namespaces with fresh tmpfs over home, temporary and runtime directories, the interpreter bound read-only, no network, a minimal environment without tokens, all capabilities dropped before execution, and cgroup limits on memory, tasks and CPU.

IV. Experimental Setup

a) Models: We evaluate 25 models. 15 are API models of the GitHub Copilot SDK [25] (Python package 1.0.9, which drives Copilot CLI 1.0.73), all enabled for the author's account on 14 October 2026, from five vendors (Anthropic, OpenAI, Google, Moonshot, Microsoft). We grouped them before the study by their names into an economy tier (mini, flash and haiku sizes, plus kimi-k3 and mai-code-1.1-flash, which carry no size label) and a standard tier (mid-size models); the SDK exposes no prices, and the measured cost per item (Table II) does not follow the grouping—kimi-k3 turned out to be the most expensive model per item. The 9 flagship models of the premium tier are not part of this version (Section VI). API models that accept a reasoning effort ran at *low*. The ten local models range from 3B to 36B parameters (Llama 3.2, Qwen2.5 7B, SahabatAI 9B—Gemma 2 further pre-trained on Indonesian—, Gemma 4 8B, Phi-4 reasoning plus, gpt-oss 20B, Gemma 3 27B, Qwen3-Coder 30B-A3B, Qwen2.5-Coder 32B and Qwen3.6 36B), in 4-bit quantisation except SahabatAI (8-bit) and gpt-oss (MXFP4), served by a shared Ollama [26] server (v0.22) with two NVIDIA L40S GPUs (48 GB). They ran at temperature 0.2 with a fixed 16k-token context (8k for SahabatAI, its trained context, and for Qwen2.5-Coder 32B after its first 103 items, when 16k contexts split it over both GPUs and requests timed out; all prompts fit in 8k and the answer budget was the same) and with their thinking mode on where they have one (*low* for gpt-oss). Every model received the same prompts; there was one run per model and item.

b) Provenance: Each record stores the requested and the served model (from the SDK's usage event for API models, from Ollama's response for local ones), the reasoning effort, input, output and reasoning tokens, latency and the answer.

c) Cost: API cost is the vendor's AI units reported per call (14–15 October 2026), converted at US$0.01 per unit. For local models we report two numbers: GPU time converted at the on-demand price of an L40S, US$1.09 per hour [27], and the energy drawn by the GPU board, integrated from `nvidia-smi` readings every 250 ms (gross, and minus the idle baseline); electricity tariffs differ, so energy is reported in kWh. The server is shared: other users' workloads and the scheduler's choice of GPU make the energy figures upper bounds for the board rather than exact per-model numbers, and for one model (Qwen2.5 7B) the GPU could not be identified, so its energy is missing. In the main run each local model served three requests in parallel (GPU time and energy then measured per run segment); the SahabatAI model, which a production service also uses, served one, and the items of a short pilot ran one at a time. Local cost per item therefore depends on this concurrency.

d) Statistics: The overall score is the unweighted mean of the eight task scores; a task score is the mean over its items, and a prose item scores the mean of its deterministic and calibrated judge scores. A failed model call scores 0; what the scorer cannot grade (an extraction field without a panel majority) is left out. Task and composite scores carry 95 % percentile bootstrap intervals (2,000 resamples [28]; composites resample items within each task). The stability of the ranking and the paired difference of every model to the leader come from 1,000 such task-stratified samples, which weight the tasks as the overall score does; a difference is called significant when its interval excludes zero. Each model is compared with the leader only, and the intervals are not adjusted for multiplicity.

V. Results

A. The leaders are not significantly different

Table II ranks the 25 models by their overall score. kimi-k3 leads with 0.941. In the task-stratified bootstrap (Section IV), the paired difference to the leader is 0.006 [−0.014, 0.027] for gpt-5.4, 0.010 [−0.010, 0.028] for gpt-6.1-sol and 0.028 [0.006, 0.050] for claude-sonnet-5.5. The three leaders are therefore not significantly different, which does not make them equivalent: kimi-k3 comes first in 70 % of the bootstrap samples, gpt-5.4 in 25 % and gpt-6.1-sol in 5 %. Their closeness is partly a ceiling effect, as two of the eight tasks hardly separate API models (Section V-C). Below them the API models form a dense band down to claude-haiku-4.5 (0.777); the ten local models follow after a gap (Section V-D).

TABLE II

LEADERBOARD (ONE RUN PER MODEL AND ITEM; API MODELS AT LOW REASONING EFFORT WHERE THE MODEL ACCEPTS ONE). PER-TASK SCORES, COMPOSITES (ACADEMIC: THE FIRST SIX TASKS; CODE: CODE AND LATEX) AND THE OVERALL SCORE WITH ITS 95 % BOOTSTRAP CI; COST PER 100 ITEMS: API MODELS IN AI UNITS AT US$0.01, LOCAL MODELS AS L40S RENTAL EQUIVALENT; KWH: GPU BOARD ENERGY OF LOCAL MODELS. T: TIER (E ECONOMY, S STANDARD, L LOCAL). BEST VALUE PER COLUMN IN BOLD.

#	Model	T	Str	Met	Ext	Grd	Ref	Lng	Cod	TeX	Acad.	Code	Overall [95 % CI]	US$/100	kWh/100
1	kimi-k3	E	**0.79**	**1.00**	0.93	0.95	**0.94**	0.98	**1.00**	0.95	**0.93**	0.97	**0.94** [0.92, 0.96]	3.119	–
2	gpt-5.4	S	0.76	**1.00**	0.95	**0.96**	0.84	0.97	**1.00**	**1.00**	0.91	**1.00**	0.94 [0.92, 0.95]	0.864	–
3	gpt-6.1-sol	S	0.74	**1.00**	0.97	0.96	0.81	0.97	**1.00**	**1.00**	0.91	**1.00**	0.93 [0.92, 0.95]	0.461	–
4	claude-sonnet-5.5	S	0.75	**1.00**	0.93	0.95	0.73	0.99	0.97	**1.00**	0.89	0.98	0.91 [0.89, 0.93]	0.783	–
5	gpt-5.6-terra	S	0.76	0.98	0.95	0.94	0.79	0.97	0.97	0.95	0.90	0.96	0.91 [0.89, 0.94]	0.585	–
6	gemini-3.7-flash	E	0.73	**1.00**	0.94	0.95	0.71	0.97	**1.00**	**1.00**	0.88	**1.00**	0.91 [0.90, 0.92]	0.141	–
7	gemini-4-argon	S	0.73	**1.00**	**0.97**	0.89	0.65	0.96	**1.00**	**1.00**	0.87	**1.00**	0.90 [0.88, 0.92]	0.396	–
8	gpt-6-luna	S	0.77	**1.00**	0.95	0.93	0.79	0.97	**1.00**	0.80	0.90	0.90	0.90 [0.87, 0.93]	0.030	–
9	claude-haiku-5.5	E	0.72	**1.00**	0.93	0.88	0.69	**0.99**	**1.00**	0.95	0.87	0.97	0.90 [0.87, 0.92]	0.056	–
10	gemini-3.8-flash	E	0.71	**1.00**	0.92	0.95	0.61	0.97	**1.00**	**1.00**	0.86	**1.00**	0.89 [0.87, 0.91]	0.145	–
11	gpt-5.4-mini	E	0.74	**1.00**	0.92	0.92	0.66	0.96	0.97	0.90	0.87	0.93	0.88 [0.86, 0.91]	0.252	–
12	claude-sonnet-5	S	0.74	**1.00**	0.90	0.93	0.45	0.98	**1.00**	**1.00**	0.83	**1.00**	0.88 [0.85, 0.90]	0.711	–
13	mai-code-1.1-flash	E	0.57	**1.00**	0.87	0.89	0.56	0.96	0.89	0.95	0.81	0.92	0.84 [0.81, 0.86]	0.157	–
14	gpt-5-mini	E	0.65	**1.00**	0.85	0.92	0.40	0.92	0.93	0.85	0.79	0.89	0.82 [0.78, 0.85]	0.136	–
15	claude-haiku-4.5	E	0.68	0.98	0.88	0.84	0.23	0.96	0.86	0.79	0.76	0.82	0.78 [0.74, 0.81]	0.598	–
16	Qwen3.6 36B	L	0.66	**1.00**	0.81	0.82	0.06	0.96	0.80	0.85	0.72	0.82	0.75 [0.71, 0.77]	0.655	0.111
17	gpt-oss 20B	L	0.50	0.93	0.80	0.75	0.06	0.93	0.87	0.95	0.66	0.91	0.72 [0.70, 0.74]	0.087	0.019
18	Gemma 3 27B	L	0.69	0.80	0.76	0.81	0.09	0.93	0.58	0.88	0.68	0.73	0.69 [0.66, 0.72]	0.170	0.029
19	Gemma 4 8B	L	0.65	0.82	0.72	0.89	0.03	0.93	0.49	0.83	0.67	0.66	0.67 [0.64, 0.70]	0.183	0.036
20	Phi-4 reasoning plus 14.7B	L	0.54	0.75	0.62	0.59	0.13	0.88	0.81	0.79	0.59	0.80	0.64 [0.60, 0.67]	0.693	0.071
21	Qwen2.5-Coder 32B	L	0.53	0.77	0.76	0.65	0.04	0.87	0.42	0.93	0.60	0.67	0.62 [0.59, 0.65]	0.259	0.046
22	Qwen3-Coder 30B-A3B	L	0.53	0.77	0.62	0.72	0.07	0.89	0.53	0.83	0.60	0.68	0.62 [0.58, 0.65]	0.236	0.026
23	Qwen2.5 7B Instruct	L	0.41	0.68	0.52	0.68	0.04	0.80	0.31	0.69	0.52	0.50	0.52 [0.48, 0.55]	0.083	–
24	Gemma2 9B CPT SahabatAI (Q8_0)	L	0.49	0.70	0.61	0.66	0.07	0.89	0.11	0.60	0.57	0.36	0.52 [0.48, 0.55]	0.299	0.052
25	Llama 3.2 3B	L	0.38	0.40	0.41	0.41	0.03	0.82	0.09	0.40	0.41	0.25	0.37 [0.34, 0.40]	0.067	0.012




Fig. 1. Overall score against cost per 100 items (log scale; API: AI units at US$0.01; local: GPU time at an on-demand L40S price). The dashed line joins the models that no other model beats at equal or lower cost.

B. Cost

The leaders are close in quality but not in price. Per 100 items, kimi-k3 costs US$3.12, gpt-5.4 US$0.86, gpt-6.1-sol US$0.46 and claude-sonnet-5.5 US$0.78. gpt-6-luna reaches 0.901, 0.04 below the leader, for US$0.030, 104 times less than kimi-k3. 5 models form the cost–quality front (Fig. 1): kimi-k3, gpt-5.4, gpt-6.1-sol, gemini-3.7-flash, gpt-6-luna. Price does not follow the tiers we assigned by model names: kimi-k3, grouped with the economy models, is the most expensive per item because it reasons at length (median 34.5 s per call against 8.3 s for gpt-6.1-sol). The whole study cost US$46.65 in API calls—US$21.52 for the answers, US$24.50 for judging them and US$0.63 for probing the premium models on two items each—and 6.1 GPU-hours for the local models.

C. What separates the models

Not the two knowledge-heavy tasks, which are near ceiling for API models: all 15 answer at least 0.98 of the methodology questions correctly, and 14 of them score at least 0.95 on formal Indonesian (the lowest 0.92). This says that these items are too easy for API models, not that the models know the same. The tasks that produce artefacts separate them (Table III).

a) References: The widest spread among API models is in the references task (0.23–0.94). Of the references the API models listed, 0–40 % are not found in Crossref, and many found ones carry a wrong DOI: the share of listed references with the correct DOI ranges from 25 to 98 %. The audit qualifies the misses. Of the 130 references of API models that Crossref does not know, 17 % exist with matching title, year and first author in another source—works the Crossref-only score misses—, 4 % match only the title of a real work (wrong year or author, or a coinciding generic title), and 79 % are found nowhere; for the 681 misses of local models the shares are 3, 11 and 86 %. The audit's first pass exposed two Crossref pitfalls that the rule now handles (split subtitles, online-first dates). Per model, 0–31 % of the references an API model listed are found nowhere (Fig. 2). Crediting the works the audit finds as the scorer would raises a references score by at most 0.03 and leaves the ranking nearly unchanged (Spearman $\rho = 0.999$, largest rank shift 1). Models also differ in caution: gpt-5-mini lists 2.4 references per item, 0 % of them

TABLE III

DIAGNOSTICS BEHIND THE SCORES. REF: SHARE OF LISTED REFERENCES NOT FOUND IN CROSSREF (NOT CR), SHARE FOUND IN NONE OF CROSSREF, DOI.ORG, SCOPUS AND OPENALEX (NONE), AND SHARE WITH THE CORRECT DOI; REFS/ITEM: REFERENCES LISTED PER ITEM (5 REQUESTED). CODE: SHARE OF TASKS SOLVED BY THE FIRST PROGRAM AND AFTER ONE REPAIR TURN. TEX FIX: BROKEN DOCUMENTS THAT COMPILE AFTER THE MODEL'S FIX. GROUNDED: NUMBERS PER REVIEW FOUND IN NO SOURCE; SHARE OF REVIEWS WITH AUTHOR–YEAR CITATIONS (FORBIDDEN). EXT. EVID.: SHARE OF QUOTED EVIDENCE FOUND VERBATIM IN THE EXCERPT. GENERIC IV: SHARE OF OUTLINES WITH A TEST-CENTRED RESULTS CHAPTER WHERE THE PROGRAMME'S THESES HAVE NONE.

		References				Code		TeX	Grounded		Ext.	Generic	Median
Model	T	not CR %	none %	DOI %	refs/item	pass@1	+repair	fix	unsup.	auth.–yr %	evid.	IV %	s/call
kimi-k3	E	2	1	89	5.0	1.00	1.00	0.88	0.03	3	0.82	6	34.5
gpt-5.4	S	0	0	91	4.4	1.00	1.00	1.00	0.00	0	0.96	23	7.9
gpt-6.1-sol	S	0	0	98	4.1	1.00	1.00	1.00	0.10	0	1.00	26	8.3
claude-sonnet-5.5	S	7	2	84	4.1	0.97	1.00	1.00	0.10	0	0.90	34	4.8
gpt-5.6-terra	S	2	2	89	4.2	0.97	1.00	0.88	0.10	0	0.96	17	5.9
gemini-3.7-flash	E	21	19	63	5.0	1.00	1.00	1.00	0.00	0	0.93	23	15.4
gemini-4-argon	S	3	1	90	3.5	1.00	1.00	1.00	0.07	0	0.92	26	5.8
gpt-6-luna	S	8	6	82	4.5	1.00	1.00	0.50	0.07	0	0.88	14	7.0
claude-haiku-5.5	E	3	1	83	3.8	1.00	1.00	0.88	0.07	10	0.99	29	6.8
gemini-3.8-flash	E	27	26	62	4.5	1.00	1.00	1.00	0.10	0	0.95	26	18.6
gpt-5.4-mini	E	8	7	57	4.4	0.97	1.00	0.75	0.00	0	0.89	17	4.8
claude-sonnet-5	S	14	8	66	3.0	1.00	1.00	1.00	0.00	7	0.89	31	5.8
mai-code-1.1-flash	E	27	22	45	4.8	0.87	0.97	0.88	0.17	3	0.88	14	7.9
gpt-5-mini	E	2	0	69	2.4	0.93	0.97	0.62	0.00	3	0.94	34	7.7
claude-haiku-4.5	E	40	31	25	2.8	0.83	0.97	0.50	0.07	0	0.47	23	10.6
Qwen3.6 36B	L	74	63	9	1.8	0.80	0.90	0.62	0.00	0	0.92	20	57.7
gpt-oss 20B	L	86	77	1	3.5	0.87	0.90	0.88	0.13	43	0.68	26	4.1
Gemma 3 27B	L	83	70	1	5.0	0.53	0.60	0.75	0.07	40	0.90	20	9.6
Gemma 4 8B	L	91	85	0	3.4	0.43	0.73	0.62	0.00	3	0.97	20	13.6
Phi-4 reasoning plus 14.7B	L	77	61	2	4.7	0.80	0.93	0.62	0.17	77	0.49	14	8.7
Qwen2.5-Coder 32B	L	90	74	0	4.7	0.40	0.80	0.88	0.17	87	0.82	20	20.2
Qwen3-Coder 30B-A3B	L	90	78	3	5.0	0.50	0.77	0.62	0.00	67	0.67	6	3.2
Qwen2.5 7B Instruct	L	86	75	0	3.2	0.13	0.30	0.50	0.10	43	0.66	26	4.7
Gemma2 9B CPT SahabatAI (Q8_0)	L	84	73	1	3.9	0.10	0.13	0.25	0.00	77	0.87	26	5.9
Llama 3.2 3B	L	95	85	0	4.5	0.03	0.03	0.25	0.80	93	0.57	6	3.4




Fig. 2. Share of listed references not found in Crossref (light) and found in none of Crossref, doi.org, Scopus and OpenAlex (dark), with the number of references each model listed for the 20 topics (at most 100).

found nowhere, gemini-3.7-flash always lists five (19 %), and kimi-k3 five (1 %). Because the score counts abstention like an unverifiable reference, cautious models are not rewarded for listing fewer; the share found nowhere is the number to read for safety.

b) Outlines: Chapter outlines score 0.57–0.79 for API models. A frequent mismatch is the test-centred results chapter: 6–34 % of the API outlines build chapter IV around assumption, instrument or hypothesis tests for programmes whose theses do not organise their results that way.

c) Code and LaTeX: 9 of the 15 API models solve every coding task with their first program. Repairing a broken LaTeX document is harder than typesetting a table or a BibTeX entry, which all API models do correctly: the weakest API models produce a compilable document for only 0.50 of the broken ones.

d) Grounded writing: By the deterministic checks, API models keep to the given sources: at most 0.17 numbers per review occur in no source, and author–year citations, which the task forbids, appear in at most 10 % of their reviews. Several local models ignore the citation format (author–year citations in up to 93 % of their reviews).

D. Local models

The best local model, Qwen3.6 36B (0.745), stays below the weakest API model, claude-haiku-4.5 (0.777). Between the group means the gap is largest for references (0.59) and code (0.47), smaller for methodology (0.24) and smallest for formal Indonesian (0.08): local models write formal Indonesian at 0.80–0.96, and Qwen3.6 36B scores 1.00 on the methodology questions. Of the references local models list, 61–85 % are found nowhere, and they solve 0.03–0.87 of the coding tasks with their first program (mean 0.46, rising to 0.61 after one repair turn). The Indonesian-tuned SahabatAI 9B scores lower on formal Indonesian than the general Gemma 4 8B (0.891




Fig. 3. GPU board energy per 100 items of the local models (gross; shared server; Qwen2.5 7B not measured), with the overall score in brackets.

against 0.925) and fails at code (0.11), so its overall score (0.517) stays below Gemma 4's (0.668). At an on-demand L40S price and three parallel requests, local models cost US$0.07–0.69 per 100 items, no less than the cheapest API models, and drew 0.012–0.111 kWh per 100 items (Fig. 3); gpt-oss 20B gives the most score per kWh in this setup (0.723 for 0.019 kWh and US$0.087 per 100 items).

E. Judges and provenance

The three judges rated 1,500 answers with 3,480 ratings. On the 480 answers that all three rated (candidates from vendors other than the judges'), their mean ratings agree with Krippendorff's $\alpha = 0.86$ (interval); single criteria agree less (α from 0.46 to 0.80, ordinal), least for instruction compliance and faithfulness. The judges' leniency differs by up to 0.07 on the 0–1 scale, which the calibration removes. Their scores follow the deterministic checks: Spearman's ρ is 0.69 (grounded) and 0.53 (language) across answers, and 0.82 and 0.82 across model means. The extraction panel agreed unanimously on 77 % of the fields; analysis techniques were the hardest field (no majority on 6 of 30 excerpts, which are therefore not scored). In all 7,356 API calls of the study the SDK reported the requested model as the one that answered: the silent substitution reported for the same SDK when an account is not entitled to a model [8] did not occur here. The check rests on the SDK's own usage event, not on an independent test of the backend.

VI. Discussion

a) Choosing a model: The leading API models are not significantly different on this benchmark, so price can decide among them: gpt-6.1-sol gives 0.931 for US$0.46 per 100 items and gemini-3.7-flash 0.911 for US$0.141, against 0.941 for US$3.12; gpt-6-luna (0.901 for US$0.030) is the economical choice for high-volume use. The cheapest good models are not the ones with *mini* or *flash* in their names, and the most expensive model was not a flagship: measured cost per item is a better guide than tier labels.

b) References need a checker, whatever the model: 12 of the 15 API models listed references that no database knows, and many listed real works with a wrong DOI, year or author (Fig. 2). A reference produced by a model should be verified before it enters a thesis; a lookup in Crossref, with a second database for the misses, costs next to nothing compared with a fabricated citation in an examined document. Thesis tools should treat references as a retrieval problem, not a generation problem.

c) Local models: Local models are the option when data may not leave the institution, and for the tasks where they come close to API models: rewriting text into formal Indonesian and answering methodology questions. They were not cheaper per item at rental prices than the cheapest API models of much higher quality, and they should not be trusted with references. The model tuned for Indonesian did not outperform a newer general model of its size, which suggests that for these tasks a recent general model is a better starting point than language specialisation alone (one pair of models with different quantisation; not a controlled comparison).

d) Benchmark design: Two tasks are near ceiling for API models (methodology, formal Indonesian) while still separating local models; harder variants—open questions, longer drafts with subtler non-standard forms—would extend their range. Judging was the largest cost item. Scoring the prose tasks by the deterministic checks alone barely changes the overall ranking (Spearman $\rho = 0.994$, largest rank shift 3), so judging a stratified sample of answers may suffice; we have not tested this.

e) Limitations: Each model answered each item once, at low reasoning effort, so run-to-run variation is not measured; the 9 premium-tier models (estimated at about US$50) and a high-effort check of the best models are not in this version. AI units are the vendor's billing measure at one point in time, hosted models change without notice, and the served-model check relies on the SDK's report. The structure references and the extraction excerpts come from the theses of one university; extraction is scored against silver labels, which for a candidate come from the panel members of other vendors and therefore differ between vendors; the extraction items are private, but without them the ranking is almost the same (Spearman $\rho = 0.999$, largest rank shift 1). Neither the LLM judges nor the item keys have yet been checked by people, and the items were drafted with LLM assistance, which may favour LLM phrasing; deterministic scoring limits this risk but does not remove it. The grounded checks test citation form, coverage and numbers, not whether each cited claim is supported, which is left to the judges. A real work that none of the four databases knows counts as not found. Local models ran 4-bit quantised in one serving stack, their energy was measured on a shared server, and their cost depends on the concurrency used.

VII. Conclusion

SkripsiBench measures several things that Indonesian thesis work needs from an LLM—outlines that fit the study programme, faithful use of sources, real references, formal Indonesian, correct analysis code and compilable LaTeX—together with what each answer costs and which model produced it. Across 25 models, the three best API models are not significantly different while the cost of the API models spans two orders of magnitude, references separate the models most, and on average local models trail on every task, least on

formal Indonesian. The practical advice is to choose by price among the leaders, to verify every reference, and to use local models where privacy requires it. The kit evaluates any further model with one command; the premium tier, high reasoning effort, repeated runs and a human check of the judges and keys are the next steps.

References

[1] D. Hendrycks, C. Burns, S. Basart, A. Zou, M. Mazeika, D. X. Song, and J. Steinhardt, "Measuring Massive Multitask Language Understanding," in *International Conference on Learning Representations (ICLR)*, 2021, arXiv:2009.03300.

[2] P. Liang, R. Bommasani, T. Lee, D. Tsipras, D. Soylu, M. Yasunaga *et al.*, "Holistic Evaluation of Language Models," *Transactions on Machine Learning Research*, 2023, arXiv:2211.09110. [Online]. Available: https://openreview.net/forum?id=iO4LZibEqW

[3] B. Wilie, K. Vincentio, G. I. Winata, S. Cahyawijaya, X. Li, Z. Y. Lim, S. Soleman, R. Mahendra, P. Fung, S. Bahar, and A. Purwarianti, "IndoNLU: Benchmark and Resources for Evaluating Indonesian Natural Language Understanding," in *Proceedings of the 1st Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 10th International Joint Conference on Natural Language Processing*. Association for Computational Linguistics, 2020, pp. 843–857, doi: 10.18653/v1/2020.aacl-main.85.

[4] F. Koto, A. Rahimi, J. H. Lau, and T. Baldwin, "IndoLEM and IndoBERT: A Benchmark Dataset and Pre-trained Language Model for Indonesian NLP," in *Proceedings of the 28th International Conference on Computational Linguistics*. International Committee on Computational Linguistics, 2020, pp. 757–770, doi: 10.18653/v1/2020.coling-main.66.

[5] G. I. Winata, A. F. Aji, S. Cahyawijaya, R. Mahendra, F. Koto, A. Romadhony, K. Kurniawan, D. Moeljadi, R. E. Prasojo, P. Fung, T. Baldwin, J. H. Lau, R. Sennrich, and S. Ruder, "NusaX: Multilingual Parallel Sentiment Dataset for 10 Indonesian Local Languages," in *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*. Association for Computational Linguistics, 2023, pp. 815–834, doi: 10.18653/v1/2023.eacl-main.57.

[6] F. Koto, N. Aisyah, H. Li, and T. Baldwin, "Large Language Models Only Pass Primary School Exams in Indonesia: A Comprehensive Test on IndoMMLU," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2023, pp. 12 359–12 374, doi: 10.18653/v1/2023.emnlp-main.760.

[7] B. Wang, Z. Liu, X. Huang, F. Jiao, Y. Ding, A. Aw, and N. Chen, "SeaEval for Multilingual Foundation Models: From Cross-Lingual Alignment to Cultural Reasoning," in *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*. Association for Computational Linguistics, 2024, pp. 370–390, doi: 10.18653/v1/2024.naacl-long.22.

[8] Andi Agung Dwi Arya B, "Which Model Actually Answered? Silent Model Substitution, Deterministic Validators, and Multi-Model Routing in an LLM Paper Agent," Manuscript, 2026, code and data: https://github.com/devnolife/paper-agent.

[9] S. Cahyawijaya, H. Lovenia, F. Koto, R. Putri, W. Cenggoro, J. Lee, S. Akbar, E. Dave, N. Nuurshadieq, M. Mahendra, R. Putri, B. Wilie, G. Winata, A. Aji, A. Purwarianti, and P. Fung, "Cendol: Open Instruction-tuned Generative Large Language Models for Indonesian Languages," in *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, 2024, pp. 14 899–14 914, doi: 10.18653/v1/2024.acl-long.796.

[10] L. Zheng, W.-L. Chiang, Y. Sheng, S. Zhuang, Z. Wu, Y. Zhuang, Z. Lin, Z. Li, D. Li, E. Xing, H. Zhang, J. Gonzalez, and I. Stoica, "Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena," in *Advances in Neural Information Processing Systems 36*, ser. NeurIPS 2023. Neural Information Processing Systems Foundation, Inc. (NeurIPS), 2023, pp. 46 595–46 623, doi: 10.52202/075280-2020.

[11] Y. Liu, D. Iter, Y. Xu, S. Wang, R. Xu, and C. Zhu, "G-Eval: NLG Evaluation using Gpt-4 with Better Human Alignment," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2023, pp. 2511–2522, doi: 10.18653/v1/2023.emnlp-main.153.

[12] C.-H. Chiang and H.-y. Lee, "Can Large Language Models Be an Alternative to Human Evaluations?" in *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. Association for Computational Linguistics, 2023, pp. 15 607–15 631, doi: 10.18653/v1/2023.acl-long.870.

[13] A. Panickssery, S. Bowman, and S. Feng, "LLM Evaluators Recognize and Favor Their Own Generations," in *Advances in Neural Information Processing Systems 37*, ser. NeurIPS 2024. Neural Information Processing Systems Foundation, Inc. (NeurIPS), 2024, pp. 68 772–68 802, doi: 10.52202/079017-2197.

[14] T. Gao, H. Yen, J. Yu, and D. Chen, "Enabling Large Language Models to Generate Text with Citations," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2023, pp. 6465–6488, doi: 10.18653/v1/2023.emnlp-main.398.

[15] S. Min, K. Krishna, X. Lyu, M. Lewis, W.-t. Yih, P. Koh, M. Iyyer, L. Zettlemoyer, and H. Hajishirzi, "FActScore: Fine-grained Atomic Evaluation of Factual Precision in Long Form Text Generation," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 2023, pp. 12 076–12 100, doi: 10.18653/v1/2023.emnlp-main.741.

[16] W. H. Walters and E. I. Wilder, "Fabrication and errors in the bibliographic citations generated by ChatGPT," *Scientific Reports*, vol. 13, no. 1, Sep. 2023, doi: 10.1038/s41598-023-41032-5.

[17] L. Huang, W. Yu, W. Ma, W. Zhong, Z. Feng, H. Wang, Q. Chen, W. Peng, X. Feng, B. Qin, and T. Liu, "A Survey on Hallucination in Large Language Models: Principles, Taxonomy, Challenges, and Open Questions," *ACM Transactions on Information Systems*, vol. 43, no. 2, pp. 1–55, Jan. 2025, doi: 10.1145/3703155.

[18] M. Chen, J. Tworek, H. Jun, Q. Yuan, H. P. de Oliveira Pinto, J. Kaplan, H. Edwards, Y. Burda, N. Joseph, G. Brockman, A. Ray, R. Puri, G. Krueger, M. Petrov, H. Khlaaf, G. Sastry, P. Mishkin, B. Chan, S. Gray, N. Ryder, M. Pavlov, A. Power, L. Kaiser, M. Bavarian, C. Winter, P. Tillet, F. P. Such, D. Cummings, M. Plappert, F. Chantzis, E. Barnes, A. Herbert-Voss, W. H. Guss, A. Nichol, A. Paino, N. Tezak, J. Tang, I. Babuschkin, S. Balaji, S. Jain, W. Saunders, C. Hesse, A. N. Carr, J. Leike, J. Achiam, V. Misra, E. Morikawa, A. Radford, M. Knight, M. Brundage, M. Murati, K. Mayer, P. Welinder, B. McGrew, D. Amodei, S. McCandlish, I. Sutskever, and W. Zaremba, "Evaluating Large Language Models Trained on Code," 2021, arXiv:2107.03374.

[19] Y. Lai, C. Li, Y. Wang, T. Zhang, R. Zhong, L. Zettlemoyer, S. Yih, D. Fried, S. Wang, and C. Yu, "DS-1000: A Natural and Reliable Benchmark for Data Science Code Generation," in *Proceedings of the 40th International Conference on Machine Learning*, 2023, arXiv:2211.11501.

[20] E. Strubell, A. Ganesh, and A. McCallum, "Energy and Policy Considerations for Deep Learning in NLP," in *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*. Association for Computational Linguistics, 2019, pp. 3645–3650, doi: 10.18653/v1/p19-1355.

[21] S. Luccioni, Y. Jernite, and E. Strubell, "Power Hungry Processing: Watts Driving the Cost of AI Deployment?" in *The 2024 ACM Conference on Fairness Accountability and Transparency*, ser. FAccT '24. ACM, Jun. 2024, pp. 85–99, doi: 10.1145/3630106.3658542.

[22] G. Hendricks, D. Tkaczyk, J. Lin, and P. Feeney, "Crossref: The sustainable source of community-owned scholarly metadata," *Quantitative Science Studies*, vol. 1, no. 1, pp. 414–427, Feb. 2020, doi: 10.1162/qss_a_00022.

[23] J. Priem, H. Piwowar, and R. Orr, "OpenAlex: A fully-open index of scholarly works, authors, venues, institutions, and concepts," 2022, arXiv:2205.01833.

[24] A. F. Hayes and K. Krippendorff, "Answering the Call for a Standard Reliability Measure for Coding Data," *Communication Methods and Measures*, vol. 1, no. 1, pp. 77–89, Apr. 2007, doi: 10.1080/19312450709336664.

[25] GitHub, "GitHub Copilot SDK for Python (github-copilot-sdk)," https://github.com/github/copilot-sdk, 2026, version 1.0.9, accessed Oct. 2026.

[26] Ollama contributors, "Ollama: get up and running with large language models locally," https://github.com/ollama/ollama, 2026, version 0.22.0.

[27] RunPod, "L40S GPU Rental: Specs and Pricing," https://www.runpod.io/gpu-models/l40s, 2026, page updated 2026-08-27, accessed 2026-10-14.

[28] B. Efron, "Bootstrap Methods: Another Look at the Jackknife," *The Annals of Statistics*, vol. 7, no. 1, Jan. 1979, doi: 10.1214/aos/1176344552.