MOSFET – N-Channel, QFET

400 V, 16 A, 270 mΩ

FQP17N40



TO−220−3
CASE 340AT



Description

This N−Channel Enhancement Mode Power MOSFET is produced using **onsemi**'s proprietary planar stripe and DMOS technology. This advanced MOSFET technology has been especially tailored to reduce on−state resistance, and to provide superior switching performance and high avalanche energy strength. These devices are suitable for switched mode power supplies, active power factor correction (PFC), and electronic lamp ballasts.

Features

- 16 A, 400 V $R_{DS(on)}$ = 270 mΩ (Max.) @ V_{GS} = 10 V, I_D = 8.0 A
- Low Gate Charge (Typ. 45 nC)
- Low C_{rss} (Typ. 30 pF)
- 100% Avalanche Tested
- This Device is Pb−Free.

ABSOLUTE MAXIMUM RATINGS

(T_C = 25°C unless otherwise noted.)

Symbol	Parameter	Value	Unit
V_{DSS}	Drain−Source Voltage	400	V
I_D	Drain Current − Continuous (T_C = 25°C) − Continuous (T_C = 100°C)	 16 10.1	A
I_{DM}	Drain Current − Pulsed (Note 1)	64	A
V_{GSS}	Gate−Source Voltage	±30	V
E_{AS}	Single Pulsed Avalanche Energy (Note 2)	1000	mJ
I_{AR}	Avalanche Current (Note 1)	16	A
E_{AR}	Repetitive Avalanche Energy (Note 1)	17	mJ
dv/dt	Peak Diode Recovery dv/dt (Note 3)	4.5	V/ns
P_D	Power Dissipation − (T_C = 25°C) − Derate Above 25°C	 170 1.35	W W/°C
T_J,T_{STG}	Operating and Storage Temperature Range	−55 to +150	°C
T_L	Maximum Lead Temperature for Soldering Purpose, 1/8" from Case for 5 Seconds	300	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

MARKING DIAGRAM



&Z	= Assembly Plant Code
&3	= Date Code (Year & week)
&K	= 2−Digit Lot Code
FQP17N40	= Specific Device Code

ORDERING INFORMATION

Device	Package	Shipping†
FQP17N40	TO−220−3 (Pb−Free)	1000 Units / Tube

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

THERMAL CHARACTERISTICS

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction−to−Case, Max	0.74	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction−to−Ambient, Max.	62.5	

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Off Characteristics						
BV_{DSS}	Drain−Source Breakdown Voltage	V_{GS} = 0 V, I_D = 250 μA	400	–	–	V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I_D = 250 μA, Referenced to 25°C	–	0.44	–	V/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 400 V, V_{GS} = 0 V	–	–	1	μA
		V_{DS} = 320 V, T_C = 125°C	–	–	10	μA
I_{GSSF}	Gate−Body Leakage Current, Forward	V_{GS} = 30 V, V_{DS} = 0 V	–	–	100	nA
I_{GSSR}	Gate−Body Leakage Current, Reverse	V_{GS} = −30 V, V_{DS} = 0 V	–	–	−100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250 μA	3.0	–	5.0	V
$R_{DS(on)}$	Static Drain−Source On−Resistance	V_{GS} = 10 V, I_D = 8.0 A	–	0.21	0.27	Ω
g_{FS}	Forward Transconductance	V_{DS} = 50 V, I_D = 8.0 A	–	13	–	S
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS} = 25 V, V_{GS} = 0 V, f = 1.0 MHz	–	1800	2300	pF
C_{oss}	Output Capacitance		–	270	350	pF
C_{rss}	Reverse Transfer Capacitance		–	30	40	pF
Switching Characteristics						
$t_{d(on)}$	Turn−On Delay Time	V_{DD} = 200 V, I_D = 17.2 A, R_G = 25 Ω (Note 4)	–	40	90	ns
t_r	Turn−On Rise Time		–	185	380	ns
$t_{d(off)}$	Turn−Off Delay Time		–	90	190	ns
t_f	Turn−Off Fall Time		–	105	220	ns
Q_g	Total Gate Charge	V_{DS} = 320 V, I_D = 17.2 A, V_{GS} = 10 V (Note 4)	–	45	60	nC
Q_{gs}	Gate−Source Charge		–	11.4	–	nC
Q_{gd}	Gate−Drain Charge		–	21.7	–	nC
Drain−Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain−Source Diode Forward Current		–	–	16	A
I_{SM}	Maximum Pulsed Drain−Source Diode Forward Current		–	–	64	A
V_{SD}	Drain−Source Diode Forward Voltage	V_{GS} = 0 V, I_S = 16 A	–	–	1.5	V
t_{rr}	Reverse Recovery Time	V_{GS} = 0 V, I_S = 17.2 A, dI_F/dt = 100 A/μs	–	290	–	ns
Q_{rr}	Reverse Recovery Charge		–	2.5	–	μC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

NOTES:
1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. L = 6.8 mH, I_{AS} = 16 A, V_{DD} = 50 V, R_G = 25, Ω starting T_J = 25°C.
3. I_{SD} ≤ 17.2 A, di/dt ≤ 200 A/μs, V_{DD} ≤ BV_{DSS}, starting T_J = 25°C.
4. Essentially independent of operating temperature.

TYPICAL CHARACTERISTICS



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance Variation vs Drain Current and Gate Voltage



Figure 4. Body Diode Forward Voltage Variation vs Source Current and Temperature



Figure 5. Capacitance Characteristics



Figure 6. Gate Charge Characteristics

TYPICAL CHARACTERISTICS (CONTINUED)



Figure 7. Breakdown Voltage Variation vs Temperature



Figure 8. On−Resistance Variation vs Temperature



Figure 9. Maximum Safe Operating Area



Figure 10. Maximum Drain Current vs. Case Temperature



Figure 11. Transient Thermal Response Curve



Figure 12. Gate Charge Test Circuit & Waveform



Figure 13. Resistive Switching Test Circuit & Waveforms



Figure 14. Unclamped Inductive Switching Test Circuit & Waveforms



Figure 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS

ON Semiconductor®

TO−220−3LD
CASE 340AT
ISSUE A

DATE 03 OCT 2017



Scale 1:1

NOTES:
A) REFERENCE JEDEC, TO-220, VARIATION AB
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS COMMON TO ALL PACKAGE SUPPLIERS EXCEPT WHERE NOTED [ ].
D) LOCATION OF MOLDED FEATURE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE)
E DOES NOT COMPLY JEDEC STANDARD VALUE.
F) "A1" DIMENSIONS AS BELOW:
SINGLE GAUGE = 0.51 - 0.61
DUAL GAUGE = 1.10 - 1.45
G PRESENCE IS SUPPLIER DEPENDENT
H) SUPPLIER DEPENDENT MOLD LOCKING HOLES IN HEATSINK.

DOCUMENT NUMBER:	**98AON13818G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**TO−220−3LD**	**PAGE 1 OF 1**

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales