GITHUB

DIFFERENCE BETWEEN PUBLIC AND PRIVATE REPO

1.PUBLIC REPOSITORY

1. Anyone can see the code (open to everyone on platforms like GitHub)
2. Good for open-source projects
3. No restriction on viewing
4. Anyone can fork or contribute (if allowed)

2.PRIVATE REPOSITORY

1. Only selected people can see the code
2. Used for company or personal projects
3. Access is restricted (need permission)
4. More secure and confidential

GIT FORK & PULL REQUEST

GIT FORK

Git Fork is a way of copying another user's repository into our repository.

1. You fork when the repo is not yours (ex: open-source project).
2. It creates a separate copy under your GitHub account.
3. You can modify your fork freely.

PULL REQUEST

PR = Asking the original repo owner to merge your changes.

1. After making changes in your fork → commit → push → then you send a PR.
2. Owner reviews → approves → merges if correct.

AUTHENTICATION (SSH/HTTP)

1.HOW TO GET THE SSH OF REMOTE REPOSITORY (SSH)

1. create a instance
2. access the instance
    1. ssh-keygen
    2. cd .ssh/
    3. ls
    4. Copy the public key (id_rsa.pub)

3. go to repo -----> settings ------> ssh & gpg keys -----> create ssh key -------> authentication -----> paste the public-key -----> add ssh key
4. create a private repository (student)
    1. copy the ssh_url of repo
5. on server
    1. mkdir student
    2. cd student
    3. git init
    4. echo “hello” > index.html
    5. git add .
    6. git commit -m “v1”
    7. git push <ssh_repo_url> master

2.HOW TO CREATE A PERSONAL ACCESS TOKEN (HTTP)

go to repo ------> settings -----> developer setting ------> personal access token -----> tokens classic -------> generate new token ------> generate new token (classic)

HOW TO CREATE A PRIVATE REPOSITORY & ACCESS USING HTTP

1. Create a private repository
2. get access on ubuntu terminal
   git clone <private_repo_url>
   username:
   password:

Note:

1. assign the username
2. But u have to create a PAT first then assign the password as a PAT token

---

HOW TO DELETE A SPECIFIC REPOSITORY

1. click on the repository
2. go to repository settings
3. at last ---------> delete these repository
4. copy the repo name and paste it to delete

TASK:

1.Host (install) a Gitea on server (self-hosted server)
