LINUX BASIC COMMANDS

HOW TO CHANGE THE DIRECTORY / FOLDER

1.cd ----------> To change the directory/folder

2.cd Document -----> To go inside the Document

3.cd .. ----------> To return to the parent directory

4.cd /etc ----------> to go inside the etc directory

5. cd ~ ----------> Go to home directory

HOW TO CREATE A FILES

1.touch file1 ----------> to create a empty file

2.touch file1.txt ----------> to create a file with extensions

3.file file1 ----------> to check type of file
***Output*: -** File1: ASCII text

4.file file1.txt ----------> to check type of file
***Output*: -** File1: ASCII text

5.cat >file2 ----------> to create a file with data
Hello World
ctrl+d

6.cat file2 ----------> to check the file content
7.ls dir1 ----------> to check the directory content

8.cat >>file2 ----------> to add data into the existing file
Hey Linux!
ctrl+d

Note: -
1. Linux does not require file extensions in Linux
2. File type is identified by content, not by extension
3.ctrl+d ----------> to save and exit the file
4. > ----------> redirector (these sign helps us to redirect content into the file)
5.>> ----------> append (these sign helps us to add the content in the existing file)

HOW TO REMOVE FILES

1.rm file1 ----------> To remove the file

2.rm -rf ----------> To remove the files & directories recursive forcefully

CLOUDBLITZ

Note: -
r -------> Recursive (delete folders and inside content)
f -------> Forcefully

HOW TO REMOVE DIRECTORIES

1.rmdir ----------> To remove the empty directory

2.rm -rf ----------> To remove the files & directories recursive forcefully

Note: -
r -------> Recursive (delete folders and inside content)
f -------> Forcefully

HOW TO COPY & PASTE THE FILES

Syntax: - cp <source path> <destination path>

1.cp file1 /opt/ ----------> to copy file into the opt directory

2.cp -r demo /opt/ ---------> to copy the demo directory into the opt directory

3.ls /opt ----------> to check files of opt directory

4.cp file1 file2 ----------> it creates the file2 with the content of file1

Note: -
r ----------> recursive (used for directories)

HOW TO MOVE & RENAME THE FILES

CLOUDBLITZ

Syntax: - mv <source path> <destination path>

1.mv file1 file2 ----------> to rename the file

2.mv file1 /opt/ ----------> move file to opt directory/folder

---

READ OPERATIONS

1.cat ----------> to read the file from bottom to top
2.head ----------> to get 1st 10 lines of a file
3.head -n 5 file -> to get the 1st 5 lines of a file (n=number of lines)
4.tail ----------> to get last 10 lines of a file
5.tail -n 5 file ---> to get the last 5 lines of a file (n=number of lines)
6.less ----------> read the file from top to bottom also scroll the file content with Up and down arrows
7.more ----------> read the file from top to bottom also scroll the file content with Enter key

BASIC COMMANDS

1.sort file1 ---------> sort the file in the alphabetical order (top to bottom)
2.sort -r file1 ------> sort the file in alphabetical order but in a recursive order (bottom to top)

Note: -
when we sort the file, we get the numbers first then capital letter words then small letters words if the number and the capital letters are in the file.

3.wc ----------> to check the word counts
1.wc -l file1 ------> to get only the lines
2.wc -w file1 -----> to get only the words
3.wc -m file1 -----> to get only the characters

UNIQ / SORT / PIPELINE COMMAND

4.uniq ----------> to filter out uniq words/sentence
Example: -
1.cat >demo
I like pizza
I like pizza
Thank you
Thank you
Bye
I like pizza
Hello
Bye
2.uniq demo
I like pizza
Thank you
Bye
I like pizza
Hello
Bye

CLOUDBLITZ

Note: -
1.uniq command works on the Adjacent (means next to or very close to something).
2.But in this command, we get the duplicate lines

3.sort demo
Bye
Bye
Hello
I like pizza

I like pizza
I like pizza
Thank you
Thank you

4.sort demo | uniq
Bye
Hello
I like pizza
Thank you

Note: -

1.In this command we simply sort the file and get the uniq content from the file because of pipeline command

2.pipeline command ----------> A pipeline (|) takes the output of the first command and sends it as the input to the second command.

CLOUDBLITZ