CourtFlex

How to run the dev server

Start the player app and the owner portal on your computer, sign in with the demo accounts, and fix the usual problems. Everything runs on one address with a built-in demo API, so no backend or database is needed.

Short version: `pnpm install` then `pnpm dev`, and open localhost:5174

1 What you need

Tool	Version	Check it with
Node.js	22 or newer (tested on 24)	`node -v`
pnpm	9.15.9	`pnpm -v`
Google Chrome	Any recent version	Only needed for the browser tests

If pnpm is missing, turn it on with Node's built-in Corepack. It picks the right version from the project automatically:

```
> corepack enable
```

2 Install, once

Open a terminal in the project folder (`E:\pickleball`) and install the packages. Run it again whenever `package.json` changes.

```
> cd E:\pickleball
> pnpm install
```

3 Start the dev server

```
> pnpm dev
```

This starts two small servers side by side and joins them into one address. Wait until the terminal shows `ready` twice, then open:

Open this	For	What you see
`http://localhost:5174/`	Everyone	The landing page
`http://localhost:5174/login`	Everyone	The one sign-in page for players, owners and staff
`http://localhost:5174/home`	Players	Courts, bookings, open play, clubs
`http://localhost:5174/owner/`	Court owners and staff	The owner portal for their venue
`http://localhost:5174/owner/style`	Designers and developers	The design system page

> `localhost:5174` and `127.0.0.1:5174` both work. Always use port **5174**. The owner portal also runs on 5173 behind the scenes, but opened directly there it can't reach the demo data or the shared sign-in.

To stop the servers, click the terminal and press `Ctrl` + `C`. Answer `Y` if Windows asks to end the batch job.

4 Sign in with a demo account

Every demo account uses the password `password`. The sign-in page also lists them, so you can fill one in with a click. After signing in, owners and staff go to the owner portal and players go to their home page.

Court owners and staff

- `owner@example.test`: Alex, owns three venues
- `manager@example.test`: Dana, manager at Mauban
- `staff@example.test`: Taylor, front desk at Mauban

Players

- `player1@example.test`: Jamie, runs the Tara Pikol club
- `carla@example.test`: Carla, runs Lucena Dinkers
- `player2@example.test`: Sam, club waiting for review
- `trisha@example.test`: Trisha, new player

People who are both, such as an owner who also plays, switch sides from the menu ("Switch to player app" in the portal, "Owner portal" on the player's Me page) without signing in again.

5 About the demo data

- There's no real backend yet. A demo API inside the browser answers every request and follows the same rules the real one will.
- Demo data is kept for the browser tab, so a booking made as a player shows up in the owner's calendar.
- To start over, click the flask button in the bottom-left corner and choose **Reset mock data**. Opening a new tab also starts fresh.
- The same flask menu can simulate being offline, and approve clubs that are waiting for review.
- New accounts use the email code `246810`. Password reset shows the link on screen instead of emailing it.

6 Other useful commands

Command	What it does
`pnpm dev:player`	Starts only the player app (the owner portal at /owner won't load)
`pnpm dev:portal`	Starts only the owner portal's server. Open it through 5174 with the player app also running
`pnpm test`	Runs the unit tests (business rules against the demo API)
`pnpm e2e`	Runs the browser tests in Chrome, on desktop and phone sizes. Starts its own servers
`pnpm typecheck`	Checks the TypeScript types
`pnpm lint` / `pnpm format`	Checks code style / fixes formatting
`pnpm build`	Builds the whole site into `apps/player/dist`, with the owner portal in `dist/owner`

7 If something goes wrong

"Port 5174 is in use" or "Port 5173 is in use"

A server from earlier is still running. Close that terminal, or find and stop it:

```
> netstat -ano | findstr :5174
> taskkill /PID <the number at the end of the line> /F
```

The owner portal page is blank or shows "not found"

Make sure you started with `pnpm dev` (both servers) and opened it at `localhost:5174/owner/`, not 5173.

The page shows old data or behaves strangely

Use **Reset mock data** in the flask menu, or close the tab and open a new one. If the app was installed as a phone or desktop app, a hard refresh (`Ctrl` + `Shift` + `R`) clears the cached copy.

"Cannot find module" or errors after pulling new code

```
> pnpm install
```

The servers stop by themselves

The computer may be low on memory. Close other heavy programs (extra browser tabs, other dev servers) and run `pnpm dev` again.

> The first page load after starting can take a few seconds while the dev server prepares the code. Later loads are fast.
