accessScan

Scan results for **codepen.io/leezee/pen/eYbXzpJ**

Non-compliant

Your scan found serious accessibility issues. Let's fix them now to help you meet accessibility requirements and mitigate legal risk.

Fri Mar 6, 2026

Your website is not inclusive and accessible to people with disabilities.
Fix issues now >

107 We found 107 issues on your page

Issue severity

Moderate	Minor	Serious	Critical
0	0	2	105

Issues detected by category

- 83 General
- 6 Tabs
- 1 Landmarks
- 0 Dragging Alternative
- 0 Lists
- 0 Tables
- 16 Graphics
- 1 Interactive Content
- 0 Forms
- 0 ARIA
- 0 Metadata

#	Element	Relevant	Successes	Failures	Score
1	The alt attribute is used to provide a text alternative for images. It is not meant to be used on elements other than images and therefore will not be read using screen-readers.	Yes	5	0	100

Code snapshots of successful elements

1
```
<img alt="Algolia" src="https://cpwebassets.codepen.io/assets/settings/algolia-9e1c0c887f4db420704b2a79926864019ef156bcecc9d5774a7e4eaa731fc5b5.svg">
```

2
```
<img alt="Algolia" src="https://cpwebassets.codepen.io/assets/settings/algolia-9e1c0c887f4db420704b2a79926864019ef156bcecc9d5774a7e4eaa731fc5b5.svg">
```

3
```
<img alt="Algolia" src="https://cpwebassets.codepen.io/assets/settings/algolia-9e1c0c887f4db420704b2a79926864019ef156bcecc9d5774a7e4eaa731fc5b5.svg">
```

4
```
<img alt="" src="https://srv.buysellads.com/static/30242/563b33185b6426eabf560dcbc5fb5adc5c8de263" style="background-color: rgb(0, 0, 0);">
```

5
```
<img alt="" class="PenAd-module_pixel-CdlDM" src="https://ad.doubleclick.net/ddm/trackimp/N718679.452584BUYSELLADS.COM/B29332811.421611927;dc_trk_aid=613858961;dc_trk_cid=235700574;ord=[timestamp];dc_lat=;dc_rdid=;tag_for_child_directed_treatment=;tf...
```

#	Element	Relevant	Successes	Failures	Score
2	Breadcrumb navigation regions are essential for user orientation. If not appropriately tagged, screen reader users will not know that such an option exists on the page and will face more difficulties browsing around.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
3	Elements with emphasis importance should have the emphasis role. If not, screen reader users may not understand the emphasis of the text.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
4	An iframe needs a label that describes its purpose to screen reader users.	Yes	Pass	-	100

Code snapshots of successful elements

```
<iframe id="result" name="CodePen" title="CodePen Preview" src="https://codepen.io/leezee/fullpage/eYbXzpJ?anon=true&amp;view=" sandbox="allow-downloads allow-forms allow-modals allow-pointer-lock allow-popups allow-popups-to-escape-sandbox allow-pre...
```

#	Element	Relevant	Successes	Failures	Score
5	Ambiguous links like "Learn More", "Shop Now" and "Start Here" are often used as a call to action. However, screen-reader users, while using link navigation, do not interact with content above or below the link and therefore don't have the same context as to what they will learn more about.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
6	Using role="application" is generally discouraged because it disables standard screen reader modes and forces users into an application mode. This removes familiar navigation shortcuts, such as heading or landmark navigation, and requires them to interact in ways they may not expect.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
7	Discounted prices often appear next to the original and distinguished with visual cues like strikethroughs or color changes. Both prices must also be conveyed by screen readers in a way that enables users to differentiate between the values, ensuring they can understand when a discount is applied.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
8	Elements with strong importance should have the strong role. If not, screen reader users may not understand the importance of the text.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
9	If content remains visible on the screen but assigned aria-hidden="true", it will be excluded from the accessibility tree. As a result, screen reader users will not have access to the same information as sighted users.	Yes	598	67	90

Code snapshots of successful elements

1
```
<header class="main-header" id="main-header"><div class="EditorHeader-module
_root-cpo0V header-wrap HeaderWrap-module_root-PsKVw"><div class="Logo-modul
e_root-ojP5q" data-component="Logo" data-test-id="logo"><a href="/" class="L
ogo-module_small-T4UEU...
```

2
```
<div class="EditorHeader-module_root-cpo0V header-wrap HeaderWrap-module_roo
t-PsKVw"><div class="Logo-module_root-ojP5q" data-component="Logo" data-test
-id="logo"><a href="/" class="Logo-module_small-T4UEU"><svg viewBox="0 0 100
100" xmlns="http://ww...
```

3
```
<div class="Logo-module_root-ojP5q" data-component="Logo" data-test-id="log
o"><a href="/" class="Logo-module_small-T4UEU"><svg viewBox="0 0 100 100" xm
lns="http://www.w3.org/2000/svg" aria-hidden="true"><path d="M100 34.2c-.4-
2.6-3.3-4-5.3-5.3-3.6-2....
```

4
```
<a href="/" class="Logo-module_small-T4UEU"><svg viewBox="0 0 100 100" xmlns
="http://www.w3.org/2000/svg" aria-hidden="true"><path d="M100 34.2c-.4-2.6-
3.3-4-5.3-5.3-3.6-2.4-7.1-4.7-10.7-7.1-8.5-5.7-17.1-11.4-25.6-17.1-2-1.3-4-
2.7-6-4-1.4-1-3.3-1-4.8...
```

5
```
<div class="ItemTitle-module_root-tJA+7" data-test-id="item-title-area"><div
class="ItemTitle-module_text-PYYCs" data-view="pen"><h1 class="ItemTitle-mod
ule_title-6kJVb" id="item-title"><span class="ItemTitle-module_titleLink-1hR
hU" id="editable-titl...
```

6
```
<div class="ItemTitle-module_text-PYYCs" data-view="pen"><h1 class="ItemTitl
e-module_title-6kJVb" id="item-title"><span class="ItemTitle-module_titleLin
k-1hRhU" id="editable-title-span">A11y testing</span></h1><div class="ItemTi
tle-module_by-nYpg9"><...
```

7
```
<h1 class="ItemTitle-module_title-6kJVb" id="item-title"><span class="ItemTi
tle-module_titleLink-1hRhU" id="editable-title-span">A11y testing</span></h1
>
```

```
8 <span class="ItemTitle-module_titleLink-1hRhU" id="editable-title-span">A11y
testing</span>
```

```
9 <div class="ItemTitle-module_by-nYpg9"><a class="ItemTitle-module_ownerLink-
CLyo7" href="/leezee">Elizabeth </a><button data-test="follow-button" data-f
ollowing="false" title="Follow Elizabeth" data-size="mini" data-has-icon="tr
ue" data-color="green"...
```

```
10 <a class="ItemTitle-module_ownerLink-CLyo7" href="/leezee">Elizabeth </a>
```

Code snapshots of failed elements

```
1 <svg viewBox="0 0 100 100" xmlns="http://www.w3.org/2000/svg" aria-hidden="t
rue"><path d="M100 34.2c-.4-2.6-3.3-4-5.3-5.3-5.3-3.6-2.4-7.1-4.7-10.7-7.1-8.5-
5.7-17.1-11.4-25.6-17.1-2-1.3-4-2.7-6-4-1.4-1-3.3-1-4.8 0-5.7 3.8-11.5 7.7-1
7.2 11.5L5.2 29C3 30.4....
```

```
2 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0p
x; width: 26px;">1</div><div class="CodeMirror-gutter-elt" style="left: 34p
x; width: 10px;"><div cl...
```

```
3 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0p
x; width: 26px;">2</div><div class="CodeMirror-gutter-elt" style="left: 34p
x; width: 10px;"><div cl...
```

```
4 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0p
x; width: 26px;">3</div><div class="CodeMirror-gutter-elt" style="left: 34p
x; width: 10px;"><div cl...
```

```
5 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0p
x; width: 26px;">4</div><div class="CodeMirror-gutter-elt" style="left: 34p
x; width: 10px;"><div cl...
```

```
6 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0p
x; width: 26px;">5</div><div class="CodeMirror-gutter-elt" style="left: 34p
x; width: 10px;"><div cl...
```

```
7 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0p
x; width: 26px;">6</div></div>
```

```
8 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
  x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0p
  x; width: 26px;">7</div></div>
```

```
9 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
  x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0p
  x; width: 26px;">8</div><div class="CodeMirror-gutter-elt" style="left: 34p
  x; width: 10px;"><div cl...
```

```
10 <div class="CodeMirror-gutter-wrapper" aria-hidden="true" style="left: -44p
   x;"><div class="CodeMirror-linenumber CodeMirror-gutter-elt" style="left: 0
   px; width: 26px;">9</div></div>
```

#	Element	Relevant	Successes	Failures	Score
10	When elements are visually hidden but still exposed to assistive technology, screen reader users may encounter content that should not be available in the current interface. This can obscure the current state of the page and lead to confusion about what information or controls are available.	Yes	813	16	98

Code snapshots of successful elements

1
```
<a href="/" class="Logo-module_large-J2pKy"><svg fill="none" stroke="#fff" s
troke-linecap="round" stroke-linejoin="round" stroke-width="2.3" viewBox="0
0 138 26" xmlns="http://www.w3.org/2000/svg" aria-hidden="true"><path d="M15
8a7 7 0 1 0 0 10m7-8....
```

2
```
<svg fill="none" stroke="#fff" stroke-linecap="round" stroke-linejoin="roun
d" stroke-width="2.3" viewBox="0 0 138 26" xmlns="http://www.w3.org/2000/sv
g" aria-hidden="true"><path d="M15 8a7 7 0 1 0 0 10m7-8.7L33 2l11 7.3v7.4L33
24l-11-7.3zm0 0 11 7.4 ...
```

3
```
<span class="ScreenReaderText-module_root-jASUi">CodePen Home</span>
```

4
```
<button aria-expanded="false" data-open="false" class="Button-module_root-xw
+9D EditorHeaderPen-module_toggleActionsButton-E+eAn MobileNavButton-module_
root-EApZk"><div class="MobileNavButton-module_icon-uF4CA" aria-hidden="tru
e"><span></span><svg vi...
```

5
```
<div class="MobileNavButton-module_icon-uF4CA" aria-hidden="true"><span></sp
an><svg viewBox="-122.9 121.1 105.9 61.9" xmlns="http://www.w3.org/2000/sv
g"><path d="m-63.2 180.3 43.5-43.5c1.7-1.7 2.7-4 2.7-6.5s-1-4.8-2.7-6.5-4-2.
7-6.5-2.7-4.8 1-6.5 2.7L...
```

6
```
<span></span>
```

7
```
<svg viewBox="-122.9 121.1 105.9 61.9" xmlns="http://www.w3.org/2000/svg"><p
ath d="m-63.2 180.3 43.5-43.5c1.7-1.7 2.7-4 2.7-6.5s-1-4.8-2.7-6.5-4-2.7-6.5
-2.7-4.8 1-6.5 2.7L-69.9 161l-37.2-37.2c-1.7-1.7-4-2.7-6.5-2.7s-4.8 1-6.5 2.
6c-1.9 1.8-2.8 4.2-2.8...
```

```
<span class="ScreenReaderText-module_root-jASUi">Pen Editor Menu</span>
```

```
<div class="DropdownControlled-module_content-mxnG0" id="_r_2_" role="menu"
data-open="false" hidden="" data-direction="bottom left"></div>
```

```
<div class="view-switcher EditorHeaderViewSwitcher_mobile-TM24l"><div class
="EditorHeaderViewSwitcher_switch-thcS-"><nav class="EditorHeaderViewSwitch
erLinks_linkList-b3AAG"><a class="EditorHeaderViewSwitcherLink_link-wYdA5 e
ditor-link pen-link activ...
```

Code snapshots of failed elements

```
<div class="unsaved-editor-message"><b>0</b> unsaved changes <span class="di
smiss"><svg class="icon-x" viewBox="0 0 100 100"><path d="M96.8 83.7L63.1 50
l33.7-33.7c3.6-3.6 3.6-9.4 0-13.1s-9.5-3.6-13.1 0L50 36.9 16.3 3.2C12.7-.4
6.9-.4 3.2 3.2s-3.6 9.5...
```

```
<span role="presentation" style="padding-right: 0.1px;"><span cm-text=""></s
pan></span>
```

```
<span role="presentation" style="padding-right: 0.1px;"><span cm-text=""></s
pan></span>
```

```
<div style="overflow: hidden; position: relative; width: 3px; height: 0px; t
op: 4px; left: 43px;"><textarea autocorrect="off" autocapitalize="off" spell
check="false" aria-label="CSS Code Editor" tabindex="0" style="position: abs
olute; bottom: -1em; p...
```

```
<span role="presentation" style="padding-right: 0.1px;"><span cm-text=""></s
pan></span>
```

```
<span role="presentation" style="padding-right: 0.1px;"><span cm-text=""></s
pan></span>
```

```
<span role="presentation" style="padding-right: 0.1px;"><span cm-text=""></s
pan></span>
```

```
<span role="presentation" style="padding-right: 0.1px;"><span cm-text=""></s
pan></span>
```

```
<span role="presentation" style="padding-right: 0.1px;"><span cm-text=""></s
pan></span>
```

```
<div style="overflow: hidden; position: relative; width: 3px; height: 0px;
top: 4px; left: 43px;"><textarea autocorrect="off" autocapitalize="off" spe
llcheck="false" aria-label="JavaScript Code Editor" tabindex="0" style="pos
ition: absolute; bottom: ...
```

#	Element	Relevant	Successes	Failures	Score
11	Buttons that do not contain visible text should be assigned labels that inform screen reader users of their purpose.	Yes	20	0	100

Code snapshots of successful elements

1
```
<button data-test="follow-button" data-following="false" title="Follow Eliza
beth" data-size="mini" data-has-icon="true" data-color="green" class="Button
-module_root-xw+9D FollowButton-module_root-Q92Q+ ItemTitle-module_followBut
ton-j5eP7 follow-user-...
```

2
```
<button title="Love" data-anon="true" data-view="pen" data-item="Pen" data-h
ashid="eYbXzpJ" class="Button-module_root-xw+9D EditorHeaderPen-module_loveB
utton-7F910 loves heart-button"><svg viewBox="-2 0 105 92" xmlns="http://ww
w.w3.org/2000/svg" clas...
```

3
```
<button id="run" title="Com/Ctrl - Shift - 7 to Run" data-has-icon="true" cl
ass="Button-module_root-xw+9D run"><svg viewBox="0 0 20 20"><path d="M10.66
1.91a.833.833 0 0 1 1.18 0l2.5 2.5a.833.833 0 0 1 0 1.18l-2.5 2.5a.833.833 0
1 1-1.18-1.18l1.078-1...
```

4
```
<button data-test-id="edit-settings" id="edit-settings" title="Pen Settings"
data-has-icon="true" class="Button-module_root-xw+9D"><svg viewBox="0 0 100
100" xmlns="http://www.w3.org/2000/svg"><path d="M87.687 45.077c-.313-2.433
-.816-4.807-1.542-7.07...
```

5
```
<button id="view-switcher-button" data-test-id="view-switcher-button" title
="Change View" aria-haspopup="menu" aria-controls="_r_2_" class="Button-modu
le_root-xw+9D"><svg viewBox="0 0 20 20" xmlns="http://www.w3.org/2000/svg" c
lass="EditorHeaderViewS...
```

6
```
<button id="settings-pane-html" class="button button-medium mini-button sett
ings-nub" data-type="html" title="Open HTML Settings"> <svg viewBox="0 0 100
100" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-
2.433-0.816-4.807-1.54...
```

7
```
<button class="button mini-button button-medium editor-dropdown-button edito
r-dropdown-button-html" data-dropdown="#editor-dropdown-html" aria-haspopup
="true" aria-expanded="false"> <span class="visually-hidden"> HTML Options
</span> <svg viewBox="-1...
```

```
<button id="settings-pane-css" class="button button-medium mini-button settings-nub" data-type="css" title="Open CSS Settings"> <svg viewBox="0 0 100 100" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-2.433-0.816-4.807-1.542-7...
```

```
<button class="button mini-button button-medium editor-dropdown-button editor-dropdown-button-css" data-dropdown="#editor-dropdown-css" aria-haspopup="true" aria-expanded="false"> <span class="visually-hidden"> CSS Options </span> <svg viewBox="-122....
```

```
<button id="settings-pane-js" class="button button-medium mini-button settings-nub" data-type="js" title="Open JS Settings"> <svg viewBox="0 0 100 100" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-2.433-0.816-4.807-1.542-7.07...
```

#	Element	Relevant	Successes	Failures	Score
12	If interactive elements cannot be identified as buttons, screen reader users may not realize the element is actionable, which can stop them from submitting forms, opening dialogs, or performing other intended actions.	Yes	20	0	100

Code snapshots of successful elements

1
```
<button data-test="follow-button" data-following="false" title="Follow Eliza
beth" data-size="mini" data-has-icon="true" data-color="green" class="Button
-module_root-xw+9D FollowButton-module_root-Q92Q+ ItemTitle-module_followBut
ton-j5eP7 follow-user-...
```

2
```
<button title="Love" data-anon="true" data-view="pen" data-item="Pen" data-h
ashid="eYbXzpJ" class="Button-module_root-xw+9D EditorHeaderPen-module_loveB
utton-7F910 loves heart-button"><svg viewBox="-2 0 105 92" xmlns="http://ww
w.w3.org/2000/svg" clas...
```

3
```
<button id="run" title="Com/Ctrl - Shift - 7 to Run" data-has-icon="true" cl
ass="Button-module_root-xw+9D run"><svg viewBox="0 0 20 20"><path d="M10.66
1.91a.833.833 0 0 1 1.18 0l2.5 2.5a.833.833 0 0 1 0 1.18l-2.5 2.5a.833.833 0
1 1-1.18-1.18l1.078-1...
```

4
```
<button data-test-id="edit-settings" id="edit-settings" title="Pen Settings"
data-has-icon="true" class="Button-module_root-xw+9D"><svg viewBox="0 0 100
100" xmlns="http://www.w3.org/2000/svg"><path d="M87.687 45.077c-.313-2.433
-.816-4.807-1.542-7.07...
```

5
```
<button id="view-switcher-button" data-test-id="view-switcher-button" title
="Change View" aria-haspopup="menu" aria-controls="_r_2_" class="Button-modu
le_root-xw+9D"><svg viewBox="0 0 20 20" xmlns="http://www.w3.org/2000/svg" c
lass="EditorHeaderViewS...
```

6
```
<button id="settings-pane-html" class="button button-medium mini-button sett
ings-nub" data-type="html" title="Open HTML Settings"> <svg viewBox="0 0 100
100" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-
2.433-0.816-4.807-1.54...
```

7
```
<button class="button mini-button button-medium editor-dropdown-button edito
r-dropdown-button-html" data-dropdown="#editor-dropdown-html" aria-haspopup
="true" aria-expanded="false"> <span class="visually-hidden"> HTML Options
</span> <svg viewBox="-1...
```

```
8 <button id="settings-pane-css" class="button button-medium mini-button setti
ngs-nub" data-type="css" title="Open CSS Settings"> <svg viewBox="0 0 100 10
0" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-2.4
33-0.816-4.807-1.542-7...
```

```
9 <button class="button mini-button button-medium editor-dropdown-button edito
r-dropdown-button-css" data-dropdown="#editor-dropdown-css" aria-haspopup="t
rue" aria-expanded="false"> <span class="visually-hidden"> CSS Options </spa
n> <svg viewBox="-122....
```

```
10 <button id="settings-pane-js" class="button button-medium mini-button setti
ngs-nub" data-type="js" title="Open JS Settings"> <svg viewBox="0 0 100 10
0" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-2.
433-0.816-4.807-1.542-7.07...
```

#	Element	Relevant	Successes	Failures	Score
13	A sticky footer remains anchored to the bottom of the screen while the rest of the page content can be scrolled. If it is not offset from interactive elements, it can overlap and obscure the item in focus.	Yes	-	Fail	0

Code snapshots of failed elements

```
1 <footer id="react-pen-footer" class="site-footer editor-footer"><div class
="footer-left"><div class="footer-actions-menu"><button id="footer-button" a
ria-expanded="false" class="Button-module_root-xw+9D toggle-footer-menu-butt
on"><svg viewBox="-122.9...
```

#	Element	Relevant	Successes	Failures	Score
14	Activating anchor links enables users to navigate to a different section within the same page by scrolling and moving keyboard focus. Anchor links that do not contain visible text or labeled images should be assigned labels that inform screen reader users of their destination.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
15	Visual cues are often used by sighted users to indicate which link represents the current page within a set of links. This information should be made available to screen reader users by assigning aria-current='page' to the link.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
16	Screen reader users may find it difficult to distinguish between links when the purpose of each link cannot be determined from its text alone or together with its immediate context.	Yes	5	0	100

Code snapshots of successful elements

1
```
<a href="/" class="Logo-module_small-T4UEU"><svg viewBox="0 0 100 100" xmlns
="http://www.w3.org/2000/svg" aria-hidden="true"><path d="M100 34.2c-.4-2.6-
3.3-4-5.3-5.3-3.6-2.4-7.1-4.7-10.7-7.1-8.5-5.7-17.1-11.4-25.6-17.1-2-1.3-4-
2.7-6-4-1.4-1-3.3-1-4.8...
```

2
```
<a class="ItemTitle-module_ownerLink-CLyo7" href="/leezee">Elizabeth </a>
```

3
```
<a data-test-id="signup-button" href="/accounts/signup/user/free" data-color
="green" class="Button-module_root-xw+9D LogInAndSignUpButtons-module_signup
Button-hxnR0">Sign Up</a>
```

4
```
<a data-test-id="login-button" href="/login" class="Button-module_root-xw+9D
LogInAndSignUpButtons-module_loginButton-XjHhF">Log In</a>
```

5
```
<a href="https://srv.buysellads.com/ads/click/x/GTND427UCVADK53WCKA4YKQUCA7D
62QECTYDCZ3JCASI6KQJF6BDL53KC6SITK3NCWBIPK7YFTYDE2QJCA7IK27JHEYI527LFT7DTK3E
CTNCYBZ52K" class="PenAd-module_searchAd-zsiuz" title="Squarespace: Grow you
r business with Square...
```

#	Element	Relevant	Successes	Failures	Score
17	Activating navigation links enables users to navigate to a different page within the site. Links that do not contain visible text or labeled images should be assigned labels that inform screen reader users of their destination.	Yes	5	0	100

Code snapshots of successful elements

1
```
<a href="/" class="Logo-module_small-T4UEU"><svg viewBox="0 0 100 100" xmlns
="http://www.w3.org/2000/svg" aria-hidden="true"><path d="M100 34.2c-.4-2.6-
3.3-4-5.3-5.3-3.6-2.4-7.1-4.7-10.7-7.1-8.5-5.7-17.1-11.4-25.6-17.1-2-1.3-4-
2.7-6-4-1.4-1-3.3-1-4.8...
```

2
```
<a class="ItemTitle-module_ownerLink-CLyo7" href="/leezee">Elizabeth </a>
```

3
```
<a data-test-id="signup-button" href="/accounts/signup/user/free" data-color
="green" class="Button-module_root-xw+9D LogInAndSignUpButtons-module_signup
Button-hxnR0">Sign Up</a>
```

4
```
<a data-test-id="login-button" href="/login" class="Button-module_root-xw+9D
LogInAndSignUpButtons-module_loginButton-XjHhF">Log In</a>
```

5
```
<a href="https://srv.buysellads.com/ads/click/x/GTND427UCVADK53WCKA4YKQUCA7D
62QECTYDCZ3JCASI6KQJF6BDL53KC6SITK3NCWBIPK7YFTYDE2QJCA7IK27JHEYI527LFT7DTK3E
CTNCYBZ52K" class="PenAd-module_searchAd-zsiuz" title="Squarespace: Grow you
r business with Square...
```

#	Element	Relevant	Successes	Failures	Score
18	In most cases, using role=menu on navigation elements within a web page can negatively impact screen reader users, especially those using JAWS. The attribute should be used for menu types that function like those found in desktop applications.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
19	In most cases, using role=menubar on navigation elements within a web page can negatively impact screen reader users, especially those using JAWS. The attribute should be used for menu types that function like those found in desktop applications.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
20	In most cases, using ARIA menu roles within a web page can negatively impact screen reader users, especially those using JAWS. role="menuitem" should be used for menu items in menu types that function like those found in desktop applications.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
21	Interactive elements that trigger additional content should only have relationship and state ARIA attributes, such as aria-expanded and aria-controls, if they have interactive roles, such as button, tab, combobox and in rarer cases, link.	Yes	3	0	100

Code snapshots of successful elements

1
```
<button class="button mini-button button-medium editor-dropdown-button edito
r-dropdown-button-html" data-dropdown="#editor-dropdown-html" aria-haspopup
="true" aria-expanded="false"> <span class="visually-hidden"> HTML Options
</span> <svg viewBox="-1...
```

2
```
<button class="button mini-button button-medium editor-dropdown-button edito
r-dropdown-button-css" data-dropdown="#editor-dropdown-css" aria-haspopup="t
rue" aria-expanded="false"> <span class="visually-hidden"> CSS Options </spa
n> <svg viewBox="-122....
```

3
```
<button class="button mini-button button-medium editor-dropdown-button edito
r-dropdown-button-js" data-dropdown="#editor-dropdown-js" aria-haspopup="tru
e" aria-expanded="false"> <span class="visually-hidden"> JS Options </span>
<svg viewBox="-122.9 1...
```

#	Element	Relevant	Successes	Failures	Score
22	Make sure that no element has an autofocus attribute.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
23	Screen readers rely on properly coded and associated labels to announce the purpose of a form field. A checkbox control without an identifiable label may prevent screen reader users from completing the form.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
24	Interacting with form controls shouldn't automatically submit a form or cause any other change in context without notifying the user in advance. Form controls that cause a context change on input can disorient a user, since the behavior is not expected.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
25	Adding type="submit" to a control that submits a form ensures that screen readers users expect a change of context when they activate the control.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
26	Main navigation elements should have role navigation to ensure that screen readers can identify them as navigation regions.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
27	Screen readers rely on properly coded and associated labels to announce the purpose of a form field. A radio control without an identifiable label may prevent screen reader users from completing the form.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
28	If a field is marked as required only through visual cues, but lacks the required attribute or aria-required="true", screen readers will not announce it as mandatory. As a result, users may experience unnecessary delays or confusion when trying to submit the form.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
29	Using an <article> tag on content that is not self-contained and that cannot stand on its own outside the context of the page, such as a blog post, news story, or forum entry, causes screen readers to announce misleading information about the purpose the content in relation to the main subject of the page.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
30	A breadcrumb region presents a trail of links showing the user’s current page in relation to higher-level pages on a site. Without a label, it may be announced by screen reades simply as "navigation", making it hard to distinguish from other navigation regions on the page.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
31	Screen readers rely on accurate tagging and labeling to provide necessary context. If an element that does not contain navigation links is tagged as a navigation landmark, screen reader users may lose orientation and find the page's structure difficult to understand.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
32	The main landmark represents the primary content of a page. It should include only content unique to that page and must remain separate from repeated elements, such as navigation, header, or footer.	Yes	-	Fail	0

Code snapshots of failed elements

```
<div class="page-wrap"> <div class="boxes"> <div class="mobile-editor-nav">
<button id="html-toggle" class="selected"><span>HTML</span></button> <button
id="css-toggle"><span>CSS</span></button> <button id="js-toggle"><span>JS</s
pan></button> <button...
```

#	Element	Relevant	Successes	Failures	Score
33	Incorrectly tagging the main landmark may cause screen reader users to misunderstand where the primary content begins or ends, leading to confusion and inefficient navigation.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
34	A page typically presents one central subject, so a single main landmark establishes the boundaries of the primary content for screen reader users. Multiple main landmarks create uncertainty about the scope, leading to confusion and difficulty navigating the page.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
35	Screen reader users rely on landmarks to quickly access important regions of a page. Defining a form as a search landmark ensures that users can quickly recognize and navigate to the search form.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
36	Functional images presented using CSS background or background-image properties should be marked up using role="img" so that they can be identified as images by screen reader users.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
37	Smaller graphics used as decorative or complementary elements, such as icons, and that do not provide additional information will often add unnecessary clutter to a screen reader user's browsing experience.	Yes	68	16	81

Code snapshots of successful elements

```
<span class="cm-attribute">id</span>
```

```
<span class="cm-tag">ul</span>
```

```
<span class="cm-tag">li</span>
```

```
<span class="cm-tag cm-bracket">&gt;&lt;</span>
```

```
<span class="cm-tag cm-bracket">&lt;/</span>
```

```
<span class="cm-tag">li</span>
```

```
<span class="cm-tag">li</span>
```

```
<span class="cm-tag cm-bracket">&gt;&lt;</span>
```

```
<span class="cm-tag cm-bracket">&lt;/</span>
```

```
<span class="cm-tag">li</span>
```

Code snapshots of failed elements

```
<svg viewBox="0 0 132.4 132.4" xmlns="http://www.w3.org/2000/svg" class="FollowButton-module_statusIcon-U62Ef"><path d="M75.4 123.1V75.4h47.7c5.1 0 9.2-4.1 9.3-9.3s-4.2-9.3-9.3-9.3H75.4V9.3c0-5.1-4.1-9.2-9.3-9.3-5.2-.1-9.3 4.2-9.3 9.3V57H9.1C4 57-.1 ...
```

```
<svg viewBox="-2 0 105 92" xmlns="http://www.w3.org/2000/svg" class="LoveButtonIcon-module_root-3tVfn"><path d="M85.24 2.67C72.29-3.08 55.75 2.67 50 14.9 44.25 2 27-3.8 14.76 2.67 1.1 9.14-5.37 25 5.42 44.38 13.33 58 27 68.11 50 86.81 73.73 68.11 87....
```

```
<svg viewBox="0 0 20 20"><path d="M10.66 1.91a.833.833 0 0 1 1.18 0l2.5 2.5a.833.833 0 0 1 0 1.18l-2.5 2.5a.833.833 0 1 1-1.18-1.18l1.078-1.077h-1.321C7.46 5.833 5 8.293 5 11.25c0 2.956 2.46 5.417 5.417 5.417 2.956 0 5.416-2.46 5.416-5.417a.833.833 0...
```

```
<svg viewBox="0 0 100 100" xmlns="http://www.w3.org/2000/svg"><path d="M87.687 45.077c-.313-2.433-.816-4.807-1.542-7.079l8.145-11.73-5.827-7.515-.094-.123-5.824-7.514-12.955 5.577c-2.041-1.265-4.192-2.362-6.459-3.219L59.42 0H40.586l-3.709 13.474c-2.2...
```

```
<svg viewBox="0 0 20 20" xmlns="http://www.w3.org/2000/svg" class="EditorHeaderViewSwitcher_iconPen-jP26l"><path d="M0 9.002C0 8.45.455 8 .992 8h18.016c.548 0 .992.456.992 1.002v9.996c0 .553-.455 1.002-.992 1.002H.992C.444 20 0 19.544 0 18.998zm0-8C0...
```

```
<svg viewBox="0 0 15 15" class="file-type-icon" id="icon-file-html"> <rect fill="#FF3C41" width="15" height="15" rx="4"></rect> <path d="M10.97 2.29a.563.563 0 0 0-.495-.29.572.572 0 0 0-.488.277l-5.905 9.86a.565.565 0 0 0-.007.574c.102.18.287.289.49...
```

```
<svg viewBox="0 0 100 100" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-2.433-0.816-4.807-1.542-7.079l8.145-11.73l-5.827-7.515l-0.094-0.123l-5.824-7.514 l-12.955,5.577c-2.041-1.265-4.192-2.362-6.459-3.219L59.42,0h-9.34h-0.153...
```

```
<svg viewBox="-122.9 121.1 105.9 61.9" class="icon-arrow-down-mini" width="10" height="10"> <path d="M-63.2,180.3l43.5-43.5c1.7-1.7,2.7-4,2.7-6.5s-1-4.8-2.7-6.5c-1.7-1.7-4-2.7-6.5-2.7s-4.8,1-6.5,2.7l-37.2,37.2l-37.2-37.2 c-1.7-1.7-4-2.7-6.5-2.7s-4.8,...
```

```
<svg viewBox="0 0 15 15" class="file-type-icon" id="icon-file-css"> <rect fill="#0EBEFF" width="15" height="15" rx="4"></rect><path d="M8 8.366l1.845 1.065a.507.507 0 0 0 .686-.181.507.507 0 0 0-.186-.685L8.5 7.5l1.845-1.065a.507.507 0 0 0 .186-.685....
```

```
<svg viewBox="0 0 100 100" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-2.433-0.816-4.807-1.542-7.079l8.145-11.73l-5.827-7.515l-0.094-0.123l-5.824-7.514 l-12.955,5.577c-2.041-1.265-4.192-2.362-6.459-3.219L59.42,0h-9.34h-0.153...
```

#	Element	Relevant	Successes	Failures	Score
38	Images require a text alternative when the image conveys meaningful content or serves a functional purpose. If the image is decorative, it must be hidden from assistive technology.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
39	Text alternatives must provide accurate descriptions of the image. Incorrect text alternatives, such as filenames or other placeholder values, may cause screen reader users to either miss essential information or hear unnecessary content that disrupts navigation.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
40	When non-graphical elements are marked up as images, screen reader users may misunderstand the intended purpose of the content.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
41	A slider should be operable with a single pointer	No	0	0	

#	Element	Relevant	Successes	Failures	Score
42	Aria labels should describe elements that don't have proper text, like icons and field labels. It should not be used to override element texts. Screen reader users need to receive the exact text as visually on the screen, with more context if it is ambiguous. An exception applies to landmarks such as nav or other landmarks: here, ARIA labels can provide additional context or clarification.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
43	A sticky header remains anchored to the top of the screen while the rest of the page content can be scrolled. If it is not offset from interactive elements, it can overlap and obscure the item in focus.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
44	An empty list will still be announced by screen readers, which may confuse users, leaving them unsure if the list is empty or an issue prevents the screen reader from announcing the list items.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
45	Specifying a default page language ensures screen readers apply the correct pronunciation rules, voices, and braille output. Without it, screen readers may guess the language incorrectly, causing mispronunciations, confusion, and reduced comprehension for users.	Yes	Pass	-	100

Code snapshots of successful elements

```
<html lang="en" data-theme="dark" class="mac chrome134 js"><head> <meta char
set="UTF-8"> <title>A11y testing</title> <style type="text/css">@font-face
{font-family:Lato;font-style:normal;font-weight:400;src:url(/cf-fonts/s/lat
o/5.0.18/latin/400/norma...
```

#	Element	Relevant	Successes	Failures	Score
46	The meta viewport should allow scalability, typically with width=device-width, initial-scale=1, so text can be resized up to 200% without loss of functionality. Using user-scalable=no or maximum-scale=1 prevents users from enlarging content, making it difficult for people with low vision to read or interact.	Yes	Pass	-	100

Code snapshots of successful elements

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

#	Element	Relevant	Successes	Failures	Score
47	A <meta> element with http-equiv="refresh" is sometimes used to automatically redirect users after a time delay. These timed changes can interrupt and disorient users who rely on assistive technology	No	0	0	

#	Element	Relevant	Successes	Failures	Score
48	A missing page title makes it difficult for screen reader users and sighted users with multiple tabs open to identify the page, reducing orientation and usability.	Yes	Pass	-	100

Code snapshots of successful elements

```
<title>A11y testing</title>
```

#	Element	Relevant	Successes	Failures	Score
49	Screen readers rely heavily on page titles to announce the purpose of a page. If titles aren't descriptive, users with low or no vision may not understand the context until they start navigating the page.	Yes	Pass	-	100

Code snapshots of successful elements

```
<title>A11y testing</title>
```

#	Element	Relevant	Successes	Failures	Score
50	A tablist without role="tablist" is not announced as a group of related tabs, which prevents screen reader users from recognizing the structure and purpose of the component. This makes it harder to navigate between tabs and understand that the controls belong to a single set.	Yes	-	Fail	0

Code snapshots of failed elements

```
<div class="footer-actions" data-expanded="false"><button data-size="mini" c
lass="Button-module_root-xw+9D console-toggle-button">Console</button><butto
n data-size="mini" class="Button-module_root-xw+9D">Assets</button><button d
ata-id="editor-comment...
```

#	Element	Relevant	Successes	Failures	Score
51	Applying role="tablist" to an element without tabs misleads screen reader users by suggesting a group of tabs that does not exist.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
52	Custom tabs must be explicitly defined for screen readers since there are no native HTML tab elements. Without assigning role="tab" to the interactive elements, assistive technology will not identify them as tabs, preventing users from understanding their function or navigating them as part of a tab interface.	Yes	0	4	0

Code snapshots of failed elements

```
<button data-size="mini" class="Button-module_root-xw+9D console-toggle-butt
on">Console</button>
```

```
<button data-size="mini" class="Button-module_root-xw+9D">Assets</button>
```

```
<button data-id="editor-comments-button" data-size="mini" class="Button-modu
le_root-xw+9D">Comments</button>
```

```
<button title="Keyboard Shortcuts" data-size="mini" class="Button-module_roo
t-xw+9D keyboard-commands-button"><span> </span></button>
```

#	Element	Relevant	Successes	Failures	Score
53	Applying role="tab" to an element that is not part of a functioning tab interface misleads screen reader users by presenting it as a tab without a corresponding panel.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
54	The role="tabpanel" identifies an element as the content region of a tab interface. Without this role, panels are exposed only by their native role (such as a generic div or a named section) and screen reader users may not perceive them as part of the tab structure.	Yes	-	Fail	0

Code snapshots of failed elements

```
<div class="footer-left"><div class="footer-actions-menu"><button id="footer-button" aria-expanded="false" class="Button-module_root-xw+9D toggle-footer-menu-button"><svg viewBox="-122.9 121.1 105.9 61.9" xmlns="http://www.w3.org/2000/svg"><path d="m...
```

#	Element	Relevant	Successes	Failures	Score
55	Applying role="tabpanel" to an element without a corresponding tab misleads screen reader users by announcing it as tab content, even though no controlling tab exists.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
56	If a column header is not marked up with the correct role or scope, screen reader users cannot determine which header applies to each cell.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
57	If a table header cell is empty, screen reader users may only hear a generic label such as “column 3” or nothing at all. This makes it harder to understand what each column or row represents.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
58	When a layout table is marked up with HTML elements like <table> or <tr>, or assigned table ARIA roles, screen readers announce a data table structure with rows, columns, and headers, even though the table is only used for page layout.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
59	Nested tables are often misinterpreted by screen readers, making it hard for users to follow the intended structure and meaning of the data.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
60	If a table row header is not marked up with the correct role or scope, screen reader users cannot determine which header applies to each cell.	No	0	0	

WCAG Best Practices (Not included in score)

#	Element	Relevant	Successes	Failures	Score
1	If an element’s aria-describedby attribute points to an id that does not exist or is not valid, assistive technologies will not convey the intended description, causing users to miss important context.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
2	Since aria-labelledby relies on valid id references, screen readers can only announce the label if the target exists. If the id is missing or invalid, the label will not be conveyed, causing users to miss important context.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
3	Figure elements are often incorrectly used to display images on the screen. Incorrectly using the figure tag, without providing a proper figcaption, adds unnecessary clutter to the screen reader user's experience.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
4	The title attribute is announced inconsistently across screen readers and browsers, making it unreliable for labeling interactive controls. Because many users may never hear the content, reliance on the attribute risks loss of information. Instead, it should be used to provide extra help text in addition to a valid label.	Yes	15	0	100

Code snapshots of successful elements

1
```
<button data-test="follow-button" data-following="false" title="Follow Eliza
beth" data-size="mini" data-has-icon="true" data-color="green" class="Button
-module_root-xw+9D FollowButton-module_root-Q92Q+ ItemTitle-module_followBut
ton-j5eP7 follow-user-...
```

2
```
<button title="Love" data-anon="true" data-view="pen" data-item="Pen" data-h
ashid="eYbXzpJ" class="Button-module_root-xw+9D EditorHeaderPen-module_loveB
utton-7F910 loves heart-button"><svg viewBox="-2 0 105 92" xmlns="http://ww
w.w3.org/2000/svg" clas...
```

3
```
<button id="run" title="Com/Ctrl - Shift - 7 to Run" data-has-icon="true" cl
ass="Button-module_root-xw+9D run"><svg viewBox="0 0 20 20"><path d="M10.66
1.91a.833.833 0 0 1 1.18 0l2.5 2.5a.833.833 0 0 1 0 1.18l-2.5 2.5a.833.833 0
1 1-1.18-1.18l1.078-1...
```

4
```
<button data-test-id="edit-settings" id="edit-settings" title="Pen Settings"
data-has-icon="true" class="Button-module_root-xw+9D"><svg viewBox="0 0 100
100" xmlns="http://www.w3.org/2000/svg"><path d="M87.687 45.077c-.313-2.433
-.816-4.807-1.542-7.07...
```

5
```
<button id="view-switcher-button" data-test-id="view-switcher-button" title
="Change View" aria-haspopup="menu" aria-controls="_r_2_" class="Button-modu
le_root-xw+9D"><svg viewBox="0 0 20 20" xmlns="http://www.w3.org/2000/svg" c
lass="EditorHeaderViewS...
```

6
```
<div class="editor-resizer html-editor-resizer" title="Double-click to expan
d."><h2 class="box-title html-editor-title box-title--resizer" id="html-edit
or-title"> <svg viewBox="0 0 15 15" class="file-type-icon" id="icon-file-htm
l"> <rect fill="#FF3C4...
```

```
7 <button id="settings-pane-html" class="button button-medium mini-button sett
ings-nub" data-type="html" title="Open HTML Settings"> <svg viewBox="0 0 100
100" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-
2.433-0.816-4.807-1.54...
```

```
8 <div class="editor-resizer css-editor-resizer" title="Double-click to expan
d."><h2 class="box-title css-editor-title box-title--resizer" id="css-editor
-title"> <svg viewBox="0 0 15 15" class="file-type-icon" id="icon-file-css">
<rect fill="#0EBEFF" w...
```

```
9 <button id="settings-pane-css" class="button button-medium mini-button setti
ngs-nub" data-type="css" title="Open CSS Settings"> <svg viewBox="0 0 100 10
0" id="icon-gear" width="10" height="10"> <path d="M87.687,45.077c-0.313-2.4
33-0.816-4.807-1.542-7...
```

```
10 <div class="editor-resizer js-editor-resizer" title="Double-click to expan
d."><h2 class="box-title js-editor-title box-title--resizer" id="js-editor-
title"> <svg viewBox="0 0 15 15" class="file-type-icon" id="icon-file-js">
<rect fill="#FCD000" width...
```

#	Element	Relevant	Successes	Failures	Score
5	The element's aria-controls points to an id that does not exist, or is not valid, breaking the link between the controlling element and the content it manages.	Yes	3	0	100

Code snapshots of successful elements

```
1 <button id="view-switcher-button" data-test-id="view-switcher-button" title
="Change View" aria-haspopup="menu" aria-controls="_r_2_" class="Button-modu
le_root-xw+9D"><svg viewBox="0 0 20 20" xmlns="http://www.w3.org/2000/svg" c
lass="EditorHeaderViewS...
```

```
2 <button aria-haspopup="menu" aria-controls="_r_0_" data-size="mini" class="B
utton-module_root-xw+9D">Export</button>
```

```
3 <button aria-haspopup="menu" aria-controls="_r_1_" data-size="mini" class="B
utton-module_root-xw+9D">Share</button>
```

#	Element	Relevant	Successes	Failures	Score
6	It's good practice to warn users about the expected behavior when activating a link triggers an image to appear.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
7	It's good practice to warn users about the expected behavior when activating a link triggers a mail application.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
8	It's good practice to warn users about the expected behavior when activating a link triggers a PDF reader.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
9	The contentinfo region, typically represented by the <footer> element, is found at the end of each page and provides screen reader users with information about the website, such as copyright, contact details, legal information, and navigation links.	Yes	Pass	-	100

Code snapshots of successful elements

```
<footer id="react-pen-footer" class="site-footer editor-footer"><div class
="footer-left"><div class="footer-actions-menu"><button id="footer-button" a
ria-expanded="false" class="Button-module_root-xw+9D toggle-footer-menu-butt
on"><svg viewBox="-122.9...
```

#	Element	Relevant	Successes	Failures	Score
10	When a region without global site information is tagged as a contentinfo landmark, screen reader users may be misled about its purpose and expect website-level details, such as copyright or contact information.	Yes	Pass	-	100

Code snapshots of successful elements

```
<footer id="react-pen-footer" class="site-footer editor-footer"><div class
="footer-left"><div class="footer-actions-menu"><button id="footer-button" a
ria-expanded="false" class="Button-module_root-xw+9D toggle-footer-menu-butt
on"><svg viewBox="-122.9...
```

#	Element	Relevant	Successes	Failures	Score
11	Each page should normally include only one contentinfo landmark (usually the site footer) to keep landmark navigation simple and predictable. Additional contentinfo landmarks are permitted when clearly justified, but they must each have a unique accessible label.	No	0	0	

#	Element	Relevant	Successes	Failures	Score
12	Assigning a valid ISO language value to the <html> lang attribute ensures that screen readers use the correct pronunciation rules, browsers apply proper spell-checking and translation, and search engines index the content in the appropriate language.	Yes	Pass	-	100

Code snapshots of successful elements

```
<html lang="en" data-theme="dark" class="mac chrome134 js"><head> <meta char
set="UTF-8"> <title>A11y testing</title> <style type="text/css">@font-face
{font-family:Lato;font-style:normal;font-weight:400;src:url(/cf-fonts/s/lat
o/5.0.18/latin/400/norma...
```

#	Element	Relevant	Successes	Failures	Score
13	Providing a meta viewport to control layout and scaling on mobile devices	Yes	Pass	-	100

Code snapshots of successful elements

```
<meta name="viewport" content="width=device-width, initial-scale=1">
```

This audit is subject to the **Terms of Service**