

Tasks To Be Performed:

1. Create a script which can add text "This text has been added by custom script" to /tmp.1.txt
2. Run this script using Ansible on all the hosts

-
1. Create a script which can add text "This text has been added by custom script" to /tmp.1.txt

```
GNU nano 7.2
echo "This text has been added by custom script" > /tmp/1.txt
```

```
ubuntu@ip-172-31-11-69:/etc/ansible$ sudo nano script1.sh
ubuntu@ip-172-31-11-69:/etc/ansible$ sudo nano script1.sh
ubuntu@ip-172-31-11-69:/etc/ansible$
```

2. Run this script using Ansible on all the hosts

```
GNU nano 7.2
---
name: Execute script on slaves
hosts: slave-1, slave-2
become: true
tasks:
  - name: Running custom script
    script: script1.sh
```

```
ubuntu@ip-172-31-11-69:/etc/ansible$ ansible-playbook play2.yaml
[WARNING]: Invalid characters were found in group names but not replaced, use -vvvv to see details

PLAY [Execute script on slaves] *****

TASK [Gathering Facts] *****
[WARNING]: Host '172.31.3.174' is using the discovered Python interpreter at '/usr/bin/python3.12', but future installati
different interpreter to be discovered. See https://docs.ansible.com/ansible-core/2.19/reference_appendices/interpreter_d
ok: [172.31.3.174]
[WARNING]: Host '172.31.12.184' is using the discovered Python interpreter at '/usr/bin/python3.12', but future installat
different interpreter to be discovered. See https://docs.ansible.com/ansible-core/2.19/reference_appendices/interpreter_
ok: [172.31.12.184]

TASK [Running custom script] *****
changed: [172.31.12.184]
changed: [172.31.3.174]

PLAY RECAP *****
172.31.12.184      : ok=2    changed=1    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0
172.31.3.174      : ok=2    changed=1    unreachable=0    failed=0    skipped=0    rescued=0    ignored=0

ubuntu@ip-172-31-11-69:/etc/ansible$
```

```
ubuntu@ip-172-31-3-174:~$ cd /tmp
ubuntu@ip-172-31-3-174:/tmp$ ls
1.txt
hsperfdata_root
hsperfdata_ubuntu
snap-private-tmp
systemd-private-dd9962fe69d849b1b56cb117e13
ubuntu@ip-172-31-3-174:/tmp$
```

i-086755b1a9aed4c53 (ansible-slave1)

```
ubuntu@ip-172-31-3-174:~$ cd /tmp
ubuntu@ip-172-31-3-174:/tmp$ ls
1.txt
hsperfdata_root
hsperfdata_ubuntu
snap-private-tmp
systemd-private-dd9962fe69d849b1b56cb117e13
ubuntu@ip-172-31-3-174:/tmp$
```

i-086755b1a9aed4c53 (ansible-slave1)