
DEVOPS INTERVIEW MASTERY

BOOK 1

CLOUD PLATFORMS

FREE SAMPLE

8 of the 50 senior-level interview questions, one from every chapter



AWS · Azure · GCP

2026 EDITION

When would you recommend a hybrid or multi-cloud strategy, and when is it a mistake?

What the interviewer is really testing: whether your architecture decisions start from business drivers like residency, negotiating position, or best-of-breed services, and whether you have the judgment to recommend a single cloud when no driver exists.

30-SECOND ANSWER


Hybrid means pairing on-prem infrastructure with public cloud; multi-cloud means running more than one public provider. I'd only recommend either with a concrete driver: a regulator demanding data residency, a workload pinned to legacy hardware, or one provider's clearly better service: BigQuery for analytics is the classic case. The default for most companies is one primary cloud, because every extra platform multiplies IAM models, networking, and on-call skills. And cross-cloud traffic rides internet egress at roughly $0.09/GB on AWS, so I'd colocate compute with data from day one.

DEEP DIVE

The core problem: a single provider concentrates risk: pricing power at renewal, outages with nothing to fail over to, and regulators who insist certain data never leaves the country or the building. The mirror-image failure gets less airtime but is more common: teams adopt a second cloud with no driver at all, because an acquisition brought one in or the architecture deck looked better with three logos. Hybrid and multi-cloud are answers to specific constraints, not aspirations.

The design: pick one primary cloud and earn every exception. Core workloads live on the primary, where committed-use discounts and a single operating model compound. A second provider enters only where its service clearly wins: BigQuery for analytics and Vertex AI for ML are the textbook cases. Snap's 2017 IPO filing shows the shape: $2 billion committed to Google Cloud, its primary infrastructure partner, and $1 billion to AWS over five years for redundancy. For the on-prem half, hybrid bridges have matured: AWS Outposts, Azure Local (formerly Azure Stack HCI), and Google Distributed Cloud run cloud services on-site, mostly managed from the cloud over Direct Connect or ExpressRoute. Unify the seams deliberately: one identity provider, Terraform for both estates, Open Policy Agent for policy-as-code, one observability stack.

The trade-offs to volunteer: every additional platform multiplies IAM models, network constructs, and the skills your on-call rotation must hold, so I'd budget a real platform-team premium before claiming savings. Egress economics bite daily: cross-cloud traffic is internet egress, about $0.09/GB from AWS, and the 2024 fee waivers cover only full exits (AWS counts a single service); outside the EU and UK, where Data Act rules now cut in-parallel transfer fees, multi-cloud traffic pays full rate. Finally, portability has a ceiling. Abstract everything to lowest-common-denominator primitives and you forfeit the managed services that justified cloud in the first place.



One primary cloud, deliberate exceptions: on-prem stays for residency and legacy, the second cloud earns its place per service, and the seams are unified once.

DECISION FRAMEWORK: CHOOSING A CLOUD POSTURE

Option	Use when	Cost shape	Watch out for
Single cloud + exit plan	No regulatory or capability driver; most startups and mid-size	Lowest: one ops model, full committed-use discounts	Concentration risk; revisit the exit plan yearly
Hybrid (on-prem + cloud)	Legacy systems, data residency, factory/edge latency	Azure Local: your hardware + per-core fee; Outposts: 3-year term	Two operating models; capacity planning returns
Multi-cloud, best-of-breed	One provider's service clearly wins (BigQuery, Vertex AI, Entra ID)	Per-service spend plus ~$0.09/GB cross-cloud egress	Split expertise; keep the inter-cloud link thin and async
Multi-cloud, active DR	Regulator mandates provider diversification (some financial services)	Near-duplicate stack: idle standby, doubled tooling	Failover that is never tested; data-layer lag
Portable-everything	Contractual exit guarantees; almost never otherwise	Highest: ~2× platform team, generic services only	Forfeits managed services; portability rarely exercised

PITFALLS & SENIOR SIGNALS

✕ What sinks candidates

- **Multi-cloud by default:** adding a second provider with no driver roughly doubles platform work for zero benefit. Default to one cloud and demand a named regulatory, capability, or risk driver first.
- **Ignoring egress gravity:** a chatty service split across clouds pays ~$0.09/GB on every call, compounding daily. Colocate compute with its data; keep cross-cloud links async and batched.
- **Lowest-common-denominator design:** wrapping everything in portable abstractions forfeits DynamoDB, BigQuery, and the managed services you came for. Keep the stateless tier portable; let data tiers go native.

✓ What signals senior

- Asking "what's the business driver?" before drawing any boxes shows you've watched multi-cloud get adopted for resume reasons and paid the bill.
- Treating lock-in as a negotiation problem first is the cheap move: a credible, costed exit plan buys most of the pricing leverage with none of the run cost.
- Separating hybrid (on-prem plus cloud, usually a residency or legacy story) from multi-cloud (two publics, usually a capability story) without being prompted signals you've operated both.

LIKELY FOLLOW-UPS

Q: How would you actually run Kubernetes across AWS and GCP with failover?

Separate EKS and GKE clusters built from shared Terraform modules, stateless services deployed to both through GitOps (Argo CD), and a provider-neutral global load balancer with health checks steering traffic. The hard part is state: active-passive Postgres with cross-cloud replication, or CockroachDB if both sides must write. I'd test failover on a schedule, not after the outage.

Q: Doesn't Kubernetes make the clouds interchangeable?

For stateless compute, mostly. The container and manifest move; everything they touch does not: load balancer annotations, storage classes, and IAM bindings (IRSA versus Workload Identity) are all provider-specific. Data is the real anchor: a multi-terabyte warehouse doesn't relocate over a weekend. I treat Kubernetes as reducing switching cost, not eliminating it.

Q: How do you keep multi-cloud spend visible and under control?

Colocate compute with data so cross-cloud chatter stays thin, then unify reporting: all three major providers now publish billing data in the FOCUS open format, so one FinOps pipeline can compare them. I'd alert on egress line items specifically; they grow silently, and committed-use discounts don't cover them.

Recall hook: "Multi-cloud is a driver, not a default." — go hybrid for residency and legacy, add a second cloud only for a service that clearly wins, and stay on one cloud when neither applies.

SENIOR AWS · INCIDENT RESPONSE Q2 / AWS Services & Architecture

Your error rate just spiked across every service you run in us-east-1. Walk me through your first 30 minutes.

What the interviewer is really testing: whether you can make a partly irreversible call on incomplete information, and whether you know AWS well enough to predict which of your recovery tools will be broken at the exact moment you need them.

30-SECOND ANSWER


I'd trust my own telemetry before the AWS Health Dashboard; in December 2021, AWS's status page couldn't update because its own tooling was caught in the outage. First I rule out a bad deploy by checking whether errors correlate with a change or span unrelated services and AZs. Then I start a pre-agreed decision clock: if the region isn't visibly recovering within 15 minutes, we fail over. Execution touches only data planes, meaning Amazon Application Recovery Controller (ARC) routing controls and capacity already in the standby region. No control-plane calls to the failing region.

DEEP DIVE

The core problem: regional events are gray, not binary. A few services degrade, some AZs limp along, and AWS's public signal trails reality: during the December 2021 us-east-1 event the Service Health Dashboard could not update because the tooling behind it was impaired, and in October 2025 a DynamoDB DNS failure cascaded through dependent services for roughly 15 hours. You are deciding whether to execute an expensive, partly irreversible failover with incomplete information. Waiting for official confirmation is the most common way teams burn their entire recovery time objective (RTO).

The design: pre-commit the decision so 2 a.m. judgment isn't required. Detection comes from external synthetics and error-budget burn alarms. Triage rules out your own deploy by checking whether failures track a recent change or span unrelated dependencies. Then a clock starts: if impact is multi-service and not trending down within 15 minutes, the incident commander flips a Route 53 ARC routing control. ARC runs on a five-Region data-plane cluster built to keep working while a region is down, and Region switch plan evaluation (readiness checks closed to new customers in April 2026) audits the standby continuously, so drift surfaces before the night it matters.

The trade-offs to volunteer: every recovery action divides into control plane and data plane, and only data-plane actions are dependable mid-incident. Creating DNS records, launching instances, and changing IAM are all control-plane operations; Route 53's control plane lives solely in us-east-1, while its data plane carries a 100% availability SLA. The ARC cluster costs $2.50 an hour, about $1,800 a month, so I reserve it for crown-jewel workloads. And failing over to dodge a 30-minute blip can cost more than riding it out: cold caches, plus whatever async replication hadn't shipped.



Minutes 0–30 of a regional event: detect on your own data, decide on a clock, and recover using only data-plane actions.

DECISION FRAMEWORK: SHIFTING TRAFFIC WHILE THE REGION BURNS

Option	Use when	Cost shape	Watch out for
Ride it out + deadline	Impact flat or falling, single dependency	$0 plus SLA burn	Sunk-cost creep; set the deadline before the incident
Route 53 health-check failover	Clean binary endpoint failure, automatable	$0.50/mo per health check	Gray failures cause flapping; resolvers that ignore TTL
ARC routing controls	Deliberate human go/no-go on regional failover	$2.50/hr cluster (~$1,800/mo)	Price means you tier it to crown-jewel workloads
Global Accelerator traffic dials	Static IPs, gradual percentage shifts	Fixed hourly + premium per GB	Dial updates are API calls; confirm the path works in drills
Console/API DNS record edits	Last resort when nothing was pre-built	Free	Route 53's control plane runs only in us-east-1; it may be down in exactly this event

PITFALLS & SENIOR SIGNALS

× What sinks candidates

- **Waiting for AWS to confirm:** the Health Dashboard has lagged its own outages, so you burn your RTO standing by. Declare on your own synthetics and error budgets.
- **A control-plane recovery plan:** runbooks that launch instances, edit DNS records, or change IAM mid-event hit APIs that are degraded or throttled exactly then. Pre-provision, and flip data-plane switches instead.
- **No decision deadline:** "it'll recover any minute" stretches into hour three. Pre-commit the failover criteria and the clock, then honor them.

✓ What signals senior

- Separating **control plane from data plane** unprompted, including that Route 53's data plane carries a 100% availability SLA while its control plane lives only in us-east-1.
- You ask about the standby's **quota and capacity posture** before anyone else does: readiness is audited continuously, not discovered at 2 a.m.
- Communication runs on rails: a **status page hosted outside the affected region**, pre-written templates, and updates on a fixed cadence even when nothing has changed.

LIKELY FOLLOW-UPS

Q: How do you tell a regional AWS event apart from your own bad deploy?

Change correlates with deploys; regional events correlate across things that share nothing. I check the deploy timeline first, then look for simultaneous errors in independent dependencies like DynamoDB, SQS, and STS, confirm with synthetics running from outside AWS, and pull the account-specific view from the AWS Health API. That triage takes two minutes and decides rollback versus failover.

Q: Why exactly are control-plane operations risky in the middle of a regional event?

Control planes are complex, regional, and for global services concentrated in us-east-1, and during an event they get hammered by every other customer failing over at once. In October 2025, new EC2 launches in us-east-1 failed for hours after the DynamoDB trigger. Static stability is the answer: pre-provision the standby so recovery needs only data-plane flips.

Q: What do ARC readiness checks actually verify?

They checked quotas, capacity, and config parity between regions, but AWS closed readiness checks to new customers on April 30, 2026; ARC Region switch plan evaluation now runs that check continuously. The job is catching drift in peacetime. AWS advises against gating a live failover on readiness status; by then you trust your rehearsals, not a dashboard.

Recall hook: "In a regional event, the control plane is inside the blast radius." — detect on your own telemetry, decide on a pre-set clock, and recover using only data-plane actions against capacity you provisioned in peacetime.

SENIOR SERVERLESS · PERFORMANCE

Your serverless p99 spikes to 10 seconds under bursty load. Walk me through cold-start mechanics and fixes.

What the interviewer is really testing: whether you understand the execution-environment lifecycle deeply enough to diagnose from telemetry and pick the cheapest effective fix, or whether you'd reflexively buy warm instances for everything.

30-SECOND ANSWER


A cold start is the platform building an execution environment before my code runs: allocate a sandbox, download the code or pull the image, boot the runtime, then execute my global initialization. Runtime choice is often the biggest lever: Node and Python typically initialize in 200–400 ms, untuned Java and .NET in 1–5 seconds. I'd measure before fixing; Lambda prints Init Duration in every cold REPORT log line. Then I'd keep instances warm where the tail matters: always-ready instances on Azure Flex Consumption or Premium, min-instances on Cloud Run. Cold starts barely move the average; they own p99.

DEEP DIVE

The core problem: every serverless platform runs the same play when a request arrives and no warm instance exists: allocate a sandbox, fetch the code or container image, boot the language runtime, then run your initialization (the static constructors, dependency-injection wiring, SDK clients, and config fetches that execute before the handler). Only that last stage is yours. On steady traffic, cold starts hit a small fraction of invocations, which is exactly why they hide: the mean looks healthy while scale-out bursts and deployments stack fresh environments and the tail explodes. Since August 2025 AWS also bills the init phase for ZIP-packaged managed runtimes, so a bloated init is now a cost bug, not just a latency bug.

The design: attack cheapest first. Shrink and defer: smaller packages download faster, anything the first request doesn't need moves to lazy init, and clients stay global so warm invocations reuse them. Then the runtime: Node and Python boot in a few hundred milliseconds, while JVM and .NET functions take seconds unless compiled ahead of time (GraalVM, Native AOT). Only then buy warmth. Azure's Flex Consumption plan adds per-function always-ready instances on top of scale-from-zero; the Premium plan pairs always-ready instances with a prewarmed buffer during HTTP scale-out. On GCP, Cloud Run and Cloud Run functions take min-instances, billed at a reduced idle rate, plus startup CPU boost for CPU-heavy init.

The trade-offs to volunteer: warm pools convert a latency problem into a fixed cost, and they're sized in instances, not requests; a burst past your always-ready count still cold-starts. Timer-based pinger hacks keep one instance warm and do nothing for concurrency. Measure honestly: Init Duration on Lambda, Application Insights traces on Azure, container startup latency metrics on Cloud Run.



Top: the init stages that run before your handler; only the last one is your code. Bottom: how each provider measures init and keeps instances warm.

DECISION FRAMEWORK: CHEAPEST EFFECTIVE COLD-START FIX

Option	Use when	Cost shape	Watch out for
Trim init code & packages	First move on every platform	Free; engineering time only	Lazy loading shifts latency into the first request
Lighter runtime or AOT	Init dominated by runtime boot (JVM, .NET)	Free at runtime; build/rewrite cost	Native AOT breaks reflection-heavy libraries
Always-ready (Azure Flex)	Azure with scale-to-zero gaps hurting p99	Billed per always-ready instance kept	Default is 0; set per function scale group
Premium plan (Azure)	Larger instances, Windows, prewarmed buffer	At least one instance billed continuously	Idle spend dwarfs Consumption at low traffic
min-instances (Cloud Run)	GCP tail latency on spiky traffic	Reduced idle rate on request billing	Set per service; idle is cheaper, not free
Startup CPU boost (GCP)	CPU-bound init like JVM class loading	Extra CPU-seconds during startup only	No help for network-bound init (config fetches)

PITFALLS & SENIOR SIGNALS

× What sinks candidates

- **The pinger hack:** a timer warming one instance does nothing when a burst needs twenty. Size warm capacity to expected concurrency, not to "not zero."
- **Tuning the average:** cold starts are usually a small share of invocations, so the mean barely moves; track init duration and p99 separately or you'll declare a false victory.
- **Blaming the platform first:** oversized dependency graphs and synchronous config fetches frequently outweigh the runtime boot. Profile your own init before paying for warmth.

✓ What signals senior

- Walking the **init pipeline stage by stage** (sandbox, code download, runtime boot, your init) and naming the one stage you control.
- Knowing **Lambda bills the init phase** for ZIP-packaged managed runtimes since August 2025, which turned package bloat into a line item.
- Keeping **provider controls straight**: Flex always-ready versus Premium prewarmed versus Cloud Run min-instances, without conflating them.

LIKELY FOLLOW-UPS

Q: How would you measure cold-start frequency and impact in production?

On Lambda, a CloudWatch Logs Insights query over REPORT lines: count invocations carrying Init Duration and chart its distribution. On Azure, Application Insights traces correlate latency spikes with scale-out events. Cloud Run exposes container startup latency in Cloud Monitoring. I'd report two numbers (percent of invocations cold, and milliseconds added at p99) because that pair decides whether warmth is worth buying.

Q: Why do Java and .NET start so much slower, and what's the fix?

The runtime boot does real work: JVM startup, class loading, JIT warm-up. Untuned Java or .NET functions commonly take 1–5 seconds against a few hundred milliseconds for Node or Python. Fixes: compile ahead of time with GraalVM native image or .NET Native AOT, slim startup-heavy frameworks, and on Lambda, SnapStart resumes from a snapshot instead of re-running init.

Q: When does Azure's Flex Consumption beat the Premium plan?

Flex when you want scale-to-zero economics with targeted warmth: per-function scaling up to 1,000 instances and always-ready counts set only where the tail hurts. Premium when you need larger instances, Windows, or containers, plus a prewarmed buffer absorbing HTTP scale-out. At low, spiky traffic, Premium's continuously billed instance is the expensive part; Flex lets warmth be selective.

Recall hook: "A cold start is a build, not a wait." — the platform assembles sandbox, code, runtime, and your init before the first request; shrink what ships, defer what can wait, and pay for warmth only where p99 justifies it.

SENIOR AWS · DDOS DEFENSE Q7 / Cloud Networking & Security

Your ALB is under a DDoS attack burning $50k a day. How do you detect it and shut it down?

What the interviewer is really testing: whether you treat DDoS as a layered cost-and-availability problem. Can you design an automated defense funnel and put a price on each layer, or do you just name-drop Shield?

30-SECOND ANSWER


I'd push the fight away from the ALB, because the ALB bills per LCU (load balancer capacity unit) and every attack request costs money. CloudFront goes in front: 750-plus edge locations absorb the volumetric layers and Shield Standard handles SYN floods for free. AWS WAF on the distribution enforces rate-based rules, configurable down to 10 requests per window, plus bot rules and CAPTCHA. CloudWatch anomaly alarms trigger a Lambda that pushes attacking IPs into a WAF IP set within minutes. At $50k a day I'd add Shield Advanced for the response team; its cost credits only cover later attacks.

DEEP DIVE

The core problem: a Layer 7 flood against an Application Load Balancer is an economic attack as much as an availability one. ALB pricing is per LCU ($0.008/LCU-hour), and the LCU is the maximum of four dimensions: new connections, active connections, processed bytes, and rule evaluations. A botnet inflates all four at once. The ALB has no built-in per-IP rate limiting, and it scales automatically, so it will happily absorb the flood and hand you the bill. Detection is the hard half: you have to separate a viral spike from an attack before automation starts blocking people.

The design: defense in depth, outermost layer first. CloudFront fronts the ALB: it caches static content, terminates TLS at the edge, supports geo-blocking, and gets Shield Standard's Layer 3/4 mitigation free. The ALB then accepts traffic only from CloudFront, using the managed prefix list in its security group plus a secret custom header verified by WAF, so attackers cannot bypass the edge and hit the origin. WAF on the distribution runs rate-based rules (evaluation window configurable from 1 to 10 minutes), AWS managed bot rules, and CAPTCHA for borderline clients. The detection loop is CloudWatch anomaly alarms on RequestCount and ProcessedBytes feeding a Lambda that queries the WAF logs in Athena for viewer IPs and updates a WAF IP set automatically.

The trade-offs to volunteer: Shield Advanced costs $3,000/month on a one-year commitment. Against a $50k/day burn that is easy math, but credits aren't automatic: protection and a Block-mode rate rule must predate the attack, then the Shield Response Team validates a billing case. Aggressive rate limits punish legitimate users behind carrier NAT, so I deploy new rules in Count mode and graduate to Challenge, then Block. Rate counters also miss low-and-slow attacks like Slowloris; for those I watch ActiveConnectionCount and tighten idle timeouts instead.



Each layer strips attack traffic before it reaches LCU billing; the detection loop pushes fresh attacker IPs back to the WAF edge within minutes.

DECISION FRAMEWORK: LAYERING THE DEFENSES

Option	Use when	Cost shape	Watch out for
Shield Standard	Always on, L3/4 floods	Free, automatic	No Layer 7 or SRT help
CloudFront + WAF rate rule	First line vs L7 floods	$0.60/M req + $1/rule/mo	NAT users share one IP
Shield Advanced	Repeat or costly attacks	$3k/mo, 1-yr commit	Credits via support case
Bot Control + CAPTCHA	Scripted bots, scrapers	Per-request add-on fee	Challenges break API SDKs
Lambda auto-block loop	Fast-rotating botnets	Pennies per invocation	False positives at scale

PITFALLS & SENIOR SIGNALS

× What sinks candidates

- **Origin bypass:** attackers resolve the ALB's public DNS name and skip every edge defense. Lock the security group to the CloudFront prefix list and verify a secret header.
- **Rate limits as the only control:** Slowloris-style requests hold connections open without tripping any counter. Watch ActiveConnectionCount and shorten idle timeout.
- **Trusting Shield Standard for Layer 7:** it mitigates network-layer floods only. An HTTP flood sails straight through unless WAF rules exist.

✓ What signals senior

- Framing the attack as **economic denial of sustainability** and doing the LCU math out loud.
- A **progressive enforcement plan**: Count mode first, then Challenge, then Block, reviewing WAF logs between steps.
- Knowing the **cost-protection fine print**: credits need protection and a Block-mode rate rule before the attack, plus a billing case.

LIKELY FOLLOW-UPS

Q: The attack targets one computationally expensive endpoint. What changes?

I'd scope a second rate-based rule to that URI path with a far lower limit, say 100 requests per window versus thousands globally. Then shrink the endpoint's cost: cache GET responses in CloudFront, require authentication, and queue heavy work through SQS so a burst degrades latency instead of taking the backend down.

Q: Your new WAF rules start blocking real customers mid-attack. Now what?

Flip the noisy rule to Count mode and read the WAF logs; false positives usually cluster on carrier-grade NAT ranges, mobile retry storms, or partner integrations. I'd add scoped exceptions for those, downgrade the action to CAPTCHA or Challenge, and re-enable hard blocking only once the false-positive rate is near zero.

Q: How do you tell a DDoS from a legitimate viral spike?

Entropy. Query the WAF logs in Athena: real spikes show diverse IPs, mixed user agents, plausible geography, and multi-page sessions. Botnets cluster in narrow CIDR ranges, repeat identical user agents, hammer one endpoint, and carry no session cookies. That analysis takes minutes and decides whether automation blocks or capacity scales.

Recall hook: "Block at the edge, pay at the ALB." — every request that reaches the load balancer costs LCU money, so push defense outward: CloudFront absorbs, WAF filters, Shield Advanced credits what slips through.

How would you cut a cloud bill by 30% without hurting reliability?

What the interviewer is really testing: whether you have an ordered playbook with an expected yield for each lever, and whether you know which savings are free versus which ones trade away flexibility or headroom.

30-SECOND ANSWER


I'd attack it in yield order. Waste first, because it's free: unattached EBS volumes, idle load balancers, aged snapshots, and unused public IPv4 addresses at $3.65 a month each. Then schedule non-prod off outside working hours; a 12-by-5 schedule cuts those environments roughly 65%. Next, rightsizing driven by p95 utilization, not averages. Only then commitments: cover the steady base with Savings Plans or committed use discounts (CUDs) at up to 66–72% off, and let Spot at up to 90% off absorb the interruption-tolerant remainder.

DEEP DIVE

The core problem: cloud waste is structural, not careless. Engineers size for launch-day guesses plus a safety margin, and nothing decommissions itself: EBS volumes attached after launch survive termination by default, snapshots pile up behind deleted AMIs, and dev environments run 168 hours a week to serve a 45-hour work week. Practitioner surveys consistently self-estimate waste at a quarter to a third of spend. Order matters more than effort here. Commit to a bloated fleet and you rent the bloat for three years.

The design: a ladder, cheapest risk first. Sweep waste with recurring automation: unattached volumes, unassociated public IPv4 addresses ($0.005/hour since 2024), idle NAT gateways and load balancers, plus gp2-to-gp3 migration for an easy 20% per GB. Schedule non-prod down out of hours with an instance scheduler and an override tag for teams that need exceptions. Then rightsize: two-plus weeks of metrics including memory (which needs an agent on EC2), recommendations from Compute Optimizer, Azure Advisor, or GCP Recommender, downsizing one step at a time against p95. Last, commitments on the post-optimization baseline: EC2 Instance Savings Plans or Standard Reserved Instances (RIs) at up to 72% for stable families, Compute Savings Plans at up to 66% for shifting workloads, and Google resource-based CUDs up to 55% (70% memory-optimized). Buy in quarterly tranches, not one annual lump.

The trade-offs to volunteer: sequencing costs time. A quarter spent sweeping and rightsizing delays the commitment discount, and it's still the right call. Laddered one-year purchases give up roughly 20 points versus three-year all-upfront but keep pace with architecture churn like a Graviton migration. And savings have diminishing returns: engineer time is the real budget, so I'd work the top ten line items of the bill and ignore the five-dollar noise.



Work left to right: every step before the last is free or reversible, so the irreversible commitments get priced against a lean fleet.

DECISION FRAMEWORK: PICKING THE OPTIMIZATION LEVER

Option	Use when	Cost shape	Watch out for
Waste sweep (automated)	Always, and first	Pure savings, low risk	Snapshots backing AMIs resist deletion
Non-prod scheduling	Dev, test, demo environments	~65% on a 12-by-5 schedule	Overnight jobs; stateful boot order
Rightsizing	p95 utilization sits under ~40%	20–50% per resource	Memory metrics need an agent
Spot / preemptible	Stateless, batch, CI workers	Up to 90% off	Notice: AWS 2 min, GCP/Azure ~30 s
EC2 Instance SP / Std RI	Stable family, 1–3 yr horizon	Up to 72% off	Locked to family and region
Compute SP / Flexible CUD	Workloads that shift families	Up to 66% AWS, 46% GCP	Still a 1–3 yr $/hr commitment

PITFALLS & SENIOR SIGNALS

× What sinks candidates

- **Committing before optimizing:** buying coverage on a bloated fleet locks the waste in for one to three years. Sweep and rightsize first, then commit against the lean baseline.
- **Rightsizing on averages:** mean CPU hides the daily peak, and EC2 reports no memory metrics without an agent. Size to p95 over at least two weeks, then step down one size at a time.
- **One-time cleanup:** orphaned volumes and idle IPs grow back within a quarter. Make the sweep a scheduled job that deletes within policy or opens tickets, not a heroic annual purge.

✓ What signals senior

- Sequencing the levers and explaining **why commitments come last**: every earlier step shrinks the baseline you're about to sign for.
- Quoting **instrument-level numbers** (72% on EC2 Instance Savings Plans versus 66% on Compute) and naming the flexibility you trade for the extra points.
- Treating commitments as a **laddered portfolio**: quarterly tranches, staggered expirations, monthly utilization review.

LIKELY FOLLOW-UPS

Q: How much of the bill should commitments cover?

Measure a 90-day baseline after the sweep and rightsizing, then cover the trough: the compute still running at 3 a.m. on a Sunday. I'd usually aim for 70–80% of steady-state usage, with Spot and on-demand absorbing the rest. Stagger purchases quarterly so each tranche reflects the current architecture and expirations spread out.

Q: Compute Optimizer says a production database is four sizes too big. Walk me through acting on that.

Slowly. I'd confirm with p95 CPU, memory, and IOPS over two-plus weeks, including month-end peaks the tool may average away. Then one instance size step in a maintenance window, a week watching latency and error SLOs, repeat. Storage goes first when possible: gp2-to-gp3 migration is online and saves about 20% with no capacity change.

Q: Finance wants three-year all-upfront because the discount is deepest. Do you take it?

Only for the floor I'd bet the architecture on: the database tier, baseline web capacity. A family-locked three-year plan strands money if you move to ARM, Fargate, or serverless mid-term. I'd split it: three-year on the certain core, one-year tranches on the rest, and accept a gap of roughly 20 points as the price of flexibility.

Recall hook: "Sweep, schedule, rightsize, then commit." — the first three steps are free or reversible, so do them first and size the one-to-three-year commitments to the lean fleet, not the bloated one.

How would you design a multi-region active-active data layer for 99.999% availability, and how would you resolve write conflicts?

What the interviewer is really testing: whether you know what multi-writer replication does to data during a partition, and whether you scope an extreme SLA instead of promising it system-wide.

30-SECOND ANSWER


Five nines is a 5.26-minute downtime budget for the entire year, so nothing in the recovery path can wait for a human. I'd serve traffic from three regions at once, fronted by Route 53 latency-based routing with health checks, or AWS Global Accelerator if I need static anycast IPs. The data layer must support multi-master replication: DynamoDB Global Tables or Redis Active-Active. Conflicts get resolved by data type: CRDT merges for counters and sets, last-writer-wins for opaque values, and keys that can't tolerate a lost write get pinned to a single home region.

DEEP DIVE

The core problem: five nines allows 5 minutes 16 seconds of downtime per year. A single regional incident usually burns more than that before a pager even fires, so active-passive with human-driven failover loses on arithmetic alone. And once two regions accept writes asynchronously, you've picked availability over consistency in CAP terms: partitions will happen, both sides keep writing, and the same key can be updated concurrently on two continents. Conflicts are guaranteed; the design question is whether your merge behavior is deterministic and acceptable to the business.

The design: three regions, each running the full stack, with bidirectional asynchronous replication between data clusters. Routing sits above. Route 53 latency-based records with health checks that probe deep health (can this region complete a real write?), or Global Accelerator for anycast IPs and traffic shifts that skip DNS TTLs. Conflict resolution is layered by data shape: counters, sets, and presence data use CRDT types, which merge mathematically without coordination; opaque values fall back to last-writer-wins by timestamp, with a deterministic tie-break; anything where a dropped write is unacceptable (balances, inventory decrements) is pinned to one home region per key, trading some latency for correctness.

The trade-offs to volunteer: cost lands at 2–3× a single-region baseline, because every region carries failover headroom. Reads can be stale for the replication-lag window, typically under a second cross-region, but unbounded during a partition. Last-writer-wins silently discards the losing write, and clock skew can make "last" the wrong answer. CRDTs only fit operations that commute, and most real schemas are mixed. I scope five nines to workloads that earn it, run the rest active-passive, and validate with chaos drills that sever a region and measure real convergence.



Every region takes writes behind global routing (two of the three shown); async replication with per-data-type conflict resolution keeps them converged.

DECISION FRAMEWORK: CHOOSING A CONFLICT STRATEGY PER DATA TYPE

Strategy	Use when	Cost shape	Watch out for
CRDT merge (Redis Active-Active)	Counters, sets, presence/session data	License + 2–3× infra	Only fits commutative operations
Last-writer-wins	Opaque values where losing one concurrent write is tolerable	Cheap, built into most stores	Silent write loss; clock skew picks wrong winner
DynamoDB Global Tables	Key-value access patterns, AWS-only stack	Replicated writes billed per region	LWW by default; strong-consistency mode (3 Regions) since 2025
Home-region pinning per key	Must-not-lose data: balances, inventory	No conflict machinery needed	Home-region outage stalls writes for those keys
Consensus store (Spanner, CockroachDB)	Strict global consistency is non-negotiable	Premium $$$$	Writes pay a cross-region round trip

PITFALLS & SENIOR SIGNALS

× What sinks candidates

- **Promising five nines system-wide:** your availability is capped by the weakest serial dependency. Scope the SLA to the tier that justifies it.
- **Treating LWW as harmless:** under clock skew it discards committed writes with no error. Bound clock drift and emit conflict metrics so losses are visible.
- **DNS-failover thinking:** resolver caching ignores your TTL, so traffic keeps hitting the dead region for minutes. Use anycast or client-side multi-endpoint retry.

✓ What signals senior

- Quoting the downtime budget (5.26 min/year) unprompted shows you've operated against a real SLA, not just read about one.
- Segmenting keys by conflict semantics (mergeable vs pin-to-home) shows you design from the data model outward.
- Asking which writes the business can afford to lose turns a technology question into a requirements conversation.

LIKELY FOLLOW-UPS

Q: Two regions update the same key at the same moment. Walk me through what happens.

Depends on the type. A CRDT counter merges by summing both increments; an OR-Set unions the adds. An opaque blob goes to last-writer-wins: the later timestamp survives and the other write is gone. If that's unacceptable for the key, expose both versions to the application Dynamo-style, or pin it to a home region.

Q: Why three regions instead of two?

Headroom and quorum. With two regions, each must be able to carry the full load alone; with three, a survivor takes only 50% more. Quorum stores like DynamoDB's strong-consistency mode need three so a majority survives a partition. Async multi-master has no quorum: every side keeps writing and reconciles later.

Q: How do you prove the design actually delivers five nines?

You can't prove it from an architecture diagram. I'd run chaos drills that sever a region and measure real traffic-shift time and replication convergence, keep synthetic canaries writing in each region and reading from the others to track effective RPO, and report against an error budget of 5.26 minutes per year.

Recall hook: "Five nines means no human in the loop." — every failover, health decision, and conflict merge must be automatic, and only the data that earns the 2–3× bill gets the active-active treatment.

How would you design a serverless e-commerce platform that absorbs a 1000x Black Friday traffic spike?

What the interviewer is really testing: whether you know where "infinitely scalable" services actually throttle, and whether you apply patterns like CQRS (Command Query Responsibility Segregation) and event sourcing where they pay for themselves rather than everywhere the blog posts suggest.

30-SECOND ANSWER


I'd put CloudFront and API Gateway in front of Lambda microservices, route domain events through EventBridge, and persist to DynamoDB in on-demand mode. The scaling math matters more than the buzzwords: each Lambda function gains 1,000 concurrent executions every 10 seconds, and DynamoDB on-demand absorbs up to double your previous traffic peak, so before Black Friday I'd load-test, pre-warm DynamoDB, and buy provisioned concurrency for checkout. CQRS and event sourcing go only where they earn their complexity: orders and inventory, not the product catalog.

DEEP DIVE

The core problem: a 1000x spike breaks the quiet assumptions of a provisioned stack: capacity planned weeks ahead, a relational database sized for an imagined peak, humans watching dashboards. Serverless removes the server math but not the physics. Lambda adds 1,000 concurrent executions per function every 10 seconds; DynamoDB on-demand can throttle if traffic jumps past double its previous peak inside 30 minutes. Under flash traffic the failure mode shifts from "not enough servers" to quota exhaustion, plus correctness races like two buyers winning the last unit of inventory.

The design: CloudFront absorbs the read traffic that never needs to reach origin; API Gateway throttles and authenticates what does. Behind it, one Lambda service per bounded context: orders, inventory, payments. Order commands append immutable events to a DynamoDB event store, and DynamoDB Streams project them into ElastiCache and dedicated read tables. That is CQRS earning its keep: the read side scales independently of writes. EventBridge carries domain events between services at-least-once, so every consumer must be idempotent. Where ordering is mandatory (per-SKU inventory decrements) I'd use SQS FIFO keyed by SKU as the message group; high-throughput mode reaches 70,000 messages per second in top Regions, but each group caps at 300 (3,000 batched). Step Functions runs the checkout saga and releases the reservation when payment capture fails.

The trade-offs to volunteer: provisioned concurrency kills cold starts on checkout but bills whether traffic arrives or not, so I'd schedule it around forecast windows. The default of 1,000 concurrent executions per account per Region is a support ticket, not a design feature. Raise it weeks early, and pre-warm DynamoDB with warm throughput. Event sourcing buys audit and replay at the price of schema versioning and snapshot maintenance, which is why I'd confine it to orders and money and leave the catalog as plain CRUD.



Commands append events, streams project read models, and ordering or sagas appear only where correctness demands them.

DECISION FRAMEWORK: PICKING THE EVENT BACKBONE

Option	Use when	Cost shape	Watch out for
EventBridge bus	Fan-out domain events; routing rules; SaaS integrations	Per event published, zero idle cost	At-least-once delivery; no ordering guarantee
SQS standard queue	Buffering bursts between one producer and one consumer	Per request, effectively free at low volume	Duplicates and reordering; consumers must be idempotent
SQS FIFO (high throughput)	Strict order per key, e.g. inventory per SKU	Per request, slightly above standard	300 msg/s per group; 3,000 batched
Kinesis Data Streams	High-volume ordered streams: clickstream, analytics	Per shard-hour, or on-demand per GB	1 MB/s per shard; hot partition keys throttle
Step Functions (Express)	Sagas and orchestration with compensation logic	Per request and duration	5-minute execution cap; at-least-once semantics

PITFALLS & SENIOR SIGNALS

✕ What sinks candidates

- **Cold starts on the money path:** checkout latency doubles exactly when traffic peaks. Buy provisioned concurrency for checkout and payment functions, and keep their deployment packages small.
- **Trusting exactly-once delivery:** EventBridge and SQS standard both deliver at-least-once, so a duplicate event double-decrements stock. Idempotency keys plus DynamoDB conditional writes make replays harmless.
- **Assuming "serverless" means unlimited:** hitting the 1,000 default account concurrency or DynamoDB's double-peak rule mid-sale is an outage. Raise quotas and pre-warm DynamoDB with a production-shaped load test weeks ahead.

✓ What signals senior

- Quoting the actual scaling rates (1,000 concurrency per 10 seconds, double the previous DynamoDB peak) instead of waving at "infinite scale".
- Scoping event sourcing to the bounded contexts where audit and replay matter is the signal that you've maintained one, not just diagrammed one.
- Planning degradation before exhaustion: feature flags that shed recommendations and reviews so checkout keeps its capacity when the spike exceeds forecast.

LIKELY FOLLOW-UPS

Q: How do you prevent overselling inventory during the spike?

Serialize per SKU and make the write conditional. Inventory decrements flow through an SQS FIFO queue with the SKU as message group ID, and the consumer applies a DynamoDB conditional write that fails when stock would go negative. The checkout saga reserves first and captures payment second; a compensating step releases the reservation if payment fails.

Q: How do you keep checkout fast while everything else is melting?

Cut work before cutting milliseconds. CloudFront and ElastiCache serve catalog reads so checkout functions only do checkout. Provisioned concurrency removes cold starts on that path, and everything non-critical (emails, analytics, recommendations) goes async behind EventBridge. Past forecast, I'd shed those features with flags before degrading payment.

Q: When is event sourcing the wrong choice?

Most of the time. It pays where you need audit trails, temporal queries, or replay: orders, payments, ledgers. For the catalog or user profiles it adds schema versioning, snapshots, and projection lag for no benefit, so those stay plain CRUD.

Recall hook: "Scale is a quota, not a promise." — Lambda ramps 1,000 concurrency per 10 seconds and DynamoDB on-demand absorbs only double its last peak at once, so pre-warm, raise limits, and make every consumer idempotent.

How do you choose a database for a new service: relational, key-value, document, graph, or vector?

What the interviewer is really testing: whether you reason from access patterns and operational cost or recite vendor catalogs, and whether you have the spine to defend an unglamorous default.

30-SECOND ANSWER


I work backwards from access patterns, not from the database catalog. My default is boring Postgres (Aurora or Cloud SQL) because it covers relational, JSON documents, and, with pgvector, similarity search for anything under roughly ten million vectors. I reach for a purpose-built engine only when a measured pattern outgrows it: DynamoDB for key-value lookups at single-digit-millisecond latency, a time-series store for high-ingest telemetry, Spanner or Aurora DSQL when I genuinely need multi-region strong consistency. Every extra engine adds backups, monitoring, and on-call expertise, so each one has to earn its place.

DEEP DIVE

The core problem: cloud catalogs list fifteen-plus purpose-built engines, and teams fail in both directions: forcing graph traversals through six-way SQL joins, or giving every microservice its own exotic store until operations drowns. Database choice is the hardest infrastructure decision to reverse, because schema, data gravity, and application code calcify around it. Choosing wrong means re-architecture, not a config change. The variable that predicts fit is the access pattern: what the queries look like, how predictable they are, the read/write ratio, and the latency budget.

The design: I run a four-question funnel: access pattern, data model, consistency and distribution, then operating model. Predictable key lookups at scale point to DynamoDB, if the access paths are known upfront. Nested fast-changing documents point to Firestore or MongoDB Atlas, multi-hop relationship queries to a graph store (Neptune), high-ingest telemetry to a time-series store such as Timestream for InfluxDB or TimescaleDB. The global tier is its own decision. Spanner offers external consistency via TrueTime with a 99.999% multi-region SLA; Aurora DSQL, GA since May 2025, brings PostgreSQL-compatible active-active writes to AWS; Cosmos DB offers five per-request consistency levels. For vectors in 2026, pgvector with an HNSW (Hierarchical Navigable Small World) index covers most RAG (retrieval-augmented generation) features below roughly ten million vectors, and dedicated stores like Pinecone or Qdrant earn their keep when vector search is the product itself.

The trade-offs to volunteer: purpose-built engines win their benchmarks, but each one brings a backup story, a monitoring stack, an upgrade cadence, and someone on call who understands it. My default is boring Postgres until a measured pattern outgrows it. That bias is operational, not sentimental. Pricing shifts the calculus: DynamoDB's late-2024 on-demand price cut to $0.625 per million writes made pay-per-request the sane default for spiky traffic. Every managed pick also trades portability for velocity, so I name the lock-in and the exit cost out loud.



Start at the access pattern, default to Postgres, and let each purpose-built engine earn its place with a measured query shape.

DECISION FRAMEWORK: MATCHING ENGINE TO ACCESS PATTERN

Option	Sweet spot	Cost shape	Watch out for
Postgres / Aurora	Joins, ad-hoc, JSONB	Instance hours + storage	Single-writer ceiling
DynamoDB (key-value)	Known paths, any scale	$0.625/M writes on-demand	Ad-hoc queries; hot keys
Document (Atlas/Firestore)	Fast-changing nested data	Per-node or per-op tiers	JSONB often enough
Spanner / Aurora DSQL	Multi-region strong writes	Spanner nodes; DSQL DPUs	Latency physics remain
Time-series (InfluxDB)	High-ingest telemetry	Ingest + tiered retention	Plan downsampling early
pgvector → dedicated	RAG under ~10M vectors	Extension first, $$ later	Recall vs latency tuning

PITFALLS & SENIOR SIGNALS

× What sinks candidates

- **Resume-driven selection:** adopting the engine you want to learn leaves the team a fleet of half-understood databases; require a measured access pattern the incumbent demonstrably fails.
- **DynamoDB without modeled access paths:** single-table design assumes you know every query upfront; a new query shape after launch means scans, bolt-on GSIs, and hot partitions. Model first or stay relational.
- **A dedicated vector store by reflex:** spinning up Pinecone for a 200K-chunk RAG feature adds a network hop and a second source of truth; pgvector handles that scale with plain SQL filters.

✓ What signals senior

- Opening with the **boring Postgres default**, plus the exact thresholds where it breaks, signals ownership of real systems rather than catalog tourism.
- Candidates who ask **"how predictable are the queries?"** before naming a product are selecting by access pattern, the senior way around.
- Knowing the **2026 vector answer** (pgvector first, dedicated if it misses targets, often past ~10M vectors) shows hands-on judgment, not 2023 hype.

LIKELY FOLLOW-UPS

Q: When does pgvector stop being enough for vector search?

Three triggers, each confirmed by benchmarks: the corpus heads past roughly ten million vectors, vector queries dominate the workload, or recall tuning needs index features Postgres lacks. Until then, pgvector's HNSW gives me similarity plus metadata filters in one SQL query. Past it, Pinecone, Qdrant, or Milvus let the index scale independently of the OLTP database.

Q: Position Aurora, Spanner, and Cosmos DB for a global application.

By consistency need and home cloud. Aurora is the regional workhorse: PostgreSQL/MySQL compatibility with a single writer. Spanner pioneered global external consistency via TrueTime and carries a 99.999% multi-region SLA. Aurora DSQL is AWS's answer: serverless, PostgreSQL-compatible, active-active across regions. Cosmos DB's edge is per-request tunable consistency, five levels, and multi-model APIs for Azure-centric estates.

Q: Isn't "Postgres for everything" just familiarity bias?

It's a deliberate ops decision, kept honest by exit criteria I write down when I pick it: sustained write throughput near the single-writer ceiling, a p99 latency SLA it misses, a vector corpus past ten million. Familiarity bias is staying put after the measurements say move; defaults with exit criteria are just engineering.

Recall hook: "The access pattern picks the database." — default to boring Postgres, let measured query shapes justify every purpose-built engine, and price each new engine in backups, monitoring, and on-call hours.

YOU JUST READ 8 OF 50 QUESTIONS

Want all 188 pages?

The full Cloud Platforms book covers all 50 questions across 8 chapters, each with the complete senior-level answer, plus a war story, rapid-fire recall and a cheat-sheet for every chapter.

THE FULL BOOK

Cloud Platforms

50 questions · 188 pages

$9.99 / INR 899

BEST VALUE

The Complete Series, 5 Books

252 questions · 948 pages

$31.99 / INR 2,999

Get it at devopsinterview.cloud

Scan to visit the store