

Tanium Client

Compatibility Bulletin — Client Version 7.5.x — Bulletin TCB-2026-014 — Published 2026-01-22

Scope

This bulletin describes co-existence requirements between Tanium Client 7.5.x and third-party endpoint security agents, with a focus on EDR sensors that hook the same kernel filter manager altitude range.

EDR Co-existence Matrix

Third-Party Agent	Version	Compatibility with Tanium 7.5.x
CrowdStrike Falcon Sensor	7.16.x	Compatible, no special configuration
CrowdStrike Falcon Sensor	7.17.x	Compatible, no special configuration
CrowdStrike Falcon Sensor	7.18.x	Compatible — recommended minimum Tanium Client 7.4.6 due to filter altitude renegotiation
SentinelOne Agent	23.4.x	Compatible, no special configuration

Tanium Client versions prior to 7.4.6 are not validated against Falcon Sensor 7.18.x's revised kernel filter altitude allocation and **MUST** be upgraded to 7.4.6 or later before Falcon Sensor 7.18.x is deployed to the same endpoint. Co-installing Falcon 7.18.x with Tanium Client below 7.4.6 has been observed to cause filter manager registration races during boot, resulting in delayed Tanium check-in (15-40 minutes) on affected endpoints.

Operating System Support

Operating System	Tanium Client 7.4.x	Tanium Client 7.5.x
Windows 11 23H2	Supported	Supported
Windows 11 24H2	Supported	Supported
Windows 11 25H2	Not validated	Supported
Ubuntu 22.04 LTS	Supported	Supported
Ubuntu 24.04 LTS	Not validated	Supported

Recommended Upgrade Sequencing

1. Upgrade Tanium Client to 7.4.6 or later.
2. Validate check-in and filter manager registration on a pilot ring (minimum 48 hours).
3. Deploy CrowdStrike Falcon Sensor 7.18.x to the same ring.
4. Monitor for FAL-2026-0091 / FAL-2026-0103 (see CrowdStrike release notes) before fleet-wide rollout.