■■ MySQL Database Schema & ERD Architecture

Database: rag_users • **Engine:** MySQL 8.4 on AWS EC2 (Port 3306) • **Host:** agent.doctorsarahhensley.com

1. Relational Architecture Overview

The rag_users database consists of 4 tightly coupled relational tables. The parent table users stores identified students and guest checkout accounts. Child tables purchases and past_records enforce foreign key integrity with ON DELETE CASCADE. The conversation_turns table tracks high-throughput multi-turn dialogue telemetry across Clinical and Advisor modes.

2. Full Table & Column Definitions

Table Name	Column Name	Data Type	Key / Index	Description
users	**id**	VARCHAR(50)	**PRIMARY KEY**	WordPress User ID or Guest Email
	name	VARCHAR(100)	NOT NULL	Full Name
	email	VARCHAR(100)	**UNIQUE KEY**	Unique Email Address
	created_at	TIMESTAMP	DEFAULT CURRENT_TS	Creation Date
purchases	**id**	INT AUTO_INCREMENT	**PRIMARY KEY**	Purchase Record ID
	user_id	VARCHAR(50)	**FOREIGN KEY**	FK -> users.id (ON DELETE CASCADE)
	item_type	VARCHAR(50)	NOT NULL	course, book, or masterclass
	item_title	VARCHAR(255)	NOT NULL	Product Title
	purchased_at	TIMESTAMP	DEFAULT CURRENT_TS	Purchase Date
past_records	**id**	INT AUTO_INCREMENT	**PRIMARY KEY**	Clinical Record ID
	user_id	VARCHAR(50)	**FOREIGN KEY**	FK -> users.id (ON DELETE CASCADE)
	interaction_type	VARCHAR(100)	NOT NULL	coaching_session, intake
	summary_notes	TEXT	NOT NULL	Attachment style & notes
	recorded_at	TIMESTAMP	DEFAULT CURRENT_TS	Record Date
conversation_turns	**id**	INT AUTO_INCREMENT	**PRIMARY KEY**	Turn ID
	session_key	VARCHAR(150)	**INDEX (idx_conv)**	Indexed Session Key
	user_id	VARCHAR(100)	NOT NULL	Persona User ID
	role	VARCHAR(20)	NOT NULL	user or assistant
	mode	VARCHAR(50)	NULL	generic or sales
	content	MEDIUMTEXT	NOT NULL	Full Markdown Dialogue
	created_at	DOUBLE	**INDEX (idx_conv)**	Unix Millisecond Timestamp