13.8. LABS



Exercise 13.2: Viewing Logs Output

Container standard out can be seen via the **kubectl logs** command. If there is no standard out, you would not see any output. In addition, the logs would be destroyed if the container is destroyed.

1. View the current Pods in the cluster. Be sure to view Pods in all namespaces.

student@cp:~\$ kubectl get po --all-namespaces

```
NAMESPACE
                                                             READY
                                                                        STATUS
                                                                                  RESTARTS
                                                                                              AGE
                                                             1/1
  kube-system
                 calico-kube-controllers-7b9dcdcc5-qg6zd
                                                                      Running
                                                                                0
                                                                                            13m
  kube-system
                 calico-node-dr279
                                                             1/1
                                                                      Running
                                                                                0
                                                                                            6d1h
5
                 etcd-cp
                                              1/1
                                                         Running
                                                                    2
                                                                               44h
  kube-system
                                                                    2
                 kube-apiserver-cp
                                              1/1
                                                         Running
                                                                               44h
  kube-system
  kube-system
                 kube-controller-manager-cp
                                              1/1
                                                         Running
                                                                    2
                                                                               44h
  kube-system
                 kube-scheduler-cp
                                              1/1
                                                         Running
                                                                               44h
  . . . .
```

2. View the logs associated with various infrastructure pods. Using the **Tab** key you can get a list and choose a container. Then you can start typing the name of a pod and use **Tab** to complete the name.

student@cp:~\$ kubectl -n kube-system logs <Tab><Tab>

```
calico-kube-controllers-7b9dcdcc5-qg6zd
calico-node-dr279
calico-node-xtvfd
coredns-5644d7b6d9-k7kts
coredns-5644d7b6d9-rnr2v
etcd-cp
kube-apiserver-cp
kube-controller-manager-cp
kube-proxy-qhc4f
kube-proxy-s56hl
kube-scheduler-f-cp
traefik-ingress-controller-mcn47
```

student@cp:~\$ kubectl -n kube-system logs \ kube-apiserver-cp

```
Flag --insecure-port has been deprecated, This flag will be removed in a future version.
I1119 02:31:14.933023
                         1 server.go:623] external host was not specified, using 10.128.0.3
I1119 02:31:14.933356
                         1 server.go:149] Version: v1.19.0
I1119 02:31:15.595131
                         1 plugins.go:158] Loaded 11 mutating admission controller(s)
successfully in the following order: NamespaceLifecycle, LimitRanger, ServiceAccount,
StorageObjectInUseProtection, MutatingAdmissionWebhook, RuntimeClass.
I1119 02:31:15.595357
                         1 plugins.go:161] Loaded 7 validating admission controller(s)
successfully in the following order: LimitRanger, ServiceAccount, Priority,
PersistentVolumeClaimResize, ValidatingAdmissionWebhook, RuntimeClass,
ResourceQuota.
<output_omitted>
```

3. View the logs of other Pods in your cluster.

