

SQL - Using Joins

The **SQL Joins** clause is used to combine records from two or more tables in a database. A JOIN is a means for combining fields from two tables by using values common to each.

Consider the following two tables, (a) CUSTOMERS table is as follows:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

(b) Another table is ORDERS as follows:

OID	DATE	CUSTOMER_ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

Now, let us join these two tables in our SELECT statement as follows:

```
SQL> SELECT ID, NAME, AGE, AMOUNT
      FROM CUSTOMERS, ORDERS
      WHERE CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

This would produce the following result:

ID	NAME	AGE	AMOUNT
3	kaushik	23	3000
3	kaushik	23	1500
2	Khilan	25	1560
4	Chaitali	25	2060

Here, it is noticeable that the join is performed in the WHERE clause. Several operators can be used to join tables, such as =, <, >, <>, <=, >=, !=, BETWEEN, LIKE, and NOT; they can all be used to join tables. However, the most common operator is the equal symbol.

SQL Join Types:

There are different types of joins available in SQL:

- **INNER JOIN:** returns rows when there is a match in both tables.
- **LEFT JOIN:** returns all rows from the left table, even if there are no matches in the right table.
- **RIGHT JOIN:** returns all rows from the right table, even if there are no matches in the left table.
- **FULL JOIN:** returns rows when there is a match in one of the tables.
- **SELF JOIN:** is used to join a table to itself as if the table were two tables, temporarily renaming at least one table in the SQL statement.
- **CARTESIAN JOIN:** returns the Cartesian product of the sets of records from the two or more joined tables.

INNER JOINS

The most frequently used and important of the joins is the **INNER JOIN**. They are also referred to as an **EQUIJOIN**.

The **INNER JOIN** creates a new result table by combining column values of two tables (table1 and table2) based upon the join-predicate. The query compares each row of table1 with each row of table2 to find all pairs of rows which satisfy the join-predicate. When the join-predicate is satisfied, column values for each matched pair of rows of A and B are combined into a result row.

Syntax:

The basic syntax of **INNER JOIN** is as follows:

```
SELECT table1.column1, table2.column2...
FROM table1
INNER JOIN table2
ON table1.common_field = table2.common_field;
```

Example:

Consider the following two tables, (a) CUSTOMERS table is as follows:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

(b) Another table is ORDERS as follows:

OID	DATE	ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

Now, let us join these two tables using INNER JOIN as follows:

```
SQL> SELECT ID, NAME, AMOUNT, DATE
      FROM CUSTOMERS
      INNER JOIN ORDERS
      ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

This would produce the following result:

ID	NAME	AMOUNT	DATE
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
2	Khilan	1560	2009-11-20 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00

LEFT JOINS

The SQL **LEFT JOIN** returns all rows from the left table, even if there are no matches in the right table. This means that if the ON clause matches 0 (zero) records in right table, the join will still return a row in the result, but with NULL in each column from right table.

This means that a left join returns all the values from the left table, plus matched values from the right table or NULL in case of no matching join predicate.

Syntax:

The basic syntax of **LEFT JOIN** is as follows:

```
SELECT table1.column1, table2.column2...
FROM table1
LEFT JOIN table2
ON table1.common_field = table2.common_field;
```

Here given condition could be any given expression based on your requirement.

Example:

Consider the following two tables, (a) CUSTOMERS table is as follows:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

(b) Another table is ORDERS as follows:

OID	DATE	CUSTOMER_ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

Now, let us join these two tables using LEFT JOIN as follows:

```
SQL> SELECT ID, NAME, AMOUNT, DATE
      FROM CUSTOMERS
      LEFT JOIN ORDERS
      ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

This would produce the following result:

ID	NAME	AMOUNT	DATE
1	Ramesh	NULL	NULL
2	Khilan	1560	2009-11-20 00:00:00
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00
5	Hardik	NULL	NULL
6	Komal	NULL	NULL
7	Muffy	NULL	NULL

RIGHT JOINS

The SQL **RIGHT JOIN** returns all rows from the right table, even if there are no matches in the left table. This means that if the ON clause matches 0 (zero) records in left table, the join will still return a row in the result, but with NULL in each column from left table.

This means that a right join returns all the values from the right table, plus matched values from the left table or NULL in case of no matching join predicate.

Syntax:

The basic syntax of **RIGHT JOIN** is as follows:

```
SELECT table1.column1, table2.column2...
FROM table1
RIGHT JOIN table2
ON table1.common_field = table2.common_field;
```

Example:

Consider the following two tables, (a) CUSTOMERS table is as follows:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00

5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

(b) Another table is ORDERS as follows:

OID	DATE	CUSTOMER_ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

Now, let us join these two tables using RIGHT JOIN as follows:

```
SQL> SELECT ID, NAME, AMOUNT, DATE
      FROM CUSTOMERS
      RIGHT JOIN ORDERS
      ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

This would produce the following result:

ID	NAME	AMOUNT	DATE
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
2	Khilan	1560	2009-11-20 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00

FULL JOINS

The SQL **FULL JOIN** combines the results of both left and right outer joins.

The joined table will contain all records from both tables, and fill in NULLs for missing matches on either side.

Syntax:

The basic syntax of **FULL JOIN** is as follows:

```
SELECT table1.column1, table2.column2...
FROM table1
FULL JOIN table2
ON table1.common_field = table2.common_field;
```

Here given condition could be any given expression based on your requirement.

Example:

Consider the following two tables, (a) CUSTOMERS table is as follows:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

(b) Another table is ORDERS as follows:

OID	DATE	CUSTOMER ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

Now, let us join these two tables using FULL JOIN as follows:

```
SQL> SELECT ID, NAME, AMOUNT, DATE
      FROM CUSTOMERS
      FULL JOIN ORDERS
      ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

This would produce the following result:

ID	NAME	AMOUNT	DATE
1	Ramesh	NULL	NULL
2	Khilan	1560	2009-11-20 00:00:00
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00
5	Hardik	NULL	NULL
6	Komal	NULL	NULL
7	Muffy	NULL	NULL
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
2	Khilan	1560	2009-11-20 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00

If your Database does not support FULL JOIN like MySQL does not support FULL JOIN, then you can use **UNION ALL** clause to combine two JOINS as follows:

```
SQL> SELECT ID, NAME, AMOUNT, DATE
      FROM CUSTOMERS
      LEFT JOIN ORDERS
```

```
        ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID  
UNION ALL  
        SELECT ID, NAME, AMOUNT, DATE  
        FROM CUSTOMERS  
        RIGHT JOIN ORDERS  
        ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID
```