

18 IT 1800 SUB

SWETON®



18 IT 1800 SUB – Precision in Power, Depth in Bass

Designed for demanding sub-bass applications, the 18 IT 1800 SUB features a high-energy motor system with a formidable BL of 33.43 N/A and a linear Xmax of more than 8 mm. It delivers clean, authoritative bass with minimal distortion thanks to its low Qts (0.42) and a robust 5.6 Ω voice coil.

Its Fs of 46 Hz and wide excursion allow it to reproduce deep frequencies with excellent control and impact. Tested on Klippel Analyzer & CLIO, it's engineered for performance, durability, and consistency — a true workhorse for professional subwoofer systems.

Recommended Enclosure Design

Type	Volume (Net)	Port Size (Dia x Length)	Tuning Frequency
Vented	130–150 Litres	6" diameter x 180 mm	~40 Hz
Sealed	80–90 Litres	—	Natural roll-off

✓ Note: Vented is recommended for maximum SPL output in large venues.

Recommended Crossover (HPF/LPF)

Filter Type	Frequency	Slope
HPF	30–35 Hz	24 dB/oct (Linkwitz-Riley)
LPF	100–120 Hz	24 dB/oct (Linkwitz-Riley)

Ideal Application Areas

- Professional DJ & PA Subwoofer Cabinets
- Large Outdoor Events & Processions
- Touring and Installed Sound Systems
- Religious & Cultural Events
- Clubs & Auditoriums requiring high SPL at low frequencies

✓ Why Choose 18 IT 1800 SUB?

- Built to handle high power and thermal load
- High BL and Motor Efficiency (198 Ns/m) = Accurate cone control
- Very low distortion at full excursion
- Tested on Klippel & CLIO for assured performance
- Reliable for continuous usage in Indian weather

SPECIFICATIONS & PARAMETERS

Specifications

Nominal Diameter	464 mm
Nominal Impedance	8 Ω
Nominal Power Handling (AES)	1800 W
Program Power	3600 W
Sensitivity (1W/1m)	95 dB
Frequency Range	35-1200 Hz
Magnet Material	Ferrite
Voice Coil Diameter	130 mm (5.12 in)
Winding Material	COPPER
Former Material	Glass Fibre
Winding Type	In/Out

Mounting Info

Overall Diameter	464 mm
Bolt Circle Diameter	448 mm
Baffle Cutout Diameter	420 mm
Depth	187 mm
Flange and Gasket Thickness	17 mm
Gross Weight	28.30 Kgs

Parameters

Resonant Frequency	Fs	46 Hz
DC Resistance	Re	5.6 Ω
Electrical Q	Qes	0.43
Mechanical Q	Qms	15.88
Total Q	Qts	0.42
Compliance Equivalent Volume	Vas	78.68 Ltrs
Peak Diaphragm Displacement Volume	Vd	1.18 Ltrs
Effective Surface Area of Cone	Sd	1176.28 cm ²
Reference Efficiency	η_0	1.75%
Moving Mass including air load	Mms	292.3 gms
Motor Strength	Bl	33.43 T-m
Voice Coil Inductance	Le	1.09 mH
Efficiency Bandwidth Product	EBP	107 Hz
Voice Coil Overhang	Xmax	± 8 mm

Recone Kit

Recone Kit Number	REC18IT1800SUB
-------------------	----------------

$Z(f, x=0)$ Impedance