STM



Sensors and IO



Communication

CAN Transciever



Note: Low power mode selected through RS

LORA



RS485 Transciever



Note: Low power mode selected through DE along with RE

USB Debug



Easy access gnd pins for debug

Power Supply and Battery



STM I2C Pullup



External Connector



Optional module



Fiducials

AB

Devtank LTD

Sheet: /
File: OSM_env01.sch

Title: Open Smart Monitor

Size: A3	Date: 2021-09-22	**Rev: B**
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2		Id: 1/9

Li_Ion Battery Charge Controller



Latched powerbutton Circuit



5V and 3V3 Power Supplies



Battery Voltage Monitor



divider ratio=47/147=31.97
5/1024=1adc=4.88mm
(4.2/4.88m)*0.3197=275.15adc=fully charged and above

Voltage Rail Monitor



AB
Devtank LTD

Sheet: /PowerSupply/
File: PowerSupply.sch

Title: Open Smart Monitor

Size: A3	Date: 2021-09-22	**Rev: B**
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2		Id: 2/9



Devtank LTD		
Sheet: /LORA/		
File: LORA.sch		
Title: Open Smart Monitor		
Size: A4	Date: 2021-09-22	**Rev: B**
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2		Id: 3/9



AB		
Devtank LTD		
Sheet: /RS485_Comms/		
File: RS485_Comms.sch		
Title: Open Smart Monitor		
Size: A4	Date: 2021-09-22	**Rev: B**
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2		Id: 4/9



AB	
Devtank LTD	
Sheet: /USB_debug/	
File: USB_debug.sch	
Title: Open Smart Monitor	
Size: A4	Date: 2021-09-22
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2	Id: 5/9
	Rev: B









I=vs-vf/R
3.3-2/1.3k=1mA







Note: For comfirmation of pin functions refer to datasheet. Symbol may not be correct
- wkup pins 2,14,16,25
-pa13, pa15, pb4 avoid as after reset internal pull up and pull down activated

SWD Programming Header



AB
Devtank LTD
Sheet: /STM32L4/
File: STM32L4.sch

Title: Open Smart Monitor

Size: A3	Date: 2021-09-22	**Rev: B**
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2		Id: 6/9



Note: C58 and 75 are filtering caps

AB		
Devtank LTD		
Sheet: /CanTransciever/		
File: CanTransciever.sch		
Title: Open Smart Monitor		
Size: A4	Date: 2021-09-22	**Rev: B**
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2		Id: 7/9

Pulse Inputs



Microphone module



Light Sensor



CT Clamp



bypass capacitor few hundred ohms
https://learn.openenergymonitor.org/electricity-monitoring/ct-sensors/interface-with-arduino

Temp and Humidity



Note: Can use HDC1080/2080. For HTU21D leave pad 3,4 and ep unconnected

Particulate Sensor



AB
Devtank LTD

Sheet: /Sensors_AND_IO/		
File: Sensors_AND_IO.sch		
Title: Open Smart Monitor		
Size: A4	Date: 2021-09-22	**Rev: B**
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2		Id: 8/9

3V3 BI-DIRECTIONAL IO (5V TOLERANT)

Max 3mA per GPIO



AB

Devtank LTD

Sheet: /Sensors_AND_IO/sheet60920843/
File: Digital_IO.sch

Title: Open Smart Monitor

Size: A3	Date: 2021-09-22	**Rev: B**
KiCad E.D.A. kicad 5.1.5+dfsg1-2build2		Id: 9/9