RSP Supply Inc. | https://www.rspsupply.com

Datasheet

ATO® Blade Fuses - Aftermarket

Rated 32V







Specifications

Voltage Rating:	32 V DC
Interrupting Rating:	1000 A @ 32 V DC
Recommended Environmental Temperature:	–40 °C to +125 °C
Terminals Material:	Tin- plated*
Housing Material:	PA66 (UL 94 Flammability rating of V-2)
Net Weight Per Fuse:	1.4 g ± 5 %
Comply With:	SAE J1284 and ISO 8820-3
UL Listed:	File AU1410
CSA Certified:	File No. 29862

*Tin plating's temperature limit is ≈130 °C.

Description

Developed by Littelfuse for the automotive industry, the ATO® fuse has become the original equipment circuit protection standard for foreign and domestic automobiles and trucks. Readily identifiable and easily replaced, this fuse can be specified for a variety of low voltage electronic applications. It is currently found on most cars, trucks, buses and off the road vehicles worldwide. Features Littelfuse designed industry standard color coding to indicate amp rating.

Applications

- Cars
- Trucks
- SUVs
- Offroad vehicles
- Buses
- Watercraft as approved by Littelfuse®

Features & Benefits

- Color coding indicates amperage rating
- See-through housings make it easier to see when fuses blow
- Checkpoints on top make it possible to measure resistance without removing the fuse
- High-contrast ampere stamps on housings aid identification
- Simple to install and remove

Ordering Information

COLOR CODE	CURRENT RATING (A)	BOXED		CARDED		PLUS PACK
		MATERIAL #	CATALOG #	MATERIAL #	CATALOG #	MATERIAL #
Black	1A	0ATO001.V	ATO1	0ATO001.VP	ATO1BP	0ATO001.ZXPRO
Gray	2A	0ATO002.V	ATO2	0ATO002.VP	ATO2BP	0ATO002.ZXPRO
Violet	3A	0ATO003.V	ATO3	0ATO003.VP	ATO3BP	0ATO003.ZXPRO
Pink	4A	0ATO004.V	ATO4	0ATO004.VP	ATO4BP	0ATO004.ZXPRO
Tan	5A	0ATO005.V	ATO5	0ATO005.VP	ATO5BP	0ATO005.ZXPRO
Brown	7.5A	0ATO07.5V	ATO7.5	0ATO07.5VP	ATO7.5BP	0ATO07.5ZXPRO
Red	10A	0ATO010.V	ATO10	0ATO010.VP	ATO10BP	0ATO010.ZXPRO
Blue	15A	0ATO015.V	ATO15	0ATO015.VP	ATO15BP	0ATO015.ZXPRO
Yellow	20A	0ATO020.V	ATO20	0ATO020.VP	ATO20BP	0ATO020.ZXPRO
Clear	25A	0ATO025.V	ATO25	0ATO025.VP	ATO25BP	0ATO025.ZXPRO
Green	30A	0ATO030.V	ATO30	0ATO030.VP	ATO30BP	0ATO030.ZXPRO
Orange	40A	0ATO040.V	ATO40	0ATO040.VP	ATO40BP	---

Please refer to the Littelfuse Aftermarket catalog for packaging information.

©2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 11/15/2022

RSP Supply Inc. | https://www.rspsupply.com

ATO® Blade Fuses - Aftermarket

Rated 32V


Ratings

Part Number	Current Rating (A)	Housing Material Color	Test Cable Size (mm^2)	Typ. Voltage Drop (mV)	Typ.Cold Resistance (mΩ)	Typ. I^2t (A^2s)
0ATO001._	1		0.35	176	123	0.4
0ATO002._	2		0.35	141	53.5	1.4
0ATO003._	3		0.35	137	31.1	7.4
0ATO004._	4		0.35	136	22.8	14
0ATO005._	5		0.5	128	17.85	26
0ATO07.5_	7.5		0.75	116	10.91	60
0ATO010._	10		1	109	7.70	115
0ATO015._	15		1.5	102	4.80	340
0ATO020._	20		2.5	98	3.38	520
0ATO025._	25		2.5	92	2.52	1,000
0ATO030._	30		4	84	1.97	1,500
0ATO035._	35		6	87	1.61	2,300
0ATO040._	40		6	96	1.44	3,300

The typical I^2t is an average value calculated from the breaking capacity tests by using the melting time before the arcing occurs.

Dimensions

Dimensions in mm for reference only.
See outline drawing for dimensions and tolerances.




©2022 Littelfuse, Inc.
Specifications are subject to change without notice.

RSP Supply Inc. | https://www.rspsupply.com

ATO® Blade Fuses - Aftermarket

Rated 32V

Time-Current Characteristic Curves




Time-Current Characteristics

% of Rating	Current Rating (A)	Opening Time Min. / Max. (s)
100	35–40	360,000 / ∞
110	1–30	360,000 / ∞
135	1–2 3–40	0.35 / 600 0.750 / 600
160	1–40	0.250 / 50
200	1–2 3–40	0.1 / 5 0.15 / 5
350	1–2 3–40	0.02 / 0.5 0.08 / 0.5
600	1–30 35–40	0.1 max 0.15 max

Typical Derating of Fuse Melting Element

Temperature security margin is 20 %.
Wire cross-section and fixture test setup refer to ISO 8820-3.
Please contact Littelfuse for details regarding derating test setup.



Derating curves may change depending on the final condition of the application (terminals' characteristics, wire size, etc.). Please ask Littelfuse® for more information.

Temperature Table

	Max. allowed current load (A) at ambient temperature (typical derating)						
	-40 °C	0 °C	20 °C	65 °C	85 °C	110 °C	125 °C
1 A	1	1	1	1	1	1	1
2 A	2	2	2	2	2	1	1
3 A	3	3	3	3	2	2	2
4 A	4	4	4	3	3	3	2
5 A	5	5	5	4	4	3	3
7.5 A	8	7	7	6	5	5	4
10 A	10	10	10	8	7	6	5
15 A	15	15	14	12	11	9	8
20 A	20	19	18	15	14	12	10
25 A	25	25	23	19	18	15	13
30 A	30	29	27	23	21	18	15
35 A	35	35	35	29	27	22	19
40 A	40	39	37	31	28	24	20

©2022 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 11/15/2022

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:
0ATO030.V 0ATO040.V 0ATO010.V 0ATO002.V 0ATO07.5V 0ATO020.V 0ATO004.V 0ATO025.V 0ATO005.V 0ATO003.V 0ATO015.V 0ATO001.V 0ATO030.ZXPROA 0ATO005.VPA 0ATO010.VPA 0ATO001.VPA 0ATO015.TPGLOA 0ATO025.VPGLOA 0ATO025.VPA 0ATO07.5VPA 0ATO015.ZXPROA 0ATO07.5VPGLOA 0ATO020.VPA 0ATO004.VPA 0ATO030.VPGLOA 0ATO020.TPGLOA 0ATO025.ZXPROA 0ATO010.ZXPROA 0ATO040.VPA 0ATO003.VPGLOA 0ATO010.VPGLOA 0ATO020.VPGLOA 0ATO020.ZXPROA 0ATO07.5ZXPROA 0ATO005.ZXPROA 0ATO015.VPA 0ATO002.VPA 0ATO030.VPA 0ATO003.VPA 0ATO015.VPGLOA 0ATO030.TPGLOA 0ATO005.VPGLOA 0ATO010.TPGLOA 0ATO025.TPGLOA 0ATO001.VXPK 0ATO040.VP 0ATO004.VXPK 0ATO010.VP 0ATO015.VXPK 0ATO003.VXPK 0ATO002.VP 0ATO040.VXPK 0ATO030.VXPK 0ATO005.VXPK 0ATO030.VP 0ATO005.VP 0ATO025.VXPK 0ATO015.VP 0ATO07.5VP 0ATO001.VP 0ATO025.VP 0ATO07.5VXPK 0ATO004.VP 0ATO002.VXPK 0ATO003.VP 0ATO010.VXPK 0ATO020.VP 0ATO020.VXPK 0ATO025.ZXPRO 0ATO010.ZXPRO 0ATO030.ZXPRO 0ATO015.ZXPRO 0ATO005.ZXPRO 0ATO07.5ZXPRO 0ATO020.ZXPRO