

PHP 5 Data Types

PHP Data Types

Variables can store data of different types, and different data types can do different things.

PHP supports the following data types:

- String
- Integer
- Float (floating point numbers - also called double)
- Boolean
- Array
- Object
- NULL
- Resource

PHP String

A string is a sequence of characters, like "Hello world!".

A string can be any text inside quotes. You can use single or double quotes:

```
<body>
```

```
<?php
```

```
$x = "Hello world!";
```

```
$y = 'Hello world!';
```

```
echo $x;
```

```
echo "<br>";
```

```
echo $y;
```

```
?>
```

```
</body>
```

PHP Integer

An integer data type is a non-decimal number between -2,147,483,648 and 2,147,483,647.

Rules for integers:

- An integer must have at least one digit
- An integer must not have a decimal point
- An integer can be either positive or negative
- Integers can be specified in three formats: decimal (10-based), hexadecimal (16-based - prefixed with 0x) or octal (8-based - prefixed with 0)

In the following example \$x is an integer. The PHP var_dump() function returns the data type and value:

```
<?php
$x = 5985;
var_dump($x);
?>
```

PHP Float

A float (floating point number) is a number with a decimal point or a number in exponential form.

In the following example \$x is a float. The PHP var_dump() function returns the data type and value:

```
<?php
$x = 10.365;
var_dump($x);
?>
```

PHP Boolean

A Boolean represents two possible states: TRUE or FALSE.

```
$x = true;
$y = false;
```

PHP Array

An array stores multiple values in one single variable.

In the following example \$cars is an array. The PHP var_dump() function returns the data type and value:

```
<?php
$cars = array("Volvo", "BMW", "Toyota");
var_dump($cars);
?>
```

PHP NULL Value

Null is a special data type which can have only one value: NULL.

A variable of data type NULL is a variable that has no value assigned to it.

Tip: If a variable is created without a value, it is automatically assigned a value of NULL.

Variables can also be emptied by setting the value to NULL:

```
<?php
$x = "Hello world!";
$x = null;
var_dump($x);
?>
```

PHP 5 Strings

PHP String Functions

In this chapter we will look at some commonly used functions to manipulate strings.

Get The Length of a String

The PHP strlen() function returns the length of a string.

The example below returns the length of the string "Hello world!":

```
<?php
echo strlen("Hello world!"); // outputs 12
?>
```

Count The Number of Words in a String

The PHP `str_word_count()` function counts the number of words in a string:

```
<?php
echo str_word_count("Hello world!"); // outputs 2
?>
```

Reverse a String

```
<?php
echo strrev("Hello world!"); // outputs !dlrow olleH
?>
```

Search For a Specific Text Within a String

The PHP `strpos()` function searches for a specific text within a string.

If a match is found, the function returns the character position of the first match. If no match is found, it will return `FALSE`.

The example below searches for the text "world" in the string "Hello world!":

```
<?php
echo strpos("Hello world!", "world"); // outputs 6
?>
```

Replace Text Within a String

The PHP `str_replace()` function replaces some characters with some other characters in a string.

The example below replaces the text "world" with "Dolly":

```
<?php
echo str_replace("world", "Dolly", "Hello world!"); // outputs Hello
Dolly!
?>
```

PHP 5 Constants

PHP Constants

A constant is an identifier (name) for a simple value. The value cannot be changed during the script.

A valid constant name starts with a letter or underscore (no \$ sign before the constant name).

Note: Unlike variables, constants are automatically global across the entire script.

```
<?php
define("GREETING", "Welcome to W3Schools.com!");
echo GREETING;
?>
```

Constants are Global

Constants are automatically global and can be used across the entire script.

The example below uses a constant inside a function, even if it is defined outside the function:

```
<?php
define("GREETING", "Welcome to W3Schools.com!");

function myTest() {
    echo GREETING;
}

myTest();
?>
```

PHP 5 Operators

Operators are used to perform operations on variables and values.

PHP divides the operators in the following groups:

- Arithmetic operators
- Assignment operators
- Comparison operators
- Increment/Decrement operators
- Logical operators
- String operators
- Array operators

PHP Arithmetic Operators

The PHP arithmetic operators are used with numeric values to perform common arithmetical operations, such as addition, subtraction, multiplication etc.

Operator	Name	Example	Result
+	Addition	$\$x + \y	Sum of $\$x$ and $\$y$
-	Subtraction	$\$x - \y	Difference of $\$x$ and $\$y$
*	Multiplication	$\$x * \y	Product of $\$x$ and $\$y$
/	Division	$\$x / \y	Quotient of $\$x$ and $\$y$
%	Modulus	$\$x \% \y	Remainder of $\$x$ divided by $\$y$
**	Exponentiation	$\$x ** \y	Result of raising $\$x$ to the $\$y$ 'th power (Introduced in PHP 5.6)

PHP Assignment Operators

The PHP assignment operators are used with numeric values to write a value to a variable.

The basic assignment operator in PHP is "=". It means that the left operand gets set to the value of the assignment expression on the right.

Assignment	Same as...	Description
<code>x = y</code>	<code>x = y</code>	The left operand gets set to the value of the expression on the right
<code>x += y</code>	<code>x = x + y</code>	Addition
<code>x -= y</code>	<code>x = x - y</code>	Subtraction
<code>x *= y</code>	<code>x = x * y</code>	Multiplication
<code>x /= y</code>	<code>x = x / y</code>	Division
<code>x %= y</code>	<code>x = x % y</code>	Modulus

PHP Comparison Operators

The PHP comparison operators are used to compare two values (number or string):

Operator	Name	Example	Result
<code>==</code>	Equal	<code>\$x == \$y</code>	Returns true if \$x is equal to \$y
<code>===</code>	Identical	<code>\$x === \$y</code>	Returns true if \$x is equal to \$y, and they are of the same type
<code>!=</code>	Not equal	<code>\$x != \$y</code>	Returns true if \$x is not equal to \$y
<code><></code>	Not equal	<code>\$x <> \$y</code>	Returns true if \$x is not equal to \$y
<code>!==</code>	Not identical	<code>\$x !== \$y</code>	Returns true if \$x is not equal to \$y, or they are not of the same type
<code>></code>	Greater than	<code>\$x > \$y</code>	Returns true if \$x is greater than \$y
<code><</code>	Less than	<code>\$x < \$y</code>	Returns true if \$x is less than \$y
<code>>=</code>	Greater than or equal to	<code>\$x >= \$y</code>	Returns true if \$x is greater than or equal to \$y
<code><=</code>	Less than or equal to	<code>\$x <= \$y</code>	Returns true if \$x is less than or equal to \$y

PHP Increment / Decrement Operators

The PHP increment operators are used to increment a variable's value.

The PHP decrement operators are used to decrement a variable's value.

Operator	Name	Description
<code>++\$x</code>	Pre-increment	Increments <code>\$x</code> by one, then returns <code>\$x</code>
<code>\$x++</code>	Post-increment	Returns <code>\$x</code> , then increments <code>\$x</code> by one
<code>--\$x</code>	Pre-decrement	Decrements <code>\$x</code> by one, then returns <code>\$x</code>
<code>\$x--</code>	Post-decrement	Returns <code>\$x</code> , then decrements <code>\$x</code> by one

PHP Logical Operators

The PHP logical operators are used to combine conditional statements.

Operator	Name	Example	Result
<code>and</code>	And	<code>\$x and \$y</code>	True if both <code>\$x</code> and <code>\$y</code> are true
<code>or</code>	Or	<code>\$x or \$y</code>	True if either <code>\$x</code> or <code>\$y</code> is true
<code>xor</code>	Xor	<code>\$x xor \$y</code>	True if either <code>\$x</code> or <code>\$y</code> is true, but not both
<code>&&</code>	And	<code>\$x && \$y</code>	True if both <code>\$x</code> and <code>\$y</code> are true
<code> </code>	Or	<code>\$x \$y</code>	True if either <code>\$x</code> or <code>\$y</code> is true
<code>!</code>	Not	<code>!\$x</code>	True if <code>\$x</code> is not true

PHP String Operators

PHP has two operators that are specially designed for strings.

Operator	Name	Example	Result
<code>.</code>	Concatenation	<code>\$txt1 . \$txt2</code>	Concatenation of <code>\$txt1</code> and <code>\$txt2</code>
<code>.=</code>	Concatenation assignment	<code>\$txt1 .= \$txt2</code>	Appends <code>\$txt2</code> to <code>\$txt1</code>

