Index.html

```
<!DOCTYPE html>
<html>

<head>
  <title>Student Marks Tracker</title>
</head>

<body>
  <h1>Student Marks Tracker</h1>
  <h3>Add / Manage Students</h3>
  <input id="name" placeholder="Student Name">
  <input id="roll" placeholder="Roll Number">
  <input id="score" type="number" placeholder="Score 0-100"><br>
  <button onclick="addStudent()">Add Student</button>
  <button onclick="sortHigh()">Sort High to Low</button>
  <button onclick="sortLow()">Sort Low to High</button>
  <button onclick="showFail()">Show Failing Only</button>
  <button onclick="showAll()">Show All</button>
  <button onclick="clearAll()">Clear All</button>
  <p>Total Students: <span id="total">0</span></p>
  <p>Average Score: <span id="avg">0</span></p>
  <p>Pass % (≥60): <span id="pass">0</span>%</p>
  <h2>Student List</h2>
  <table>
    <thead>
      <tr>
```

```
            <th>#</th>
            <th>Roll</th>
            <th>Name</th>
            <th>Score</th>
            <th>Result</th>
            <th>Action</th>
          </tr>
        </thead>
        <tbody id="table"></tbody>
    </table>
    <script src="script.js"></script>
</body>

</html>
```

Script.js

```
let students = []
function addStudent() {
    let name = document.getElementById("name").value.trim()
    let roll = document.getElementById("roll").value.trim()
    let score = Number(document.getElementById("score").value)
    if (name.length < 2) return
    if (roll === "") return
    if (score < 0 || score > 100 || isNaN(score)) return
    let i = students.findIndex(s => s.roll === roll)
    if (i !== -1) return
    students.push({ name, roll, score })
```

```
  render(students)
}
function deleteStudent(roll) {
  let i = students.findIndex(s => s.roll === roll)
  if (i !== -1) students.splice(i, 1)
  render(students)
}
function render(list) {
  let rows = list.map((s, i) => `
<tr>
<td>${i + 1}</td>
<td>${s.roll}</td>
<td>${s.name}</td>
<td>${s.score}</td>
<td>${s.score >= 60 ? "Pass" : "Fail"}</td>
<td><button onclick="deleteStudent('${s.roll}')">Delete</button></td>
</tr>
`).join("")
  document.getElementById("table").innerHTML = rows
  document.getElementById("total").textContent = students.length
  let total = students.reduce((sum, s) => sum + s.score, 0)
  let avg = students.length ? (total / students.length).toFixed(2) : 0
  document.getElementById("avg").textContent = avg
  let passCount = students.filter(s => s.score >= 60).length
  let percent = students.length ? ((passCount / students.length) * 100).toFixed(2) : 0
  document.getElementById("pass").textContent = percent
}
function sortHigh() {
```

```
  students.sort((a, b) => b.score - a.score)
  render(students)
}
function sortLow() {
  students.sort((a, b) => a.score - b.score)
  render(students)
}
function showFail() {
  render(students.filter(s => s.score < 60))
}
function showAll() {
  render(students)
}
function clearAll() {
  students = []
  render(students)
}
```

Output:

Student Marks Tracker

Add / Manage Students

www | 2 | 65

Add Student | Sort High to Low | Sort Low to High | Show Failing Only | Show All | Clear All

Total Students: 2

Average Score: 60.00

Pass % (≥60): 50.00%

Student List

#	Roll	Name	Score	Result	Action
1	1	drs	55	Fail	Delete
2	2	www	65	Pass	Delete

Student Marks Tracker

Add / Manage Students

www | 2 | 65

Add Student | Sort High to Low | Sort Low to High | Show Failing Only | Show All | Clear All

Total Students: 2

Average Score: 60.00

Pass % (≥60): 50.00%

Student List

#	Roll	Name	Score	Result	Action
1	2	www	65	Pass	Delete
2	1	drs	55	Fail	Delete

Student Marks Tracker

Add / Manage Students

www | 2 | 65

Add Student | Sort High to Low | Sort Low to High | Show Failing Only | Show All | Clear All

Total Students: 0

Average Score: 0

Pass % (≥60): 0%

Student List

#	Roll	Name	Score	Result	Action