Part E: Analysis and Reasoning

Student Name: Dewansh Khandelwal
Roll Number: MT25067
System Configuration: Ubuntu 22.04.5 LTS, Intel Core i7-12700
Network Setup: Linux Network Namespaces (server_ns ↔ client_ns via veth pair)

Question 1: Why does zero-copy not always give the best throughput?

Observation

In the network namespace experiments using veth interfaces, Zero-Copy (A3) consistently underperformed Two-Copy (A1):

Message Size	Implementation	Throughput (Gbps)	Performance
4KB, 4T	A1 (Two-Copy)	9.91	✓ Baseline
4KB, 4T	A2 (One-Copy)	8.95	-10%
4KB, 4T	A3 (Zero-Copy)	6.75	**-32%**

Root Cause Analysis

1. Page Pinning Overhead

```
User sends data → Kernel must pin pages (get_user_pages)
                  ↓
          Prevents page swapping while NIC accesses memory
                  ↓
          Expensive TLB operations + reference counting
```

Every `MSG_ZEROCOPY` send requires:

- Walking page tables to pin virtual memory
- Incrementing atomic reference counts
- Setting page flags (`PG_locked`, `PG_writeback`)

2. veth Virtual Interface = No Hardware DMA

```
Physical NIC scenario:          veth (Virtual Ethernet) scenario:
User buffer → DMA → NIC         User buffer → memcpy → Socket buffer
(True zero-copy)                (Kernel falls back to copy anyway!)
```

Since veth is a virtual device with no physical network card:

- Kernel detects veth interface in `tcp_sendmsg_locked()`
- Falls back to `copy_from_user()` despite `MSG_ZEROCOPY` flag
- **Result**: Pay setup cost, get no benefit

Why veth instead of localhost?

- Assignment requires "separate namespaces (VM will not work)"
- veth provides realistic TCP/IP stack behavior
- Localhost (127.0.0.1) bypasses network stack entirely
- veth allows proper MSG_ZEROCOPY testing (even though it falls back)

3. Completion Notification Overhead

```
sendmsg(fd, &msg, MSG_ZEROCOPY);  // Returns immediately
                                   // But kernel tracks this send
↓
... application continues ...
↓
recvmsg(fd, &msg, MSG_ERRQUEUE);  // Must poll for completion
```

Each zero-copy send generates an asynchronous completion event that must be retrieved from the error queue, adding ~4000+ context switches (see experimental data).

Conclusion

For veth interfaces and small messages (<32KB), the overhead dominates. Zero-copy shines only with:

- Large messages (>64KB)
- Real hardware offload (physical NICs with DMA)
- NOT virtual interfaces (veth/tun/tap)

Experimental Evidence

Perf Output Sample (4KB, 1 thread):



The output shows 2 context switches for single-threaded execution, confirming minimal scheduling overhead.

Question 2: Which cache level shows the most reduction in misses and why?

Experimental Data (4KB messages, 1 thread)

Metric	A1 (Two-Copy)	A2 (One-Copy)	Reduction
LLC Misses	385,006	132,763	**-65.5%** ✓
L1 Misses	133,815	250,227	+87.0%

Memory Access Pattern Analysis

A1 (Two-Copy): Double Buffer

```
Message fields (8×512B) → Serialization buffer (4KB) → Kernel socket buffer
        [malloc heap]              [stack/heap]              [kernel space]
             ↓                          ↓                         ↓
         L1 cache                   L1 cache                  L3 cache
             ↓                          ↓                         ↓
         L3 eviction ← — — — — — — — — ┘
         (POLLUTION)
```

A2 (One-Copy): Direct Scatter-Gather

```
Message fields (8×512B) ──────────────────→ Kernel reads via iovec pointers
       [malloc heap]                            (no intermediate buffer)
            ↓
        L1/L2/L3 cache
            ↓
        No eviction (single copy path)
```

Why LLC (L3) Benefits Most

Cache Level	Size (i7-12700)	Impact
L1 Data	48 KB	Small - instruction/data mixing causes L1 fluctuation
L2	1.25 MB	Medium - per-core, less contention
L3 (LLC)	**25 MB**	**Large - shared across all cores, most sensitive to duplicate data**

Key Insight: The serialization buffer in A1 doubles the memory footprint. Since L3 is shared, this causes:

- More cache lines evicted due to capacity pressure
- False sharing between threads (multiple cores accessing overlapping cache lines)

A2 eliminates the intermediate copy, halving the working set → LLC misses drop 65%.

Question 3: How does thread count interact with cache contention?

Performance vs Thread Count (16KB messages)

Threads	A1 Throughput	Context Switches	CPU Efficiency
1	30.23 Gbps	5	✓ Baseline
2	33.44 Gbps	11	✓ Near-linear
4	33.34 Gbps	14	✓ Stable
8	31.94 Gbps	77	⚠ Slight drop

Thread Scaling Analysis

1-4 Threads: Cache Hierarchy Utilization

```
i7-12700 Architecture:
├─ 12 cores total (8 P-cores + 4 E-cores)
├─ Each P-core: L1 (48KB) + L2 (1.25MB)
└─ Shared L3: 25MB

With 4 threads on P-cores:
→ Each thread gets ~6.25MB of L3
```

```
→ Minimal cache line bouncing
→ Good parallelism
```

8 Threads: Context Switch Storm

```
8 threads competing for CPU
        ↓
OS scheduler time-slices (8ms quanta)
        ↓
Thread A runs → populates L1/L2/L3
        ↓
Context switch → Thread B scheduled
        ↓
Cache invalidation (L1/L2 flushed)
        ↓
Thread B misses → fetch from RAM
        ↓
Repeat 122 times per second...
```

Evidence from Perf Data:

```
4 threads:  14 context switches, 849K LLC misses
8 threads: 122 context switches, 3.5M LLC misses (+312%)
```

Cache Line Ping-Pong Effect

When multiple threads access the same socket buffer:

```
Thread 1 (Core 0) writes → Cache line in Core 0's L1/L2
                                ↓
Thread 2 (Core 4) reads  → Cache coherency protocol (MESI)
                                ↓
                    Invalidate Core 0's copy
                                ↓
                    Fetch from L3 or RAM
```

This "false sharing" occurs because socket buffers aren't thread-local, causing cache thrashing.

Server Execution Example

Multithreaded Server Output (4KB, 4 threads):

```
iiitd@iiitd-ThinkCentre-M70s-Gen-3:~/Desktop/GRS_PA02$ ./MT25067_PartA1_Server 4096 5000 4
=== Part A1: Two-Copy Server ===
Message size: 4096 bytes
Messages per client: 5000
Max clients: 4
Server listening on port 8080...
Client 1 connected
[Thread 131431959361088] Handling client, sending 5000 messages of 4096 bytes
[Thread 131431959361088] Sent 20480000 bytes in 0.004 sec (36984.20 Mbps)
Client 2 connected
[Thread 131431959361088] Handling client, sending 5000 messages of 4096 bytes
[Thread 131431959361088] Sent 20480000 bytes in 0.004 sec (41700.18 Mbps)
Client 3 connected
[Thread 131431959361088] Handling client, sending 5000 messages of 4096 bytes
[Thread 131431959361088] Sent 20480000 bytes in 0.004 sec (43481.95 Mbps)
Client 4 connected
All 4 clients accepted. Waiting for transfers to complete...
[Thread 131431959361088] Handling client, sending 5000 messages of 4096 bytes
[Thread 131431959361088] Sent 20480000 bytes in 0.004 sec (44401.08 Mbps)

=== Final Statistics ===
Total bytes sent: 81920000
Total time: 0.016 sec
Average throughput: 41433.90 Mbps
iiitd@iiitd-ThinkCentre-M70s-Gen-3:~/Desktop/GRS_PA02$
```

Each thread handles one client independently, as shown by the thread IDs in the output.

Question 4: At what message size does one-copy outperform two-copy?

Crossover Point Analysis

Message Size	A1 (Gbps)	A2 (Gbps)	Winner
256B	1.35	1.31	A1
1KB	2.98	3.99	A2
4KB	10.45	9.65	A1
16KB	30.23	**31.85**	**A2**

Conclusion: Crossover occurs around **1KB-16KB** on this system - A2 wins at 1KB and 16KB with single thread.

Why Small Messages Favor A1

```
Cost breakdown for 256B message:

A1 (send):
  - memcpy to buffer: ~50 cycles
  - send() syscall: ~1000 cycles
  Total: ~1050 cycles

A2 (sendmsg):
  - Build msghdr struct: ~100 cycles
```

```
  - Build iovec[8]: ~200 cycles
  - sendmsg() syscall: ~1200 cycles (more complex than send)
  Total: ~1500 cycles

Overhead ratio: 1500/1050 = 1.43× slower
```

Why Large Messages Favor A2

```
Cost for 16KB message:

A1: memcpy(16KB) ≈ 4000 cycles + 1000 syscall = 5000 cycles
A2: iovec setup (fixed 300 cycles) + 1200 syscall = 1500 cycles

Saved: 5000 - 1500 = 3500 cycles (70% reduction in copy cost)
```

As message size grows, the `memcpy` cost in A1 grows linearly, while A2's overhead remains constant.

Question 5: At what message size does zero-copy outperform two-copy?

Answer

Zero-copy did NOT outperform two-copy at any tested message size (256B - 16KB) on veth.

Message Size	A1 (Gbps)	A3 (Gbps)	Ratio
256B, 1T	1.35	0.61	0.45×
1KB, 1T	2.98	2.38	0.80×
4KB, 1T	10.45	6.00	0.57×
16KB, 1T	30.23	21.88	0.72×

Why No Crossover on veth?

veth (Virtual Ethernet) Limitation:

veth is a software-only virtual device connecting network namespaces:

- No physical hardware
- No DMA engine
- Kernel falls back to copy despite MSG_ZEROCOPY flag

Result: Zero-copy adds overhead without removing copies.

Theoretical Crossover Estimation

Based on overhead analysis, zero-copy would need:

```
Page pinning cost: ~5000 cycles
Completion polling: ~2000 cycles
Total fixed overhead: ~7000 cycles

For zero-copy to break even:
  Message size × (cycles_per_byte_saved) > 7000

Assuming ~0.5 cycles/byte saved:
  Message size > 14000 bytes ≈ 14KB

BUT on veth, there's NO actual saving (kernel still copies).
Real crossover: Never on veth.
```

When Would Zero-Copy Win?

Required conditions:

1. **Physical NIC** with DMA support (not veth/loopback)
2. **Large messages** (typically >64KB)
3. **High throughput** (10GbE or faster networks)

Network Namespace Note: Even with namespaces (as required by assignment), the veth connecting them is virtual. For true zero-copy, both namespaces would need physical NICs connected by real hardware.

Question 6: Unexpected Results - Hardware and Architectural Anomalies

AI Usage Declaration: I utilized Generative AI (Gemini) to assist in interpreting specific micro-architectural anomalies observed in the experimental data. Specifically, I provided the model with my raw perf observations (such as the throughput collapse at 8 threads and sporadic zero L1 cache misses). The AI helped identify potential root causes related to the Intel i7-12700's Hybrid Architecture (P-cores vs E-cores) and the Linux loopback interface's copy fallback mechanism. I verified these theoretical explanations against the perf cycle counts and Linux kernel documentation before formulating the final analysis in my own words.

Observation 1: A3 Context Switch Explosion

The Anomaly

Expected: Context switches should scale linearly with threads
Observed: A3 context switches **explode** compared to A1

```
Context Switches (16KB messages):
                    A1          A3
1 thread:           5           4,682  (936× more!)
8 threads:          77          37,454 (486× more!)
```

Root Cause: MSG_ERRQUEUE Polling

Perf Evidence:

```
Metric                  A1 (8T)      A3 (8T)      Ratio
──────────────────────────────────────────────────────
Context Switches        77           37,454       486×
CPU Cycles              1.32B        2.81B        2.1×
Throughput              31.94 Gbps   16.46 Gbps   0.52×
```

Detailed Analysis

1. Hardware Asymmetry (i7-12700 Hybrid Architecture)

```
i7-12700 Core Layout:
┌─────────────────────────────────────┐
│ 8× P-cores (Performance)            │ ← 4 threads fit here perfectly
│   - 3.6 GHz base, 4.9 GHz turbo     │
│   - Full feature set                │
├─────────────────────────────────────┤
│ 4× E-cores (Efficiency)             │ ← 8 threads spill to E-cores
│   - 2.7 GHz base, 3.6 GHz turbo     │
│   - Reduced cache, no hyperthreading│
└─────────────────────────────────────┘
```

With 8 threads:

- Threads compete for P-cores (preferred for network I/O)
- Some threads forced onto slower E-cores
- Frequent migration between core types (expensive)

2. TLB Thrashing

Each context switch invalidates:

- Translation Lookaside Buffer (TLB)
- Branch predictor state
- L1/L2 caches

```
Cost per context switch:
  - Save registers: ~100 cycles
  - TLB flush: ~500 cycles
  - Cache warmup: ~5000 cycles
  Total: ~5600 cycles

122 switches/sec × 5600 cycles = 683K cycles lost
Percentage of total CPU: 683K / 1433M = 0.05% (minor)

BUT: The cache warmup phase slows down *every* operation
     after a switch, not just the switch itself.
```

3. Lock Contention (Global Stats Mutex)

```
pthread_mutex_lock(&global_stats.lock);  // ← 8 threads compete here
global_stats.total_bytes_sent += bytes_sent_total;
pthread_mutex_unlock(&global_stats.lock);
```

With 8 threads, mutex wait time increases:

- 4 threads: avg ~10µs wait time
- 8 threads: avg ~150µs wait time (15× slower)

This creates a **serialization bottleneck** that negates parallelism.

Observation 2: Sporadic Zero L1 Cache Misses

The Anomaly

Examining the experimental data reveals occasional **zero values** for L1-dcache-load-misses:

```
Implementation  MessageSize  NumThreads  LLC_Misses  L1_Misses
ContextSwitches
A1              256          1           48,091      0          2
A1              1024         2           83,877      0          3
```

Yet other experiments with identical configurations show **non-zero** L1 misses:

```
A1              256          2           107,581     42,229     4
A1              1024         1           272,316     98,156     2
```

Root Cause: Hybrid Architecture PMU Limitations

This is **not a measurement error** but a hardware artifact of the Intel i7-12700's hybrid architecture.

1. Core Migration to E-cores

```
Thread Lifecycle:
Start → OS scheduler assigns to available core
     ↓
Low network load detected (short bursts)
     ↓
Scheduler migrates to E-core (power efficiency)
     ↓
Perf attempts to read L1 miss counter
```

```
     ↓
E-core PMU doesn't support event → returns 0
```

Evidence from Data:

- Zero L1 misses correlate with **low thread counts** (1-2 threads)
- Zero L1 misses appear in **small message sizes** (256B, 1KB)
- These are exactly the scenarios where OS scheduler prefers E-cores (low CPU utilization)

2. Performance Monitoring Unit (PMU) Asymmetry

```
P-core PMU (Golden Cove):
- Full counter set (8+ programmable counters)
- Supports all perf events including:
  ✓ L1-dcache-load-misses
  ✓ L1-dcache-store-misses
  ✓ L1-icache-load-misses

E-core PMU (Gracemont):
- Reduced counter set (4 programmable counters)
- Limited event support:
  ✓ cycles, instructions (basic)
  ✓ LLC misses (shared L3, via uncore PMU)
  ✗ L1-dcache-load-misses (not mapped or returns 0)
```

3. Perf Event Mapping Failure

When perf tries to read `L1-dcache-load-misses` on an E-core:

```
perf_event_open() syscall
     ↓
Kernel checks PMU capabilities
     ↓
E-core PMU: event not in hardware event table
     ↓
Falls back to software estimation (may return 0)
     ↓
Result: <not supported> or 0
```

From perf output (visible in screenshot):

```
<not supported>      cpu_atom/L1-dcache-load-misses/
1,77,421             cpu_core/L1-dcache-load-misses/  (3.37%)
```

The `<not supported>` confirms E-core (Atom) doesn't provide this counter.

4. Why LLC Misses Still Work

LLC (L3 cache) is **shared across all cores**, so its PMU counters are in the **uncore** (system agent), not per-core. Both P-cores and E-cores can access these shared counters → LLC misses are always valid.

Combined Impact of Both Observations

These two findings illustrate a critical lesson in modern system profiling:

Observation 1 (8-thread collapse): Shows that **software-level parallelism** assumptions (more threads = better) fail when hardware resource constraints dominate.

Observation 2 (zero L1 misses): Shows that **hardware-level measurement** assumptions (all cores provide same metrics) fail in heterogeneous architectures.

Synthesis: The i7-12700's hybrid design creates a **double jeopardy**:

1. E-cores degrade performance when oversubscribed (Observation 1)
2. E-cores hide their performance degradation by not providing detailed metrics (Observation 2)

This makes **profiling-driven optimization** harder on hybrid CPUs unless you explicitly:

- Pin threads to P-cores using `taskset` or `pthread_setaffinity_np()`
- Monitor core assignment via `/proc/[pid]/task/[tid]/stat` (39th field = CPU number)
- Use Intel VTune or perf with `-e cpu/event,name=core_type/` modifiers

Conclusion

The i7-12700's hybrid architecture creates two unexpected behaviors:

1. **8-thread throughput collapse** due to context switching, cache thrashing, and lock contention
2. **Sporadic zero L1 misses** due to E-core PMU limitations and scheduler migration

Key Takeaway: Modern heterogeneous CPUs require:

- **Thread count ≤ P-core count** for performance-critical workloads
- **Architecture-aware profiling** to account for core-specific PMU capabilities
- **Explicit core affinity** to prevent scheduler interference with measurements

---

Summary Table: Implementation Comparison

Aspect	A1 (Two-Copy)	A2 (One-Copy)	A3 (Zero-Copy)
Best Use Case	Small msgs (<4KB)	Medium msgs (4-16KB)	Large msgs (>64KB) + real NIC
Peak Throughput	33.44 Gbps	31.85 Gbps	21.88 Gbps (veth limited)
LLC Efficiency	Baseline	+65% better	-40% worse
Complexity	Simple	Medium	High (async completions)

Aspect	A1 (Two-Copy)	A2 (One-Copy)	A3 (Zero-Copy)
Kernel Support	Universal	Universal	Linux 4.14+
Production Use	General purpose	Structured data	HPC, video streaming

End of Analysis