

```

medicalcoder::comorbidities(
  ### Required inputs:
  data      = ,      # object inheriting data.frame; one ICD code per row
  icd.codes = ,      # character; name of column in data containing ICD codes
  method    = ,      # <family>_<variant>, e.g., "charlson_quan2005"

  ### Optional inputs controlling grouping and code attributes:
  id.vars   = NULL,  # character; encounter identifiers (see text below)

  icdv.var  = NULL,  # character; column name for ICD version (9 or 10)
  icdv      = NULL,  # integer; constant ICD version for all rows

  dx.var     = NULL,  # character; column name indicating
                      #   diagnosis (1) or procedure (0)
  dx         = NULL,  # integer; constant dx indicator for all rows

  poa.var    = NULL,  # character; column name for present-on-admission indicator
  poa        = NULL,  # integer; constant POA indicator for all rows

  age.var    = NULL,  # character; column name for age in years (Charlson only)

  primarydx.var = NULL, # character; column name indicating primary diagnosis
  primarydx     = NULL, # integer; constant primary dx indicator

  ### Defaults:
  flag.method   = "current", # "current" (encounter-level) or
                             # "cumulative" (longitudinal)
  full.codes    = TRUE,     # reference data[[icd.codes]] against
                             #   full ICD codes, e.g., C4A.111
  compact.codes = TRUE,     # reference data[[icd.codes]] against
                             #   compact ICD codes, e.g., C4A111
  subconditions = FALSE    # PCCC only: return subcondition flags when available
)

```