1.7 Описание запросов API

Таблица 1.7.1 — Описание Запросов API

Метод	Curl (входные данные)	URL (Строка запроса)	Response body (возвращаемый результат)	Код результата
1	2	3	4	5
POST	curl -X POST http://localhost:5012/api/auth/login -H "Content-Type: application/json" -d '{"email":"example@mail.ru","password":"1234"}'	/api/auth/login	{"token":"eyJhbGciOi...","userNoHash":{"id":1,"email":"example@mail.ru","role":"Student","first_name":"example","surname":"example","patronymic":"example","created_at":"...","updated_at":"..."}}	200; 400; 500;
GET	curl http://localhost:5012/api/auth/get-me -H "Authorization: Bearer $T"	/api/auth/get-me	{"id":1,"email":"...","role":"Student","first_name":"...","surname":"...","patronymic":"...","student":{"id":5,"user_id":1,"class_id":2,"birthday":"2012-05-20"}}	200; 400; 500;
POST	curl -X POST http://localhost:5012/api/admin/create-student -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"email":"example@m.ru","password":"1234","first_name":"ex","surname":"ex","patronymic":"ex","class_id":1,"birthday":"2012-05-20"}'	/api/admin/create-student	{"id":5,"user_id":12,"class_id":1,"birthday":"2012-05-20"}	200; 400; 500;

Продолжение таблицы 1.7.1

1	2	3	4	5
PUT	curl -X PUT http://localhost:5012/api/admin/update-student/5 -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"class_id":3,"password":"example"}'	/api/admin/update-student/:id	{"id":5,"user_id":12,"class_id":3,"birthday":"2012-05-20"}	200; 400; 500;
POST	curl -X POST http://localhost:5012/api/admin/create-teacher -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"email":"example@mail.ru","password":"1234", "first_name":"example", "surname":"example","subject_id":2}'	/api/admin/create-teacher	{"id":3,"user_id":15,"subject_id":2}	200; 400; 500;

Продолжение таблицы 1.7.1

1	2	3	4	5
PUT	curl -X PUT http://localhost:5012/api/admin/update-teacher/3 -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"subject_id":4}'	/api/admin/update-teacher/:id	{"id":3,"user_id":15,"subject_id":4}	200; 400; 500;
POST	curl -X POST http://localhost:5012/api/admin/create-admin -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"email":"admin2@mail.ru","password":"1234","first_name":"example","surname":"example"}'	/api/admin/create-admin	{"id":7,"email":"admin2@mail.ru","password_hash":"$2a$10$...","role":"Admin","first_name":"example","surname":"example","patronymic":null,...}	200; 400; 500;

Продолжение таблицы 1.7.1

1	2	3	4	5
PUT	curl -X PUT http://localhost:5012/api/admin/update-admin/7 -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d'{"first_name":"example"}'	/api/admin/update-admin/:id	{"id":7,"email":"example@mail.ru","role":"Admin","first_name":"example",...}	200; 400; 500;
DELETE	curl -X DELETE http://localhost:5012/api/admin/delete-admin/7 -H "Authorization: Bearer $T"	/api/admin/delete-admin/:id	{"message":"Админ удалён"}	200; 400; 500;
GET	curl http://localhost:5012/api/admin/list-users -H "Authorization: Bearer $T"	/api/admin/list-users	[{"id":1,"email":"...","first_name":"...","surname":"...","patronymic":"..."}, ...]	200; 400; 500;
POST	curl -X POST http://localhost:5012/api/admin/create-schedule -H "Authorization: Bearer$T" -H "Content-Type: application/json" -d '{"date":"2026-1015","lesson_number":1,"subject_id":2,"teacher_id":3,"class_id":1,"classroom_id":4}'	/api/admin/create-schedule	{"id":10,"date":"2026-10-15","lesson_number":1,"subject_id":2,"teacher_id":3,"class_id":1,"classroom_id":4}	200; 400; 500;

Продолжение таблицы 1.7.1

1	2	3	4	5
PUT	curl -X PUT http://localhost:5012/api/admin/update-schedule/10 -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"date":"2026-10-16","lesson_number":2,"subject_id":2,"teacher_id":3,"class_id":1,"classroom_id":4}'	/api/admin/update-schedule/:id	{"id":10,"date":"2026-10-16","lesson_number":2,...}	200; 400; 500;
DELETE	curl -X DELETE http://localhost:5012/api/admin/delete-schedule/10 -H "Authorization: Bearer $T"	/api/admin/delete-schedule/:id	{"message":"Удалено"}	200; 400; 500;

Продолжение таблицы 1.7.1

1	2	3	4	5
POST	curl -X POST http://localhost:5012/api/admin/create-class -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"name":"A","year":5}'	/api/admin/create-class	{"id":7,"name":"A","year":5}	200; 400; 500;
PUT	curl -X PUT http://localhost:5012/api/admin/update-class/7 -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"name":"A","year":5}'	/api/admin/update-class/:id	{"id":7,"name":"A","year":5}	200; 400; 500;
DELETE	curl -X DELETE http://localhost:5012/api/admin/delete-class/7 -H "Authorization: Bearer $T"	/api/admin/delete-class/:id	{"message":"Удалено"}	200; 400; 500;

Продолжение таблицы 1.7.1

1	2	3	4	5
PUT	curl -X PUT http://localhost:5012/api/admin/set-current-day -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"date":"2026-10-20"}'	/api/admin/set-current-day	{"message":"Изменено"}	200; 400; 500;
POST	curl -X POST http://localhost:5012/api/admin/create-subject -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"name":"example","educ_level":3}'	/api/admin/create-subject	{"id":4,"name":"example","educ_level":3}	200; 400; 500;

Продолжение таблицы 1.7.1

1	2	3	4	5
PUT	curl -X PUT http://localhost:5012/api/admin/update-subject/4 -H "Authorization: Bearer $T" -H "Content-Type: application/json" -d '{"name":"example","educ_level":3}'	/api/admin/update-subject/:id	{"id":4,"name":"example","educ_level":3}	200; 400; 500;
DELETE	curl -X DELETE http://localhost:5012/api/admin/delete-subject/4 -H "Authorization: Bearer $T"	/api/admin/delete-subject/:id	{"message":"Удалено"}	200; 400; 500;
GET	curl http://localhost:5012/api/grades/get-grades -H "Authorization: Bearer $T"	/api/grades/get-grades	[{"id":1,"schedule_id":10,"student_id":5,"value":5,"comment":"example","created_at":"...","schedule":{...},"student":{"id":5,"user_id":12,"class_id":1,"birthday":"..."}}, ...]	200; 400; 500;