



Hierarchical Modeling

CS 432 Interactive Computer Graphics
Prof. David E. Breen
Department of Computer Science

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1



Objectives

- Examine the limitations of linear modeling
 - Symbols and instances
- Introduce hierarchical models
 - Articulated models
 - Robots
- Introduce Tree and DAG models


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2



Instance Transformation

- Start with a prototype object (a *symbol*)
- Each appearance of the object in the model is an *instance*
 - Must scale, orient, position
 - Defines instance transformation



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3



Symbol-Instance Table

Can store a model by assigning a number to each symbol and storing the parameters for the instance transformation

Symbol	Scale	Rotate	Translate
1	s_x, s_y, s_z	$\theta_x, \theta_y, \theta_z$	d_x, d_y, d_z
2			
3			
1			
1			
.			
.			


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4



Relationships in Car Model

- Symbol-instance table does not show relationships between parts of model
- Consider model of car
 - Chassis + 4 identical wheels
 - Two symbols



- Rate of forward motion determined by rotational speed of wheels

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

5




Structure Through Function Calls

```
car(speed)
{
    chassis()
    wheel(right_front);
    wheel(left_front);
    wheel(right_rear);
    wheel(left_rear);
}
```

- Fails to show relationships well
- Look at problem using a graph


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

6




Graphs

- Set of *nodes* and *edges (links)*
- Edge connects a pair of nodes
 - Directed or undirected
- *Cycle*: directed path that is a loop




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012
7




Tree


- Graph in which each node (except the root) has exactly one parent node
 - May have multiple children
 - Leaf or terminal node: no children




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012
8



Tree Model of Car




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012
9




DAG Model

- If we use the fact that all the wheels are identical, we get a *directed acyclic graph*
 - Not much different than dealing with a tree




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012
10



Modeling with Trees


- Must decide what information to place in nodes and what to put in edges
- Nodes
 - What to draw
 - Pointers to children
- Edges
 - May have information on incremental changes to transformation matrices (can also store in nodes)


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012
11



Transformations to Change Coordinate Systems

- Issue: the world has many different relative frames of reference
- How do we transform among them?
- Example: CAD Assemblies & Animation Models






Transformations to Change Coordinate Systems

- 4 coordinate systems
- 1 point P

$$M_{1 \leftarrow 2} = T(4, 2)$$

$$M_{2 \leftarrow 3} = T(2, 3) \cdot S(0.5, 0.5)$$


$$M_{3 \leftarrow 4} = T(6.7, 1.8) \cdot R(45^\circ)$$



$$M_{i \leftarrow k} = M_{i \leftarrow j} \cdot M_{j \leftarrow k}$$

13

1994 Foley/VanDam/FourHugues/Phillips ICG




Coordinate System Example (1)

- Translate the House to the origin

$$M_{1 \leftarrow 2} = T(x_1, y_1)$$


$$M_{2 \leftarrow 1} = (M_{1 \leftarrow 2})^{-1} = T(-x_1, -y_1)$$



The matrix M_{ij} that maps points from coordinate system j to i is the inverse of the matrix M_{ji} that maps points from coordinate system j to coordinate system i .

14


1994 Foley/VanDam/FourHugues/Phillips ICG



Coordinate System Example (2)


- Transformation Composition:

$$M_{5 \leftarrow 1} = M_{5 \leftarrow 4} \cdot M_{4 \leftarrow 3} \cdot M_{3 \leftarrow 2} \cdot M_{2 \leftarrow 1}$$



15

1994 Foley/VanDam/FourHugues/Phillips ICG




World Coordinates and Local Coordinates

- To move the tricycle, we need to know how all of its parts relate to the WCS
- Example: front wheel rotates on the ground wrt the front wheel's z axis:

$$P^{(wo)} = T(ax, 0, 0) \cdot R_z(\alpha) \cdot P^{(wh)}$$


Coordinates of P in wheel coordinate system:

$$P^{(wh)} = R_z(\alpha) \cdot P^{(wh)}$$




16

1994 Foley/VanDam/FourHugues/Phillips ICG



Robot Arm




robot arm

parts in their own coordinate systems


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

17




Articulated Models

- Robot arm is an example of an *articulated model*
- Parts connected at joints
- Can specify state of model by giving all joint angles




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

18




Relationships in Robot Arm

- Base rotates independently
 - Single angle determines position
- Lower arm attached to base
 - Its position depends on rotation of base
 - Must also translate relative to base and rotate about connecting joint
- Upper arm attached to lower arm
 - Its position depends on both base and lower arm
 - Must translate relative to lower arm and rotate about joint connecting to lower arm




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
9




Required Matrices

- Rotation of base: R_b
 - Apply $M = R_b$ to base
- Translate lower arm relative to base: T_{lu}
- Rotate lower arm around joint: R_{lu}
 - Apply $M = R_b T_{lu} R_{lu}$ to lower arm
- Translate upper arm relative to upper arm: T_{uu}
- Rotate upper arm around joint: R_{uu}
 - Apply $M = R_b T_{lu} R_{lu} T_{uu} R_{uu}$ to upper arm



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
0




OpenGL Code for Robot

```


mat4 ctm; // current transformation matrix
robot_arm()
{
    ctm = RotateY(theta);
    base();
    ctm *= Translate(0.0, h1, 0.0);
    ctm *= RotateZ(phi);
    lower_arm();
    ctm *= Translate(0.0, h2, 0.0);
    ctm *= RotateZ(psi);
    upper_arm();
}

```



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
1




OpenGL Code for Robot

- At each level of hierarchy, calculate **ctm** matrix in application.
- Send matrix to shaders
- Draw geometry for one level of hierarchy
- Apply **ctm** matrix in shader


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
2




Tree Model of Robot

- Note code shows relationships between parts of model
 - Can change “look” of parts easily without altering relationships
- Simple example of tree model
- Want a general node structure for nodes




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
3



Possible Node Structure



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
4



Generalizations

- Need to deal with multiple children
 - How do we represent a more general tree?
 - How do we traverse such a data structure?
- Animation
 - How to use dynamically?
 - Can we create and delete nodes during execution?

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
5



Objectives


- Build a tree-structured model of a humanoid figure
- Examine various traversal strategies
- Build a generalized tree-model structure that is independent of the particular model

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
6



Humanoid Figure



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
7



Building the Model


- Can build a simple implementation using quadrics: ellipsoids and cylinders
- Access parts through functions
 - torso()
 - left_upper_arm()
- Matrices describe position of node with respect to its parent
 - M_{lla} positions left lower arm with respect to left upper arm

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
8



Tree with Matrices



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
9



Display and Traversal

- The position of the figure is determined by 11 joint angles (two for the head and one for each other part)
- Display of the tree requires a *graph traversal*
 - Visit each node once
 - Display function at each node that describes the part associated with the node, applying the correct transformation matrix for position and orientation

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
0



Transformation Matrices

- There are 10 relevant matrices
 - M positions and orients entire figure through the torso which is the root node
 - M_h positions head with respect to torso
 - M_{lua} , M_{rua} , M_{lul} , M_{rul} position arms and legs with respect to torso
 - M_{lla} , M_{rla} , M_{lll} , M_{rll} position lower parts of limbs with respect to corresponding upper limbs

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
1



Stack-based Traversal

- Set model-view matrix to M and draw torso
- Set model-view matrix to MM_h and draw head
- For left-upper arm need MM_{lua} and so on
- Rather than recomputing MM_{lua} from scratch or using an inverse matrix, we can use the matrix stack to store M and other matrices as we traverse the tree

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
2



Traversal Code

```
figure() {
  PushMatrix()  ← save present current's xform matrix
  torso();      ← update ctm for head
  Rotate(...);
  head();
  PopMatrix();  ← recover original ctm
  PushMatrix(); ← save it again
  Translate(...);
  Rotate(...);  ← update ctm for left upper arm
  left_upper_arm();
  PopMatrix();  ← recover and save original ctm again
  PushMatrix(); ← rest of code
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
3



Analysis

- The code describes a particular tree and a particular traversal strategy
 - Can we develop a more general approach?
- Note that the sample code does not include state changes, such as changes to colors
 - May also want to use a `PushAttrib` and `PopAttrib` to protect against unexpected state changes affecting later parts of the code

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
4



General Tree Data Structure


- Need a data structure to represent tree and an algorithm to traverse the tree
- We will use a *left-child right sibling* structure
 - Uses linked lists
 - Each node in data structure is two pointers
 - Left: linked list of children
 - Right: next node (i.e. siblings)

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
5



Left-Child Right-Sibling Tree



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
7



Tree node Structure

- At each node we need to store
 - Pointer to sibling
 - Pointer to child
 - Pointer to a function that draws the object represented by the node
 - Homogeneous coordinate matrix to multiply on the right of the current model-view matrix
 - Represents changes going from parent to node
 - In OpenGL this matrix is a 1D array storing matrix by columns

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
8



C Definition of treeNode

```
typedef struct treeNode
{
    mat4 m;
    void (*f)();
    struct treeNode *sibling;
    struct treeNode *child;
} treeNode;
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
9



torso and head nodes

```
treenode torso_node, head_node, lua_node, ... ;
```

```
torso_node.m = RotateY(theta[0]);
torso_node.f = torso;
torso_node.sibling = NULL;
torso_node.child = &head_node;
```

```
head_node.m = translate(0.0, TORSO_HEIGHT
+0.5*HEAD_HEIGHT, 0.0)*RotateX(theta[1])
*RotateY(theta[2]);
head_node.f = head;
head_node.sibling = &lua_node;
head_node.child = NULL;
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4
0



Notes

- The position of figure is determined by 11 joint angles stored in `theta[11]`
- Animate by changing the angles and redisplaying
- We form the required matrices using `Rotate` and `Translate`
 - Because the matrix is formed using the model-view matrix, we may want to first push original model-view matrix on matrix stack

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4
1



Preorder Traversal

```
void traverse(treenode* root)
{
    if(root==NULL) return;
    mvstack.push(ctm);
    ctm = ctm*root->m;
    root->f();
    if(root->child!=NULL) traverse(root->child);
    ctm = mvstack.pop();
    if(root->sibling!=NULL)
        traverse(root->sibling);
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012


4
2



Traversal Code & Matrices

• <code>figure()</code> called with CTM set	<u>Stack</u>	<u>CTM</u>
• M_{fig} defines figure's place in world	M_{fig}	M_{fig}
<code>figure()</code> {	<u>Stack</u>	<u>CTM</u>
<code>PushMatrix()</code>	M_{fig}	M_{fig}
<code>torso()</code> ;	<u>Stack</u>	<u>CTM</u>
<code>Rotate(...)</code> ;	M_{fig}	$M_{fig}M_h$
<code>head()</code> ;	<u>Stack</u>	<u>CTM</u>
<code>PopMatrix()</code> ;	M_{fig}	M_{fig}
<code>PushMatrix()</code> ;	<u>Stack</u>	<u>CTM</u>
<code>Translate(...)</code> ;	M_{fig}	M_{fig}
<code>Rotate(...)</code> ;	<u>Stack</u>	<u>CTM</u>
<code>left_upper_arm()</code> ;	M_{fig}	$M_{fig}M_{lua}$


4
3



Traversal Code & Matrices

<code>PushMatrix()</code>	<u>Stack</u>	<u>CTM</u>
<code>Translate(...);</code>	$M_{fig} \cdot M_{lua}$	$M_{fig} \cdot M_{lua}$
<code>Rotate(...);</code>	M_{fig}	
<code>left_lower_arm();</code>	<u>Stack</u>	<u>CTM</u>
<code>PopMatrix();</code>	$M_{fig} \cdot M_{lua}$	$M_{fig} \cdot M_{lua} \cdot M_{lla}$
<code>PopMatrix();</code>	M_{fig}	
<code>PushMatrix();</code>	<u>Stack</u>	<u>CTM</u>
<code>Translate(...);</code>	M_{fig}	$M_{fig} \cdot M_{lua}$
<code>Rotate(...);</code>	<u>Stack</u>	<u>CTM</u>
<code>right_upper_arm();</code>	M_{fig}	M_{fig}
<code>...</code>	<u>Stack</u>	<u>CTM</u>
<code>...</code>	M_{fig}	$M_{fig} \cdot M_{lua}$


4
4



Notes

- We must save current transformation matrix before multiplying it by node matrix
 - Updated matrix applies to children of node but not to siblings which contain their own matrices
- The traversal program applies to any left-child right-sibling tree
 - The particular tree is encoded in the definition of the individual nodes
- The order of traversal matters because of possible state changes in the functions

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012
 5



Dynamic Trees


- If we use pointers, the structure can be dynamic

```

typedef treeNode *tree_ptr;
tree_ptr torso_ptr;
torso_ptr = malloc(sizeof(treeNode));
  
```

- Definition of nodes and traversal are essentially the same as before but we can add and delete nodes during execution


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012
 6



Solids and Solid Modeling


- Solid modeling introduces a mathematical theory of solid shape
 - Domain of objects
 - Set of operations on the domain of objects
 - Representation that is
 - Unambiguous
 - Accurate
 - Unique
 - Compact
 - Efficient

47




Solid Objects and Operations

- Solids are point sets
 - Boundary and interior
- Point sets can be operated on with boolean algebra (union, intersect, etc)




48
Foley/Stein/Clark, 1990/1994



Constructive Solid Geometry (CSG)

- A tree structure combining primitives via regularized boolean operations
- Primitives can be solids or *half spaces*




49



A Sequence of Boolean Operations

- Boolean operations
- Rigid transformations




50

PixMath courtesy of Dave Mount @ UMD-CP



The Induced CSG Tree




51

PixMath courtesy of Dave Mount @ UMD-CP



The Induced CSG Tree

- Can also be represented as a directed acyclic graph (DAG)



52

PixMath courtesy of Dave Mount @ UMD-CP



Issues with Constructive Solid Geometry


- Non-uniqueness
- Choice of primitives
- How to handle more complex modeling?
 - Sculpted surfaces? Deformable objects?

53



Issues with Constructive Solid Geometry

- Non-Uniqueness
 - There is more than one way to model the same artifact
 - Hard to tell if A and B are identical




54



Issues with CSG

- Minor changes in primitive objects greatly affect outcomes
- Shift up top solid face




55

PixMath courtesy of Dave Mount @ UMD-CP



Uses of Constructive Solid Geometry

- Found (basically) in every CAD system
- Elegant, conceptually and algorithmically appealing
- Good for
 - Rendering, ray tracing, simulation
 - BRL CAD



56