



Programming with OpenGL Part 5: More GLSL

CS 432 Interactive Computer Graphics
Prof. David E. Breen
Department of Computer Science

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1



Objectives

- Coupling shaders to applications
 - Reading
 - Compiling
 - Linking
- Vertex Attributes
- Setting up uniform variables
- Example applications

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2



Linking Shaders with Application

- Read shaders
- Compile shaders
- Create a program object
- Link everything together
- Link variables in application with variables in shaders
 - Vertex attributes
 - Uniform variables

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3



Program Object

- Container for shaders
 - Can contain multiple shaders
 - Other GLSL functions

```
GLuint myProgObj;  
myProgObj = glCreateProgram();  
/* define shader objects here */  
glUseProgram(myProgObj);  
glLinkProgram(myProgObj);
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4



Reading a Shader

- Shaders are added to the program object and compiled
- Usual method of passing a shader is as a null-terminated string using the function **glShaderSource**
- If the shader is in a file, we can write a reader to convert the file to a string

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

5



Shader Reader

```
#include <stdio.h>  
  
static char*  
readShaderSource(const char* shaderFile)  
{  
    FILE* fp = fopen(shaderFile, "r");  
  
    if ( fp == NULL ) { return NULL; }  
  
    fseek(fp, 0L, SEEK_END);  
    long size = ftell(fp);
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

6



Shader Reader (cont)

```
fseek(fp, 0L, SEEK_SET);
char* buf = new char[size + 1];
fread(buf, 1, size, fp);

buf[size] = '\0';
fclose(fp);

return buf;
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

7



Adding a Vertex Shader

```
GLuint vShader;
GLchar vShaderfile[] = "my_vertex_shader";
GLchar* vSource =
    readShaderSource(vShaderfile);
vShader = glCreateShader(GL_VERTEX_SHADER);
glShaderSource(vShader, 1, &vSource, NULL);
glCompileShader(vShader);
glAttachShader(myProgObj, vShader);
```

Go to InitShader.cpp

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

8



Vertex Attributes

- Vertex attributes are named in the shaders
- Linker forms a table
- Application can get index from table and tie it to an application variable
- Similar process for uniform variables

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

9



Vertex Attribute Example

```
#define BUFFER_OFFSET( offset )
((GLvoid*) (offset))

GLuint loc =
    glGetAttribLocation( program, "vPosition" );
glEnableVertexAttribArray( loc );
glVertexAttribPointer( loc, 2, GL_FLOAT,
    GL_FALSE, 0, BUFFER_OFFSET(0) );
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

10



Uniform Variable Example

```
GLuint angleParam;
angleParam = glGetUniformLocation(myProgObj,
    "angle");
/* angle defined in shader */

/* my_angle set in application */
GLfloat my_angle;
my_angle = 5.0 /* or some other value */

glUniform1f(angleParam, my_angle);
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

11



Double Buffering

- Updating the value of a uniform variable opens the door to animating an application
 - Execute glUniform in display callback
 - Force a redraw through glutPostRedisplay()
- Need to prevent a partially redrawn frame buffer from being displayed
- Draw into back buffer
- Display front buffer
- Swap buffers after updating finished

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

12



Adding Double Buffering

- Request a double buffer
 - `glutInitDisplayMode(GLUT_DOUBLE)`
- Swap buffers

```
void mydisplay()
{
    glClear(...);
    glDrawArrays();
    glutSwapBuffers();
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
3



Idle Callback

- Idle callback specifies function to be executed when no other actions pending
 - `glutIdleFunc(myIdle)`;

```
void myIdle()
{
    // recompute display
    glutPostRedisplay();
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
4



Attribute and Varying Qualifiers

- Starting with GLSL 1.5 attribute and varying qualifiers have been replaced by in and out qualifiers
- No changes needed in application
- Vertex shader example:

<code>#version 1.4</code>	<code>#version 1.5</code>
<code>attribute vec3 vPosition;</code>	<code>in vec3 vPosition;</code>
<code>varying vec3 color;</code>	<code>out vec3 color;</code>

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
5



Adding Color

- If we set a color in the application, we can send it to the shaders as a vertex attribute or as a uniform variable depending on how often it changes
- Let's associate a color with each vertex
- Set up an array of same size as positions
- Send to GPU as a buffer object

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
6



Setting Colors

```
typedef vec3 color3;
color3 base_colors[4] = {color3(1.0, 0.0, 0.0), ....
color3 colors[NumVertices];
vec3 points[NumVertices];

//in loop setting positions

colors[i] = basecolors[color_index]
position[i] = .....
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
7



Setting Up Buffer Object

```
//need larger buffer

glBufferData(GL_ARRAY_BUFFER, sizeof(points) +
sizeof(colors), NULL, GL_STATIC_DRAW);

//load data separately

glBufferSubData(GL_ARRAY_BUFFER, 0,
sizeof(points), points);
glBufferSubData(GL_ARRAY_BUFFER, sizeof(points),
sizeof(colors), colors);
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
8



Second Vertex Array

// vPosition and vColor identifiers in vertex shader

```
loc = glGetAttribLocation(program, "vPosition");
glEnableVertexAttribArray(loc);
glVertexAttribPointer(loc, 3, GL_FLOAT, GL_FALSE, 0,
    BUFFER_OFFSET(0));

loc2 = glGetAttribLocation(program, "vColor");
glEnableVertexAttribArray(loc2);
glVertexAttribPointer(loc2, 3, GL_FLOAT, GL_FALSE, 0,
    BUFFER_OFFSET(sizeof(points)));
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
9



Coloring Each Vertex (deprecated)

```
attribute vec3 vPosition, vColor;
varying vec3 color;

void main()
{
    gl_Position = vec4(vPosition, 1);
    color = vColor;
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
0



Coloring Each Vertex

```
in vec3 vPosition, vColor;
out vec3 color;

void main()
{
    gl_Position = vec4(vPosition, 1);
    color = vColor;
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
1



Coloring Each Fragment (deprecated)

```
varying vec3 color;

void main()
{
    gl_FragColor = vec4(color, 1);
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
2



Coloring Each Fragment

```
in vec3 color;
out vec4 fragcolor;

void main()
{
    fragcolor = vec4(color, 1);
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
3



Vertex Shader Applications

- Moving vertices
 - Morphing
 - Wave motion
 - Fractals
- Lighting
 - More realistic models
 - Cartoon shaders

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
4



Wave Motion Vertex Shader

```
in vec4 vPosition;
out vec4 color;
uniform float xs, zs, // frequencies
uniform float h; // height scale
uniform float time; // time from app
void main()
{
    vec4 t = vPosition;
    t.y = vPosition.y
        + h*sin(time + xs*vPosition.x)
        + h*sin(time + zs*vPosition.z);
    gl_Position = t;
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
5



Particle System


```
in vec3 vPosition;
uniform mat4 ModelViewProjectionMatrix;
uniform vec3 vel;
uniform float g, m, t;
void main()
{
    vec3 object_pos;
    object_pos.x = vPosition.x + vel.x*t;
    object_pos.y = vPosition.y + vel.y*t
        + g/(2.0*m)*t*t;
    object_pos.z = vPosition.z + vel.z*t;
    gl_Position =
        ModelViewProjectionMatrix*vec4(object_pos,1);
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
6



Vertex vs Fragment Lighting



per vertex lighting
Gouraud shading

per fragment lighting
Phong shading


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
9




Fragment Shader Applications


Texture mapping



smooth shading



environment
mapping



bump mapping

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
0



Programming with OpenGL Part 6: Three Dimensions

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
1



Objectives

- Develop a more sophisticated three-dimensional example
 - Sierpinski gasket: a fractal
- Introduce hidden-surface removal

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
2



Three-dimensional Applications

- In OpenGL, two-dimensional applications are a special case of three-dimensional graphics
- Going to 3D
 - Not much changes
 - Use `vec3`, `glUniform3f`
 - Have to worry about the order in which primitives are rendered or use hidden-surface removal


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
3



Sierpinski Gasket (2D)

- Start with a triangle
- Connect bisectors of sides and remove central triangle
- Repeat




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
4



Example

- Five subdivisions



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
5



The gasket as a fractal

- Consider the filled area (black) and the perimeter (the length of all the lines around the filled triangles)
- As we continue subdividing
 - the area goes to zero
 - but the perimeter goes to infinity
- This is not an ordinary geometric object
 - It is neither two- nor three-dimensional
- It is a *fractal* (fractional dimension) object

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
6



Gasket Program

```
#include <GL/glut.h>

/* initial triangle */

point2 v[3] = {point2(-1.0, -0.58),
               point2(1.0, -0.58),
               point2(0.0, 1.15)};

int n; /* number of recursive steps */
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
7



Draw one triangle

```
void triangle( point2 a, point2 b, point2 c)

/* display one triangle */
{
    // static int i = 0; // This doesn't
    // make sense

    points[i] = a;
    i++;
    points[i] = b;
    i++;
    points[i] = c;
    i++;
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
8



Triangle Subdivision

```
void divide_triangle(point2 a, point2 b, point2 c, int m)
{
    /* triangle subdivision using vertex numbers */
    point2 ab, ac, bc;
    if(m>0)
    {
        ab = (a + b)/2;
        ac = (a + c)/2;
        bc = (b + c)/2;
        divide_triangle(a, ab, ac, m-1);
        divide_triangle(c, ac, bc, m-1);
        divide_triangle(b, bc, ab, m-1);
    }
    else(triangle(a,b,c));
    /* draw triangle at end of recursion */
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
9



display and init Functions

```
void display()
{
    glClearColor(GL_COLOR_BUFFER_BIT);
    glDrawArrays(GL_TRIANGLES, 0, NumVertices);
    glFlush();
}

void myinit()
{
    vec2 v[3] = {point2(.....
    .
    .
    .
    divide_triangles(v[0], v[1], v[2], n);
    .
    .
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4
0



main Function

```
int main(int argc, char **argv)
{
    n=4;
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_SINGLE|GLUT_RGB);
    glutInitWindowSize(500, 500);
    glutCreateWindow("2D Gasket");
    glutDisplayFunc(display);
    myinit();
    glutMainLoop();
}
```


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4
1



Example

- Five subdivisions



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4
2



Moving to 3D

- We can easily make the program three-dimensional by using `point3 v[3]` and we start with a tetrahedron

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4
3



3D Gasket


- We can subdivide each of the four faces



- Appears as if we remove a solid tetrahedron from the center leaving four smaller tetrahedra
- Code almost identical to 2D example


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4
4




Almost Correct

- Because the triangles are drawn in the order they are specified in the program, the front triangles are not always rendered in front of triangles behind them




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4
5




Hidden-Surface Removal

- We want to see only those surfaces in front of other surfaces
- OpenGL uses a *hidden-surface* method called the z-buffer algorithm that saves depth information as objects are rendered so that only the front objects appear in the image



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012


4
6




Z-buffering

- Z-buffering (depth-buffering) is a visible surface detection algorithm
- Implementable in hardware and software
- Requires data structure (z-buffer) in addition to frame buffer.
- Z-buffer stores values [0 .. ZMAX] corresponding to depth of each point.
- If the point is closer than one in the buffers, it will replace the buffered values


4
7



Z-buffering



48
1994 Foley/VanDam/Principles of Computer Graphics




Z-buffering w/ front/back clipping

```

for (y = 0; y < YMAX; y++)
  for (x = 0; x < XMAX; x++) {
    F[x][y] = BACKGROUND_VALUE;
    Z[x][y] = -1; /* Back value in NPC */
  }
for (each polygon)
  for (each pixel in polygon's projection) {
    pz = polygon's z-value at pixel coordinates (x,y)
    if (pz < FRONT && pz > Z[x][y]) { /* New point is behind front
                                     plane & closer than previous point */
      Z[x][y] = pz;
      F[x][y] = polygon's color at pixel coordinates (x,y)
    }
  }

```

49



Using the z-buffer algorithm

- It must be
 - Requested in `main.c`

```
glutInitDisplayMode(
  GLUT_SINGLE | GLUT_RGB | GLUT_DEPTH)
```
 - Enabled in `init.c`

```
glEnable(GL_DEPTH_TEST)
```
 - Cleared in the display callback

```
glClear(GL_COLOR_BUFFER_BIT |
  GL_DEPTH_BUFFER_BIT)
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

5
0



Surface vs Volume Subdivision


- In our example, we divided the surface of each face
- We could also divide the volume using the same midpoints
- The midpoints define four smaller tetrahedrons, one for each vertex
- Keeping only these tetrahedrons removes a *volume* in the middle
- See text for code

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

5
1



Volume Subdivision



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

5
2