



Programming with OpenGL Part 3: Shaders

CS 432 Interactive Computer Graphics
Prof. David E. Breen
Department of Computer Science

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1



Objectives

- Simple Shaders
 - Vertex shader
 - Fragment shaders
- Programming shaders with GLSL
- Finish first program



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2



Vertex Shader Applications

- Moving vertices
 - Transformations
 - Modeling
 - Projection
 - Morphing
 - Wave motion
 - Fractals
 - Particle systems
- Lighting
 - More realistic shading models
 - Cartoon shaders

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3



Fragment Shader Applications

Per fragment lighting calculations



per vertex lighting

per fragment lighting


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

4




Fragment Shader Applications


Texture mapping



smooth shading



environment mapping



bump mapping

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

5



Writing Shaders

- First programmable shaders were programmed in an assembly-like manner
- OpenGL extensions added for vertex and fragment shaders
- Cg (C for graphics) C-like language for programming shaders
 - Works with both OpenGL and DirectX
 - Interface to OpenGL complex
- OpenGL Shading Language (GLSL)

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

6



GLSL

- OpenGL Shading Language
- Part of OpenGL 2.0 and up
- High level C-like language
- New data types
 - Matrices
 - Vectors
 - Samplers
- As of OpenGL 3.1, application **must** provide shaders

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

7



Simple Vertex Shader

```

input from application (GLSL 1.5)
in vec4 vPosition;
void main(void)
{
    gl_Position = vPosition;
}

```

must link to variable in application

Simple pass-through

built in variable


Use "attribute vec4 vPosition" for GLSL 1.4

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

8



Execution Model



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

9



Simple Fragment Program

```

out vec4 fragcolor;
void main(void)
{
    fragcolor = vec4(1.0, 0.0, 0.0, 1.0);
}

```


Every fragment simply colored red

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

10



Execution Model



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

11



Data Types

- C types: int, float, bool, uint, double
- Vectors:
 - float vec2, vec3, vec4
 - Also int (ivec), boolean (bvec), uvec, dvec
- Matrices: mat2, mat3, mat4
 - Stored by columns
 - Standard referencing m[row][column]
- C++ style constructors
 - vec3 a = vec3(1.0, 2.0, 3.0)
 - vec2 b = vec2(a)

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

12



Pointers

- There are no pointers in GLSL
- We can use C structs which can be copied back from functions
- Because matrices and vectors are basic types they can be passed into and out from GLSL functions, e.g.
mat3 func(mat3 a)

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
3



Qualifiers

- GLSL has many of the same qualifiers such as **const** as C/C++
- Need others due to the nature of the execution model
- Variables can change
 - Once per primitive
 - Once per vertex
 - Once per fragment
 - At any time in the application
- Vertex attributes are interpolated by the rasterizer into fragment attributes

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
4



Attribute Qualifier

- Attribute-qualified variables can change at most once per vertex
- There are a few built in variables such as `gl_Position` but most have been deprecated
- User defined (in application program)
 - Use 'in' qualifier to get to shader
 - in float temperature
 - in vec3 velocity

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
5



Uniform Qualified

- Variables that are constant for an entire primitive
- Can be changed in application and sent to shaders
- Cannot be changed in shader
- Used to pass information to shader such as the bounding box of a primitive

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
6



Varying Qualified

- Variables that are passed from vertex shader to fragment shader
- Automatically interpolated by the rasterizer
- Old style used the varying qualifier
`varying vec4 color;`
- Now use **out** in vertex shader and **in** in the fragment shader
`out vec4 color;`

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
7



Example: Vertex Shader

```
const vec4 red = vec4(1.0, 0.0, 0.0, 1.0);
in vec4 vPosition;
out vec4 color_out;
void main(void)
{
    gl_Position = vPosition;
    color_out = vPosition.x * red;
}
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
8



Required Fragment Shader

```
in vec4 color_out;
void main(void)
{
    gl_FragColor = color_out;
}
// in latest version use form
// out vec4 fragcolor;
// fragcolor = color_out;
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

1
9



User-defined functions

- Similar to C/C++ functions
- Except
 - Cannot be recursive
 - Specification of parameters

```
returnType MyFunction(in float inputValue,
                      out int outputValue,
                      inout float inAndOutValue);
```

2
0



Passing values

- call by **value-return**
- Variables are copied in
- Returned values are copied back
- Three possibilities
 - in
 - out
 - inout

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
1



Operators and Functions

- Standard C functions
 - Trigonometric
 - Arithmetic
 - Normalize, reflect, length
- Overloading of vector and matrix types


```
mat4 a;
vec4 b, c, d;
c = b*a; // a column vector stored as a 1d array
d = a*b; // a row vector stored as a 1d array
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
2



Swizzling and Selection

- Can refer to array elements by element using `[]` or selection `(.)` operator with
 - x, y, z, w
 - r, g, b, a
 - s, t, p, q
 - `a[2]`, `a.b`, `a.z`, `a.p` are the same
- **Swizzling** operator lets us manipulate components


```
vec4 a, b;
a.yz = vec2(1.0, 2.0);
a.xw = b.yy;
```

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
3



Programming with OpenGL Part 4: Color and Attributes

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
4



Objectives


- Expanding primitive set
- Adding color
- Vertex attributes
- Uniform variables

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
5



OpenGL Primitives




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
6



Polygon Issues

- OpenGL will only display triangles
 - Simple: edges cannot cross
 - Convex: All points on line segment between two points in a polygon are also in the polygon
 - Flat: all vertices are in the same plane
- Application program must tessellate a polygon into triangles (triangulation)
- OpenGL 4.1 contains a tessellator



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
7



Polygon Testing

- Conceptually simple to test for simplicity and convexity
- Time consuming
- Earlier versions assumed both and left testing to the application
- Present version only renders triangles
- Need algorithm to triangulate an arbitrary polygon


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
8



Good and Bad Triangles

- Long thin triangles render badly



- Equilateral triangles render well
- Maximize minimum angle
- Delaunay triangulation for unstructured points


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

2
9



Triangularization


- Convex polygon




- Start with abc, remove b, then acd,

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
0




Non-convex (concave)




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
1




Recursive Division

- There are a variety of recursive algorithms for subdividing concave polygons



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
2




Attributes

- Attributes determine the appearance of objects
 - Color (points, lines, polygons)
 - Size and width (points, lines)
 - Stipple pattern (lines, polygons)
 - Polygon mode
 - Display as filled: solid color or stipple pattern
 - Display edges
 - Display vertices
- Only a few (glPointSize) are supported by OpenGL functions


E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
3




RGB color

- Each color component is stored separately in the frame buffer
- Usually 8 bits per component in buffer
- Color values can range from 0.0 (none) to 1.0 (all) using floats or over the range from 0 to 255 using unsigned bytes




E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
4




Smooth Color

- Default is *smooth* shading
 - OpenGL interpolates vertex colors across visible polygons
- Alternative is *flat shading*
 - Color of first vertex determines fill color
 - Handle in shader



E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
6



Setting Colors

- Colors are ultimately set in the fragment shader but can be determined in either shader or in the application
- Application color: pass to vertex shader as a uniform variable (next lecture) or as a vertex attribute
- Vertex shader color: pass to fragment shader as varying variable (next lecture)
- Fragment color: can alter via shader code

E. Angel and D. Shreiner: Interactive Computer Graphics 6E © Addison-Wesley 2012

3
7