

Linux and Bash Command Cheat Sheet: The Basics

Getting information

return your user name

`whoami`

return your user and group id

`id`

return operating system name, username, and other info

`uname -a`

display reference manual for a command

`man top`

get help on a command

`curl --help`

return the current date and time

`date`

Monitoring performance and status

list selection of or all running processes and their PIDs

`ps`

`ps -e`

display resource usage

`top`

list mounted file systems and usage

`df`

Working with files

copy a file

`cp file.txt new_path/new_name.txt`

change file name or path

`mv this_file.txt that_path/that_file.txt`

remove a file verbosely

`rm this_old_file.txt -v`

create an empty file, or update existing file's timestamp

`touch a_new_file.txt`

change/modify file permissions to 'execute' for all users

```
chmod +x my_script.sh
```

get count of lines, words, or characters in file

```
wc -l table_of_data.csv
```

```
wc -w my_essay.txt
```

```
wc -m some_document.txt
```

return lines matching a pattern from files matching a filename pattern - case insensitive and whole words only

```
grep -iw hello \*.txt
```

return file names with lines matching the pattern 'hello' from files matching a filename pattern

```
grep -l hello \*.txt
```

Navigating and working with directories

list files and directories by date, newest last

```
ls -lrt
```

find files in directory tree with suffix 'sh'

```
find -name '\*.sh'
```

return present working directory

```
pwd
```

make a new directory

```
mkdir new_folder
```

change the current directory: up one level, home, or some other path

```
cd ../
```

```
cd ~ or cd
```

```
cd another_directory
```

remove directory, verbosely

```
rmdir temp_directory -v
```

Printing file and string contents

print file contents

```
cat my_shell_script.sh
```

print file contents page-by-page

```
more ReadMe.txt
```

print first N lines of file

```
head -10 data_table.csv
```

```
# print last N lines of file
tail -10 data_table.csv
```

```
# print string or variable value
echo "I am not a robot"
echo "I am $USERNAME"
```

Compression and archiving

```
# archive a set of files
tar -cvf my_archive.tar.gz file1 file2 file3

# compress a set of files
zip my_zipped_files.zip file1 file2
zip my_zipped_folders.zip directory1 directory2
```

```
# extract files from a compressed zip archive
unzip my_zipped_file.zip
unzip my_zipped_file.zip -d extract_to_this_directory
```

Performing network operations

```
# print hostname
hostname

# send packets to URL and print response
ping www.google.com

# display or configure system network interfaces
ifconfig
ip

# display contents of file at a URL
curl <url>

# download file from a URL
wget <url>
```

Bash shebang

```
#!/bin/bash
```

Pipes and Filters

```
# chain filter commands using the pipe operator
ls | sort -r
```

pipe the output of manual page for ls to head to display the first 20 lines
`man ls | head -20`

Shell and Environment Variables

list all shell variables
`set`

define a shell variable called my_planet and assign value Earth to it
`my_planet=Earth`

display shell variable
`echo $my_planet`

list all environment variables
`env`

environment vars: define/extend variable scope to child processes
`export my_planet`
`export my_galaxy='Milky Way'`

Metacharacters

comments
`# The shell will not respond to this message`

command separator
`echo 'here are some files and folders'; ls`

file name expansion wildcard
`ls *.json`

single character wildcard
`ls file_2021-06-??.json`

Quoting

single quotes - interpret literally
`echo 'My home directory can be accessed by entering: echo $HOME'`

double quotes - interpret literally, but evaluate metacharacters
`echo "My home directory is $HOME"`

backslash - escape metacharacter interpretation
`echo "This dollar sign should render: \$"`

I/O Redirection

redirect output to file

```
echo 'Write this text to file x' > x
```

append output to file

```
echo 'Add this line to file x' >> x
```

redirect standard error to file

```
bad_command_1 2> error.log
```

append standard error to file

```
bad_command_2 2>> error.log
```

redirect file contents to standard input

```
$ tr "[a-z]" "[A-Z]" < a_text_file.txt
```

the input redirection above is equivalent to

```
$cat a_text_file.txt | tr "[a-z]" "[A-Z]"
```

Command Substitution

capture output of a command and echo its value

```
THE_PRESENT=$(date)
```

```
echo "There is no time like $THE_PRESENT"
```

Command line arguments

```
./My_Bash_Script.sh arg1 arg2 arg3
```

Batch vs. concurrent modes

run commands sequentially

```
start=$(date); ./MyBigScript.sh ; end=$(date)
```

run commands in parallel

```
./ETL_chunk_one_on_these_nodes.sh & ./ETL_chunk_two_on_those_nodes.sh
```

Scheduling jobs with Cron

open crontab editor

```
crontab -e
```

job scheduling syntax

```
m h dom mon dow command
```

minute, hour, day of month, month, day of week

** means any*

append the date/time to file every Sunday at 6:15 pm

```
15 18 * * 0 date >> sundays.txt
```

run a shell script on the first minute of the first day of each month

```
1 0 1 * * ./My_Shell_Script.sh
```

back up your home directory every Monday at 3 am

```
0 3 * * 1 tar -cvf my_backup_path\my_archive.tar.gz $HOME\
```

deploy your cron job

Close the crontab editor and save the file

list all cron jobs

```
crontab -l
```