MINIATURE RELAY

2 POLES—1 to 2 A (FOR SIGNAL SWITCHING)


NA SERIES

RoHS compliant



■ FEATURES

- · Slim type relay for high density mounting
- Conforms to Bellcore specification and FCC Part 68
 - —Dielectric strength 1,500 VAC between coil and contacts
- —Surge strength 2,500 V between coil and contacts (at 2 × 10 s surge wave)
- Maximum switching capability 4.2A, 700VAC
- · UL, CSA recognized
- · High sensitivity and low consumption power
- High reliability—bifurcated contacts
- · DIL pitch terminals
- · Plastic sealed type
- RoHS compliant since date code: 0437B8
 Please see page 7 for more information



ORDERING INFORMATION

	NA	L	_	D	12	W	_	K
[Example]	(a)	(b)	(*)	(c)	(d)	(e)		(f)

(a)	Series Name	NA : NA Series
(b)	Operation Function	Nil:Standard type L:Latching type
(c)	Number of Coil	Nil: Single winding type D: Double winding type
(d)	Nominal Voltage	Refer to the COIL DATA CHART
(e)	Contact	W : Bifurcated type
(f)	Enclosure	K : Plastic sealed type

Note: Actual marking omits the hyphen (-) of (*)

1

■ COIL DATA CHART

	MODEL	Nominal voltage	Coil resistance (±10%)	Must operate voltage*1	Must release voltage*	Nominal power
	NA-1.5 W-K	1.5 VDC	16.1 Ω	+1.13 VDC	+0.15 VDC	140 mW
	NA- 3 W-K	3 VDC	64.3 Ω	+2.25 VDC	+0.3 VDC	140 mW
l m	NA-4.5 W-K	4.5 VDC	145 Ω	+3.38 VDC	+0.45 VDC	140 mW
Туре	NA- 5 W-K	5 VDC	178 Ω	+3.75 VDC	+0.5 VDC	140 mW
	NA- 6 W-K	6 VDC	257 Ω	+4.5 VDC	+0.6 VDC	140 mW
Standard	NA- 9 W-K	9 VDC	579 Ω	+6.75 VDC	+0.9 VDC	140 mW
Sta	NA-12 W-K	12 VDC	1,028 Ω	+9.0 VDC	+1.2 VDC	140 mW
	NA-18 W-K	18 VDC	1,620 Ω	+13.5 VDC	+1.8 VDC	200 mW
	NA-24 W-K	24 VDC	2,880 Ω	+18.0 VDC	+2.4 VDC	200 mW
	NA-48 W-K	48 VDC	7,680 Ω	+36.0 VDC	+4.8 VDC	300 mW

Note: $^{\star 1}$ Specified values are subject to pulse wave voltage. All values in the table are measured at 20°C.

	MODEL	Nominal voltage	Coil resistance (±10%)	Set voltage	Reset voltage	Nominal power
	NAL-1.5W-K	1.5 VDC	22.5 Ω	+1.13 VDC	-1.13 VDC	100 mW
Lype	NAL- 3 W-K	3 VDC	90 Ω	+2.25 VDC	-2.25 VDC	100 mW
ing	NAL-4.5W-K	4.5 VDC	203 Ω	+3.38 VDC	-3.38 VDC	100 mW
atch	NAL- 5 W-K	5 VDC	250 Ω	+3.75 VDC	-3.75 VDC	100 mW
ing L	NAL- 6 W-K	6 VDC	360 Ω	+4.5 VDC	-4.5 VDC	100 mW
Vind	NAL- 9 W-K	9 VDC	810 Ω	+6.75 VDC	-6.75 VDC	100 mW
Single Winding Latching Type	NAL-12 W-K	12 VDC	1,440 Ω	+9.0 VDC	-9.0 VDC	100 mW
Si	NAL-18 W-K	18 VDC	2,160 Ω	+13.5 VDC	-13.5 VDC	150 mW
	NAL-24 W-K	24 VDC	3,840 Ω	+18.0 VDC	-18.0 VDC	150 mW
	NAL-D1.5W-K	1.5 VDC	Ρ 11.25 Ω	+1.13 VDC		200 mW
			S 11.25 Ω		+1.13 VDC	200 11100
	NAL-D 3 W-K	3 VDC	Ρ 45 Ω	+2.25 VDC		200 mW
			S 45 Ω		+2.25 VDC	200 11100
e e	NAL-D4.5W-K	4.5 VDC	Ρ 101 Ω	+3.38 VDC		200 mW
<u>F</u>			S 101 Ω		+3.38 VDC	200 11100
ling	NAL-D 5 W-K	5 VDC	Ρ 125 Ω	+3.75 VDC		200 mW
atc			S 125 Ω		+3.75 VDC	200 11100
J g	NAL-D 6 W-K	6 VDC	Ρ 180 Ω	+4.5 VDC		200 mW
Jdi.			S 180 Ω		+4.5 VDC	200 11100
Š	NAL-D 9 W-K	9 VDC	Ρ 405 Ω	+6.75 VDC		200 mW
Jouble Winding Latching Type			S 405 Ω		+6.75 VDC	200 11100
P	NAL-D12 W-K	12 VDC	Ρ 720 Ω	+9.0 VDC		200 mW
⁻			S 720 Ω		+9.0 VDC	200 11100
	NAL-D18 W-K	18 VDC	Ρ 1,080 Ω	+13.5 VDC		300 mW
			S 1,080 Ω		+13.5 VDC	300 11100
	NAL-D24 W-K	24 VDC	Ρ 1,920 Ω	+18.0 VDC		300 mW
			S 1,920 Ω		+18.0 VDC	000 11100

Note: $^{\star 1}$ Specified values are subject to pulse wave voltage. All values in the table are measured at 20°C.

P: Primary coil S: Secondary coil

■ SPECIFICATIONS

ltem -		Standard Type	Standard Type Single Winding Latching Type Double Winding La				
		NA-() W-K	NAL-() W-K	NAL-D()W-K			
Contact	ntact Arrangement		2 form C (DPDT)				
	Material		Gold overlay silver all	оу			
	Style		Bifurcated				
	Resistance ((initial)	Maximum 50 mΩ (at 1	I A 6 VDC)			
	Rating (resis	stive)	0.5 A 125 VAC or 1 A	30 VDC			
	Maximum C	arrying Current	2 A				
	Maximum S	witching Power	62.5 AV, 30 W				
	Maximum S	witching Voltage	250 VAC, 220 VDC				
	Maximum S	witching Current	2 A	2 A			
Minimum Switching Load*1		0.01 mA 10 mVDC					
	Capacitance		Approximately 0.5 pF (between open contacts, adjacent contacts) Approximately 1.0 pF (between coil and contacts)				
Coil	Coil Nominal Power (at 20°C) Operate Power (at 20°C) Operating Temperature		140 to 300 mW	100 to 150 mW	200 to 300 mW		
			80 to 170 mW	60 to 85 mW	115 to 170 mW		
			-40°C to +85°C (no frost)(refer to the CHARACTERISTIC DATA)				
Time Value	le Operate (at nominal voltage)		Maximum 6 ms	Maximum 6 ms (set)			
	Release (at nominal voltage)		Maximum 4 ms	Maximum 6 ms (reset)			
Life	Mechanical		1×10^8 operations minimum 1×10^7 operations minimum				
	Electrical		2 × 10 ⁵ ops. min. (0.5 A 125 VAC), 5 × 10 ⁵ ops. min. (1 A 30 VDC)				
Other	Vibration Resistance	Misoperation	10 to 55 Hz (double amplitude of 3.3 mm)				
		Endurance	10 to 55 Hz (double amplitude of 5.0 mm)				
	Shock Resistance	Misoperation	500 m/s ² (11 ±1 ms)				
		Endurance	1,000 m/s ² (6 ±1 ms)				
	Weight		Approximately 1.5 g				

^{*1} Minimum switching loads mentioned above are reference values. Please perform the confirmation test with the actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

■ INSULATION


Item	Standard	Single latching	Double latching	
Resistance (initial) (500 VDC)	Minimum 1,000 M Ω			
Dielectric Strength	1,000 VAC 1 min. (open contacts / adjacent contents)			
	1,500 VAC 1 mi	in. (coil and contacts)	1,000 VAC 1 min. (coil and contacts)	
Surge Voltage	1,500V (open contact and adjacent contact) 10 x 700µs standard w			
	2,500V (coil and standard wave	d contact) 2 x 10µs	1,500V (coil and contact) 10 x 160µs standard wave	


■ SAFETY STANDARDS


Туре	Compliance	Contact rating
UL	UL 508, UL 1950 E45026	Flammability: UL 94-V0 (plastics) 0.5A, 125VAC (general use) 2A, 30VDC (resistive)
CSA	C22.2 No. 14, No. 950 LR 35579	0.3A, 110VDC (resistive)


4


■ CHARACTERISTIC DATA































■ REFERENCE DATA




























■ DIMENSIONS


Dimensions

- Schematics (Bottom View)
- PC board mounting hole layout (Bottom View)


NA, NAL type (Non-latching type, single winding latching type)










NAL-D type (double winding latching type)









Unit: mm

RoHS Compliance and Lead Free Relay Information

1. General Information

- Relays produced after the specific date code that is indicated on each data sheet are lead-free now. All of our signal and power relays are lead-free. Please refer to Lead-Free Status Info. (http://www.fujitsu.com/us/downloads/MICRO/fcai/relays/lead-free-letter.pdf)
- Lead free solder paste currently used in relays is Sn-3.0Ag-0.5Cu.
- All signal and power relays also comply with RoHS. Please refer to individual data sheets. Relays that are RoHS compliant do not contain the 5 hazardous materials that are restricted by RoHS directive (lead, mercury, chromium IV, PBB, PBDE).
- It has been verified that using lead-free relays in leaded assembly process will not cause any problems (compatible).
- "LF" is marked on each outer and inner carton. (No marking on individual relays).
- To avoid leaded relays (for lead-free sample, etc.) please consult with area sales office.
- We will ship leaded relays as long as the leaded relay inventory exists.

Note: Cadmium was exempted from RoHSon October 21, 2005. (Amendment to Directive 2002/95/EC)

2. Recommended Lead Free Solder Profile

Recommended solder paste Sn-3.0Ag-0.5Cu.

Reflow Solder condition

Flow Solder condition:

maximum 120°C Pre-heating: Soldering: dip within 5 sec. at 260°C soler bath

Solder by Soldering Iron:

Soldering Iron

Temperature: maximum 360°C Duration: maximum 3 sec.

We highly recommend that you confirm your actual solder conditions

3. Moisture Sensitivity

Moisture Sensitivity Level standard is not applicable to electromechanical realys.

4. Tin Whisker

Dipped SnAgCu solder is known as low risk tin whisker. No considerable length whisker was found by our in house test.

Fujitsu Components International Headquarter Offices

Japan

Fujitsu Component Limited Gotanda-Chuo Building

3-5, Higashigotanda 2-chome, Shinagawa-ku

Tokyo 141, Japan Tel: (81-3) 5449-7010 Fax: (81-3) 5449-2626

Email: promothq@ft.ed.fujitsu.com

Web: www.fcl.fujitsu.com

North and South America

Fujitsu Components America, Inc. 250 E. Caribbean Drive Sunnyvale, CA 94089 U.S.A. Tel: (1-408) 745-4900

Fax: (1-408) 745-4970

Email: components@us.fujitsu.com

Web: http://www.fujitsu.com/us/services/edevices/components/

Europe

Fujitsu Components Europe B.V.

Diamantlaan 25 2132 WV Hoofddorp Netherlands Tel: (31-23) 5560910

Fax: (31-23) 5560950 Email: info@fceu.fujitsu.com Web: emea.fujitsu.com/components/

Asia Pacific

Fujitsu Components Asia Ltd. 102E Pasir Panjang Road #01-01 Citilink Warehouse Complex

Singapore 118529 Tel: (65) 6375-8560 Fax: (65) 6273-3021 Email: fcal@fcal.fujitsu.com

Web: http://www.fujitsu.com/sg/services/micro/components/

©2008 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice. Rev. January 8, 2008.