

## Replacement Tags for Articles

{  
AUTHOR}

<b>Use:</b>	Distributes the Author of the article
<b>Notation:</b>	<b>{ AUTHOR }</b>
<b>Result:</b>	Oliver
<b>Remark:</b>	

[^ TOP](#)

{  
DATE\_ARTICLE}

<b>Use:</b>	Distributes the construction date of the article
<b>Notation:</b>	<b>{ DATE_ARTICLE }</b>
<b>Result:</b>	Tuesday, 4. January 2011
<b>Remark:</b>	To display date in other languages you must edit: config/phpwcms/conf.template_default.inc.php \$template_default["date"]["language"]="EN";

[^ TOP](#)

{  
TIME\_ARTICLE}

<b>Use:</b>	Distributes the construction time of the article
<b>Notation:</b>	<b>{ TIME_ARTICLE }</b>
<b>Result:</b>	13:47
<b>Remark:</b>	The Time format can be changed in config/phpwcms/conf.template_default.inc.php beginning from line 159

[^ TOP](#)

[  
b]Text[  
/b]

**Use:**

[^ TOP](#)

[  
i]Text[  
/i]

Notation:  
Result:  
Remark:

With this tag you can format text to  
**bold**  
**[ b]Text[/b]**  
**Text**  
This tag is made for plain text  
content parts. But it can used as well  
in templates, headlines, captions ...

Use:

Notation:  
Result:  
Remark:

With this tag you can format text to  
*italic*  
**[ i]Text[/i]**  
*Text*  
This tag is made for plain text content  
parts. But it can used as well in  
templates, headlines, captions ...

[^ TOP](#)

[  
u]Text[  
/u]

Use:

Notation:  
Result:  
Remark:

With this tag you can decorate text  
underline  
**[ u]Text[ /u]**  
Text  
This tag is made for plain text  
content parts. But it can used as well  
in templates, headlines, captions ...

[^ TOP](#)

[  
s]Text[  
/s]

Use:

Notation:  
Result:  
Remark:

With this tag you can decorate text  
~~strikeout~~  
**[ s]Text[/s]**  
~~Text~~  
This tag is made for plain text content  
parts. But it can used as well in  
templates, headlines, captions ...

[^ TOP](#)

[  
BR]

**Use:**

With this tag you can force a linebreak

**Notation:**

**the forced line break is >[ BR]**

**Result:**

the forced line break is >

**Remark:**

This tag can be used in all content parts and in templates, headlines, captions ...

[^ TOP](#)

{  
SHOW\_CONTENT:MODE,id,id,id}

**Use:**

Shows one or more content parts (>=V1.2.8)

**Notation:**

**{ SHOW\_CONTENT:MODE,id,id,id}**

**Result:**

{ SHOW\_CONTENT:CP,1,2,3}

the CPs with the CP-ID 1,2 und 3 was spent here.

**Remark :**

There are 3 different MODE'S

1. { SHOW\_CONTENT:**CP**, cp-id, cp-id, cp-id}

List of Content Parts but based on selected cp | id = id of cp, comma separated.

2. { SHOW\_CONTENT:**CPA**, art-id, art-id, art-id}

ascending list of Content Parts but based on selected article | id = id of article, comma separated.

3. { SHOW\_CONTENT:**CPAD**, art-id, art-id, art-id}

same as CPA, but descending (this slows rendering)

4. { SHOW\_CONTENT:**AS**, art-id, art-id, art-id}

List of Article Summaries | id = id of articles, comma separated.

- **Sort order:**

- **AS:** Sorted as given

- **ASL:** Sorted by "lifedate ASC" ("begins date" ascending)

- **ASLD:** Sorted by "lifedate DESC" ("begins date" descending)

- **ASK:** Sorted by "killdate ASC" ("ends date" ascending)

- **ASKD:** Sorted by "killdate DESC" ("ends date" descending)

- **ASC:** Sorted by "changedate ASC" ("change date" ascending)

- **ASCD:** Sorted by "changedate DESC" ("change date" descending)

- **ASR:** Sorted by "random"

- **Mode expansion:**

- **Mode|Limit|Template:** Output article maximum number or list template (e.g.. ASL|3, ... , ASL|MyTemplate.tpl, ...)
- **AxxxP:** Include prioritize article value too. (e.g. ASP oder ASLDP ....)

[^ TOP](#)

**URL:** <http://www.phpwcms-docu.de/index.php?id=80,36,0,0,1,0>