Supervised learning

Inteligencia Artificial en los Sistemas de Control Autónomo Máster en Ciencia y Tecnología desde el Espacio

Departamento de Automática





Objectives

- 1. Extend supervised learning algorithms
- 2. Apply supervised learning to real-world problems

Bibliography

- Géron, Aurélien. Hands-On Machine Learning with Scikit-Learn, Keras & TensorFlow. O'Reilly. 2020
- Müller, Andreas C., Guido, Sarah. Introduction to Machine Learning with Python. O'Reilly. 2016

Table of Contents

- k-Nearest Neighbors
 - kNN classification
 - kNN regression
 - Summary
- 2. Linear models
 - Ordinary least squares
 - Ridge regression
 - Lasso regression
 - ElasticNet
 - Linear models for classification
 - Summary
- 3. Naive Bayes Classifiers

- Summary
- 4. Decission Trees
 - Summary
- 5. Ensembles of Decision Trees
 - Summary
- 6. Support Vector Machines
 - Kernelized Support Vector Machines
 - Summary
- 7. A
 - b
 - A: Summary
 - ARIMA

k-Nearest Neighbors

kNN classification (I)

Diagrama 1-NN y 3-NN.



k-Nearest Neighbors

kNN classification (II)

k-Nearest Neighbors

Diagrama frontera para varios valores de K



k-Nearest Neighbors

kNN regression

k-Nearest Neighbors



k-Nearest Neighbors Linear models Naive Bayes Classifiers Decission Trees Ensembles of Decision Trees Support Vector Machines

○○○

○○

○○

○○

○○

○○

○○

k-Nearest Neighbors

Summary



Linear models


Linear regression (I)

Lineal regression assumes a linear relationship among variables

- This limitation can be easely overcome
- Surprisingly good results in high dimensional spaces

Lineal regression

$$y = a_0 + a_1 x_1 + a_2 x_2 + \dots + a_n x_n$$





Linear models (II)

Several methods to fit coefficients

- Ordinary Least Squares (OLS)
- Generalized Least Squares (GSL)
- Weighted Least Squares (WLS)
- Generalized Least Squares with AR Covariance Structure (GLSAR)

Regularization: Term that penalizes complexity

- L1 (Lasso regression)
- L2 (Ridge regression)
- ElasticNet: Lt and L2

Lasso

$$\lambda \sum_{i}^{n} \beta_{j}^{2}$$

Ridge

$$\lambda \sum_{i=1}^{n} |\beta_{i}|$$

ElasticNet

$$\alpha \sum_{j}^{n} \beta_{j}^{2} + (1 - \alpha) \sum_{j}^{n} |\beta_{j}|$$



earest Neighbors Linear models Naive Bayes Classifiers Decission Trees Ensembles of Decision Trees Support Vector Machines

Linear models

Summary



Naive Bayes Classifiers



rrest Neighbors Linear models **Naive Bayes Classifiers** Decission Trees Ensembles of Decision Trees Support Vector Machines

OO OO OO OO

Naive Bayes Classifiers

Summary



Decission Trees



rest Neighbors Linear models Naive Bayes Classifiers **Decission Trees** Ensembles of Decision Trees Support Vector Machines

Decission Trees

Summary



Ensembles of Decision Trees



bors Linear models Naive Bayes Classifiers Decission Trees **Ensembles of Decision Trees** Support Vector Machines

OOO OO OO OO OO

Ensembles of Decision Trees

Summary



Support Vector Machines



Support Vector Machines

Kernelized Support Vector Machines



phbors Linear models Naive Bayes Classifiers Decission Trees Ensembles of Decision Trees **Support Vector Machines**

Support Vector Machines

Summary



A

E





B: Summary

Hyperparameters Advantages Disadvantages



0000

ARIMA (I)

AR: Autoregressive model

- Current observation depends on the last p observations
- Long term memory

MA: Moving Average model

- Current observation linearly depends on the last q innovations
- Short term memory

$ARMA \mod el = AR + MA$

ARMA(p, q): Two hyperparameters, p and q

AR(p)

$$X_t = c + \sum_{i=1}^p \phi_i X_{t-1} + \epsilon_t$$

MA(q)

$$X_t = \mu + \epsilon_t + \theta_1 \epsilon_{t-1} + ... + \theta_q \epsilon_{t-q}$$




ecission Trees Ensembles of Decision Trees Support Vector Machines
O OO OO

Algorithms

ARIMA (II)

ARIMA = AR + i + MA (AR integrated MA)

- ARIMA(p, d, q)
- Three integer parameters: p, q and d (in practice, low order models)



autoarima: search over p, q and d



0000