

# Machine Learning Foundations

Inteligencia Artificial en los Sistemas de Control Autónomo  
Máster en Ciencia y Tecnología desde el Espacio

Departamento de Automática

## Objectives

1. Define Machine Learning (ML)
2. Delimite ML scope
3. Introduce the main ML tasks
4. Recognize problems as ML tasks

## Bibliography

- Géron, Aurélien. Hands-On Machine Learning with Scikit-Learn, Keras & TensorFlow. 2nd edition. O'Reilly. 2019
- Müller, Andreas C., Guido, Sarah. Introduction to Machine Learning with Python. O'Reilly. 2016

# Table of Contents

## 1. Introduction

- Justification
- Definition
- The alphabet soup of data analysis

## 2. The data analysis process

- The big picture
- Data acquisition
- Selection, cleaning and transformation
- Machine Learning
- Learning evaluation
- Model exploitation

## 3. Types of Machine Learning systems

- Overview
- Classification
- Regression

## ■ Unsupervised learning

- Clustering
- Association rules
- Dimensionality reduction

## 4. Main challenges of Machine Learning

- Under and overfitting
- The curse of dimensionality
- Other challenges

## 5. Case studies

- Bank propensity model
- Social media campaign impact
- Hubble FGS-3 servo failure prediction
- Fall detection with accelerometer
- Fall detection with sound
- NASA JPL BioSleeve
- UAV terrain classification

# Introduction

## Justification

### New opportunities

- Huge amount of new data sources: banking, social media, IoT, DNA, ...
- Increased computational power

### New needs

- Manual data analysis is unfeasible
- Need of automatic methods

### New goal

- Transform data into knowledge

# Introduction

## Definition (I)

### ML definition

ML is the science (and art) of programming computers so they can learn from data.


A. Géron, 2017

### Alternative definitions

- Machine Learning is the field of study that gives computers the ability to learn without being explicitly programmed. Arthur Samuel, 1959.
- A computer program is said to learn from experience E with respect to some task T and some performance measure P, if its performance on T, as measured by P, improves with experience. E. Tom Mitchell, 1997.

# Introduction

## The alphabet soup of data analysis



(Source)

### Many related terms

- Artificial Intelligence
- Machine Learning
- Deep Learning
- Big Data


### And new careers

- Data Science
- Data scientist
- Data engineer
- ML engineer


# Introduction

## Definition (II)

### Traditional approach




### ML approach



# The data analysis process

## The big picture



### Steps in any ML application:

1. Data adquisition
2. Selection, cleaning and transformation  
(preprocessing)
3. Machine Learning
4. Learning evaluation
5. Exploitation

The goal in ML is to get a representation of those patterns



# The data analysis process

## Data adquisition

Goal: Adquire data to perform ML


- From extremely easy -CSV file- to extremely complex -full Big Data system-

Public data repositories

- (Kaggle), (NASA Open Data Portal), (Omniweb), (UCI Machine Learning Repository)

Customized adquisition and integration

- Integration from several data sources usually needed



# The data analysis process

## Data acquisition: Space data sources

Data sources highly dependent on domain and mission


- Many missions have their own website to download data
- Each mission contains data from different instruments

There are, however, some integrated data products sources

- (OMNIWeb) - Heliophysics / Space Weather
- (CDAWeb) - Non-solar Heliophysics
- (SSCWeb) - Satellite situation
- (Heliophysics Data Portal) - Heliophysics
- (HAPI) - “Integration of integrated” data sources
- Python packages
  - SunPy, AstroPy, SpacePy, PySat, PySPEDAS, etc

# The data analysis process

## Data acquisition: Famous datasets - Iris (I)



**Iris Versicolor**



**Iris Setosa**



**Iris Virginica**

### Iris dataset

- First used by Roland Fisher in 1936
- Classification problem: three iris species
- Balanced dataset: 150 instances, three classes, 50 instances each
- Four attributes (petal width, petal length, sepal width, sepal length)

# The data analysis process


## Data adquisition: Famous datasets - Iris (II)

	sepal_length	sepal_width	petal_length	petal_width	species
0	5.1	3.5	1.4	0.2	Iris-setosa
1	4.9	3.0	1.4	0.2	Iris-setosa
2	4.7	3.2	1.3	0.2	Iris-setosa
3	4.6	3.1	1.5	0.2	Iris-setosa
4	5.0	3.6	1.4	0.2	Iris-setosa
...	...	...	...	...	...
145	6.7	3.0	5.2	2.3	Iris-virginica
146	6.3	2.5	5.0	1.9	Iris-virginica
147	6.5	3.0	5.2	2.0	Iris-virginica
148	6.2	3.4	5.4	2.3	Iris-virginica
149	5.9	3.0	5.1	1.8	Iris-virginica

(More info in Kaggle)

# The data analysis process

## Data acquisition: Famous datasets - MNIST



### Hand-written digit recognition

- 60,000 training samples, 10,000 test samples
- 8x8 images
- 10 classes
- (More in Kaggle)

# The data analysis process

## Data acquisition: data file formats - CSV

### CSV (Comma-Separated Values)

- Text format for tabular data
- Editable with system tools and Excel
- Rows store records
- Columns store attributes
- Fields are separated by commas

Year	Make	Model	Description	Price
1997	Ford	E350	ac, abs, moon	3000.00
1999	Chevy	Venture "Extended Edition"		4900.00
1999	Chevy	Venture "Extended Edition, Very Large"		5000.00
1996	Jeep	Grand Cherokee	MUST SELL! air, moon roof, loaded	4799.00

filename.csv

```
Year , Make , Model , Description , Price
1997 , Ford , E350 , "ac , abs , moon" , 3000.00
1999 , Chevy , " Venture " " Extended Edition " " " , " " , 4900.00
1999 , Chevy , " Venture " " Extended Edition , Very Large " " " , " " , 5000.00
1996 , Jeep , Grand Cherokee , " MUST SELL !
air , moon roof , loaded " , 4799.00
```

# The data analysis process

## Data adquisition: data file formats - JSON

- JSON: Data format for hierarchical data
- Created in 2001 for stateless client-server communication
  - Text-based
  - Complex data structures

filename.json

```
{
  "firstName": "John",
  "isAlive": true,
  "age": 27,
  "address": {
    "streetAddress": "21 2nd Street",
    "city": "New York",
    "state": "NY",
  },
  "phoneNumbers": [
    {
      "type": "home",
      "number": "212 555-1234"
    },
    {
      "type": "office",
      "number": "646 555-4567"
    }
  ]
}
```

# The data analysis process

## Data acquisition: data file formats - Space data

Several formats designed for space applications

- NASA CDF (Common Data Format)
  - (More info)
- FITS (Flexible Image Transport System)
  - Astronomical image format supported by NASA and IAU
  - (More info)
- HDF5: Big Data format, not specific for space

Specific tools for files manipulation and loading



# The data analysis process

## Selection, cleaning and transformation (I)

- Goal: Prepare data for ML
- This phase is usually named **preprocess**

ML requires a clean data table

- Rows are named **instances**
- Columns are named **features** or **attributes**
- We refer the number of features as **dimensionality**

$f_1$	$f_2$	$\dots$	$f_n$
$a_{1,1}$	$a_{2,1}$	$\dots$	$a_{n,1}$
$a_{1,2}$	$a_{2,2}$	$\dots$	$a_{n,2}$
$a_{1,3}$	$a_{2,3}$	$\dots$	$a_{n,3}$
$a_{1,4}$	$a_{2,4}$	$\dots$	$a_{n,4}$
$a_{1,5}$	$a_{2,5}$	$\dots$	$a_{n,5}$

In some ML problems we use graphs instead of tables

# The data analysis process

## Selection, cleaning and transformation (II)

Example: Bank data base

IDC	Years	Euros	Salary	Own house	Defaults
101	15	60000	2200	Yes	2
102	2	30000	3500	Yes	0
103	9	9000	1700	Yes	1
104	15	18000	1900	No	0
...	...	...	...	...	...

Example: Robot sensors

Timestamp	Sonar1	Sonar2	Sonar3	Sonar4
1	1.687	0.445	2.332	0.429
2	0.812	0.481	1.702	0.473
3	1.572	0.471	1.654	0.513
...	...	...	...	...



# The data analysis process

## Selection, cleaning and transformation (IV)

### Example: Text classification (bag-of-words representation)

#### 1. Original text

- (1) John likes to watch movies. Mary likes movies too.
- (2) John also likes to watch football games.

#### 2. Build list

- (1) "John", "likes", "to", "watch", "movies", "Mary", "likes", "movies", "too"
- (2) "John", "also", "likes", "to", "watch", "football", "games"

#### 3. Build dictionary

- (1) {"John":1, "likes":2, "to":1, "watch":1, "movies":2, "Mary":1, "too":1};
- (2) {"John":1, "also":1, "likes":1, "to":1, "watch":1, "football":1, "games":1};

John	likes	to	watch	movies	Mary	too	also	games	...
1	2	1	1	2	1	1	0	0	...
1	1	1	1	0	0	0	1	1	...

# The data analysis process

## Selection, cleaning and transformation (V)

### Preprocessing tasks

- Handle outliers (remove or leave them)
- Sample data (in case there are too much)
- Handle missing values
- Remove irrelevant or redundant features (**feature selection**)
  - For instance, attributes “social class” and “salary” contain highly correlated information
- Compute new attributes (**feature engineering**)
  - For instance, compute “population density” from “area” and “population”
- Transform attributes
  - Discretization, normalization, numerization, ...

# The data analysis process

## Data processing levels

Three levels of processing for data products in space applications

- Level 0: Unprocessed data from payload
- Level 1: Processed data
- Level 2: Processed data with geophysical variables

(More info)

# The data analysis process

## Machine Learning

Goal: Train an algorithm to perform a task

- As result, we obtain a **model** (or **classifier** or **predictor** depending on the context)

Machine Learning training methods (or ML tasks)

- Supervised learning: **classification** and **regression**
- Unsupervised learning: **clustering**, association, **dimensionality reduction** and anomaly detection
- Reinforcement learning
- Many others

### No Free-Lunch Theorem

No learning algorithm is a priori  
guaranteed to work better  
More info: (D. Wolpert, 1996)

# The data analysis process

## Learning evaluation (I)

We do need to evaluate the trained model

- Models should perform well on new data

A naïve and wrong approach. Why is it wrong?

1. Train the model
2. Use the model to predict labels
3. Compute accuracy comparing predicted labels with known labels

Solution: Training and validation datasets

- **Training set:** Data used to train the models. Usually 70 %
- **Validation set:** Data used to validate the models. Usually 30 %
- Problems: Bias and loose of relevant data (serious in small datasets)




# The data analysis process

## Learning evaluation (II)

### Crossvalidation

1. Divide dataset in folds
2. Take one fold for validation
3. Train with the other folds
4. Validate and compute performance
5. Take another fold and repeat until finish
6. Average performance measures



(Source)

Usually we use 10 folds

- 10-fold cross validation (or 10-CV)

# The data analysis process

## Learning evaluation (III)

Select a measure to evaluate learning

- Proper measures depends on the problem

Classification learning measures

- Accuracy: Ratio of correct predictions
- F-Measure
- Confusion matrix
- ROC curve

Regression learning measures

- Mean Absolute Error (MAE)
- Mean Squared Error (MSE)
- $R^2$

Validation error must be taken, always, on the validation set

### Confusion matrix

		Predicted class		
		Class A	Class B	Class C
Actual class	Class A	100	0	10
	Class B	10	80	10
	Class C	30	0	70

(Source)

# The data analysis process

## Model exploitation

Model exploitation depends on the objectives

- In Data Science, the model is interpreted and a report written
  - Formal report, bussiness intelligence dashboard, ...
- In Machine Learning, the model is integrated into a software system
  - Web application, app, robot controller, ...

The model may need maintenance

# Types of Machine Learning systems

## Overview

We can classify ML systems based on several (non-exclusive) criteria

- Whether or not they are trained with supervision
  - Supervised, unsupervised, semisupervised and Reinforcement Learning
- Whether or not they can learn incrementally
  - Online vs. batch learning
- When forecasting is done
  - Nowcasting vr. forecasting
- Type of analytics
  - Descriptive, predictive or prescriptive
- The goal of the system
  - Discriminative models vs. generative models
- The interpretation of the model
  - Predictive models (blackbox) vs. explicative models (whitebox)

# Types of Machine Learning systems

## Supervised learning (I)

In supervised learning input data comes along with the desired output

- Usually human beings label the output (named **labels**)

$f_1$	$f_2$	$\dots$	$f_n$	$\gamma$
$a_{1,1}$	$a_{2,1}$	$\dots$	$a_{n,1}$	$\gamma_1$
$a_{1,2}$	$a_{2,2}$	$\dots$	$a_{n,2}$	$\gamma_2$
$a_{1,3}$	$a_{2,3}$	$\dots$	$a_{n,3}$	$\gamma_3$
$a_{1,4}$	$a_{2,4}$	$\dots$	$a_{n,4}$	$\gamma_4$
$a_{1,5}$	$a_{2,5}$	$\dots$	$a_{n,5}$	$\gamma_5$

Two main tasks in supervised learning

- Classification** if  $\gamma$  is a categorical attribute. Target attribute named **class**
- Regression** if  $\gamma$  is numerical


Advanced supervised learning tasks

- Semi-supervised learning, weakly supervised learning and multilabel classification

# Types of Machine Learning systems


## Supervised learning (II)

### Classification



(Source)

### Regression



(Source)

# Types of Machine Learning systems

## Supervised learning (III)

### Important classification algorithms:

- k-Nearest Neighbors
- Support Vector Machines (SVMs)
- Decision Trees
  - ID3, C4.5 (J48), ...
- Rules
  - PART, CN2, AQ, ...
- Random Forests
- Bayesian Networks
- Neural Networks
- Ensembles

### Important regression algorithms:

- Linear Regression
- Logistic Regression
- Symbolic Regression
- Regression trees
  - LM3 (M5), ...
- Neural Networks

# Types of Machine Learning systems

## Supervised learning: Classification (I)

Example: Bank credit risk management

IDC	Years	Euros	Salary	Own house	Defaulter accounts	Returns credit
101	15	60000	2200	Yes	2	No
102	2	30000	3500	Yes	0	Yes
103	9	9000	1700	Yes	1	No
104	15	18000	1900	No	0	Yes
105	10	24000	2100	No	0	No
...	...	...	...	...	...	...

Objective: Predict if a customer would return a credit or not



# Types of Machine Learning Systems

## Supervised learning: Classification (II)

Años	Euros	Salario	Casa propia	Cuentas morosas	Crédito
10	50000	3000	Si	0	??

Años	Euros	Salario	Casa propia	Cuentas morosas	Crédito
15	60000	2200	Si	2	No
2	30000	3500	Si	0	Si
9	9000	1700	Si	1	No
15	18000	1900	No	0	Si
10	24000	2100	No	0	No
	...	...	...	...	...

Algoritmo  
ML

IF CM > 0 THEN NO


IF CM = 0 Y S > 2500  
THEN SI

Crédito = Si

# Types of Machine Learning systems

## Supervised learning: Classification (III)

Example: Cancerous cells prediction




ID	Colour	nuclei	tails	<i>class</i>
H1	light	1	1	healthy
H2	dark	1	1	healthy
H3	light	1	2	healthy
H4	light	2	1	healthy
C1	dark	1	2	cancer
C2	dark	2	1	cancer
C3	light	2	2	cancer
C4	dark	2	2	cancer

# Types of Machine Learning systems

## Supervised learning: Classification (IV)

Example: Cancerous cells prediction



### Decision rules

```


if colour = light and nuclei = 1
then cell = healthy    ^^I
^^I^^I^^I^^I
if nuclei = 2 and colour = dark
then cell = cancerous

(and 4 rules more)
    
```

# Types of Machine Learning systems

## Supervised learning: Classification (V)

Example: Cancerous cells prediction



Hierarchical decision rules

```

if colour = light and nuclei = 1
then cell = healthy    ^^I
^^I^^I^^I^^I
else
    if nuclei = 2 and colour = dark
    then cell = cancerous



    else
        if tails = 1
        then cell = healthy

        else cell = cancerous
    
```

# Types of Machine Learning systems

## Supervised learning: Classification (VI)



Example: Cancerous cells prediction



# Types of Machine Learning systems

## Supervised learning: Classification (VII)

Example: Cancerous cells prediction




# Types of Machine Learning systems

## Supervised learning: Regression (I)

Example: Does money make people happier? (example from (Géron, 2017))

Country	GDP	LS
Hungary	12,240	4.9
Korea	27,195	5.8
France	37,675	6.5
Australia	50,962	7.3
USA	55,805	7.2

LS =Life satisfaction



# Types of Machine Learning systems

## Unsupervised learning

In unsupervised learning there are no labels

$f_1$	$f_2$	$f_3$	$\dots$	$f_n$
$a_{1,1}$	$a_{2,1}$	$a_{3,1}$	$\dots$	$a_{n,1}$
$a_{1,2}$	$a_{2,2}$	$a_{3,2}$	$\dots$	$a_{n,2}$
$a_{1,3}$	$a_{2,3}$	$a_{3,3}$	$\dots$	$a_{n,3}$
$a_{1,4}$	$a_{2,4}$	$a_{3,4}$	$\dots$	$a_{n,4}$
$a_{1,5}$	$a_{2,5}$	$a_{3,5}$	$\dots$	$a_{n,5}$

Tasks in unsupervised learning

- Clustering
- Association rules
- Dimensionality reduction
- Anomaly detection





# Types of Machine Learning systems

## Unsupervised learning: Clustering (I)

Clustering is a set of techniques that identify groups of data (**clusters**)

- Algorithms: K-means, db-scan, Gaussian Mixture Models (GMM), Expectation Maximization (EM), ...




(Source)

# Types of Machine Learning systems

## Unsupervised learning: Clustering (II)

Example: Cluster word-sentence length in a books corpus



Clusters interpretation

- Long words and sentences: Philosophy?
- Short words and sentences: Novel?

# Types of Machine Learning systems

## Unsupervised learning: Clustering (III)

Example: Human resources department wants to know their employees profiles

Salary	Married	Car	Child.	Rent/owner	Syndicated	Leaves	Sen.	Sex
1000	Yes	No	0	Rent	No	7	15	M
2000	No	Yes	1	Rent	Yes	3	3	F
1500	Yes	Yes	2	Owner	Yes	5	10	M
3000	Yes	Yes	1	Rent	No	15	7	F
1000	Yes	Yes	0	Owner	Yes	1	6	M

# Types of Machine Learning systems

## Unsupervised learning: Clustering (IV)

	Group 1	Group 2	Group 3
Salary	1535	1428	1233
Married	77 %	98 %	0 %
Car	82 %	1 %	5 %
Child.	0.05	0.3	2.3
Rent/owner	99 %	75 %	17 %
Syndicated	80 %	0 %	67 %
Leaves	8.3	2.3	5.1
Seniority	8.7	8	8.1
Sex (M/F)	61 %	25 %	83 %


### Analysis:

- Group 1: No children, with rented house. Low syndication. Many sick leaves.
- Group 2: No children, with car. High syndication. Low sick leaves. Usually women and rent.
- Group 3: With children, married, with car. Usually owners men. Low syndication.

# Types of Machine Learning systems

## Unsupervised learning: Clustering (V)

Example: Cells number count



# Types of Machine Learning systems

## Unsupervised learning: Association rules (I)

Association rules seek relations among attributes

$f_1$	$f_2$	$f_3$	$\dots$	$f_n$
$a_{1,1}$	$a_{2,1}$	$a_{3,1}$	$\dots$	$a_{n,1}$
$a_{1,2}$	$a_{2,2}$	$a_{3,2}$	$\dots$	$a_{n,2}$
$a_{1,3}$	$a_{2,3}$	$a_{3,3}$	$\dots$	$a_{n,3}$
$a_{1,4}$	$a_{2,4}$	$a_{3,4}$	$\dots$	$a_{n,4}$
$a_{1,5}$	$a_{2,5}$	$a_{3,5}$	$\dots$	$a_{n,5}$

Main association algorithms

- Apriori, Eclat, GP-growth

Algorithm output

- Rules
- Confidence: How often the rule is true
- Support: How often the rule applies

# Types of Machine Learning systems

## Unsupervised learning: Association rules (II)

Example: Market basket analysis

- A supermarket wants to gather information about its clients shopping behaviour

Objective

- Identify complementary items
- Enhance product placement

Id	Eggs	Oil	Diapers	Wine	Milk	Butter	Salmon	Lettuce	...
1	Yes	No	No	Yes	No	Yes	Yes	Yes	...
2	No	Yes	No	No	Yes	No	No	Yes	...
3	No	No	Yes	No	Yes	No	No	No	...
4	No	Yes	Yes	No	Yes	No	No	No	...
5	Yes	Yes	No	No	No	Yes	No	Yes	...
6	Yes	No	No	Yes	Yes	Yes	Yes	No	...
7	No	No	No	No	No	No	No	No	...
8	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	...
...	...	...	...	...	...	...	...	...	...

# Types of Machine Learning systems

## Unsupervised learning: Association rules (IV)

### Association rules

```
if  diapers=yes  
then milk=yes (100 %, 37 %)
```

```
if  eggs=yes  
then  oil=yes (50 %, 25 %)
```

```
if  wine=yes  
then lettuce=yes (33 %, 12 %)
```

where (confidence, support)



# Types of Machine Learning systems

## Unsupervised learning: Dimensionality reduction (I)

Dimensionality reduction transforms data into more convenient representations

- Reduce data dimensionality
- Visualize multidimensional data


Main algorithms

- Isomap
- Principal Components Analysis (PCA)
- T-distributed Stochastic Neighbor Embedding (t-SNE)

# Types of Machine Learning systems

## Unsupervised learning: Dimensionality reduction (II)

### Example: Isomap




(Source)

# Types of Machine Learning systems

## Unsupervised learning: Dimensionality reduction (III)

### Example: PCA





(Source)

# Types of Machine Learning systems

## Unsupervised learning: Dimensionality reduction (IV)

Example: Hand-written digits recognition

- Images of hand-written digits
- 8x8 images (64 dimensions)
- 10 digits
- Classification problem




# Main challenges of Machine Learning

## Under and overfitting

**Underfitting:** Does not learn

- Topology too simple
- The model does not fit data
- Solution:
  - Increase model complexity



(Source)

**Overfitting:** Memorizes samples

- Topology too complex
- Very serious concern in ML
- The model does not generalize data
- Model fails when exposed to new data
- Solutions:
  - Reduce model complexity
  - Increase dataset
  - Apply regularization

# Main challenges of Machine Learning

## The curse of dimensionality


ML algorithms are statistical by nature

- Count frequency of observations in regions

Fewer observations per region as dimensionality increases

- Data become sparser
- Need of more data to keep patterns
- Increased overfitting risk

Goal: Reduce dimensionality as much as possible




(Source)

# Main challenges of Machine Learning

## Other challenges

- Insufficient data
  - Given enough data, algorithms tend to similar performance
  - Remember: ML is data-centric
- Non representative training data
- Poor quality data
- Irrelevant features
- Unbalanced datasets



(Source)

# Case studies

## Case study 1: Bank propensity model

### Client

- Bank

### Business problem

- Identify those clients prone to buy a service

### Data

- Available on several databases
- Historical data on service acquisition available

### Propose a solution to:

- Data acquisition
- ML task
- Predictive or explicative model
- Model exploitation
- Model maintenance



# Case studies

## Case study 2: Social media campaign impact

### Client

- Car manufacturer

### Business problem

- Real-time analysis of a campaign impact in Twitter
- Answer if people have a positive reaction to the campaign

### Data

- None

### Propose a solution to:

- Data adquisition
- ML task
- Predictive or explicative model
- Model explotation
- Model maintenance

# Case studies

## Case study 3: Hubble FGS-3 servo failure prediction

### Client

- NASA

### Business problem


- Predict Hubble FGS-3 servo failure

### Data

- Compensated error telemetry
- Servo will fail if compensated error exceeds a threshold

### Propose a solution to:

- ML task
- Predictive or explicative model
- Model exploitation
- Model maintenance



# Case studies

## Case study 4: Fall detection with triaxial accelerometer

### Client

- Technological start-up

### Business problem


- Detect falls with a smartwatch
- Improve elderly people attention

### Data

- None

### Propose a solution to:

- Data adquisition
- ML task
- Data preprocessing
- Model explotation
- Model maintenance



(More info)

# Case studies

## Case study 5: Fall detection with sound

### Client

- Technological start-up

### Business problem


- Detect falls with sound
- Improve elderly people attention

### Data

- None

### Propose a solution to:

- Data adquisition
- ML task
- Data preprocessing
- Model explotation
- Model maintenance



Energy Mean	Energy Std
Number of Zeros Mean	Number of Zeros Std
Spectral Flux Mean	Spectral Flux Std
Roll off Factor Mean	Roll off Factor Std
Spectral centroid Mean	Spectral Centroid Std

(More info)

# Case studies

## Case study 6: NASA JPL BioSleeve

### Client

- NASA JPL Advanced Robotics Group

### Business problem

- Recognize hand gestures (more info)

### Data

- None

### Propose a solution to:

- Data adquisition
- ML task



(Source)



(Source)

Wolf, Michael T., et al. Decoding static and dynamic arm and hand gestures from the JPL BioSleeve. IEEE Aerospace Conference. IEEE, 2013.

(Solution) (Results)

# Case studies

## Case study 7: UAV terrain classification

### Client

- NASA JPL Advanced Robotics Group

### Business problem

- Recognize terrain type for automatic UAV landing
- (Video)

### Data

- UAV down-looking camera
- No dataset available

### Propose a solution to:

- Data adquisition
- ML task
- Feature extraction