Quantitative Residual-Risk Validation for SOTIF

From acceptance criteria to scenario-based evidence for an L4 automated driving system

David Feldmann

26 October 2026

Abstract

This report collects, in one place, the quantitative chain needed to argue that the residual risk of an automated driving system is acceptable under ISO 21448 (SOTIF). It starts from an acceptance criterion, derives validation targets for field operational testing, and shows why those targets become infeasible for an L4 system. It then develops scenario-based residual-risk estimation (exposure, parameter distributions with a Gaussian copula, importance sampling), works through a fully synthetic example with 100 logical and 1,000 concrete scenarios for unintended braking, and derives the field data, statistics and safety performance indicators (SPIs) that the argument needs. It closes with a vehicle-level validation strategy for L4, the role of a scenario database, automatic scenario identification, the granularity of ODD tags, arguments for completeness, and how the approach scales from ACC to an urban robotaxi. Every statement taken from the literature carries a pinpoint citation (section, equation, table, page or slide), so the reader can check it at the source.

Highlights

- The Annex C validation target $\tau = -\ln(1-C)/R_{\mathrm{HB}}$ rests on five assumptions that an assessor can attack; each is stated with its source.
- Counting critical scenario runs is not a risk estimate; only weights $w = f/q$ connect test runs to real-world exposure.
- In the synthetic example, the Bayesian 95% bound passes the budget while a Bonferroni bound over 120 estimates fails: the inference method decides the evidence plan.
- Ignoring parameter dependence changed $P(\text{collision} \mid \text{HB})$ by a factor of 1.06 to 3.2 in the example.
- Completeness of a scenario concept cannot be proven; it is argued from construction, explained time, saturation, a risk-weighted remainder and operational monitoring.

Contents

1 Introduction **3**
1.1 Purpose and scope . . . 3
1.2 How sources are cited . . . 3
1.3 Structure . . . 3

2 The SOTIF framework for quantitative validation **3**

3 From acceptance criterion to validation target **4**
3.1 Decomposition of the acceptance criterion . . . 4
3.2 The zero-failure test . . . 5
3.3 Plans that allow k events . . . 6
3.4 What a passed test silently assumes . . . 6
3.5 Ways to reduce the effort . . . 7

4 Scenario-based residual risk **7**
4.1 Direction of the calculation . . . 7
4.2 The estimator . . . 7
4.3 Counting critical runs is not a risk estimate . . . 8
4.4 Relation to validation targets . . . 9
4.5 Parameterising logical scenarios . . . 10
4.6 Where each conditional probability comes from . . . 10

5 Gaussian copula for scenario parameters **10**
5.1 Definition . . . 10
5.2 Sampling and density . . . 10
5.3 Fitting . . . 11
5.4 Limitation: no tail dependence . . . 11

6 Worked example: unintended braking with 1,000 concrete scenarios **12**
6.1 Set-up . . . 12
6.2 Checks of the importance sampling . . . 13
6.3 Results . . . 14
6.4 Evidence needed . . . 17

7 Field data, statistics and safety performance indicators **18**
7.1 Data to collect . . . 18
7.2 Statistics . . . 19
7.3 Safety performance indicators . . . 20

8 L4 validation, the scenario database and completeness **21**
8.1 Vehicle-level V&V strategy . . . 21
8.2 What the scenario database contributes . . . 22
8.3 From recordings to the database . . . 22

8.4 Identifying scenarios automatically 22
8.5 ODD tags: coverage and granularity 23
8.6 Arguing completeness 24
8.7 OpenLABEL and ISO 34504 26

9 Scaling to ACC and an L4 robotaxi **26**

10 Limitations **27**

A Code and reproduction **27**

1 Introduction

1.1 Purpose and scope

The report supports a SOTIF engineer who must build and defend the quantitative part of a residual-risk argument for a Level 4 system. It covers the statistics behind validation targets, scenario-based risk estimation, the data that feeds it, and how the pieces fit into a vehicle-level validation strategy. It does not cover ISO 26262 hardware metrics or cybersecurity.

1.2 How sources are cited

Citations give the location inside the source in square brackets, for example [9, Sec. IV-B, Eq. (1)] or [11, p. 3, Eq. 2]. Every location was checked twice against the source texts in October 2026, the second time by verbatim quotation. Four conventions apply:

- **ISO 21448.** All references to ISO 21448 were checked directly against ISO 21448:2022(E), first edition 2022-06, and give clause, formula, figure or table and the page number as printed in the standard, e.g. [1, C.3, Formula (C.7), p. 137].
- **Other standards.** ISO/TS 5083 and UL 4600 were not available; their clause and page references are taken from the secondary source named in the same citation, e.g. "ISO/TS 5083, p. 146, as cited in [10, Sec. I]".
- **Location not verified.** Where only the source, not the location, could be checked, the citation says so.
- **Own results.** Numbers computed for this report are marked *(this report, Sec. x / Fig. y)*. All example data are synthetic, marked ^{S}, and describe no real system. The code that produces them is listed in Appendix A.

1.3 Structure

Section 2 summarises the SOTIF framework for quantitative validation. Section 3 derives validation targets from acceptance criteria. Section 4 develops scenario-based risk estimation, and Section 5 the Gaussian copula for scenario parameters. Section 6 works through the unintended-braking example. Section 7 covers field data, statistics and SPIs. Section 8 treats the L4 vehicle-level strategy, the scenario database and completeness. Section 9 discusses scaling to ACC and a robotaxi, and Section 10 lists limitations.

2 The SOTIF framework for quantitative validation

ISO 21448 defines the SOTIF as the absence of unreasonable risk due to hazards resulting from functional insufficiencies of the intended functionality or its implementation [1, 3.25, p. 8]. The scenarios of the relevant use cases are classified into four areas: known not hazardous (area 1), known hazardous (area 2), unknown hazardous (area 3) and unknown not hazardous (area 4); the goal is to reduce areas 2 and 3 to an acceptable level, area 3 through the V&V strategy of Clauses 9 and 11 [1, 4.2.2, Figures 5–6, pp. 12–14]. The standard stresses that the size of the areas represents the number of scenarios, not the risk, and is not measurable [1, 4.2.2, Notes 2–3, p. 14]. The clauses relevant here are:

- **Clause 6:** acceptance criteria are specified for the risks associated with each hazardous behaviour [1, 6.5, p. 30]; an acceptance criterion is a "criterion representing the absence of an unreasonable level of risk" [1, 3.1, p. 2].

- **Clause 9:** the V&V strategy, "including validation targets", shall consider the "sufficient coverage of the relevant scenario space" and a rationale for the selected methods and validation targets [1, 9.1 a)–b), p. 42]. A validation target is a "value to argue that the acceptance criterion is met", and more than one validation target can be needed for one acceptance criterion [1, 3.33 and Note 3, p. 10].
- **Clause 10:** known hazardous scenarios are not unreasonable if their probability of causing hazardous behaviour complies with the validation targets and no known scenario leads to unreasonable risk for specific road users [1, 10.7, pp. 49–50].
- **Clause 11:** "the validation results shall demonstrate that the residual risk from unknown hazardous scenarios meets the acceptance criteria with sufficient confidence" [1, 11.1, p. 50]; Table 11 lists the methods, including fleet tests, simulation of random scenario sequences, sensitivity analysis and scenario exploration in the real world [1, 11.3, Table 11, p. 51].
- **Clause 12:** the evaluation asks whether the V&V strategy covers all known hazardous scenarios and argues that the residual risk from unknown ones meets the acceptance criteria with sufficient confidence [1, 12.3 c), p. 54].
- **Clause 13:** a field monitoring process shall be defined before release and executed during operation [1, 13.1, p. 55].
- **Annex C:** guidance on V&V, from deriving validation targets (C.2) to statistics (C.3), scenario parameterisation and sampling (C.5) and reductions of testing (C.6) [1, C.1, pp. 125–126].

Acceptance criteria can be justified by GAMAB/GAME, a positive risk balance, ALARP or MEM, alone or in combination [1, 6.5, pp. 30–31]; Betschinske et al. give the same list [10, Sec. III-B, item 2]. A secondary summary of the clauses is in [12, Sec. 2.1, pp. 6–10].

ISO 21448 also defines a *vehicle-level SOTIF strategy* (VLSS): a set of vehicle-level *requirements* for the intended functionality, such as transitions to degraded states on ODD exit [1, 3.34, p. 10; D.1, p. 159]. The VLSS is the overarching specification and is itself verified according to the V&V strategy of Clause 9 [1, D.1, p. 159]. This report therefore calls the test plan the *vehicle-level V&V strategy*, not the VLSS.

For L4 systems, ISO 21448 is complemented by:

- **ISO/TS 5083**, the ADS-level standard (positive risk balance is already one of the rationales of ISO 21448 6.5). Betschinske et al. quote its statement that, for L3, "a similar amount of real-world test driving as for state-of-the-art L2 systems" seems appropriate (ISO/TS 5083, p. 146, as cited in [10, Sec. I]), and argue that carrying the L2 derivation to higher levels gives infeasible targets [10, Sec. I].
- **ANSI/UL 4600**, which defines safety performance indicators (Sec. 7.3) (UL 4600 Ch. 16, as cited in [21, Sec. 2] and [22, slide 12]).
- **The UNECE NATM multi-pillar approach** (audit, simulation, track, real-world testing, in-service monitoring; ECE/TRANS/WP.29/2021/61), on which Commission Implementing Regulation (EU) 2022/1426 builds [8, web article, no sections].

3 From acceptance criterion to validation target

3.1 Decomposition of the acceptance criterion

ISO 21448 decomposes the acceptance criterion A_H for a harm H, "assuming that a hazardous behaviour does not lead always to a harm", as

$$A_H = R_{\mathrm{HB}} \cdot P(E \mid \mathrm{HB}) \cdot P(\bar{C} \mid E) \cdot P(S \mid \bar{C}) \tag{1}$$

[1, C.2.1, Formula (C.1), p. 127]; the same formula is discussed in [9, Sec. IV-B(a), Eq. (1)] and [10, Sec. V, Eqs. (6)–(7)]. The standard writes $P_{E|HB}$, $P_{C|E}$ and $P_{S|C}$: $P_{C|E}$ is "the probability that the hazardous behaviour is not controllable", and $P_{S|C}$ the probability of a degree of severity "assuming that the controllability action was not successful" [1, C.2.1, p. 126]; this report writes $\bar{C}$ to make that explicit. Solving for R_{HB} gives the tolerable hazardous-behaviour rate [1, C.2.1, Formula (C.2), p. 127]. The standard's example: $A_H = 10^{-8}/\mathrm{h}$, $P_{C|E} = 10\%$, $P_{S|C} = 1\%$, $P_{E|HB} = 5\%$ give $R_{\mathrm{HB}} = 2 \times 10^{-4}/\mathrm{h}$, and 5,000 h without hazardous behaviour show the criterion met with 63% confidence [1, C.2.1, Formula (C.3) and Example, p. 127].

Putze et al. raise three objections [9, Sec. IV-B(b)]; the standard's own wording, given after each, answers them only in part:

1. A correct chain-rule decomposition needs further conditioning, e.g. $P(S \mid \bar{C}, E, \mathrm{HB})$ instead of $P(S \mid \bar{C})$. The standard notes that the product of simple probabilities applies when the triggering conditions are independent of the exposure [1, C.2.1, Note 5, p. 127].
2. Annex C.2.1 omits the aggregation over several hazardous behaviours leading to the same harm, without flagging this as a simplification. The standard links every hazardous behaviour to its own acceptance criterion and derives A_H "from original acceptance criteria in combination with safety margin" [1, C.2.1, p. 126], but does not say how the original criterion is split.
3. Field-data quantities are not system-independent: exposure depends on route planning and the ODD; their example is the probability of a truck in front [9, Sec. IV-B(c)]. The standard says the parameters "can be checked for consistency" with the ISO 26262 HARA [1, C.2.1, Note 4, p. 127].

They therefore bound the harm probability over triples of triggering condition T, behaviour B and event E:

$$P(H) \leq \sum_{T,B,E} P(T)\, P(B \mid T)\, P(E \mid B, T)\, P(H \mid E, B, T) \tag{2}$$

[9, Sec. IV-B(b), Eq. (2); severity-stratified form Eq. (3)], and conclude that "it is not sufficient to derive a single validation target" [9, Sec. IV-B(b), last paragraph].

3.2 The zero-failure test

Assuming that incidents have a Poisson distribution, ISO 21448 gives the driving τ without potentially hazardous behaviour needed to show an incident rate $\leq A_H$ "with a confidence α" as $\tau = -\ln(1-\alpha)/A_H$ [1, C.3, Example 3 and Formula (C.7), p. 137], taken from Littlewood and Wright [24]. Applied to the tolerable rate of Eq. (1), as in the standard's own example [1, C.2.1, p. 127] and in [9, Sec. IV-B(a)], and writing C for the confidence:

$$\tau = \frac{-\ln(1-C)}{R_{\mathrm{HB}}} \tag{3}$$

For $C \approx 0.63$, $\tau = 1/A_H$ [1, C.3, Note 2, p. 137]. The standard adds that τ "can be quite large and therefore not practical in some cases" and can be lessened with expert knowledge and MIL, SIL and HIL kilometres [1, C.3, p. 137]; Betschinske et al. call it the real-world driving requirement [10, Sec. III-C, item 5, Eq. (5)]. Betschinske et al. write the test as $H_0 : R > A_H$ against $H_1 : R \leq A_H$ with the type-I error bound $P(X \leq k) \leq \alpha$, $\lambda = A_H \tau_k$ [10, Sec. III-C, Eqs. (3)–(4)].

Notation trap. In Formula (C.7) α is the *confidence* [1, C.3, p. 137], and Putze et al. follow this [9, Sec. IV-B(a)]. In C.6.3.2 the same standard writes the confidence as $1-\alpha$, i.e. α is an error level [1, C.6.3.2, Example 1, p. 156], and Betschinske et al. use α as type-I error, so their Eq. (5) reads $-\ln(\alpha)/A_H$ [10, Sec. III-C, Eq. (5)]. This report writes C for confidence throughout.

At $C = 0.95$, $-\ln 0.05 \approx 3.00$ (the "rule of three"). Kalra and Paddock use the per-mile form $n = \ln(1-C)/\ln(R)$ with reliability $R = 1-F$ [11, Sec. 1, p. 3, Eq. 2]. With the US fatality rate of 1.09 per 100 million miles in 2013 [11, Introduction, p. 2], this gives 275 million failure-free miles, or about 12.5 years for 100 vehicles driving 24/7 at 25 mph [11, Sec. 1, p. 3; Table 1, p. 10]. Demonstrating a fatality rate 20% below the human rate with 95% confidence and 80% power takes more than 11 billion miles, about 518 years [11, Sec. 3, p. 8].

The standard notes that acceptance criteria are usually very small, e.g. 10^{-8}/h [1, C.2.1, p. 126]. Schaller et al. give the example criterion "overlooking a car on the other lane is at most 10^{-9} per hour", the order of magnitude used in civil aviation for extremely improbable failure conditions, and call the testing needed to prove it prohibitive [12, Sec. 5.1, p. 14]. Equation (3) gives 3.0×10^9 h, about 342,000 vehicle-years of 24/7 operation *(this report, Sec. 3)*.

3.3 Plans that allow k events

If the plan allows k events, the pass condition $P(X \le k \mid \lambda) \le 1 - C$ is solved by

$$\tau_k = \frac{\lambda_k(C)}{R_{\mathrm{HB}}}, \qquad \lambda_k(C) = \tfrac{1}{2}\,\chi^2_{2(k+1)}(C), \tag{4}$$

the classical relation between Poisson confidence limits and the χ^2 distribution [25, location not verified]. Table 1 gives the factors *(this report, computed with SciPy)*.

Table 1: Factors $\lambda_k(C)$ for plans allowing k events *(this report, computed)*.

$C \setminus k$	0	1	2	3	4	5
0.90	2.303	3.890	5.322	6.681	7.994	9.275
0.95	2.996	4.744	6.296	7.754	9.154	10.513
0.99	4.605	6.638	8.406	10.045	11.605	13.108

k and τ must be fixed before testing: under classical hypothesis testing, the test cannot be extended after a failure without inflating the type-I error [10, Sec. III-C, item 6]. ISO 21448 likewise lists, among what the system owner specifies prior to testing, the validation target as "stopping rule" and the "criterion for restarting distance counter" [1, C.3, p. 136]. Raising C from 0.95 to 0.99 multiplies τ by $\ln 0.01/\ln 0.05 = 1.54$; allowing $k = 1$ at $C = 0.95$ multiplies it by 1.58 *(this report, Table 1)*.

3.4 What a passed test silently assumes

1. **Homogeneous Poisson process**: constant rate and independent events (the Poisson assumption in [9, Sec. IV-B(a)]).
2. **Representative exposure**: the tested mix of conditions equals the deployed mix; the factors in Eq. (1) are system-dependent [9, Sec. IV-B(b)–(c)].
3. **Frozen software**: a fix invalidates earlier hours unless carry-over is argued; the standard's example assumes "sensor and algorithms are fixed during testing and real-world use" [1, C.6.3.2, p. 154], and new unknown hazardous scenarios can arise with algorithm, ODD or driving-policy changes [1, 11.3, Note 1, p. 52]; reusing earlier systems' data is a main validity gap [10, Sec. V, RA "Decomposition of Hazardous Behavior" and "Bayesian Statistics"].
4. **One behaviour per harm**: otherwise rates add, Eq. (2) [9, Sec. IV-B(b)]. Aggregating separately validated terms gives a joint confidence of at least $1 - (\alpha_1 + \alpha_2)$ [1, C.6.3.2, Example 1 and footnote 1, p. 156]. (Betschinske et al. cite this as "p. 165" [10, Sec. V, RA "Decomposition of Hazardous Behavior"]; in the printed standard it is on p. 156.)

5. **Frequentist meaning**: a system exactly at the limit passes with probability at most $1-C$; a posterior statement needs a prior. The flat prior Gamma$(1, 0)$ reproduces the base model, Jeffreys' Gamma$(0.5, 0)$ lowers the requirement [10, Sec. V, RA "Bayesian Statistics"].

3.5 Ways to reduce the effort

The standard itself offers: focusing validation on the most severe modality of a partitioned usage variable [1, C.6.1, p. 153]; sufficient conditions at component level, e.g. $E[\text{collisions}] \leq P(D_m > c)\, E[\text{objects}]$ with separately estimated factors [1, C.6.2, p. 153; C.6.3.2, pp. 154–156]; and redundant, independent channels [1, C.6.3.3, pp. 156–158]. Betschinske et al. review further reduction approaches. Sequential testing (Wald's SPRT) allows optional stopping only if both hypotheses are set at or stricter than the acceptance threshold, $\theta_0, \theta_1 \geq \theta_{A_H}$, and gives a reduction only if $\beta > 1 - c$ with $c = \frac{\theta_0}{\theta_1}\alpha^{\theta_0/\theta_1}$ [10, Sec. V, RA "Sequential Testing", Eqs. (14)–(15)]. Further approaches are decomposition of the hazardous behaviour [10, Sec. V, Eqs. (8)–(9)], high-yield route profiles with importance-sampling correction [10, Sec. V, RA "High Yield Route Profiles", Fig. 12], extreme value analysis [10, Sec. V, RA "Extreme Value Analysis", Table IX] and scenario-based testing [10, Sec. V, RA "Scenario Based Testing", Table XI]. Direct mileage-based validation of upper bounds on harm probability is not feasible for ADS [9, Sec. IV-A(b), citing Wachenfeld and Winner], and a residual dependence on field testing is likely to remain [10, Sec. VII].

4 Scenario-based residual risk

4.1 Direction of the calculation

A HARA is built from the system outward: hazardous behaviour, hazardous event, scenarios. Probability flows the other way: the world produces situations at some rate, and the system responds with a hazardous behaviour or not. For the risk calculation the scenario is the random variable and the behaviour is conditioned on it. Logical scenarios must partition the ODD; overlapping scenarios double-count exposure, and then only the bound (2) holds [9, Sec. IV-B(b), Eq. (2)].

4.2 The estimator

For a severity class s and logical scenarios ℓ with exposure ν_ℓ (occurrences or time share per operating hour) and parameter distribution $f_\ell(\theta)$:

$$R_s = \sum_\ell \nu_\ell\, p_{\ell,s}, \qquad p_{\ell,s} = \int P(\text{HB} \mid \theta, \ell)\, P(S \geq s \mid \text{HB}, \theta, \ell)\, f_\ell(\theta)\, d\theta. \tag{5}$$

De Gelder computes risk in the same spirit, by combining the outcome of virtual simulations with the estimated likelihood of scenarios, and decomposes it into exposure, crash probability and severity [14, Ch. 1 and Ch. 7, Secs. 7.3.2, 7.3.4, 7.3.5]. From N concrete runs drawn from a test distribution q_ℓ, the importance-sampling estimator is

$$\hat{p}_{\ell,s} = \frac{1}{N}\sum_{i=1}^{N} w_i h_i, \qquad w_i = \frac{f_\ell(\theta_i)}{q_\ell(\theta_i)}, \qquad \text{ESS} = \frac{(\sum_i w_i)^2}{\sum_i w_i^2} \tag{6}$$

(importance sampling and effective sample size: [32, Ch. 9]). ISO 21448 describes the same building blocks: parameter distributions determined from naturalistic driving data, e.g. by kernel density estimation [1, C.5, Figures C.9–C.11, pp. 146–148], importance sampling that biases the test parameters towards riskier areas [1, C.5, Figures C.12–C.14, pp. 149–151], and a final risk estimate "based on the simulation results and depending on the acceptance criteria" [1, C.5,

p. 151]. Zhao et al. apply importance sampling with cross-entropy-optimised proposals to lane-change scenarios from naturalistic data and report acceleration factors of about 2,000 to 20,000 [20, Abstract].

4.3 Counting critical runs is not a risk estimate

Figure 1 shows why. In a toy cut-in model, a uniform test design puts 5.4% of its runs in the failure region, while the real-world probability of failure per cut-in is 4.9×10^{-5} *(this report, Fig. 1[S])*. Non-critical runs are evidence too. Falsification and criticality search find triggering conditions (Clause 10), but do not estimate risk unless q is known. Figure 2 shows importance sampling converging long before plain Monte Carlo sees its first collision.




Figure 1: Toy cut-in[S]: test runs of a uniform design against the real-world density. 5.4% of runs are critical; the real-world failure probability is 4.9×10^{-5} *(this report, computed)*.




Figure 2: Running estimate of $P(\text{collision} \mid \text{HB})$ for one logical scenario[S]: plain Monte Carlo versus importance sampling, against a 200,000-run reference of 0.0157 *(this report, computed).*

4.4 Relation to validation targets

The single target τ of Eq. (3) is replaced by one claim with several evidence targets:

$$\sum_{\ell} \nu_{\ell}^{U}\, p_{\ell,s}^{U} + R_{\text{unknown}}^{U} \le A_s \quad \text{at confidence } C, \qquad \sum_{i} (1 - C_i) \le 1 - C, \tag{7}$$

where superscript U marks upper confidence bounds and the confidence budget is split by Bonferroni's inequality.

Table 2: Evidence targets that replace the single field-test target.

Term	Validation target	Measured in
ν_{ℓ}^{U}	enough naturalistic data per scenario class (Poisson bound on counts)	hours of ODD data
f_{ℓ}	estimation error of the fitted distribution below a threshold; de Gelder quantifies completeness via the expected approximation error of a KDE [14, Ch. 3]	scenario instances
p_{ℓ}^{U}	upper bound per scenario; plain Monte Carlo with zero failures needs $N = 3/p^{*}$ runs, so importance sampling is required	runs, ESS
simulation credibility	real-versus-simulated agreement for the same θ; "how accurately the models represent the real world is part of the safety argument" [1, C.1, p. 125]; NATM includes a credibility assessment framework [8, web article]	proving ground, replays
R_{unknown}^{U}	field driving without unexplained HB, Eq. (3) restricted to what the taxonomy misses	hours

Scenario-based testing lacks a direct quantitative link to mileage and an agreed coverage threshold [10, Sec. V, RA "Scenario Based Testing", Table XI]. It shrinks the field-testing target but does not remove it [10, Sec. VII].

4.5 Parameterising logical scenarios

1. Define the scenario type and its parameters, following the logical/concrete distinction of ISO 34502 [2, location not verified]; ISO 21448 parameterises a lead-braking scenario by v_{end}, t_{brake} and Δv [1, C.5, Figure C.10, p. 147].
2. Keep θ small (3–6 dimensions) by sensitivity analysis; ISO 21448 asks that parameter selection be argued "by, for example, sensitivity analysis or statistical analysis" [1, 11.3, Table 11 Note, p. 51]; Glasmacher et al. list parameter sensitivity analysis in simulation as data-driven evidence [16, Sec. III-D, Table I].
3. Mine instances from drive logs with a scenario tagger [17, Secs. III-A–III-C]; each detection gives one θ sample and one count towards ν.
4. Fit f_ℓ: marginals plus copula (Sec. 5) or kernel density estimation [14, Ch. 3 and Ch. 6].
5. Estimate $\hat{\nu}_\ell = n_\ell/T$ with a Poisson or Gamma interval.
6. Check the partition: no instance may belong to two logical scenarios.

4.6 Where each conditional probability comes from

Table 3: Sources of the terms in Eq. (5).

Quantity	Primary source	Caveat
$\nu_\ell, f_\ell(\theta)$	own fleet logs; public naturalistic data only if the ODD matches	system-dependent, e.g. exposure depends on routing and ODD [9, Sec. IV-B(b)–(c)]
$P(\text{HB} \mid \theta)$	simulation with a perception error model learned from labelled field data; runtime monitors flag near-failure situations [12, Sec. 6.2, pp. 16–17]	simulation fidelity is limited [10, Sec. V, RA "Simulation-based Testing"]
$P(\bar{C} \mid E)$	for L4: evasion by other road users, via reactive agent models, or 1	an assumption to justify
$P(S \mid \text{HB}, \theta)$	simulated Δv and impact angle, then an injury-risk curve, e.g. an omni-directional injury model [23, web page]	carry the curve's confidence band

5 Gaussian copula for scenario parameters

5.1 Definition

By Sklar's theorem, every joint distribution function can be written as $F(x_1, \dots, x_d) = C(F_1(x_1), \dots, F_d(x_d))$ with a copula C [33, Sec. 2.3]. The Gaussian copula is $C_R(u) = \Phi_R(\Phi^{-1}(u_1), \dots, \Phi^{-1}(u_d))$. Each scenario parameter keeps its own marginal, and the correlation matrix R alone sets the dependence.

5.2 Sampling and density

Sampling: $\varepsilon \sim \mathcal{N}(0, I)$, $Z = L\varepsilon$ with $R = LL^\top$, $U_i = \Phi(Z_i)$, $X_i = F_i^{-1}(U_i)$. The copula density, needed for the weights in Eq. (6), is

$$c_R(u) = |R|^{-1/2} \exp\Big(-\tfrac{1}{2} z^\top (R^{-1} - I) z \Big), \quad z = \Phi^{-1}(u), \qquad f(x) = c_R(F(x)) \prod_i f_i(x_i). \tag{8}$$




Figure 3: Marginals of the real-world model f and the importance-sampling proposal q used in Sec. 6[S].




Figure 4: Independent uniforms, the Gaussian copula with $\rho = -0.4$, and the same draws in physical units[S].

5.3 Fitting

Transform each parameter to pseudo-observations $u = \text{rank}/(n+1)$ and normal scores $z = \Phi^{-1}(u)$, and estimate R as their correlation matrix. Pairwise, Kendall's τ [33, Ch. 5] converts to $\rho = \sin(\pi\tau/2)$ for elliptical copulas [30, location not verified]. R must be positive definite; pairwise estimates may need projection to the nearest correlation matrix.

5.4 Limitation: no tail dependence

For $\rho < 1$ the Gaussian copula has zero upper tail dependence, whereas the t-copula with ν degrees of freedom has $\lambda_U = 2\,t_{\nu+1}\!\left(-\sqrt{(\nu+1)(1-\rho)/(1+\rho)}\right) > 0$ [31, location not verified]. Joint extremes, such as a late reaction combined with weak braking, are therefore under-represented if real data show tail dependence (Fig. 5).




Figure 5: Same correlation, different joint extremes[S]: 33 (Gaussian) versus 77 (t, $\nu = 3$) draws in the top-1% corner out of 20,000; independence would give about 2 *(this report, computed).*

6 Worked example: unintended braking with 1,000 concrete scenarios

6.1 Set-up

Everything in this section is synthetic[S]. The set-up follows the structure of the standard's own AEB example, in which unintended braking for longer than 340 ms with a closely following vehicle can lead to a rear-end collision, and a Monte Carlo simulation over trailing distance and reaction time estimates the collision probability [1, C.2.2.3, Figures C.1–C.2, pp. 129–130]. The standard finds the collision probability "higher at lower speeds because of the short trailing distance" [1, C.2.2.3, Figure C.3, pp. 130–131], as does this example (Fig. 12). Validation target: MAIS2+ injuries from rear-end collisions caused by unintended (phantom) braking $\leq A_H = 10^{-7}$/h, with 10% reserved for unknown triggers, leaving a budget of 9×10^{-8}/h. The ODD is partitioned into 100 logical scenarios: 5 trigger contexts $\times$ 4 ego speed bands $\times$ 5 follower-headway classes. The hazardous-behaviour rate λ depends on trigger and speed only, so 20 evidence cells serve 100 scenarios. Per logical scenario, 2,000 plain runs from f and 10 importance-sampled runs from q are simulated with a one-dimensional kinematic model ($\Delta t = 0.01$ s); ego speed, follower headway, reaction time and deceleration are coupled by a Gaussian copula with $\rho(v, h) = 0.25$, $\rho(h, T_r) = -0.30$, $\rho(T_r, a_f) = -0.40$. The illustrative injury curve is $P(\text{MAIS2+} \mid \Delta v) = 1/(1 + e^{-(\Delta v - 45)/7})$, Δv in km/h *(this report, App. A).*




Figure 6: Two concrete scenarios with the same phantom brake[S]: contact with a short headway and a late, weak reaction; no contact otherwise.

6.2 Checks of the importance sampling

On 200,000 proposal draws the mean weight is 0.996, and the IS estimate (0.0161) matches 100,000 plain runs (0.0157). Over the 1,000 concrete scenarios the mean weight is 0.98, weights range from 5×10^{-4} to 67, 117 runs end in a collision, and the median ESS per logical scenario is 4.3 of 10 *(this report, Fig. 7)*.




Figure 7: Weights of the 1,000 runs and effective sample size per logical scenario[S].




Figure 8: All 1,000 concrete scenarios[S]; collisions concentrate at short headway and late reaction.

6.3 Results




Figure 9: Verdict[S]: point estimates 2.1×10^{-8} (200,000 runs) and 1.5×10^{-8}/h (1,000 IS runs), Bayesian 95% quantile 7.3×10^{-8}/h (passes), Bonferroni bound over 120 estimates 7.3×10^{-7}/h (fails) *(this report, computed)*.




Figure 10: Exposure shares per factor[S]; scenario share = product (independence assumed).




Figure 11: Hazardous-behaviour rate per evidence cell[S]: observed k/h with exact 95% interval, and the synthetic true rate.




Figure 12: Collision probability, mean Δv and injury probability by speed band and headway[S].




Figure 13: Where the risk sits[S]: attribution from observed counts (left) against attribution with the true rates (right). With 0–4 events per cell, point-estimate attribution is largely Poisson noise.




Figure 14: Cumulative share of the point estimate over the 100 logical scenarios[S]; the top 10 carry 85%.




Figure 15: Posterior of total risk with Jeffreys priors[S], against point estimate, budget and Bonferroni bound. Jeffreys and flat priors as discussed in [10, Sec. V, RA "Bayesian Statistics"].




Figure 16: Per-scenario agreement of 10 IS runs with 2,000 plain runs[S]. 22 scenarios saw no collision in their 10 IS runs although plain Monte Carlo did.




Figure 17: Ratio of $P(\text{collision} \mid \text{HB})$ with the Gaussian copula to the same model with independent parameters, 20,000 runs per cell[S]: 1.06 to 3.2.

6.4 Evidence needed

Minimising total test hours $\sum_j \lambda_k G_j/B_j$ subject to $\sum_j B_j = B$, with G_j the harm weight of cell j, gives $B_j \propto \sqrt{G_j}$ and $T_{\text{total}} = \lambda_k(\sum_j \sqrt{G_j})^2/B$ *(this report, Lagrange multiplier)*. For the Bonferroni claim, 567,800 h are required against 73,500 h available (Fig. 18).




Figure 18: Replay hours per evidence cell, available versus required under the square-root allocation[S].

7 Field data, statistics and safety performance indicators

7.1 Data to collect

Table 4: Field data organised by the term of Eq. (5) it feeds.

Feeds	Data	How
exposure	hours and km with ODD tags per time step, including periods without any scenario	continuous signals plus map and weather lookup
scenario distributions	every occurrence with its parameters	scenario tagger [17, Sec. III]
HB rate	every brake request with its cause, plus suppressed near-HBs	event-triggered raw-data buffer
perception error model	misses and false positives against labelled ground truth, by class, range, occlusion, weather	labelled samples
outcomes	collisions with Δv, near-miss surrogates (min TTC, PET)	rear sensors, incident process
responses	minimal-risk manoeuvres, remote assistance, monitor flags [12, Sec. 4]	system logs
provenance	software hash, configuration, map version, calibration	attached to every hour

Clause 13 lists as topics for observation incidents that caused or could have caused harm or exceeded defined values, the body of knowledge, and context evolution [1, 13.3 a)–c), pp. 56–57]. For higher levels of automation it names on-board monitoring that detects functional insufficiencies before accidents occur, e.g. capturing violations of a minimum distance, scenarios close to triggering a system reaction, unexpected take-overs and scenarios leading to a minimal risk condition, and data storage such as DSSAD/EDR [1, 13.3, Note 1 and Examples 1–2, p. 56]. These are leading SPIs in the sense of Sec. 7.3.

7.2 Statistics

Rates are bounded with Eq. (4) per stratum and software version (Fig. 19); binomial proportions with Clopper–Pearson bounds [26, location not verified]. Near misses can be extrapolated to crash frequencies with extreme value analysis: a generalised Pareto distribution is fitted to exceedances over a threshold [34, Ch. 4]; Betschinske et al. review its use for validation and its open issues [10, Sec. V, RA "Extreme Value Analysis", Table IX].




Figure 19: 95% upper bound on a rate against exposure for 0, 1, 2 observed events *(this report, Eq. (4))*.




Figure 20: Extreme-value extrapolation of synthetic minimum-TTC data[S]: the lowest 5% are fitted with a generalised Pareto tail and extrapolated.

7.3 Safety performance indicators

UL 4600 defines: "An SPI is a metric supported by evidence that uses a threshold comparison to condition a claim in a safety case" (UL 4600, as cited in [21, Sec. 2, "UL4600"]), and states that "relying solely on lagging indicators is not acceptable" (UL 4600 note 16.2.2.6.2, as cited in [21, Sec. 2]). Lagging indicators detect shortcomings from past events; leading indicators identify potential issues before losses, e.g. unexpected fail-safe activations [21, Sec. 2]. Koopman contrasts KPIs ("how well do we drive") with SPIs ("how often are we potentially unsafe") [22, slide 12], lists lagging SPIs [22, slide 6] and leading SPIs [22, slide 7], and gives examples such as a false negative for more than k consecutive frames and violations of a safe clearance limit [22, slide 10]. An SPI violation means its claim is violated, but a claim can be violated without its SPI firing [21, Sec. 2; Sec. 3.1]. Responses range from updating the safety case and SPIs, through restricting operation (reduced speed, geofences) and updating the system, to grounding the fleet [21, Sec. 3.3].

Table 5: Example SPI register for unintended braking *(this report, Sec. 6)*.

Type	SPI	Claim conditioned	Threshold
lagging	rear-end collisions with ego struck, per h, by severity	overall target	A_H
leading	unexplained brake requests per 1,000 h per trigger context	HB rate per context	λ target, Fig. 18
leading	suppressed false-positive brake detections	margin before HB	trend alarm
leading	rear TTC < 1.5 s within 3 s after ego braking	$P(\text{coll} \mid \text{HB})$	simulation prediction
safety case	share of time with follower < 1 s	exposure assumption	χ^2 test
safety case	Kendall's τ(headway, reaction)	copula assumption	CI contains assumed ρ
safety case	rate of unclassifiable scenarios	reserve ε	Eq. (11)

The time an SPI needs to detect a doubling of its rate depends only on the expected count: for a one-sided exact Poisson test at $\alpha = 0.05$ and power 0.8 it takes $\mu^* \approx 9.1$ expected events, so

$T = \mu^*/\lambda$ *(this report, computed).* Lagging SPIs near the acceptance criterion would take decades to centuries for a 50-vehicle fleet (Fig. 21).




Figure 21: Fleet time to detect a 2× drift for 50 vehicles × 3,000 h/yr *(this report, computed).*

8 L4 validation, the scenario database and completeness

8.1 Vehicle-level V&V strategy

Note that ISO 21448 reserves "vehicle-level SOTIF strategy" for a set of vehicle-level requirements (Sec. 2) [1, 3.34, p. 10]; the strategy below is the V&V strategy of Clause 9.

Table 6: Pillars of the vehicle-level V&V strategy (ISO 21448 Clause 9) and the term they feed.

Pillar	SOTIF	Feeds
ODD spec, HARA, triggering-condition analysis	Cl. 5–7	A_s, HB/HE list, scenario taxonomy
component V&V: perception KPIs per ODD stratum, planner checks	Cl. 10	perception error models
scenario-based simulation from the database	Cl. 10	p_ℓ, coverage [12, Sec. 6.2, pp. 16–17]
log replay, XiL, proving ground	Cl. 10	λ per context; sim-to-real bounds
public-road exploration and FOT	Cl. 11	ν, f, R_{unknown} [12, Sec. 6.3, p. 17]
shadow mode, operation	Cl. 13	SPIs [12, Sec. 7, p. 18]
release argument	Cl. 12	Eq. (7) per harm

ISO 21448 expects validation to combine physical (test track, real-world) and simulation testing, with the quantitative target often allocated between them [1, C.1, p. 125], and the V&V strategy to address the ODD boundaries and outside of the ODD as part of the coverage argument [1, 9.2 and Note, p. 43]. The structure matches the NATM pillars of virtual, track and real-world testing, audit and in-service monitoring [8, web article]. Schaller et al. show how a runtime monitor ensemble contributes evidence to Clauses 6, 9–11 and 13 without by itself establishing SOTIF compliance [12, Sec. 1.2, p. 3; Secs. 5–7, pp. 14–18], and propose that the standard make

explicit that residual risk can be quantified from a statistical argument over traffic situations sourced from monitoring data [12, Sec. 8.2, p. 19].

8.2 What the scenario database contributes

1. It makes "known" explicit: the taxonomy is the boundary between known and unknown scenarios.
2. It holds the weights ν_ℓ and $f_\ell(\theta)$, derived from recordings.
3. It generates tests and keeps traceability from triggering condition to hazardous behaviour, hazardous event, requirement and test.
4. It shows coverage per scenario × triggering condition × software version.
5. It stores every run with θ, $q(\theta)$, software hash and outcome, so risk can be recomputed after changes.
6. It moves unknown to known: discovered types become categories.

```
Recording(id, vehicle, sw_hash, map_ver, calib_state, route, hours, raw_uri)
ExposureSlice(recording_id, t0, t1, odd_tags...) -- denominators
ScenarioCategory(id, version, tag_rule, param_schema, partition_key)
Occurrence(id, recording_id, t0, t1, category_id, theta..., odd_tags, min_ttc, hb_flag)
HazardLink(category_id, hb_id, he_id, triggering_condition_id)
TestRun(id, category_id, theta..., q_density, platform, sw_hash, outcome, dv)
```

8.3 From recordings to the database

Raw logs are turned into a reference world model by offline perception and labels, enriched with map, weather and ODD tags for every time step, tagged with actor activities and interactions, and converted into scenario occurrences with parameters read at defined anchor events. This is the tag-based pipeline of Guo et al.: preprocessing [17, Sec. III-A], tagging of actor activities [17, Sec. III-B.1] and interactions [17, Secs. III-B.2, III-B.3], and categorisation by tag combinations [17, Sec. III-C], applied to the Waymo Open Motion Dataset and CARLA data [17, Sec. IV]. Four rules matter: extract with a reference world model, not the stack under test; tag every driven second; attach provenance and a pointer to the raw log window; version the taxonomy and re-tag historical data when it changes.

8.4 Identifying scenarios automatically

Known types. Guo et al. report no incorrect extraction among 116 randomly examined of 215,090 extracted WOMD scenarios, but no precision or recall of individual tags [17, Sec. IV]. A tagger is a classifier, and its errors bias exposure. With measured precision and recall, $\hat{\nu}_\ell = n_{\text{detected}} \cdot \text{precision}/(\text{recall} \cdot T)$ *(this report, Fig. 22).*




Figure 22: Synthetic cut-in tagger[S]: at 0.35 m/s it finds 82% of real cut-ins, and 66% of its detections are real *(this report, computed)*.

New types (Clause 11). (1) A queue of unexplained critical events (low TTC, hard braking, HB flags, monitor flags, disengagements) that match no category, for human review; Schaller et al. propose monitors that flag novel input/output behaviour and unfamiliar activation patterns as candidates for hazard identification [12, Sec. 5.1, pp. 14–15]. (2) Unsupervised clustering of time-window embeddings with outlier flags [18, Abstract]. (3) ODD novelty: conditions outside the specification or rare tag combinations.

8.5 ODD tags: coverage and granularity

ISO 34503 specifies the ODD taxonomy [3, location not verified] and ISO 34504 a tag-based scenario categorisation; ISO 34504 "provides examples rather than instructions on its application and tags" and does not fix values such as the speed difference in "moving faster or slower" [5, web article]. Both are a shared vocabulary, not a sufficient resolution. Tags missing for a given function (overhead structures, road spray or low sun for phantom braking) are derived from the triggering-condition analysis and from structured environment models: Reich's SEM use guide phrases with an environment ontology to identify the environment factors that influence hazardous situations and their risks [13, Sec. 1.3, p. 4], giving a hazard-specific environment model with explicit coverage checks [13, Sec. 1.4, contribution 1.1, p. 6; Sec. 4.1, p. 49].

Granularity criterion. A class may lump values together if a shift of the distribution inside the class cannot move the risk materially:

$$|\Delta R_c| = \nu_c \left| \int_c p(\theta)(f_c^{\text{dep}} - f_c^{\text{test}})d\theta \right| \le \nu_c \, (p_c^{\max} - p_c^{\min}) \, \mathrm{TV}(f_c^{\text{dep}}, f_c^{\text{test}}) \tag{9}$$

(this report, derived). Classes are refined until the sum over classes fits a reserved share δ of the budget. In the example, $P(\text{collision} \mid \text{HB})$ falls from 0.137 to 0.030 inside the shortest headway class, while the 2–3 s class is flat (Fig. 23).




Figure 23: $P(\text{collision} \mid \text{HB})$ on a 0.1 s grid against current headway classes[S].

Combinatorial coverage. ISO 21448 lists random combinations of known parameters and of known scenarios among the tests addressing area 3 [1, C.1, items 1)–2), p. 125]. De Gelder et al. define tag-based coverage

$$\text{Coverage}_{\text{tag}}(n) = \frac{1}{n|L||C|} \sum_{L} \sum_{C} \min\left(n, N(L, C)\right) \tag{10}$$

[15, Sec. III-A, Eq. (1)], together with time-based, actor-based and actor-over-time coverage [15, Secs. III-B–III-D, Eqs. (2)–(4)]. On HighD with 10 categories and 18 tags, $\text{Coverage}_{\text{tag}}(10) = 1$ [15, Sec. IV-B], while about 75% of time instants are covered by at least one scenario [15, Sec. IV-C]. Applied to tag pairs, the metric exposes untested combinations (Fig. 24).




Figure 24: Synthetic exposure hours per weather × road-type pair[S]: 26 of 42 pairs have fewer than 30 h; $\text{Coverage}_{\text{tag}}(30) = 0.67$ *(this report, computed).*

8.6 Arguing completeness

Glasmacher et al. argue the completeness of a scenario concept in goal structuring notation by testing counter-hypotheses [16, Sec. III-C; applied in Sec. IV-B]. They define completeness as binary and applying to the concept, and coverage as quantifiable and applying to parameter

spaces and value assignments [16, Secs. III-A, III-B]; evidence is knowledge-based or data-driven [16, Sec. III-D, Table I]. On inD they assign 59,253 base scenarios with no unassigned seconds and use saturation curves [16, Sec. IV-C, Fig. 5], noting that "unforeseen scenarios cannot be identified with argumentation, but with external input" [16, Sec. IV-C] and that completeness claims can expire and need review in a dev-ops process [16, Sec. V]. De Gelder et al. distinguish Type I coverage (all relevant aspects of the ODD) from Type II (all relevant aspects in the driving data) [15, Sec. III, Table III] and leave completeness metrics to future work [15, Secs. V–VI]. Table 11 of ISO 21448 lists "scenario exploration in real world", defined as searching "for unknown scenarios by covering a diverse set of the real-world scenarios" [1, 11.3, Table 11, method O and footnote e, p. 51]. Hauer et al. [19] estimate the number of scenario types not yet addressed in testing (as summarised in [15, Sec. II]).

ISO 21448 requires "sufficient coverage of the relevant scenario space" in the V&V strategy [1, 9.1 a) 2), p. 42], notes "a representative coverage of the possible scenario space" as one aspect of Clause 11 [1, 11.1, Note, p. 50], and describes an iterative constrained-random process that converts area 3 into area 2 "until sufficient coverage of the used functionality space is achieved" [1, C.3, Figure C.4, p. 135]. Five legs of an argument follow:

1. construction: systematic derivation of the taxonomy, independent review;
2. explained time: the share of driven time assigned to a category (Type II coverage);
3. saturation: a flattening discovery curve and small missing mass;
4. risk-weighted remainder: bounded by Clause 11 field evidence within the reserve εA_H;
5. monitoring in operation, because completeness claims expire: new unknown hazardous scenarios can arise with algorithm, ODD, OEDR or driving-policy changes and new vehicle types [1, 11.3, Note 1, p. 52].

For leg 3, the Good–Turing estimate of the probability that the next occurrence is of an unseen type [27, location not verified] and the Chao1 richness estimator [28, location not verified] are

$$\hat{M}_0 = \frac{f_1}{N}, \qquad \hat{S} = S_{\text{obs}} + \frac{f_1(f_1-1)}{2(f_2+1)}, \qquad R_{\text{unknown}} \lesssim \hat{M}_0\, \nu_{\text{tot}}\, \bar{p}_{\text{unk}} \tag{11}$$

with f_1, f_2 the numbers of types seen once or twice and N the number of occurrences.




Figure 25: Synthetic: 1,000 scenario types with Zipf frequencies (exponent 1.8)[S]. After 200,000 occurrences, 731 types are seen and Chao1 estimates 902, a lower bound; the Good–Turing missing mass is 1.06×10^{-3} (true 1.14×10^{-3}) *(this report, computed).*

8.7 OpenLABEL and ISO 34504

Table 7: ASAM OpenLABEL compared with ISO 34504.

	ASAM OpenLABEL 1.0.0 (2021)	ISO 34504:2024
nature	data format (JSON schema) for annotations [6, standard page]	vocabulary and structure for scenario categories [5, web article]
content	elements (objects, actions, events, contexts, relations) with name, uid, type and ontology id [7, Sec. 2.3.1]; relations as RDF triples [7, Sec. 2.3.4]; frames and frame intervals [7, Secs. 2.3, 2.3.2]; streams [7, Secs. 2.3, 2.3.6]; coordinate systems [7, Secs. 2.3.7, 3.1]	tags for vehicle types, environments, light, weather, road conditions, grouped into categories; examples, no exact values [5, web article]
semantics	none of its own: elements point to external ontologies [7, Secs. 2.3, 2.3.3]	a semantic source to point to
scenario tags	labels selected from a pool and stored with scenario files for search [7, Secs. 5.1–5.2]	tags define the categories
related	lists BSI PAS 1883 and ASAM OpenODD [7, Sec. 1.3]	part of the ISO 3450x family [5, web article]

They complement each other: ISO 34503/34504 plus custom tags form the ontology; OpenLABEL stores per-recording, per-interval annotations that reference it; the scenario database indexes them; OpenSCENARIO describes executable tests.

9 Scaling to ACC and an L4 robotaxi

The estimator (5) does not change; the scenario space, the agent interaction and the cost of exploring rare regions do.

Table 8: Three levels compared *(this report, assessment)*.

	unintended braking (Sec. 6)	ACC / L2 longitudinal	L4 urban robotaxi
hazardous behaviours	1	about 5–10	dozens across all DDT subtasks
scenario types	1	follow, lead braking, cut-in, cut-out, queue approach	hundreds: intersections, occluded VRUs, pick-up/drop-off, emergency vehicles
parameters	7	about 10–20	about 50–100 and more
interaction	open loop	closed loop, driver as fallback	closed loop, many reactive agents
acceptance	one A_H	per HE, human benchmark (Annex C)	positive risk balance per harm type (ISO/TS 5083)

ACC is specified in ISO 15622 [4, location not verified]; ISO 21448 uses an ACC lead-braking scenario as its example for parameter distributions and importance sampling [1, C.5, Figure C.9, pp. 146–147]. It also warns that the traffic-statistics approach of its AEB example "can prove impractical" for a fully automated vehicle "unless specific considerations with respect to system architecture are made" [1, C.2.2.6, p. 134]. With d parameters shifted by δ standard deviations, a Gaussian proposal gives $E_q[w^2] = e^{d\delta^2}$ and $\mathrm{ESS}/N \approx e^{-d\delta^2}$ *(this report, derived; Fig. 26)*.

Fixed-proposal importance sampling therefore degrades in high dimension, which motivates the cross-entropy method [35, location not verified], subset simulation [29, location not verified] and adaptive importance sampling [32, Ch. 10]. Runtime risk models can restrict exposure to risky situations: SINADRA derives monitorable risk-implausibility hypotheses from HARA work products and turns them into Boolean or Bayesian-network runtime models [13, Sec. 1.3, pp. 4–5; Sec. 4.3, p. 77]; in its urban case study, behaviour-intent likelihoods weight a collision-risk signal [13, Sec. 5.2.5, p. 131]. Such a reduction of ν_ℓ must be argued inside Eq. (5).




Figure 26: Effective sample size of importance sampling against the number of shifted parameters *(this report, derived and simulated).*

10 Limitations

- All example data are synthetic; correlations, rates, distributions and the injury curve are illustrative.
- ISO 21448 references were checked against the standard; ISO/TS 5083, UL 4600, ISO 34502/34503/34504 and ISO 15622 were not available (Sec. 1.2).
- The kinematic model is one-dimensional, without lateral escape, brake build-up or reaction to brake release.
- Scenario shares are products of factor shares (independence between trigger, speed and headway).
- The Bayesian result depends on the prior, which must be defended to an assessor.

A Code and reproduction

All numbers marked *this report* and all figures are reproducible from the repository `dfeldmann-bot/sotif-risk-course` (private): `tools/ub_sim.py` (scenario generation, copula, simulation, weights), `tools/build_ub_example.py` (workbook with live formulas), `tools/build_docs_html.py` (figures and HTML docs) and `tools/gen_report_figs.py` (the figures of this report). Random seed: 2026.

References

[1] ISO 21448:2022(E). *Road vehicles — Safety of the intended functionality.* First edition, 2022-06. ISO, Geneva. Page numbers as printed.

[2] ISO 34502:2022. *Road vehicles — Test scenarios for automated driving systems — Scenario based safety evaluation framework.* ISO.

[3] ISO 34503:2023. *Road vehicles — Test scenarios for automated driving systems — Specification for operational design domain.* ISO.

[4] ISO 15622. *Intelligent transport systems — Adaptive cruise control systems — Performance requirements and test procedures.* ISO.

[5] TNO (2024). New ISO 34504 provides guidance for safety assessment of automated driving systems. https://www.tno.nl/en/newsroom/insights/2024/05/iso-34504-safety-and-automated-driving/

[6] ASAM e.V. (2021). ASAM OpenLABEL 1.0.0. https://www.asam.net/standards/detail/openlabel/

[7] ASAM e.V. OpenLABEL Concept Paper. https://www.asam.net/fileadmin/Projects/Project-Details/P_2020_12_OpenLABEL_V1.0.0/OpenLABEL_Concept_paper.html

[8] Siemens Digital Industries Software. Multi-pillar approach for safety validation of automated vehicles (on UNECE NATM, ECE/TRANS/WP.29/2021/61, and Regulation (EU) 2022/1426). https://blogs.sw.siemens.com/simcenter/multi-pillar-approach-for-safety-validation-of-automated-vehicles/

[9] L. Putze, L. Westhofen, T. Koopmann, E. Böde, C. Neurohr (2023). On quantification for SOTIF validation of automated driving systems. arXiv:2304.10170.

[10] D. Betschinske, M. Schrimpf, S. Peters, K. Klonecki, J. P. Karch, M. Lippert (2025). Towards more efficient quantitative safety validation of residual risk for assisted and automated driving. arXiv:2506.10363.

[11] N. Kalra, S. M. Paddock (2016). *Driving to Safety: How Many Miles of Driving Would It Take to Demonstrate Autonomous Vehicle Reliability?* RAND Corporation, RR-1478-RC.

[12] F. Schaller, R. Ehlers, I. Aslam, A. Deshpande, R. Gräfe, W. Guedri, N. Habib, N. Maslov, A. Rausch, S. S. Qutub, M. Zhang (2026). Addressing SOTIF with a runtime monitor ensemble for AI-based perception systems. *Discover Artificial Intelligence* 6:1172. doi:10.1007/s44163-026-02186-z.

[13] J. Reich (2026). *SINADRA: Situation-Aware Dynamic Risk Assessment for Safe and Permissive Autonomous Systems.* Dr.-Ing. thesis, RPTU Kaiserslautern-Landau / Fraunhofer IESE. Page numbers as printed.

[14] E. de Gelder (2022). *Safety assessment of automated vehicles using real-world driving scenarios.* PhD thesis, TU Delft.

[15] E. de Gelder, M. Buermann, O. Op den Camp (2024). Coverage metrics for a scenario database for the scenario-based assessment of automated driving systems. arXiv:2409.01139 (v2).

[16] C. Glasmacher, H. Weber, L. Eckstein (2024). Towards a completeness argumentation for scenario concepts. arXiv:2404.01934.

[17] D. Guo, M. Muñoz Sánchez, E. de Gelder, T. P. J. van der Sande (2023). Scenario extraction from a large real-world dataset for the assessment of automated vehicles. arXiv:2306.07815.

[18] Toward unsupervised test scenario extraction for automated driving systems from urban naturalistic road traffic data. arXiv:2202.06608.

[19] F. Hauer, T. Schmidt, B. Holzmüller, A. Pretschner (2019). Did we test all scenarios for automated and autonomous driving systems? *IEEE ITSC 2019.*

[20] D. Zhao, H. Lam, H. Peng, S. Bao, D. J. LeBlanc, K. Nobukawa, C. S. Pan (2016). Accelerated evaluation of automated vehicles safety in lane-change scenarios based on importance sampling techniques. arXiv:1605.04965; doi:10.1109/TITS.2016.2582208.

[21] D. Ratiu, T. Rohlinger, T. Stolte, S. Wagner (2024). Towards an argument pattern for the use of safety performance indicators. arXiv:2410.00578.

[22] P. Koopman (2022). Safety Performance Indicators (SPIs) for Autonomous Vehicles. Lecture slides, Carnegie Mellon University. https://users.ece.cmu.edu/~koopman/lectures/L124_SPI_vs_KPI.pdf

[23] Waymo. An omni-directional model of injury risk in planar crashes. https://waymo.com/research/an-omni-directional-model-of-injury-risk-in-planar/

[24] B. Littlewood, D. Wright (1997). Some conservative stopping rules for the operational testing of safety-critical software. *IEEE Transactions on Software Engineering* 23(11):673–683. Source of ISO 21448 Formula (C.7).

[25] F. Garwood (1936). Fiducial limits for the Poisson distribution. *Biometrika* 28:437–442.

[26] C. J. Clopper, E. S. Pearson (1934). The use of confidence or fiducial limits illustrated in the case of the binomial. *Biometrika* 26:404–413.

[27] I. J. Good (1953). The population frequencies of species and the estimation of population parameters. *Biometrika* 40:237–264.

[28] A. Chao (1984). Nonparametric estimation of the number of classes in a population. *Scandinavian Journal of Statistics* 11:265–270.

[29] S.-K. Au, J. L. Beck (2001). Estimation of small failure probabilities in high dimensions by subset simulation. *Probabilistic Engineering Mechanics* 16(4).

[30] F. Lindskog, A. McNeil, U. Schmock (2003). Kendall's tau for elliptical distributions. In *Credit Risk*, Physica.

[31] P. Embrechts, F. Lindskog, A. McNeil (2003). Modelling dependence with copulas and applications to risk management. In *Handbook of Heavy Tailed Distributions in Finance*, Elsevier.

[32] A. B. Owen (2013). *Monte Carlo theory, methods and examples.* Ch. 9 (importance sampling), Ch. 10 (advanced variance reduction). https://artowen.su.domains/mc/

[33] R. B. Nelsen (2006). *An Introduction to Copulas*, 2nd ed. Springer.

[34] S. Coles (2001). *An Introduction to Statistical Modeling of Extreme Values.* Springer.

[35] R. Y. Rubinstein, D. P. Kroese (2016). *Simulation and the Monte Carlo Method*, 3rd ed. Wiley.

Further reading: statistics books

- L. Wasserman (2004). *All of Statistics.* Springer. Compact rigorous inference; a good first book.
- G. Casella, R. L. Berger (2002). *Statistical Inference*, 2nd ed. Duxbury. Estimators, confidence intervals, tests.
- W. Q. Meeker, G. J. Hahn, L. A. Escobar (2017). *Statistical Intervals*, 2nd ed. Wiley. Exact Poisson and binomial intervals, demonstration tests (chapter not verified).
- M. Rausand, A. Barros, A. Høyland (2020). *System Reliability Theory*, 3rd ed. Wiley. Failure rates and Bayesian reliability (chapter not verified).
- A. Gelman et al. (2013). *Bayesian Data Analysis*, 3rd ed. CRC. Priors and posteriors; Ch. 2 single-parameter models including the Poisson model. Free PDF: https://sites.stat.columbia.edu/gelman/book
- A. B. Owen (2013), see [32]: Ch. 9 for importance sampling diagnostics and effective sample size.
- C. P. Robert, G. Casella (2004). *Monte Carlo Statistical Methods*, 2nd ed. Springer.
- R. Y. Rubinstein, D. P. Kroese (2016), see [35]: rare events and the cross-entropy method.
- R. B. Nelsen (2006), see [33]: Sec. 2.3 Sklar's theorem; Ch. 5 dependence and Kendall's τ.
- H. Joe (2014). *Dependence Modeling with Copulas.* CRC. Vine copulas (chapter not verified).
- S. Coles (2001), see [34]: Ch. 4 threshold models and the generalised Pareto distribution.