

A: Datasheet

Algorithm: dilusense\_001

Developer: DiluSense Technology

Submission Date: 2022\_12\_24

Template size: 4096 bytes

Template time (2.5 percentile): 883 msec

Template time (median): 884 msec

Template time (97.5 percentile): 897 msec

Investigation:

Frontal mugshot ranking 56 (out of 388) -- FNIR(1600000, 0, 1) = 0.0015 vs. lowest 0.0008 from sensetime\_009

Mugshot webcam ranking 53 (out of 350) -- FNIR(1600000, 0, 1) = 0.0096 vs. lowest 0.0054 from sensetime\_009

Mugshot profile ranking 100 (out of 319) -- FNIR(1600000, 0, 1) = 0.2500 vs. lowest 0.0517 from sensetime\_009

Immigration visa-border ranking 131 (out of 277) -- FNIR(1600000, 0, 1) = 0.0060 vs. lowest 0.0006 from cloudwalk\_mt\_001

Immigration visa-kiosk ranking 77 (out of 222) -- FNIR(1600000, 0, 1) = 0.0796 vs. lowest 0.0395 from cloudwalk\_mt\_001

Identification:

Frontal mugshot ranking 62 (out of 388) -- FNIR(1600000, T, L+1) = 0.0084, FPIR=0.001000 vs. lowest 0.0011 from idemia\_010


Mugshot webcam ranking 59 (out of 348) -- FNIR(1600000, T, L+1) = 0.0343, FPIR=0.001000 vs. lowest 0.0072 from sensetime\_009

Mugshot profile ranking 32 (out of 318) -- FNIR(1600000, T, L+1) = 0.4569, FPIR=0.001000 vs. lowest 0.0698 from cloudwalk\_mt\_001


Immigration visa-border ranking 64 (out of 276) -- FNIR(1600000, T, L+1) = 0.0152, FPIR=0.001000 vs. lowest 0.0013 from cloudwalk\_mt\_001

Immigration visa-kiosk ranking 42 (out of 222) -- FNIR(1600000, T, L+1) = 0.1254, FPIR=0.001000 vs. lowest 0.0532 from cloudwalk\_mt\_001


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (idemia\_010)




C: Evolution of accuracy for DILUSENSE algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects



# H: Reduced length candidate lists for human review


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image






# I: FNIR and FPIR dependence on threshold


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_009)



L: Investigational mode: FNIR(1600000, R, 0) by probe type




M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.

Algorithm: dilusense\_001, Dataset: Border-Crossing Ageing N = 1600000  
Text encodes FNIR, Color encodes log(FNIR)



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: dilusense\_001, Dataset: Border-Crossing Ageing  
Threshold: 0.831678 set to achieve FPIR(30–45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

