

A: Datasheet

Algorithm: lineclova_002

Developer: Line Corporation

Submission Date: 2022_07_29

Template size: 2048 bytes

Template time (2.5 percentile): 824 msec

Template time (median): 825 msec

Template time (97.5 percentile): 829 msec

Investigation:

Mugshot webcam ranking 20 (out of 331) -- FNIR(1600000, 0, 1) = 0.0075 vs. lowest 0.0055 from sensetime_008

Mugshot profile ranking 27 (out of 300) -- FNIR(1600000, 0, 1) = 0.0700 vs. lowest 0.0521 from sensetime_007

Immigration visa-border ranking 247 (out of 258) -- FNIR(1600000, 0, 1) = 0.7161 vs. lowest 0.0006 from cloudwalk_mt_001

Immigration visa-kiosk ranking 201 (out of 203) -- FNIR(1600000, 0, 1) = 0.6968 vs. lowest 0.0395 from cloudwalk_mt_001

Identification:

Frontal mugshot ranking 349 (out of 369) -- FNIR(1600000, T, L+1) = 0.8452, FPIR=0.001000 vs. lowest 0.0013 from sensetime_008


Mugshot webcam ranking 176 (out of 329) -- FNIR(1600000, T, L+1) = 0.1264, FPIR=0.001000 vs. lowest 0.0090 from sensetime_008

Mugshot profile ranking 114 (out of 299) -- FNIR(1600000, T, L+1) = 0.9808, FPIR=0.001000 vs. lowest 0.0698 from cloudwalk_mt_001

Immigration visa-border ranking 223 (out of 257) -- FNIR(1600000, T, L+1) = 0.7171, FPIR=0.001000 vs. lowest 0.0013 from cloudwalk_mt_001

Immigration visa-kiosk ranking 151 (out of 203) -- FNIR(1600000, T, L+1) = 0.7375, FPIR=0.001000 vs. lowest 0.0532 from cloudwalk_mt_001


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (hyperverge_002)




C: Evolution of accuracy for LINECLOVA algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects



H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image



I: FNIR and FPIR dependence on threshold

Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image

False {Negative | Positive} Identification Rate

FNIR(T)

FPIR(T)


0.2

0.4


0.6

0.8


Threshold value




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_007)




L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.
The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations




O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: lineclova_002, Dataset: Border-Crossing Ageing
Threshold: 0.382274 set to achieve FPIR(30–45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

