

A: Datasheet

Algorithm: dermalog_011

Developer: Dermalog

Submission Date: 2022_12_12

Template size: 128 bytes

Template time (2.5 percentile): 239 msec

Template time (median): 249 msec

Template time (97.5 percentile): 263 msec

Investigation:

Frontal mugshot ranking 86 (out of 416) -- FNIR(1600000, 0, 1) = 0.0016 vs. lowest 0.0008 from interna_001

Mugshot webcam ranking 81 (out of 376) -- FNIR(1600000, 0, 1) = 0.0103 vs. lowest 0.0054 from sensetime_009

Mugshot profile ranking 71 (out of 345) -- FNIR(1600000, 0, 1) = 0.0965 vs. lowest 0.0517 from sensetime_009

Immigration visa--border ranking 107 (out of 305) -- FNIR(1600000, 0, 1) = 0.0032 vs. lowest 0.0006 from cloudwalk_mt_002

Immigration visa--kiosk ranking 103 (out of 249) -- FNIR(1600000, 0, 1) = 0.0829 vs. lowest 0.0387 from cloudwalk_mt_002

Identification:

Frontal mugshot ranking 143 (out of 416) -- FNIR(1600000, T, L+1) = 0.0215, FPIR=0.001000 vs. lowest 0.0011 from idemia_010


Mugshot webcam ranking 161 (out of 374) -- FNIR(1600000, T, L+1) = 0.0864, FPIR=0.001000 vs. lowest 0.0072 from sensetime_009

Mugshot profile ranking 231 (out of 344) -- FNIR(1600000, T, L+1) = 0.9982, FPIR=0.001000 vs. lowest 0.0634 from cloudwalk_mt_002


Immigration visa--border ranking 199 (out of 303) -- FNIR(1600000, T, L+1) = 0.1292, FPIR=0.001000 vs. lowest 0.0010 from cloudwalk_mt_002

Immigration visa--kiosk ranking 191 (out of 248) -- FNIR(1600000, T, L+1) = 0.7583, FPIR=0.001000 vs. lowest 0.0517 from cloudwalk_mt_002


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (idemia_010)




C: Evolution of accuracy for DERMALOG algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_009)



L: Investigational mode: FNIR(1600000, R, 0) by probe type




M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.
The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.


Algorithm: dermalog_011, Dataset: Border-Crossing Ageing
Threshold: 93.025504 set to achieve FPIR(30–45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



R: Decline of genuine scores with ageing, with some eventually dropping below typical thresholds shown by the horizontal lines

