

A: Datasheet

Algorithm: hzailu_001

Developer: Hangzhuo Allu Network Information Technology

Submission Date: 2022_08_18

Template size: 2048 bytes

Template time (2.5 percentile): 772 msec

Template time (median): 777 msec

Template time (97.5 percentile): 782 msec

Investigation:

Mugshot webcam ranking 72 (out of 331) -- FNIR(1600000, 0, 1) = 0.0110 vs. lowest 0.0055 from sensetime_008

Mugshot profile ranking 47 (out of 300) -- FNIR(1600000, 0, 1) = 0.1058 vs. lowest 0.0521 from sensetime_007

Immigration visa-border ranking 46 (out of 258) -- FNIR(1600000, 0, 1) = 0.0023 vs. lowest 0.0006 from cloudwalk_mt_001

Immigration visa-kiosk ranking 73 (out of 203) -- FNIR(1600000, 0, 1) = 0.0854 vs. lowest 0.0395 from cloudwalk_mt_001

Identification:

Frontal mugshot ranking 54 (out of 369) -- FNIR(1600000, T, L+1) = 0.0086, FPIR=0.001000 vs. lowest 0.0013 from sensetime_008


Mugshot webcam ranking 217 (out of 329) -- FNIR(1600000, T, L+1) = 0.1809, FPIR=0.001000 vs. lowest 0.0090 from sensetime_008

Mugshot profile ranking 128 (out of 299) -- FNIR(1600000, T, L+1) = 0.9865, FPIR=0.001000 vs. lowest 0.0698 from cloudwalk_mt_001


Immigration visa-border ranking 184 (out of 257) -- FNIR(1600000, T, L+1) = 0.1961, FPIR=0.001000 vs. lowest 0.0013 from cloudwalk_mt_001

Immigration visa-kiosk ranking 146 (out of 203) -- FNIR(1600000, T, L+1) = 0.6649, FPIR=0.001000 vs. lowest 0.0532 from cloudwalk_mt_001


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (hyperverge_002)




C: Evolution of accuracy for HZAILU algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_007)



L: Investigational mode: FNIR(1600000, R, 0) by probe type




M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.

Algorithm: hzailu_001, Dataset: Border-Crossing Ageing N = 1600000
Text encodes FNIR, Color encodes log(FNIR)



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.



Algorithm: hzailu_001, Dataset: Border-Crossing Ageing
Threshold: 0.901124 set to achive FPIR(30-45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



R: Decline of genuine scores with ageing, with some eventually dropping below typical thresholds shown by the horizontal lines

