

A: Datasheet

Algorithm: armatura\_000

Developer: Armatura LLC

Submission Date: 2023\_04\_13

Template size: 6144 bytes

Template time (2.5 percentile): 653 msec

Template time (median): 655 msec

Template time (97.5 percentile): 664 msec

Investigation:

Frontal mugshot ranking 117 (out of 416) — FNIR(1600000, 0, 1) = 0.0019 vs. lowest 0.0008 from intema\_001

Mugshot webcam ranking 126 (out of 376) — FNIR(1600000, 0, 1) = 0.0127 vs. lowest 0.0054 from sensetime\_009

Mugshot profile ranking 46 (out of 345) — FNIR(1600000, 0, 1) = 0.0704 vs. lowest 0.0517 from sensetime\_009

Immigration visa–border ranking 54 (out of 305) — FNIR(1600000, 0, 1) = 0.0017 vs. lowest 0.0006 from cloudwalk\_mt\_002

Immigration visa–kiosk ranking 42 (out of 249) — FNIR(1600000, 0, 1) = 0.0579 vs. lowest 0.0387 from cloudwalk\_mt\_002

Identification:

Frontal mugshot ranking 48 (out of 416) — FNIR(1600000, T, L+1) = 0.0043, FPIR=0.001000 vs. lowest 0.0011 from idemia\_010


Mugshot webcam ranking 49 (out of 374) — FNIR(1600000, T, L+1) = 0.0250, FPIR=0.001000 vs. lowest 0.0072 from sensetime\_009

Mugshot profile ranking 22 (out of 344) — FNIR(1600000, T, L+1) = 0.2237, FPIR=0.001000 vs. lowest 0.0634 from cloudwalk\_mt\_002


Immigration visa–border ranking 28 (out of 303) — FNIR(1600000, T, L+1) = 0.0059, FPIR=0.001000 vs. lowest 0.0010 from cloudwalk\_mt\_002

Immigration visa–kiosk ranking 24 (out of 248) — FNIR(1600000, T, L+1) = 0.0859, FPIR=0.001000 vs. lowest 0.0517 from cloudwalk\_mt\_002


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (idemia\_010)




C: Evolution of accuracy for ARMATURA algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects



# H: Reduced length candidate lists for human review


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image






# I: FNIR and FPIR dependence on threshold


Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_009)



L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations




O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.


Algorithm: armatura\_000, Dataset: Border-Crossing Ageing  
Threshold: 243.638000 set to achive FPIR(30–45, Male) = 0.001

Color encodes  $\log(\text{FPIR})$



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801





R: Decline of genuine scores with ageing, with some eventually dropping below typical thresholds shown by the horizontal lines

