

A: Datasheet

Algorithm: sensetime_009

Developer: Sensetime Group

Submission Date: 2023_01_04

Template size: 1032 bytes

Template time (2.5 percentile): 991 msec

Template time (median): 995 msec

Template time (97.5 percentile): 1071 msec

Investigation:

Frontal mugshot ranking 1 (out of 388) -- FNIR(1600000, 0, 1) = 0.0008

Mugshot webcam ranking 1 (out of 350) -- FNIR(1600000, 0, 1) = 0.0054

Mugshot profile ranking 1 (out of 319) -- FNIR(1600000, 0, 1) = 0.0517

Immigration visa-border ranking 3 (out of 277) -- FNIR(1600000, 0, 1) = 0.0007 vs. lowest 0.0006 from cloudwalk_mt_001

Immigration visa-kiosk ranking 52 (out of 222) -- FNIR(1600000, 0, 1) = 0.0689 vs. lowest 0.0395 from cloudwalk_mt_001

Identification:

Frontal mugshot ranking 2 (out of 388) -- FNIR(1600000, T, L+1) = 0.0011, FPIR=0.001000 vs. lowest 0.0011 from idemia_010


Mugshot webcam ranking 1 (out of 348) -- FNIR(1600000, T, L+1) = 0.0072, FPIR=0.001000

Mugshot profile ranking 82 (out of 318) -- FNIR(1600000, T, L+1) = 0.8900, FPIR=0.001000 vs. lowest 0.0698 from cloudwalk_mt_001


Immigration visa-border ranking 2 (out of 276) -- FNIR(1600000, T, L+1) = 0.0015, FPIR=0.001000 vs. lowest 0.0013 from cloudwalk_mt_001

Immigration visa-kiosk ranking 9 (out of 222) -- FNIR(1600000, T, L+1) = 0.0763, FPIR=0.001000 vs. lowest 0.0532 from cloudwalk_mt_001


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (idemia_010)




C: Evolution of accuracy for SENSETIME algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_009)



L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: sensetime_009, Dataset: Border-Crossing Ageing
Threshold: 0.797736 set to achive FPIR(30-45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

