



# Technical notes

## Browser compatibility

The recordSDK is dependent on the MediaRecorder API which limits availability to ~89% of global audience. The `isSupported` method prevents activation if it detects that it is being invoked in an environment in which the MediaRecorder API is not supported. See [Can I use MediaRecorder API](#).

| IE   | Edge * | Firefox | Chrome  | Safari    | Opera   | Safari on iOS * | Opera Mini * | Android Browser * | Opera Mobile * | Chrome for Android | Firefox for Android | UC Browser for Android | Samsung Internet | QQ Browser | Baidu Browser | KaiOS Browser |
|------|--------|---------|---------|-----------|---------|-----------------|--------------|-------------------|----------------|--------------------|---------------------|------------------------|------------------|------------|---------------|---------------|
|      |        |         | 4-46    |           | 10-33   | 3.2-11.4        |              |                   |                |                    |                     |                        |                  |            |               |               |
|      | 12-18  | 2-28    | 1 47-48 | 3.1-12    | 1 34-35 | 2 12-14.4       |              |                   |                |                    |                     |                        | 4                |            |               |               |
| 6-10 | 79-92  | 29-91   | 49-92   | 2 12.1-14 | 36-78   | 14.7            |              | 2.1-4.4.4         | 12-12.1        |                    |                     |                        | 5-13.0           |            |               |               |
| 11   | 93     | 92      | 93      | 14.1      | 79      | 15              | all          | 93                | 64             | 93                 | 92                  | 12.12                  | 14.0             | 10.4       | 7.12          | 2.5           |
|      |        | 93-94   | 94-96   | 15-TP     |         |                 |              |                   |                |                    |                     |                        |                  |            |               |               |

The current browser matrix support (subject to change as more browsers get added to the list and as performance is tuned) is as follows:

- Google Chrome v90+
- Microsoft Edge v90+
- Brave v1.22+

Firefox is currently unsupported because even though the MediaRecorder API is supported, performance does not meet our quality bar. We will continue to evaluate Firefox support for future inclusion.

Safari recently made MediaRecorder support GA, and we will look to add Safari support soon.

## Error handling

The recordSDK will swallow errors and prevent them from cascading to the containing application. The `setup` method will return an error if initialization of the recordSDK fails. The `isSupported` method is meant to prevent loading the SDK in environments which prevent a successful

recording. These methods exist to allow you to hide the recordSDK UI in your application as appropriate. If for whatever reason the recordSDK experiences a failure even after these checks, the UI will update to show an error state to the end-user.

## Referrer header

Your API key is associated with an allow list of domains. Attempts to instantiate the recordSDK will compare the provided API key with the `Referrer` header on the request to [loom.com](https://loom.com) (as part of the `setup` call, described below).

If you encounter a `403` when attempting to load the recordSDK, please inspect the `Referrer` header on the request to Loom to ensure it matches a domain in your allow list. Also note that a strict `referrer policy` in your web app may prevent sending the `Referrer` header for iFrames with a different origin.

## Eval safe bundle #

The default bundle includes a `globalThis` polyfill that falls back to `Function('return this')()` in some cases. If your runtime environment has a strict CSP that doesn't allow `unsafe-eval` then there is a separate bundle available which avoids the polyfill. The bundle can be imported directly from the `@loomhq/record-sdk` package's dist folder.

```
import { /* ... */ } from '@loomhq/record-sdk/dist/cjs/safe';
```

## `isSupported` bundle

`v2.25.0+`.

To check sdk compatibility without downloading the full `@loomhq/record-sdk` bundle you can import a smaller bundle that only includes the `isSupported` function.

**Deprecation Warning:** As of v3.0.0, this is the only method to import the `isSupported` function

```
import { isSupported } from '@loomhq/record-sdk/is-supported';
```

## Server-side rendering

We recommend async loading of the recordSDK as a package. Rendering on the server is not fully supported. Trying to do so can raise errors in an application using Next.js by Vercel, for example. A workaround for that particular situation would be loading the import dynamically. Usage might look like this:

```
import dynamic from 'next/dynamic';  
  
...  
  
const DynamicLoomSDK = dynamic(() => import('@components/LoomSDK'), {  
  ssr: false,  
});
```