



Seance: Divination of Tool-Breaking Changes in Forensically Important Binaries

By:

Ryan Maggio (Louisiana State University), Andrew Case (Volatility Foundation), Aisha Ali-Gombe (Towson University), and Golden G. Richard III (Louisiana State University)

From the proceedings of

The Digital Forensic Research Conference

DFRWS USA 2021

July 12-15, 2021

DFRWS is dedicated to the sharing of knowledge and ideas about digital forensics research. Ever since it organized the first open workshop devoted to digital forensics in 2001, DFRWS continues to bring academics and practitioners together in an informal environment.

As a non-profit, volunteer organization, DFRWS sponsors technical working groups, annual conferences and challenges to help drive the direction of research and development.

<https://dfrws.org>



SEANCE: FORENSIC DIVINATION

Ryan Maggio

Overview

- Motivation
 - Memory forensics tools require frequent checks for compatibility with new software versions
 - Data structure reconstruction is a historically tricky problem
 - Existing work is brittle or manual
- Internals
 - Existing tools used to build Seance
 - Two Components, API and controlling code
 - Example workflow for analysis and database construction
- Testing
 - Tested on Objective-C and Windows networking stack binaries
 - Objective-C results
 - Windows Networking Stack results
- Future Work

Motivation

- Verifying compatibility of a forensic tool and a target binary is a time consuming, error prone task
 - Largely based on data structure reconstruction
 - Existing work is brittle or incomplete
- Compatibility-breaking changes have caused real world issues, e.g. issues raised with Volatility
- Our previous projects on malware analysis used emulation, we wanted to see if that technique works here, too
 - In that space, encountered issues where certain behavior would be missed by emulation
 - Instead of just emulating, try symbolic execution for better capturing behavior

Seance

- Built on top of angr
- Explores “true behavior” of code under analysis
- Get more detailed execution data
 - Produce a CFG
 - Record all memory accesses
 - Get concrete results
- Can answer questions about tool compatibility
 - Potentially useful in other domains, too



The glowing bit is code

Internals - API

- Much of the functionality implemented in an API
 - Does not integrate with Volatility (yet)
- Four angr callbacks, mostly helper functions
 - Assumes an instantiated angr project
- Callbacks for memory reads, writes and register reads, writes
 - Check if execution is ongoing
 - Check that target can be concretized
 - Record access length, target, conditions, ordered list of basic blocks
- Handle stashes
 - Associate memory accesses with correct end states
 - Concretize values
 - Generate permit-list for CFG
- Generate CFG
- Print CFG

Internals - Controlling Code

- Input
 - Binary
 - Symbol
 - Well, maybe a bit more
 - Database
- Output
 - CFG of target symbol
 - Detailed execution data
 - Offsets referenced
 - From memory addresses
 - From memory addresses accessed via pointer
- Post processing
 - Comparison against database
 - Updated database

Test Data

- Two sets of test data
- Objective-C
 - Open source
 - Many important algorithms and data structures
 - Abused by malware
 - Research efforts are dated
- Windows networking stack
 - Closed source
 - Debug information not published
 - Network activities are often central to investigations
 - Updated often, causing issues

Example from TcpConnectTimeout

State through blocks 1c0102a05 1c0102a3e 1c0102a54

> Register Access:

Register rbp

Accesses occurred at offsets: ['10', '18', '72', '70']

Register r8

Accesses occurred at offsets: []

> Pointer Access:

Pointer ffff8000000000ff0

Accesses occurred at offsets: ['10', '18', '72', '70']

Pointer f0000000000000000

Accesses occurred at offsets: ['18']

Pointer 0

Accesses occurred at offsets: []

Pointer ffffffff8000

Accesses occurred at offsets: ['8', '10', '0']

Pointer 7fffffffefe58

Accesses occurred at offsets: ['28', '20', '-8', '60', '58', '-10']

Pointer 1c0102a3e

Accesses occurred at offsets: []

Pointer 7fffffffefe50

Accesses occurred at offsets: ['30', '28', '0', '68', '60', '-8']

Pointer 1c0102a54

Accesses occurred at offsets: []

> Traced Pointer Access:

Traced Pointer rbp -> ffff800000001008 -> ffffffff8000

Accesses occurred at offsets: ['8', '10', '0']

Traced Pointer rsp -> 7fffffffefe50

Accesses occurred at offsets: ['30', '28', '0', '68', '60', '-8']

0x1c0102a05 (0x1c0102a05)

```
0x1c0102a05: mov    r10, qword ptr [rbp + 0x10]
0x1c0102a09: movzx  r14d, word ptr [r10 + 0x18]
0x1c0102a0e: mov    rcx, qword ptr [rbp + 0x18]
0x1c0102a12: test   r8d, r8d
0x1c0102a15: movzx  edx, word ptr [rbp + 0x72]
0x1c0102a19: mov    r8d, 1
0x1c0102a1f: mov    word ptr [rsp + 0x28], dx
0x1c0102a24: setne  bl
0x1c0102a27: mov    dl, bl
0x1c0102a29: mov    eax, dword ptr [rcx + 8]
0x1c0102a2c: mov    r9, qword ptr [rcx + 0x10]
0x1c0102a30: movzx  ecx, word ptr [r10 + 0x18]
0x1c0102a35: mov    dword ptr [rsp + 0x20], eax
0x1c0102a39: call  0x1c00040f0
```

0x1c0102a3e (0x1c0102a05)

```
0x1c0102a3e: and    qword ptr [rsp + 0x68], 0
0x1c0102a44: movzx  ecx, di
0x1c0102a47: mov    rsi, rax
0x1c0102a4a: mov    qword ptr [rsp + 0x60], rbp
0x1c0102a4f: call  0x1c007e220
```

0x1c0102a54 (0x1c0102a05)

```
0x1c0102a54: mov    r8, qword ptr [rbp + 0x18]
0x1c0102a58: mov    dl, bl
0x1c0102a5a: movzx  r9d, word ptr [rbp + 0x70]
0x1c0102a5f: mov    rcx, qword ptr [rbp + 0x10]
0x1c0102a63: movzx  edi, al
0x1c0102a66: mov    r8, qword ptr [r8]
0x1c0102a69: call  0x1c00033c8
```

Was that actually helpful?

- Targets the TCP_ENDPOINT data structure
 - Complicated, nested structure
 - Despite this, offsets correctly recognized

```
'_IN_ADDR' : [ None, {  
    'addr4' : [ 0x0, ['IpAddress']],  
    'addr6' : [ 0x0, ['Ipv6Address']],  
}],  
'_INETAF' : [ None, {  
    'AddressFamily' : [ 0x18, ['unsigned short']],  
}],  
'_LOCAL_ADDRESS' : [ None, {  
    'pData' : [ 0x10, ['pointer', ['pointer',['_IN_ADDR']]]],  
}],  
'_ADDRINFO' : [ None, {  
    'Local' : [ 0x0, ['pointer',['_LOCAL_ADDRESS']]],  
    'Remote' : [ 0x10, ['pointer',['_IN_ADDR']]],  
}],  
'_TCP_ENDPOINT': [ None, {  
    'InetAF' : [ 0x10, ['pointer',['_INETAF']]],  
    'AddrInfo' : [ 0x18, ['pointer',['_ADDRINFO']]],  
    'State' : [ 0x6C, ['Enumeration', ...],  
    'LocalPort' : [ 0x70, ['unsigned be short']],  
    'RemotePort' : [ 0x72, ['unsigned be short']],  
    'Owner' : [ 0x258, ['pointer',['_EPROCESS']]],  
    'CreateTime' : [ 0x268, ['WinTimeStamp', dict(is_utc = True)]],  
}],
```

State through blocks 1c0102a05 1c0102a3e 1c0102a54

> Register Access:

Register rbp

Accesses occurred at offsets: ['10', '18', '72', '70']

Register r8

Accesses occurred at offsets: []

> Pointer Access:

Pointer ffff8000000000ff0

Accesses occurred at offsets: ['10', '18', '72', '70']

Pointer f0000000000000000

Accesses occurred at offsets: ['18']

Pointer 0

Accesses occurred at offsets: []

Pointer ffffffff8000

Accesses occurred at offsets: ['8', '10', '0']

Pointer 7fffffffefef58

Accesses occurred at offsets: ['28', '20', '-8', '60', '58', '-10']

Pointer 1c0102a3e

Accesses occurred at offsets: []

Pointer 7fffffffefef50

Accesses occurred at offsets: ['30', '28', '0', '68', '60', '-8']

Pointer 1c0102a54

Accesses occurred at offsets: []

> Traced Pointer Access:

Traced Pointer rbp -> ffff800000001008 -> ffffffff8000

Accesses occurred at offsets: ['8', '10', '0']

Traced Pointer rsp -> 7fffffffefef50


Accesses occurred at offsets: ['30', '28', '0', '68', '60', '-8']

```
'_IN_ADDR' : [ None, {
  'addr4' : [ 0x0, ['IpAddress']],
  'addr6' : [ 0x0, ['Ipv6Address']],
}],
'_INETAF' : [ None, {
  'AddressFamily' : [ 0x18, ['unsigned short']],
}],
'_LOCAL_ADDRESS' : [ None, {
  'pData' : [ 0x10, ['pointer', ['pointer', ['_IN_ADDR']]]],
}],
'_ADDRINFO' : [ None, {
  'Local' : [ 0x0, ['pointer', ['_LOCAL_ADDRESS']]],
  'Remote' : [ 0x10, ['pointer', ['_IN_ADDR']]],
}],
'_TCP_ENDPOINT': [ None, {
  'InetAF' : [ 0x10, ['pointer', ['_INETAF']]],
  'AddrInfo' : [ 0x18, ['pointer', ['_ADDRINFO']]],
  'State' : [ 0x6C, ['Enumeration', ...]],
  'LocalPort' : [ 0x70, ['unsigned be short']],
  'RemotePort' : [ 0x72, ['unsigned be short']],
  'Owner' : [ 0x258, ['pointer', ['_EPROCESS']]],
  'CreateTime' : [ 0x268, ['WinTimeStamp', dict(is_utc = True)]],
}],
```


method_getImplementation

```
IMP
method_getImplementation(Method m)
{
    return m ? m->imp : nil;
}
```

Parameter Access:	Parameter 1 (rdi)	Accesses occurred at offsets: ['10']
Parameter 2 (rsi)	Accesses occurred at offsets: []	
Parameter 3 (rdx)	Accesses occurred at offsets: []	
Parameter 4 (rcx)	Accesses occurred at offsets: []	
Parameter 5 (r8)	Accesses occurred at offsets: []	
Parameter 6 (r9)	Accesses occurred at offsets: []	



Database Matching Results

Structure Function	Parameter Register	Exact Match	Offset Match	CFG Match
NXHashTable NXEmptyHashTable	NXHashTable * rdi	10.14.0-10.15.6	ALL	-
NXHashTable NXInitHashState	NXHashTable * rdi	ALL	ALL	-
NXHashTable NXFreeHashTable	NXHashTable * rdi	10.13.0-10.14.3 10.14.4-10.14.6 10.15.0-10.15.6	ALL ALL ALL	-
NXHashTable NXResetHashTable	NXHashTable * rdi	10.13.4-10.14.3 10.14.4-10.14.6 10.15.0-10.15.6	$\neg(10.13.0 - 10.13.3)$ $\neg(10.13.0 - 10.13.3)$ $\neg(10.13.0 - 10.13.3)$	-
ivar getName	Ivar rdi	ALL	ALL	-
ivar getOffset	Ivar rdi	ALL	ALL	-
ivar getTypeEncoding	Ivar rdi	ALL	ALL	-

Structure Function	Parameter Register	Exact Match	Offset Match	CFG Match
method getImplementation	Method rdi	10.11.0-10.15.3 10.15.4-10.15.6	SAME SAME	-
method getName	Method rdi	10.11.0-10.15.3 10.15.4-10.15.6	SAME SAME	-
objc_object getClass	id rdi	10.12.0-10.14.6 10.15.0-10.15.6	SAME SAME	ALL ALL
objc_class removeSubclass	Class rdi	-	10.13.4-10.13.6 10.14.4 10.11.4-10.13.5, 10.14.5-10.15.0 10.15.1-10.15.6	-
objc_class removeSubclass	Class rsi	-	10.13.4-10.13.6 10.14.4 10.11.4-10.13.5, 10.14.5-10.15.0 10.12.6, 10.15.2, 10.15.6 10.15.3	-

Future Work

- Rework database construction
 - Include pointers, second degree pointers
- Make publicly available
 - Clean up code
 - Containerize environment, write detailed instructions for setting one up
- Volatility integration

Questions?