



Automated Identification of Installed Malicious Android Applications

By

**Mark Guido, Justin Grover, Jared Ondricek,
Dave Wilburn, Drew Hunt and Thanh Nguyen**

Presented At

The Digital Forensic Research Conference

DFRWS 2013 USA Monterey, CA (Aug 4th - 7th)

DFRWS is dedicated to the sharing of knowledge and ideas about digital forensics research. Ever since it organized the first open workshop devoted to digital forensics in 2001, DFRWS continues to bring academics and practitioners together in an informal environment. As a non-profit, volunteer organization, DFRWS sponsors technical working groups, annual conferences and challenges to help drive the direction of research and development.

<http://dfrws.org>



Detecting Maliciousness Using Periodic Mobile Forensics

**Authors: Mark Guido, Jared Ondricek, Justin Grover,
David Wilburn, Thanh Nguyen, Drew Hunt**




Problem

- **Use case**
 - Enterprise deployments
- **Be proactive!**
 - Can we apply media forensics techniques to detect activities that are indicative of malicious behavior?
 - Measure changes to block devices
- **Organizations no longer own their phone infrastructure**
 - Centrally manage and audit phone usage



We want to make use of a richer set of user data on a phone as compared to a laptop




Client, Server, Database, Analysis Framework, Forensic Tools

Tractor Beam



Process – Live Phone Forensics


Reassemble forensic images



All forensic techniques are performed offline on image snapshots




Reconstructing Images





Forensic Tools


- Modern phones run Fourth Extended Filesystem (ext4)
 - Can apply forensic tools on reconstructed images
 - The Sleuth Kit 4.0.0b1 with experimental ext4 support
 - Identify when .apks are installed
 - Identify deleted files
 - Reconstruct .apk file
 - Fiwalk 0.6.15
 - Identify all file system Modified, Accessed, Created, Entry Modified (MACE) times
 - Generate DFXML to feed analysis tools






Mobile Malware

- **Certain phone partitions change continuously, others only when user initiates.**



- **Enterprise use case:**
 - We should only rarely see changes to blue system partitions

Tractor Beam is already set up to easily identify when these changes occur



7 Detectors and Loggers

- **Detector 1. Alerts on changes to boot.img**
- **Detector 2. Alerts on changes to recovery.img**
- **Detector 3. Alerts on changes to bootloader**
- **Detector 4. Alerts on changes to system.img**
 - **Useful for establishing persistence, surviving a reboot**
- **Logger 5. Compares image, logs all timestamp MACE time changes since previous snapshot**
- **Logger 6. Identifies and logs all deleted files since previous snapshot**
- **Detector 7. Identifies newly installed .apks and parses AndroidManifest.xml for BOOT_COMPLETED registration**

Experimentation



- Needed real mobile malware
- Android Malware Genome Project
 - MITRE obtained dataset of 1200 samples
 - No source code
 - Functionality of samples were not fully characterized
- Ran experiments in MITRE's Network Attack Investigations Laboratory (NAIL)
 - No wireless, Faraday bag
 - No SIM card in phone
- Used real phone
 - Nexus S running Android 2.3.1





Experimentation

■ Round 1

- 20 malware apps
- Goal: Test effectiveness of detectors

■ Round 2

- 100 apps
 - 90 legitimate
 - 10 malware
- Goal: Test the “BOOT_COMPLETED” detector

■ Round 3

- Custom malware app
- Goal: Test effectiveness against sophisticated malware



Round 3 – Frozen Bubble

- **Demo malware**
 - Have source code
- **Targeted at Nexus S**
 - Gingerbreak exploit
- **Contains malware-like capabilities**
 - Modifies boot.img for persistence
 - Modifies system.img - root
 - Phone emulates USB keyboard



Exploiting Smart-Phone USB Connectivity For Fun And Profit

Zhaohui Wang
Department of Computer Science
George Mason University, Fairfax, VA
zwange@gmu.edu

Angelos Stavrou
Department of Computer Science
George Mason University, Fairfax, VA
astavrou@gmu.edu


ABSTRACT

The Universal Serial Bus (USB) connection has become the

sal Serial Bus (USB) [7] led the phone device manufacturers to equip the majority of third-generation phones with USB



Round 3



Sample	Logged		Detected			Detection Result
	Installed	Exploit Dropped	BOOT_COMPLETED	system.img Change	boot.img Change	
1	x	x		x	x	Success

Application dropped no files and installed to /mnt/secure/asec.




Summary

- **Project focused on mobile malware on the enterprise:**
 - Paper concluded that there are alternative methods that showed promise for identifying and classifying mobile malware on running phone

- **We also developed:**
 - a method of extracting only changed blocks of data and reassembling an image from them
 - Normalized storage and fast reassembly
 - An analysis framework for running forensic detectors
 - 7 detectors were developed

- **This provides us a platform for future work**
 - New detectors are just Python scripts



Future Directions

- **Insider threat – identifying events and patterns of events that are indicative of malicious behavior by the phone owners**
- **Masquerading users – identifying when phones may be being used by someone other than the phone owner based upon observed behavior**
 - CERIAS collaboration
 - 30 Samsung Galaxy SIII's
- **Application of techniques for generalized forensics acquisition**
 - Forensics laboratory use case

Questions?






Backup Slides



Approach


Observed Malicious Behavior – deviation from profile.



- Take initial full forensic image
- Periodically send only changed data Over The Air (OTA) to server
- Reconstruct images at collection times
- Run series of detectors that incorporate various best practice media forensic techniques
- Eventize the results



Masquerading Experimentation



A successful result would be to identify each user/phone combination based solely on behavioral usage information.





BOOT_COMPLETED

- Applications can register to receive **BOOT_COMPLETED** event
 - Triggered when the phone finishes its boot process
 - Can use event notification to restart service
- 83% of samples in Android Malware Genome Project set registered for this event
- Must register to receive this event in the **AndroidManifest.xml** file
- .apk files typically installed in **/data/app**

Dissecting Android Malware: Characterization and Evolution

Yajin Zhou
Department of Computer Science
North Carolina State University
yajin_zhou@ncsu.edu

Xuxian Jiang
Department of Computer Science
North Carolina State University
jiang@cs.ncsu.edu

Abstract—The popularity and adoption of smartphones has greatly stimulated the spread of mobile malware, especially on

The goals and contributions of this paper are three-fold. First, we define the need by presenting the first large

RECON

WEAPONIZE


DELIVER

EXPLOIT

CONTROL


EXECUTE

MAINTAIN



Choosing Malware

- Narrowed sample set by filtering on
 - mount -o remount,rw /system
- This was what we thought was indicative of the sample establishing persistence
 - Wrong!!
- Samples were then chosen randomly





Round 1 – Test Tractor Beam Detectors

Sample	Logged		Detected		Detection Result
	Installed	Files Dropped	BOOT_COMPLETED	system.img Change	
1	x	x	x		Success
2	x	x	x		Success
3	x	x	x		Success
4	x		x		Success
5	x	x			Fail
6	x	x	x		Success
7	x	x	x		Success
8	x	x	x		Success
9	x	x	x		Success
10	x		x		Success
11	x	x	x		Success
12	x	x	x		Success
13	x	x		x	Success
14	x	x	x		Success
15	x	x	x		Success
16	x		x		Success
17	x	x	x		Success
18	x	x	x		Success
19	x	x	x		Success
20	x	x	x		Success



Round 2 – BOOT_COMPLETED Detector

		Detected	
		Malware	Non-Malware
Actual	Malware	10	0
	Non-Malware	29	61

Accuracy	71%
Error	29%
Precision	25.6%
Recall	100%

3 .apks were not observed installing – installed to /mnt/secure/asec